

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 12.01.2021, Revision 12.01.2021

Version 04. Supersedes version: 03

Page 1 / 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

SWAG 50 10 1150 Engine Oil 5W-30

Article number: 50 10 1150, 50 10 1151, 50 10 1152, 50 10 1153, 50 10 1154

UFI: Q641-V918-Q00H-C01N

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Engine oil

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company

SWAG Autoteile GmbH
Am Kiesberg 4-6
42117 Wuppertal / GERMANY
Phone +49 (0)202 26454-0
Fax +49 (0)202 26454-5000
Homepage www.swag.de
E-mail info@swag.de

Address enquiries to

Technical information

info@swag.de

Safety Data Sheet

info@swag.de

1.4 Emergency telephone number

Advisory body

+49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (EC) No 1272/2008]

Skin Sens. 1B: H317 May cause an allergic skin reaction.

2.2 Label elements

Hazard pictograms



Signal word

WARNING

Contains:

C14-16-18 Alkyl phenol

Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P280 Wear protective gloves.
P333+P313 If skin irritation or rash occurs: Get medical advice / attention.
P501 Dispose of contents / container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

2.3 Other hazards

Physico-chemical hazards

No particular hazards known.

Human health dangers

Frequent persistent contact with the skin can cause skin irritation.

Environmental hazards

Does not contain any PBT or vPvB substances.

Other hazards

Further hazards were not determined with the current level of knowledge.

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 12.01.2021, Revision 12.01.2021

Version 04. Supersedes version: 03

Page 2 / 12

SECTION 3: Composition / Information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
30 - < 60	Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)
	CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 2,5	Bis(nonylphenyl)amine
	CAS: 36878-20-3, EINECS/ELINCS: 253-249-4, Reg-No.: 01-2119488911-28-XXXX
	GHS/CLP: Aquatic Chronic 4: H413
1 - < 2,5	C14-16-18 Alkyl phenol
	CAS: 1190625-94-5, EINECS/ELINCS: 931-468-2, Reg-No.: 01-2119498288-19-XXXX
	GHS/CLP: Skin Sens. 1B: H317 - STOT RE 2: H373
1 - < 2,5	Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)
	CAS: 93819-94-4, EINECS/ELINCS: 298-577-9, Reg-No.: 01-2119543726-33-XXXX
	GHS/CLP: Skin Irrit. 2: H315 - Eye Dam. 1: H318 - Aquatic Chronic 2: H411
	SCL [%]: >6,25 - 100: Skin Irrit. 2, >10 - 12,5: Eye Irrit. 2, > 12,5: Eye Dam. 1

Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
For full text of H-statements and R-phrases: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information	Change soaked clothing.
Inhalation	Ensure supply of fresh air. In the event of symptoms seek medical treatment.
Skin contact	In case of contact with skin wash off immediately with soap and water. Consult a doctor if skin irritation persists.
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Consult a doctor immediately. Rinse out mouth and give plenty of water to drink. Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

If swallowed or in the event of vomiting, risk of product entering the lungs.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
Forward this sheet to your doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media	foam, dry powder, water spray jet, carbon dioxide
Extinguishing media that must not be used	Full water jet.

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 12.01.2021, Revision 12.01.2021

Version 04. Supersedes version: 03

Page 3 / 12

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.
Carbon monoxide (CO)
Sulphur oxides (SO_x).
Nitrogen oxides (NO_x).
Hydrogen sulfide ((H₂S).

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.
Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.
Forms slippery surfaces with water.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder).
Dispose of absorbed material in accordance with the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid formation of aerosols.
Do not smoke.
Fire class (DIN EN 2): B
Wash hands before breaks and after work.
Do not eat, drink or smoke when using this product.
Use barrier skin cream.
Take off contaminated clothing and wash before reuse.
Cloths contaminated with product should not be kept in trouser pockets.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.
Prevent penetration into the ground.
Do not store together with oxidizing agents.
Do not store together with food and animal food/diet.
Keep container tightly closed.
Protect from heat/overheating.

7.3 Specific end use(s)

See product use, SECTION 1.2

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 12.01.2021, Revision 12.01.2021

Version 04. Supersedes version: 03

Page 4 / 12

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational
exposure limits to be monitored (GB)

Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)
CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX
Long-term exposure: 5 mg/m ³ , oil mist
Short-term exposure (15-minute): 10 mg/m ³

DNEL

Substance
Bis(nonylphenyl)amine, CAS: 36878-20-3
Industrial, dermal, Long-term - systemic effects: 5 mg/kg bw/day.
general population, oral, Long-term - systemic effects: 0,25 mg/kg bw/day.
general population, dermal, Long-term - systemic effects: 2,5 mg/kg bw/day.
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
Industrial, dermal, Long-term - systemic effects: 1 mg/kg bw/day.
Industrial, inhalative, Long-term - local effects: 5,6 mg/m ³ .
Industrial, inhalative, Long-term - systemic effects: 2,7 mg/m ³ .
general population, oral, Long-term - systemic effects: 0,74 mg/kg bw/day.
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4
Industrial, dermal, Long-term - systemic effects: 0,58 mg/kg bw/day.
Industrial, inhalative, Long-term - systemic effects: 8,31 mg/m ³ .
general population, oral, Long-term - systemic effects: 0,24 mg/kg bw/day.
general population, dermal, Long-term - systemic effects: 0,29 mg/kg bw/day.
general population, inhalative, Long-term - systemic effects: 2,11 mg/m ³ .
C14-16-18 Alkyl phenol, CAS: 1190625-94-5
Industrial, dermal, Long-term - systemic effects: 300 µg/kg bw/d.
Industrial, inhalative, Long-term - systemic effects: 1,17 mg/m ³ .

PNEC

Substance
Bis(nonylphenyl)amine, CAS: 36878-20-3
seawater, 0,01 mg/l.
sewage treatment plants (STP), 1 mg/l.
sediment (freshwater), 132000 mg/kg.
sediment (seawater), 13200 mg/kg.
soil, 263000 mg/kg.
freshwater, 0,1 mg/l.
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
oral (food), 9,33 mg/kg.
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4
sediment (seawater), 0,001 mg/kg dw.
freshwater, 0,004 mg/l.
seawater, 0,004 mg/l.
sediment (freshwater), 0,012 mg/kg dw.

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 12.01.2021, Revision 12.01.2021

Version 04. Supersedes version: 03

Page 5 / 12

soil, 0,005 mg/kg.
oral (food), 10,67 mg/kg.
sewage treatment plants (STP), 100 mg/l.
C14-16-18 Alkyl phenol, CAS: 1190625-94-5
oral (food), 3,3 mg/kg.
freshwater, 100 µg/l.
seawater, 10 µg/l.
sewage treatment plants (STP), 100 mg/l.
sediment (freshwater), 4266,16 mg/kg dw.
sediment (seawater), 426,62 mg/kg dw.
soil, 852,58 mg/kg dw.

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.
Eye protection	Safety glasses. (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. > 0,11 mm: Nitrile rubber, >480 min (EN 374-1/-2/-3).
Skin protection	Light protective clothing.
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Avoid contact with eyes and skin.
Respiratory protection	Breathing apparatus in the event of aerosol or mist formation. Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)
Thermal hazards	No information available.
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 12.01.2021, Revision 12.01.2021

Version 04. Supersedes version: 03

Page 6 / 12

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Color	light brown
Odor	characteristic
Odour threshold	No information available.
pH-value	not applicable
pH-value [1%]	No information available.
Boiling point [°C]	No information available.
Flash point [°C]	> 195 (ISO 2592)
Flammability (solid, gas) [°C]	not applicable
Lower explosion limit	No information available.
Upper explosion limit	No information available.
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	<0,01 (20°C)
Density [g/ml]	ca. 0,85 (DIN 51757) (15 °C / 59,0 °F)
Bulk density [kg/m³]	not applicable
Solubility in water	virtually insoluble
Solubility other solvents	No information available.
Partition coefficient [n-octanol/water]	No information available.
Kinematic viscosity	ca. 10,2 mm²/s (100°C) (DIN 51562/T1) > 20,5 mm²/s (40°C)
Relative vapour density	No information available.
Evaporation speed	No information available.
Melting point [°C]	< -36 (DIN ISO 3016)
Auto-ignition temperature	No information available.
Decomposition temperature [°C]	> 65°C
Particle characteristics	No information available.

9.2 Other information

Pour point: ca. -36°C

SECTION 10: Stability and reactivity

10.1 Reactivity

See SECTION 10.3.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

Strong acids.
Strong heating, because the thermal decomposition starts from > 65°C.



SWAG Autoteile GmbH
42117 Wuppertal

Date printed 12.01.2021, Revision 12.01.2021

Version 04. Supersedes version: 03

Page 7 / 12

10.5 Incompatible materials

Oxidizing agent
Acids
Strong basic compounds

10.6 Hazardous decomposition products

In the case of heating following (decomposition) products may occur:
Hydrogen sulfide (H₂S).

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 12.01.2021, Revision 12.01.2021

Version 04. Supersedes version: 03

Page 8 / 12

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity

Substance
Bis(nonylphenyl)amine, CAS: 36878-20-3
LD50, oral, Rat: >5000 mg/kg (OECD 401).
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
LD50, oral, Rat: > 5000 mg/kg.
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4
LD50, oral, Rat: 2600 mg/kg.
C14-16-18 Alkyl phenol, CAS: 1190625-94-5
LD50, oral, Rat (female): >2000 mg/kg bw.

Acute dermal toxicity

Substance
Bis(nonylphenyl)amine, CAS: 36878-20-3
LD50, dermal, Rat: >2000 mg/kg (OECD 402).
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
LD50, dermal, Rabbit: > 2000 mg/kg.
LC50, dermal, Rat: 2,18 mg/l.
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4
LD50, dermal, Rabbit: >3160 mg/kg bw/day.
C14-16-18 Alkyl phenol, CAS: 1190625-94-5
LD50, dermal, Rat: >2000 mg/kg bw.

Acute inhalational toxicity

Substance
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4
LC50, inhalative, Rat: >2 mg/l.

Serious eye damage/irritation

Toxicological data of complete product are not available.
CAS 93819-94-4: >10% - <12,5% Eye Irrit. 2 No classification.
Classification was carried out based on substance-specific concentration limits.

Skin corrosion/irritation

Based on the available information, the classification criteria are not fulfilled.

Respiratory or skin sensitisation

Toxicological data of complete product are not available.
May cause an allergic skin reaction.
Calculation method

Specific target organ toxicity — single exposure

Based on the available information, the classification criteria are not fulfilled.

Specific target organ toxicity — repeated exposure

Based on the available information, the classification criteria are not fulfilled.

Mutagenicity

Based on the available information, the classification criteria are not fulfilled.

Reproduction toxicity

Based on the available information, the classification criteria are not fulfilled.

Carcinogenicity

Based on the available information, the classification criteria are not fulfilled.

Aspiration hazard

Based on the available information, the classification criteria are not fulfilled.

General remarks

Toxicological data of complete product are not available.
The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists.

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 12.01.2021, Revision 12.01.2021

Version 04. Supersedes version: 03

Page 9 / 12

SECTION 12: Ecological information

12.1 Toxicity

Substance
Bis(nonylphenyl)amine, CAS: 36878-20-3
EC50, (48h), Daphnia magna: >100 mg/l (OECD 202).
LC0, (96h), Brachidanio rerio: 58 mg/l (OECD 203).
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
EL50, (24h), Daphnia magna: > 10000 mg/l.
NOELR, (14d), Oncorhynchus mykiss: >= 1000 mg/l.
LL50, (96h), Pimephales promelas: >100 mg/l.
NOEL, (72h), Pseudokirchneriella subcapitata: >= 100 mg/l.
NOEL, (21d), Daphnia magna: 10 mg/l.
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4
EC50, (3h), Activated sludge: >10000 mg/l.
EC50, (48h), Daphnia magna: 5,4 mg/l (OECD 202).
EC50, (72h), Selenastrum capricornutum: 2,1 mg/l.
IC50, (21d), Daphnia magna: >0,8 mg/l.
LL50, (96h), Oncorhynchus mykiss: 4,5 mg/l.
C14-16-18 Alkyl phenol, CAS: 1190625-94-5
LC50, (96h), Cyprinus carpio: >100 mg/l.
EC50, (24h), Daphnia magna: >100 mg/l.
EC50, (72h), Pseudokirchneriella subcapitata: >100 mg/l.
NOEC, (72h), Pseudokirchneriella subcapitata: 100 mg/l.
NOELR, (24h), Daphnia magna: >100 mg/l.

12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	Can be separated out mechanically in purification plants.
Biological degradability	The product is not readily biodegradable.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Endocrine disrupting properties

No information available.

12.7 Other adverse effects

Ecological data of complete product are not available.
Do not discharge product unmonitored into the environment or into the drainage.
The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 12.01.2021, Revision 12.01.2021

Version 04. Supersedes version: 03

Page 10 / 12

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Coordinate disposal with the authorities if necessary.
Disposal in an incineration plant in accordance with the regulations of the local authorities.
In according to RoHS!

Waste no. (recommended)

130205* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.
Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended)

150110* packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to ADR/RID NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

Marine transport in accordance with IMDG NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 12.01.2021, Revision 12.01.2021

Version 04. Supersedes version: 03

Page 11 / 12

14.4 Packing group

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.5 Environmental hazards

Transport by land according to ADR/RID no

Inland navigation (ADN) no

Marine transport in accordance with IMDG no

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS 2008/98/EC 2000/532/EC; 2010/75/EU; 2004/42/EC; (EC) 648/2004; (EC) 1907/2006 (REACH); (EU) 1272/2008; 75/324/EEC ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131; (EU) 517/2014

TRANSPORT-REGULATIONS ADR (2019); IMDG-Code (2019, 39. Amdt.); IATA-DGR (2020)

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011).

- Observe employment restrictions for people Observe employment restrictions for mothers-to-be and nursing mothers. Observe employment restrictions for young people.

- VOC (2010/75/CE) not applicable

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H413 May cause long lasting harmful effects to aquatic life.
H373 May cause damage to organs through prolonged or repeated exposure.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
H318 Causes serious eye damage.
H315 Causes skin irritation.
H304 May be fatal if swallowed and enters airways.

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 12.01.2021, Revision 12.01.2021

Version 04. Supersedes version: 03

Page 12 / 12

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ATE = acute toxicity estimate
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging
DMEL = Derived Minimum Effect Level
DNEL = Derived No Effect Level
EC50 = Median effective concentration
ECB = European Chemicals Bureau
EEC = European Economic Community
EINECS = European Inventory of Existing Commercial Chemical Substances
EL50 = Median effective loading
ELINCS = European List of Notified Chemical Substances
EmS = Emergency Schedules
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50 = Inhibition concentration, 50%
IMDG = International Maritime Code for Dangerous Goods
IUCLID = International Uniform Chemical Information Database
IVIS = In vitro irritation score
LC50 = Lethal concentration, 50%
LD50 = Median lethal dose
LC0 = lethal concentration, 0%
LOAEL = lowest-observed-adverse-effect level
LL50 = Median lethal loading
LQ = Limited Quantities
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration
PBT = Persistent, Bioaccumulative and Toxic substance
PNEC = Predicted No-Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
STP = Sewage Treatment Plant
TLV®/TWA = Threshold limit value – time-weighted average
TLV®STEL = Threshold limit value – short-time exposure limit
VOC = Volatile Organic Compounds
vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Skin Sens. 1B: H317 May cause an allergic skin reaction. (Calculation method)

Modified position

none