

Page 1 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 11.09.2019 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 11.09.2019 PDF print date: 12.09.2019 Hypoid Getriebeoel TDL SAE 80W-90 1 L Art.: 20645

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Hypoid Getriebeoel TDL SAE 80W-90 1 L Art.: 20645

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Gear lubricant

അ

Sector of use [SU]: SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC17 - Hydraulic fluids

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions.

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC20 - Use of functional fluids in small devices

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 9a - Widespread use of functional fluid (indoor)

ERC 9b - Widespread use of functional fluid (outdoor)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

œ

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture



Page 2 of 11

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 11.09.2019 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 11.09.2019 PDF print date: 12.09.2019 Hypoid Getriebeoel TDL SAE 80W-90 1 L Art.: 20645

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains Magnesium metaborate, Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), Polysulfides, di-tert-Bu. May produce an allergic reaction. EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

Product can compose a film on the water surface, which can prevent oxygen exchange.

Endangerment of potable water possible.

SECTION 3: Composition/information on ingredients

3.1 Substance

Polysulfides, di-tert-Bu	Substance with specific conc. limit(s) acc. to REACh- registration
Registration number (REACH)	01-2119540515-43-XXXX
Index	
EINECS, ELINCS, NLP	273-103-3
CAS	68937-96-2
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Sens. 1B, H317
	Aquatic Chronic 3, H412
Baseoil - unspecified *	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	
CAS	
content %	0,1-2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid	Substance with specific conc. limit(s) acc. to REACh-
with phosphorus oxide, propylene oxide and amines, C12-14-alkyl	registration
(branched)	
Registration number (REACH)	01-2119493620-38-XXXX
Index	
EINECS, ELINCS, NLP	931-384-6 (REACH-IT List-No.)
CAS	
content %	0,1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302
, ,	Eye Dam. 1, H318
	Aquatic Chronic 2, H411
	Skin Sens. 1B, H317

* The contained mineral oil can be described by one or more of the following numbers:



Page 3 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 11.09.2019 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 11.09.2019 PDF print date: 12.09.2019 Hypoid Getriebeoel TDL SAE 80W-90 1 L Art.: 20645

EINECS, ELINCS, NLP	Registration number (REACH)	Chemical name
265-157-1	01-2119484627-25-XXXX	Distillates (petroleum), hydrotreated heavy paraffinic
265-169-7	01-2119471299-27-XXXX	Distillates (petroleum), solvent-dewaxed heavy paraffinic
265-158-7	01-2119487077-29-XXXX	Distillates (petroleum), hydrotreated light paraffinic
265-159-2	01-2119480132-48-XXXX	Distillates (petroleum), solvent-dewaxed light paraffinic

The substances named in this section are given with their actual, appropriate classification! For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may

be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

ആ

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary. Keep Data Sheet available.

Ingestion

Rinse the mouth thoroughly with water. Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur: Irritation of the eyes Drying of the skin. Dermatitis (skin inflammation) Irritation of the skin.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media CO2 Foam Dry extinguisher Water jet spray Unsuitable extinguishing media High volume water jet 5.2 Special hazards arising from the substance or mixture In case of fire the following can develop: Oxides of carbon Oxides of nitrogen Oxides of sulphur Flammable vapour/air mixtures 5.3 Advice for firefighters In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply.



Page 4 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 11.09.2019 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 11.09.2019 PDF print date: 12.09.2019 Hypoid Getriebeoel TDL SAE 80W-90 1 L Art.: 20645

According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air. Avoid contact with eyes or skin. If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

ആ

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid formation of oil mist.

Ensure good ventilation. Do not heat to temperatures close to flash point.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Avoid long lasting or intensive contact with skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells. Store product closed and only in original packing.

Protect against moisture and store closed.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

B	Chemical Name	Oil mist, mineral			Content %:
W	EL-TWA: 5 mg/m3 (Mineral oil,	excluding metal	WEL-STEL:		
wo	rking fluids, ACGIH)				
Mo	onitoring procedures:	-	Draeger - Oil 10/a-P (67 28 371)		
		-	Draeger - Oil Mist 1/a (67 33 031)		
BN	1GV:			Other information:	



Page 5 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 11.09.2019 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 11.09.2019 PDF print date: 12.09.2019 Hypoid Getriebeoel TDL SAE 80W-90 1 L Art.: 20645

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

ആ

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN 374). If applicable Protective nitrile gloves (EN 374). Minimum layer thickness in mm: 0,35 Permeation time (penetration time) in minutes: >= 480 Protective hand cream recommended. The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments). Respiratory protection:

If OES or MEL is exceeded. Filter A2 P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.



Page 6 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 11.09.2019 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 11.09.2019 PDF print date: 12.09.2019 Hypoid Getriebeoel TDL SAE 80W-90 1 L Art.: 20645

8.2.3 Environmental exposure controls

No information available at present.

œ

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Yellow, Brown
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	200 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,9 g/ml
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	14,5 mm2/s (100°C)
Viscosity:	142 mm2/s (40°C)
Explosive properties:	Not determined
Oxidising properties:	Not determined
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No decomposition if used as intended. 10.4 Conditions to avoid See also section 7. Protect from humidity. Open flame, ignition sources **10.5 Incompatible materials** See also section 7. Avoid contact with strong oxidizing agents. **10.6 Hazardous decomposition products** See also section 5.2 No decomposition when used as directed.

SECTION 11: Toxicological information



Page 7 of 11

œ)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 11.09.2019 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 11.09.2019 PDF print date: 12.09.2019 Hypoid Getriebeoel TDL SAE 80W-90 1 L Art.: 20645

11.1 Information on toxicological effects

Possibly more information on hea	alth effects, see	e Section 2.1 (classification).			
Hypoid Getriebeoel TDL SAE 8	0W-90 1 L		, , , , , , , , , , , , , , , , , , , ,			
Art.: 20645						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification
						according to
						calculation
						procedure.
	1		1	1		
Baseoil - unspecified						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Respiratory or skin	-			-		Not sensitizising
sensitisation:						
Aspiration hazard:						Yes
Reaction products of bis(4-met alkyl (branched)	thylpentan-2-y	/l)dithiophosp	phoric acid with	n phosphorus ox	ide, propylene oxide and a	mines, C12-14-
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral	

Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit		Corrosive
Respiratory or skin				Mouse	OECD 429 (Skin	Skin Sens. 1B
sensitisation:					Sensitisation - Local	
					Lymph Node Assay)	
Germ cell mutagenicity:						Negative
Reproductive toxicity:						Negative
Specific target organ toxicity -	NOAEL	150	mg/kg	Rat	OECD 407 (Repeated	
repeated exposure (STOT-RE),			bw/d		Dose 28-Day Oral	
oral:					Toxicity Study in	
					Rodents)	

SECTION 12: Ecological information Possibly more information on environmental effects, see Section 2.1 (classification). Hypoid Getriebeoel TDL SAE 80W-90 1 L Art.: 20645 Toxicity / effect Endpoint Time Value Unit Organism Test method Notes 12.1. Toxicity to fish: n.d.a. 12.1. Toxicity to daphnia: n.d.a.



Page 8 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 11.09.2019 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 11.09.2019 PDF print date: 12.09.2019 Hypoid Getriebeoel TDL SAE 80W-90 1 L Art.: 20645

œ

12.1. Toxicity to algae:			n.d.a.
12.2. Persistence and			n.d.a.
degradability:			
12.3. Bioaccumulative			n.d.a.
potential:			
12.4. Mobility in soil:			n.d.a.
12.5. Results of PBT			n.d.a.
and vPvB assessment			
12.6. Other adverse			n.d.a.
effects:			

Baseoil - unspecified							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	48h	>10000	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Scenedesmus quadricauda		
12.2. Persistence and degradability:		28d	31	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24	mg/l			
12.2. Persistence and degradability:	DOC	28d	3,6	%	activated sludge		
12.1. Toxicity to daphnia:	EC50	21d	0,66	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,12	mg/l	Daphnia magna		
12.1. Toxicity to fish:	NOEC/NOEL	96h	3,2	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	91,4	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	96h	6,4	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	96h	1,7	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	7,4	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable
Toxicity to bacteria:	EC50	3h	~2433	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

SECTION 13: Disposal considerations



Page 9 of 11

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 11.09.2019 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 11.09.2019 PDF print date: 12.09.2019 Hypoid Getriebeoel TDL SAE 80W-90 1 L Art.: 20645

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no .: The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU) 13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils Recommendation: Sewage disposal shall be discouraged. Pay attention to local and national official regulations. E.g. dispose at suitable refuse site. E.g. suitable incineration plant. For contaminated packing material Pay attention to local and national official regulations. 15 01 01 paper and cardboard packaging 15 01 02 plastic packaging 15 01 04 metallic packaging Empty container completely. Uncontaminated packaging can be recycled. Dispose of packaging that cannot be cleaned in the same manner as the substance. **SECTION 14: Transport information** General statements 14.1. UN number: n.a. Transport by road/by rail (ADR/RID) 14.2. UN proper shipping name: 14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a. Classification code: n.a. LQ: n.a. 14.5. Environmental hazards: Not applicable Tunnel restriction code: Transport by sea (IMDG-code) 14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a. Marine Pollutant: n.a 14.5. Environmental hazards: Not applicable Transport by air (IATA) 14.2. UN proper shipping name: 14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a. 14.5. Environmental hazards: Not applicable 14.6. Special precautions for user Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions: General hygiene measures for the handling of chemicals are applicable.



Page 10 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 11.09.2019 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 11.09.2019 PDF print date: 12.09.2019 Hypoid Getriebeoel TDL SAE 80W-90 1 L Art.: 20645

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

ആ

2, 3, 8, 11, 12, 15

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3). H317 May cause an allergic skin reaction.

H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

Skin Sens. — Skin sensitization Aquatic Chronic - Hazardous to the aquatic environment - chronic Asp. Tox. — Aspiration hazard Acute Tox. — Acute toxicity - oral Eye Dam. - Serious eye damage

Any abbreviations and acronyms used in this document:

according, according to acc., acc. to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Article number Art., Art. no. ASTM ASTM International (American Society for Testing and Materials) Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BSEF The International Bromine Council body weight bw CAS **Chemical Abstracts Service** CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. ΕČ European Community ECHA European Chemicals Agency EEC European Economic Community EINECS European Inventory of Existing Commercial Chemical Substances European List of Notified Chemical Substances ELINCS ΕN **European Norms** FPA United States Environmental Protection Agency (United States of America) et cetera etc. EU European Union EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number gen. general



ദ്ര Page 11 of 11 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 11.09.2019 / 0013 Replacing version dated / version: 21.08.2015 / 0012 Valid from: 11.09.2019 PDF print date: 12.09.2019 Hypoid Getriebeoel TDL SAE 80W-90 1 L Art.: 20645 Globally Harmonized System of Classification and Labelling of Chemicals GHS GWP Global warming potential International Agency for Research on Cancer IARC IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLID International Uniform Chemical Information Database LQ Limited Quantities International Convention for the Prevention of Marine Pollution from Ships MARPOL n.a. not applicable n.av. not available not checked n.c. no data available n.d.a. OECD Organisation for Economic Co-operation and Development org. organic PBT persistent, bioaccumulative and toxic PE Polyethylene PNEC Predicted No Effect Concentration parts per million ppm PVC Polyvinylchloride REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No. Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Tel. Telephone UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds vPvB very persistent and very bioaccumulative wwt wet weight The statements made here should describe the product with regard to the necessary safety precautions - they are

not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.