SAFETY DATA SHEET



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

Comma White Grease

of the mixture

Registration number -

Synonyms None.

Product code WGR500M

Issue date 23-December-2018

Version number 08

Revision date 28-May-2022 Supersedes date 28-May-2022

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified usesService sprayUses advised againstNone known.

1.3. Details of the supplier of the safety data sheet

Manufactured by Moove Lubricants

Address Dering Way, Gravesend, Kent DA12 2QX UK

Telephone +44 (0) 1474 564 311

Address Operations Plant Dering Way, Gravesend, Kent DA12 2QX UK

Telephone +44 (0) 1474 564 311

Email technical@uk.moovelub.com

1.4. Emergency telephone

 Asia Pacific
 + (1) 760 476 3960

 China
 + (86) 4001 2001 74

 Europe
 + (44) 8 08 189 0979

 Middle East/Africa
 + (1) 760 476 3959

Access Code 334498

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Aerosols Category 1 H222 - Extremely flammable

aerosol.

dizziness.

H229 - Pressurized container: May

burst if heated.

Health hazards

Acute toxicity, inhalation Category 4

Skin corrosion/irritation Category 2 H315 - Causes skin irritation.

Specific target organ toxicity - single Category 3 narcotic effects H336 - May cause drowsiness or

exposure

Environmental hazards
Hazardous to the aquatic environment, Category 2

Category 2 H411 - Toxic to aquatic life with

long lasting effects.

Hazard summary Not available.

long-term aquatic hazard

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

UFI MR80-H02A-K006-V4PC

Contains: Naphtha (petroleum), hydrotreated light

Material name: Comma White Grease - Moove Lubricants Itd.

WGR500M Version #: 08 Revision date: 28-May-2022 Issue date: 23-December-2018

Hazard pictograms



Signal word Danger

Hazard statements

Extremely flammable aerosol. H222

Pressurized container: May burst if heated. H229

Causes skin irritation. H315

May cause drowsiness or dizziness. H336

Toxic to aquatic life with long lasting effects. H411

Precautionary statements

Prevention

Keep out of reach of children. P102

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

Do not spray on an open flame or other ignition source. P211

Do not pierce or burn, even after use. P251

Avoid breathing spray. P261

Use only outdoors or in a well-ventilated area. P271

Response

If medical advice is needed, have product container or label at hand. P101

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P410 + P412

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

Supplemental label information

Not a PBT or vPvB substance or mixture. 2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name		%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Naphtha (petroleum), hy light	/drotreated	40 - < 50	64742-49-0 265-151-9	-	649-328-00-1	
Classification:	Flam. Liq. 2 Chronic 2;H		Tox. 1;H304, Skin Ir	rit. 2;H315, STOT SE 3;H33	6, Aquatic	Р

Other components below reportable 50 - < 60

levels

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

centre or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause

4.2. Most important symptoms and effects, both acute and

redness and pain.

delayed

Material name: Comma White Grease - Moove Lubricants Itd.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards

Extremely flammable aerosol.

5.1. Extinguishing media

Suitable extinguishing

media

Powder. Carbon dioxide (CO2).

Unsuitable extinguishing

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire fighting procedures

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s) Service spray

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Exposure Limits (WELs)

Components	Туре	Value
BUTANE (CAS 106-97-8)	STEL	1810 mg/m3
		750 ppm
	TWA	1450 mg/m3
		600 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Follow standard monitoring procedures.

Derived no effect levels

(DNELs)

Not available.

Predicted no effect concentrations (PNECs)

Not available.

8.2. Exposure controls

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection

Chemical respirator with organic vapour cartridge and full facepiece.

Skin protection

- Hand protection Wear appropriate chemical resistant gloves.
 - Other Wear appropriate chemical resistant clothing.

Respiratory protection Chemical respirator with organic vapour cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures When using do not smoke. Always observe good personal hygiene measures, such as washing

after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

Environmental exposure

controls

Inform appropriate managerial or supervisory personnel of all environmental releases. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical stateLiquid.FormAerosolColourWhite.

Odour Characteristic.
Odour threshold Not available.
pH Not available.
Melting point/freezing point Not available.
Initial boiling point and boiling Not available.

range

Flash point < 0 °C (< 32.0 °F)

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Inper/leger flammability or explosive limits

Upper/lower flammability or explosive limits Flammability limit - lower 0.8 %

(%)

Flammability limit - upper

(%)

Vapour pressure Not available.
Vapour density Not available.

Relative density 0.67

Relative density temperature 20 °C (68 °F)

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Explosive properties Not explosive.

Oxidising properties Not oxidising.

9.2. Other information No relevant additional information available.

9 %

SECTION 10: Stability and reactivity

10.1. ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

10.5. Incompatible materials10.6. HazardousStrong oxidising agents. Chlorine. Fluorine. Nitrates.No hazardous decomposition products are known.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact Causes skin irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause

redness and pain.

11.1. Information on toxicological effects

Acute toxicity Not known.

Product Species Test Results

Comma White Grease

Acute

Dermal

LD50 Rabbit 4222 mg/kg, 24 Hours

Inhalation

LC50 Rat 3290 mg/m3, 4 hours

Oral

 LD50
 Rat
 10710 mg/kg

 Components
 Species
 Test Results

Components Species

Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

<u>Acute</u>

Oral

LD50 Rat > 2000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory sensitisation

Due to partial or complete lack of data the classification is not possible.

Skin sensitisation

Due to partial or complete lack of data the classification is not possible.

Germ cell mutagenicity

Reproductive toxicity

Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible.

Carcinogenicity

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

Other information

No information available.

Not available.

formation

SECTION 12: Ecological information

12.1. ToxicityToxic to aquatic life with long lasting effects. Based on available data, the classification criteria are

not met for hazardous to the aquatic environment, acute hazard.

Product		Species	Test Results
Comma White Grease			
Aquatic			
Crustacea	EC50	Daphnia	8.3333 mg/l, 48 hours estimated
Fish	LC50	Fish	20 mg/l, 96 hours estimated
Components		Species	Test Results
Naphtha (petroleum), hydr	otreated light (CAS	64742-49-0)	
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours

Crustacea EC50 Water flea (Daphnia pulex) 2.7 - 5.1 mg/l, 48 hours
Fish LC50 Rainbow trout,donaldson trout (Oncorhynchus mykiss) 8.8 mg/l, 96 hours

8.8 mg/l, 96 hours

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Bioconcentration factor (BCF) 12.4. Mobility in soil

No data available.

Not available.

12.5. Results of PBT and vPvB assessment

Not a PBT or vPvB substance or mixture.

12.6. Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

EU waste codeThe Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Special precautionsDispose in accordance with all applicable regulations.

Material name: Comma White Grease - Moove Lubricants Itd.

WGR500M Version #: 08 Revision date: 28-May-2022 Issue date: 23-December-2018

SECTION 14: Transport information

ADR

UN1950 14.1. UN number 14.2. UN proper shipping **AEROSOLS**

14.3. Transport hazard class(es)

Class 2 Subsidiary risk 2.1 Label(s) Hazard No. (ADR) Tunnel restriction code D

14.4. Packing group Not available.

14.5. Environmental hazards Yes

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

RID

14.1. UN number UN1950 14.2. UN proper shipping **AEROSOLS**

14.3. Transport hazard class(es)

2 Class Subsidiary risk 2.1 Label(s)

Not available. 14.4. Packing group

14.5. Environmental hazards Yes

Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions

for user

ADN

UN1950 14.1. UN number 14.2. UN proper shipping **AEROSOLS**

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s) 2 1

Not available. 14.4. Packing group

14.5. Environmental hazards Yes

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IATA

UN1950 14.1. UN number

Aerosols, flammable 14.2. UN proper shipping

name

14.3. Transport hazard class(es)

Class Subsidiary risk

14.4. Packing group Not available.

14.5. Environmental hazards Yes **ERG Code**

14.6. Special precautions

for user Other information Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Allowed with restrictions. Cargo aircraft only

IMDG

14.1. UN number UN1950

AEROSOLS, MARINE POLLUTANT 14.2. UN proper shipping

14.3. Transport hazard class(es)

2 Class Subsidiary risk

14.4. Packing group Not available.

14.5. Environmental hazards

Marine pollutant Yes EmS F-D, S-U

Not established.

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC

Code

ADN; ADR; IATA; IMDG; RID



Marine pollutant



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

UFI MR80-H02A-K006-V4PC

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

National regulations Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as

amended.

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations Not available.

References Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation

methods and test data, if available.

Full text of any H-statements not written out in full under Sections 2 to 15

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Revision information None.

Training information Follow training instructions when handling this material.

Disclaimer Moove Lubricants Itd. cannot anticipate all conditions under which this information and its product,

or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in

the sheet was written based on the best knowledge and experience currently available.

Material name: Comma White Grease - Moove Lubricants Itd.

WGR500M Version #: 08 Revision date: 28-May-2022 Issue date: 23-December-2018