Valvoline, N

SAFETY DATA SHEET

Valvoline™ ALL CLIMATE C3 5W40 Synthetic Blend Motor Oil

Version: 10.0 Revision Date: 02.07.2020 Print Date: 29/09/2022

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Valvoline™ ALL CLIMATE C3 5W40

Synthetic Blend Motor Oil

Product code : 872277

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data

Ellis Enterprises B.V., an affiliate of Valvoline

Wieldrechtseweg 39 3316 BG Dordrecht

Netherlands +31 (0)78 654 3500 (in the Neth

+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person

SDS@valvoline.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number at 112

Product Information

+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling:

EUH210 Safety data sheet available on request.

EUH208 Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.



Valvoline™ ALL CLIMATE C3 5W40 Synthetic Blend Motor Oil

Version: 10.0 Revision Date: 02.07.2020 Print Date: 29/09/2022

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional advice

No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7 265-157-1 01-2119484627-25-xxxx	Asp. Tox.1; H304	>= 10,00 - < 15,00
bis(nonylphenyl)amine	36878-20-3 253-249-4 01-2119488911-28-xxxx	Aquatic Chronic4; H413	>= 1,00 - < 2,50
C14-16-18 Alkyl phenol	931-468-2 01-2119498288-19-xxxx	Skin Sens.1B; H317 STOT RE2; H373	>= 1,00 - < 2,50

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Do not leave the victim unattended.

Show this safety data sheet to the doctor in attendance.

Move out of dangerous area.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is



Valvoline™ ALL CLIMATE C3 5W40 Synthetic Blend Motor Oil

Version: 10.0 Revision Date: 02.07.2020 Print Date: 29/09/2022

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : If eye irritation persists, consult a specialist.

Protect unharmed eye. Remove contact lenses.

Flush eyes with water as a precaution.

If swallowed : If symptoms persist, call a physician.

Never give anything by mouth to an unconscious person.

Do not give milk or alcoholic beverages.

Obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray

Foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

products

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

n

: Nitrogen oxides (NOx)

carbon dioxide and carbon monoxide

Valvoline

SAFETY DATA SHEET

Valvoline™ ALL CLIMATE C3 5W40 Synthetic Blend Motor Oil

Revision Date: 02.07.2020 Print Date: 29/09/2022 Version: 10.0

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing

methods

: Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

Environmental precautions : If the product contaminates rivers and lakes or drains inform

respective authorities.

Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Dispose of rinse water in accordance with local and national

regulations.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Container hazardous when empty.

Do not smoke.

Do not breathe vapours/dust.

Valvoline, TM

SAFETY DATA SHEET

Valvoline™ ALL CLIMATE C3 5W40 Synthetic Blend Motor Oil

Version: 10.0 Revision Date: 02.07.2020 Print Date: 29/09/2022

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Hygiene measures : Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

: Keep container tightly closed in a dry and well-ventilated

place.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eves.

Hand protection

Remarks : Nitrile rubber butyl-rubber

The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Safety shoes Impervious clothing Wear as appropriate:



Valvoline™ ALL CLIMATE C3 5W40 Synthetic Blend Motor Oil

Version: 10.0 Revision Date: 02.07.2020 Print Date: 29/09/2022

Respiratory protection : No personal respiratory protective equipment normally

required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : amber

Odour : oily

Odour Threshold : No data available

pH : Not applicable

Pour point : < -42 °C

Boiling point/boiling range : not determined

Flash point : 206 °C

Method: Pensky-Martens closed cup

Flammability (solid, gas) : No data available

Upper explosion limit / Upper :

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : No data available

No data available

Relative vapour density : No data available

Relative density : No data available

Density : ca. 0,854 g/cm3 (15,6 °C)

Bulk density : Not applicable

Solubility(ies)



Valvoline™ ALL CLIMATE C3 5W40 Synthetic Blend Motor Oil

Version: 10.0 Revision Date: 02.07.2020 Print Date: 29/09/2022

Water solubility : insoluble

Solubility in other solvents : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : < 6.400 mPa.s (-30 °C)

Viscosity, kinematic : 87 mm2/s (40 °C)

Oxidizing properties : No data available

9.2 Other information

Self-ignition : No data available

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Product will not undergo hazardous polymerization.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Strong bases

Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition

products

: No hazardous decomposition products are known.

SAFETY DATA SHEET

Valvoline™ ALL CLIMATE C3 5W40 Synthetic Blend Motor Oil

Version: 10.0 Revision Date: 02.07.2020 Print Date: 29/09/2022

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of : Inhalation

exposure

Skin contact Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Components:

HEAVY PARAFFINIC DISTILLATE:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Components:

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Remarks: Information given is based on data obtained from

similar substances.

Components:

C14-16-18 Alkyl phenol:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

Assessment: Not classified as acutely toxic by ingestion under

GHS.

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified based on available information.

Components:

HEAVY PARAFFINIC DISTILLATE:



Valvoline™ ALL CLIMATE C3 5W40 Synthetic Blend Motor Oil

Version: 10.0 Revision Date: 02.07.2020 Print Date: 29/09/2022

Result: Slight, transient irritation

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Rabbit

Result: Mild skin irritation

Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol:

Method: OECD Test Guideline 431

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

HEAVY PARAFFINIC DISTILLATE:

Result: No eye irritation

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Rabbit

Result: Slight, transient irritation

Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol:

Species: Rabbit

Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitisation.

Remarks: Based on similar product.

Components:

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Remarks: Information given is based on data obtained from similar substances.

Valvoline,

SAFETY DATA SHEET

Valvoline™ ALL CLIMATE C3 5W40 Synthetic Blend Motor Oil

Version: 10.0 Revision Date: 02.07.2020 Print Date: 29/09/2022

C14-16-18 Alkyl phenol:

Test Type: Local lymph node assay

Species: Mouse

Assessment: The product is a skin sensitiser, sub-category 1B.

Method: OECD Test Guideline 429

Germ cell mutagenicity

Not classified based on available information.

Components:

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

C14-16-18 Alkyl phenol:

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

C14-16-18 Alkyl phenol:

Target Organs: Liver

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Aspiration toxicity

Not classified based on available information.

Components:

HEAVY PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

Valvoline™ ALL CLIMATE C3 5W40 Synthetic Blend Motor Oil

Version: 10.0 Revision Date: 02.07.2020 Print Date: 29/09/2022

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Distillates (petroleum), hydrotreated heavy paraffinic

Toxicity to fish : LL50 (Fish): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10.000 mg/l

Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

NOEC 10 mg/l

Species: Fish

Toxicity to daphnia and other : NOEC: 10 mg/l

aquatic invertebrates

(Chronic toxicity)

Species: Aquatic invertebrates

bis(nonylphenyl)amine

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 96 h

Test Type: static test

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l

> End point: Growth inhibition Exposure time: 72 h

Test Type: static test

C14-16-18 Alkyl phenol



Valvoline™ ALL CLIMATE C3 5W40 Synthetic Blend Motor Oil

Version: 10.0 Revision Date: 02.07.2020 Print Date: 29/09/2022

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l

Exposure time: 96 h
Test Type: static test
Test substance: WAF

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h
Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l

End point: Growth inhibition

Exposure time: 72 h
Test Type: static test
Test substance: WAF

12.2 Persistence and degradability

Components:

bis(nonylphenyl)amine

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 301B

C14-16-18 Alkyl phenol

Biodegradability : Result: Readily biodegradable.

Remarks: Expert judgement

12.3 Bioaccumulative potential

Components:

bis(nonylphenyl)amine

Partition coefficient: n- : log Pow: > 7.5

octanol/water

C14-16-18 Alkyl phenol

Partition coefficient: n- : log Pow: > 7,2

octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Valvoline_{TM}

SAFETY DATA SHEET

Valvoline™ ALL CLIMATE C3 5W40 Synthetic Blend Motor Oil

Version: 10.0 Revision Date: 02.07.2020 Print Date: 29/09/2022

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

Product:

Additional ecological

information

: No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Send to a licensed waste management company.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Do not dispose of waste into sewer.

Contaminated packaging : Do not re-use empty containers.

Empty containers should be taken to an approved waste

handling site for recycling or disposal.

Dispose of as unused product. Empty remaining contents.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

SAFETY DATA SHEET

Valvoline™ ALL CLIMATE C3 5W40 Synthetic Blend Motor Oil

Version: 10.0 Revision Date: 02.07.2020 Print Date: 29/09/2022

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

: Not applicable

Regulation (EC) No 850/2004 on persistent organic

pollutants

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

Regulation (EC) No 649/2012 of the European

Parliament and the Council concerning the export and

import of dangerous chemicals

Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

Not applicable

Directive 96/82/EC does not apply

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

Valvoline,

SAFETY DATA SHEET

Valvoline™ ALL CLIMATE C3 5W40 Synthetic Blend Motor Oil

Version: 10.0 Revision Date: 02.07.2020 Print Date: 29/09/2022

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI: On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : Not in compliance with the inventory

TSCA : On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Further information

Internal information: R0517872

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H373 May cause damage to organs through prolonged or repeated exposure.

H413 May cause long lasting harmful effects to aquatic life.

Other information : The information accumulated herein is believed to be accurate

but is not warranted to be whether originating with the

SAFETY DATA SHEET

Valvoline™ ALL CLIMATE C3 5W40 Synthetic Blend Motor Oil

Version: 10.0 Revision Date: 02.07.2020 Print Date: 29/09/2022

company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department ('+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment STEL : Short-term exposure limit STOT : Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level



Valvoline™ ALL CLIMATE C3 5W40 Synthetic Blend Motor Oil

Version: 10.0 Revision Date: 02.07.2020 Print Date: 29/09/2022

ABM: Water Hazard Class for the Netherlands

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine

CLP: Classification, Labelling and Packaging

CSA: Chemical Safety Assessment CSR: Chemical Safety Report DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

ELINCS: European List of Notified Chemical Substances

PEC : Predicted Effect Concentration PEL : Permissible Exposure Limits

PNEC: Predicted No Effect Concentration

R-phrase: Risk phrase

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail

S-phrase: Safety phrase

WGK: German Water Hazard Class