


SAFETY DATA SHEET

Revision Date: 24.06.2019

Print Date: 27.05.2021

SDS Number: 000000197928

SynPower™ POWER ST.FL Power Steering Fluid

Version: 2.0

VE18320

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking
1.1 Product identifier

Trade name : SynPower™ POWER ST.FL
Power Steering Fluid

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Hydraulic oil

1.3 Details of the supplier of the safety data sheet

Ellis Enterprises B.V., an affiliate of Valvoline
Wieldrechtseweg 39
3316 BG Dordrecht
Netherlands
+31 (0)78 654 3500 (in the Netherlands), or
contact your local CSR contact person

SDS@valvoline.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact
your local emergency telephone number at 112

Product Information

+31 (0)78 654 3500 (in the Netherlands), or
contact your local CSR contact person

SECTION 2: Hazards identification
2.1 Classification of the substance or mixture
Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4

H332: Harmful if inhaled.

Aspiration hazard, Category 1

H304: May be fatal if swallowed and enters
airways.

2.2 Label elements
Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :




SAFETY DATA SHEET

Revision Date: 24.06.2019

Print Date: 27.05.2021

SDS Number: 000000197928

SynPower™ POWER ST.FL Power Steering Fluid

Version: 2.0

VE18320

Signal word	:	Danger	
Hazard statements	:	H304	May be fatal if swallowed and enters airways.
		H332	Harmful if inhaled.
Precautionary statements	:	P101	If medical advice is needed, have product container or label at hand.
		P102	Keep out of reach of children.
		Prevention:	
		P271	Use only outdoors or in a well-ventilated area.
		Response:	
		P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
		P331	Do NOT induce vomiting.
	Storage:		
	P405	Store locked up.	
	Disposal:		
	P501	Dispose of contents/ container to an approved waste disposal plant.	

Hazardous components which must be listed on the label:

1-DECENE, DIMER, HYDROGENATED

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based
White mineral oil

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional advice

No information available.

SECTION 3: Composition/information on ingredients
3.2 Mixtures
Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
1-DECENE, DIMER, HYDROGENATED	68649-11-6 500-228-5 01-2119493069-28-xxxx	Acute Tox.4; H332 Asp. Tox.1; H304	>= 70,00 - < 80,00
Lubricating oils (petroleum), C15-30,	72623-86-0 276-737-9	Asp. Tox.1; H304	>= 15,00 - < 25,00


SAFETY DATA SHEET

Revision Date: 24.06.2019

Print Date: 27.05.2021

SDS Number: 000000197928

SynPower™ POWER ST.FL Power Steering Fluid

Version: 2.0

VE18320

hydrotreated neutral oil-based			
--------------------------------	--	--	--

For explanation of abbreviations see section 16.

SECTION 4: First aid measures
4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Move to fresh air.
IF INHALED: Call a POISON CENTER/ doctor if you feel unwell.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No symptoms known or expected.
- Risks : May be fatal if swallowed and enters airways.
Harmful if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No hazards which require special first aid measures.


SAFETY DATA SHEET

Revision Date: 24.06.2019

Print Date: 27.05.2021

SDS Number: 000000197928

SynPower™ POWER ST.FL Power Steering Fluid

Version: 2.0

VE18320

SECTION 5: Firefighting measures
5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Water spray
 Foam
 Carbon dioxide (CO₂)
 Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.
 Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
 Hydrocarbons
 Hydrogen chloride gas

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures
6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
 Ensure adequate ventilation.
 Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.


SAFETY DATA SHEET

Revision Date: 24.06.2019

Print Date: 27.05.2021

SDS Number: 000000197928

SynPower™ POWER ST.FL Power Steering Fluid

Version: 2.0

VE18320

Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage
7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Wash hands before breaks and at the end of workday. When using do not eat or drink. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)


SAFETY DATA SHEET

Revision Date: 24.06.2019

Print Date: 27.05.2021

SDS Number: 000000197928

SynPower™ POWER ST.FL Power Steering Fluid

Version: 2.0

VE18320

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection
8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

1-DECENE, DIMER, HYDROGENATED	: End Use: Workers Exposure routes: Inhalation Potential health effects: Acute systemic effects Value: 60 mg/m3Acute toxicity End Use: Consumer use Exposure routes: Inhalation Potential health effects: Acute systemic effects Value: 50 mg/m3Acute toxicity
--	---

8.2 Exposure controls
Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Hand protection

Remarks : Nitrile rubber

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection

: Wear as appropriate:
Impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection

: In the case of vapour formation use a respirator with an approved filter.

SECTION 9: Physical and chemical properties


SAFETY DATA SHEET

Revision Date: 24.06.2019

Print Date: 27.05.2021

SDS Number: 000000197928

SynPower™ POWER ST.FL Power Steering Fluid

Version: 2.0

VE18320

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: dark green
Odour	: characteristic
Odour Threshold	: No data available
pH	: Not applicable
Pour point	: -60 °C
Boiling point/boiling range	: > 300 °C
Flash point	: 160 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: 6,5 %(V)
Lower explosion limit / Lower flammability limit	: 0,6 %(V)
Vapour pressure	: < 0,001 hPa
Relative vapour density	: No data available
Relative density	: No data available
Density	: ca. 0,825 g/cm ³ (20 °C)
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: 235 °C
Decomposition temperature	: No data available
Viscosity	


SAFETY DATA SHEET

Revision Date: 24.06.2019

Print Date: 27.05.2021

SDS Number: 000000197928

SynPower™ POWER ST.FL Power Steering Fluid

Version: 2.0

VE18320

Viscosity, dynamic : No data available

Viscosity, kinematic : 19 mm²/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : No data available

9.2 Other information

Self-ignition : not auto-flammable

SECTION 10: Stability and reactivity
10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Product will not undergo hazardous polymerization.

10.4 Conditions to avoid
Conditions to avoid : excessive heat
Exposure to sunlight.
10.5 Incompatible materials
Materials to avoid : Iron
steel
Strong acids
Strong oxidizing agents
10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11: Toxicological information
11.1 Information on toxicological effects
Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact


SAFETY DATA SHEET

Revision Date: 24.06.2019

Print Date: 27.05.2021

SDS Number: 000000197928

SynPower™ POWER ST.FL Power Steering Fluid

Version: 2.0

VE18320

Ingestion
Acute toxicity

Harmful if inhaled.

Product:

Acute inhalation toxicity : Acute toxicity estimate : 2 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: Calculation method

Components:
1-DECENE, DIMER, HYDROGENATED:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 1,81 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 403
 GLP: yes
 Assessment: The component/mixture is classified as acute inhalation toxicity, category 4.

Acute dermal toxicity : LD50 (Rabbit): > 3.000 mg/kg
 Method: OECD Test Guideline 402
 Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Components:
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:
1-DECENE, DIMER, HYDROGENATED:

Species: Rabbit
 Result: Slight, transient irritation

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.



SAFETY DATA SHEET

Revision Date: 24.06.2019

Print Date: 27.05.2021

SDS Number: 000000197928

SynPower™ POWER ST.FL Power Steering Fluid

Version: 2.0

VE18320

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

1-DECENE, DIMER, HYDROGENATED:

Species: **Rabbit**Result: **No eye irritation**

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Result: **No eye irritation**

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

1-DECENE, DIMER, HYDROGENATED:

Test Type: **Maximisation Test**Species: **Guinea pig**Method: **OECD Test Guideline 406**

Germ cell mutagenicity

Not classified based on available information.

Components:

1-DECENE, DIMER, HYDROGENATED:

Genotoxicity in vitro : Test Type: **Ames test**
 Test species: **Salmonella typhimurium**
 Metabolic activation: **with and without metabolic activation**
 Method: **OECD Test Guideline 471**
 Result: **negative**
 GLP: **yes**

Genotoxicity in vivo : Test Type: **In vivo micronucleus test**
 Test species: **Mouse**
 Method: **OECD Test Guideline 474**
 Result: **negative**
 GLP: **yes**

Carcinogenicity

Not classified based on available information.

Components:

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Carcinogenicity - Assessment : **Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)**

SAFETY DATA SHEET

Revision Date: 24.06.2019

Print Date: 27.05.2021

SDS Number: 000000197928

SynPower™ POWER ST.FL Power Steering Fluid

Version: 2.0

VE18320

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:**1-DECENE, DIMER, HYDROGENATED:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Further information**Product:**

Remarks: Solvents may degrease the skin.

SECTION 12: Ecological information**12.1 Toxicity****Components:****1-DECENE, DIMER, HYDROGENATED**

Toxicity to fish : **LL50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l**
 Exposure time: 96 h
 Test Type: **semi-static test**
 Test substance: **WAF**
 Method: **OECD Test Guideline 203**
 GLP: **yes**

Toxicity to daphnia and other aquatic invertebrates : **EL50 (Daphnia magna (Water flea)): > 1.000 mg/l**
 Exposure time: 48 h
 Test Type: **static test**
 Test substance: **WAF**
 Method: **OECD Test Guideline 202**
 GLP: **yes**

Toxicity to algae : **EL50 (Scenedesmus capricornutum (fresh water algae)): > 1.000 mg/l**
 Exposure time: 72 h
 Test Type: **static test**
 Test substance: **WAF**

SAFETY DATA SHEET

Revision Date: 24.06.2019

Print Date: 27.05.2021

SDS Number: 00000197928

SynPower™ POWER ST.FL Power Steering Fluid

Version: 2.0

VE18320

Method: **OECD Test Guideline 201**
GLP: **yes****12.2 Persistence and degradability****Components:****1-DECENE, DIMER, HYDROGENATED**Biodegradability : Result: **Inherently biodegradable**
Biodegradation: **15 %**
Exposure time: **28 d**
Method: **OECD Test Guideline 301D**
GLP: **yes****12.3 Bioaccumulative potential****Components:****1-DECENE, DIMER, HYDROGENATED**Partition coefficient: n- : log Pow: **> 6,5**
octanol/water**12.4 Mobility in soil**

No data available

12.5 Results of PBT and vPvB assessment**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., May cause long lasting harmful effects to aquatic life.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.


SAFETY DATA SHEET

Revision Date: 24.06.2019

Print Date: 27.05.2021

SDS Number: 000000197928

SynPower™ POWER ST.FL Power Steering Fluid

Version: 2.0

VE18320

Contaminated packaging : Empty remaining contents.
 Dispose of as unused product.
 Empty containers should be taken to an approved waste
 handling site for recycling or disposal.
 Do not re-use empty containers.

SECTION 14: Transport information
14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that : Not applicable
 deplete the ozone layer

Regulation (EC) No 850/2004 on persistent organic : Not applicable
 pollutants

REACH - List of substances subject to authorisation : Not applicable
 (Annex XIV)

**SAFETY DATA SHEET**

Revision Date: 24.06.2019

Print Date: 27.05.2021

SDS Number: 00000197928

SynPower™ POWER ST.FL Power Steering Fluid

Version: 2.0

VE18320

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

The components of this product are reported in the following inventories:

TSCA	: On TSCA Inventory
DSL	All components of this product are on the Canadian DSL
AICS	On the inventory, or in compliance with the inventory
ENCS	Not in compliance with the inventory
KECI	On the inventory, or in compliance with the inventory
IECSC	Not in compliance with the inventory
PICCS	Not in compliance with the inventory
TCSI	Not in compliance with the inventory

Inventories


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information**Further information**

Revision Date: 24.06.2019

		Page: 15
SAFETY DATA SHEET		Revision Date: 24.06.2019
		Print Date: 27.05.2021
		SDS Number: 000000197928
SynPower™ POWER ST.FL Power Steering Fluid		Version: 2.0
VE18320		

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.
H332 Harmful if inhaled.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement


SAFETY DATA SHEET

Revision Date: 24.06.2019

Print Date: 27.05.2021

SDS Number: 000000197928

SynPower™ POWER ST.FL Power Steering Fluid

Version: 2.0

VE18320

PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

ABM : Water Hazard Class for the Netherlands
 ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.
 ADN: Regulation for the Carriage of Dangerous Substances on the Rhine
 CLP : Classification, Labelling and Packaging
 CSA : Chemical Safety Assessment
 CSR : Chemical Safety Report
 DNEL : Derived No Effect Level.
 EINECS : European Inventory of Existing Commercial Chemical Substances.
 ELINCS : European List of Notified Chemical Substances
 PEC : Predicted Effect Concentration
 PEL : Permissible Exposure Limits
 PNEC : Predicted No Effect Concentration
 R-phrase : Risk phrase
 REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals
 RID : Regulation Concerning the International Transport of Dangerous Goods by Rail
 S-phrase: Safety phrase
 WGK : German Water Hazard Class