

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : LHM PLUS
Product code : 32897
Product description : Not available.
Product type : Liquid.
Other means of identification : Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Base oil
Formulation additives, lubricants and greases - Industrial
General use of lubricants and greases in vehicles or machinery - Industrial
General use of lubricants and greases in vehicles or machinery - Professional

Uses advised against

Not applicable.

1.3 Details of the supplier of the safety data sheet

TotalEnergies Lubrifiants
562 Avenue du Parc de L'île
92029 Nanterre Cedex FRANCE
Tél: +33 (0)1 41 35 40 00
Fax: +33 (0)1 41 35 84 71
rm.msds-lubs@totalenergies.com

TotalEnergies Marketing UK Limited
10 Upper Bank Street (19th floor)
Canary Wharf,
London E14 5BF
UNITED KINGDOM
Tel: +44 (0)20 7339 8000
Fax: +44 (0)20 7339 8033
rm.gb-msds@totalenergies.com

H.S.E

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : National Poisons Information Service (NPIS): 111

Supplier

Telephone number : Emergency telephone: +44 1235 239670

Hours of operation : Edit the content of sentence <GB Telephone Number - Supplier - Hours of operation> to define this output

Information limitations : Edit the content of sentence <GB Telephone Number - Supplier - Information limitations> to define this output

**SECTION 1: Identification of the substance/mixture and of the company/
undertaking****SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Product definition** : Mixture**Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**Asp. Tox. 1, H304
Aquatic Chronic 3, H412

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements**Hazard pictograms** :**Signal word** : **Danger****Hazard statements** : H304 - May be fatal if swallowed and enters airways.
H412 - Harmful to aquatic life with long lasting effects.**Precautionary statements**

- General** : P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P103 - Read carefully and follow all instructions.
- Prevention** : P273 - Avoid release to the environment.
- Response** : P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P331 - Do NOT induce vomiting.
- Storage** : P405 - Store locked up.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Contains** : Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics
Distillates (petroleum), hydrotreated light paraffinic
- Supplemental label elements** : Not applicable.
- Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

2.3 Other hazards**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII**

**SECTION 2: Hazards identification**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration $\geq 0,1\%$.

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

Other hazards which do not result in classification : Hazard of slipping on spilt product.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	REACH #: 01-2119826592-36 EC: 934-954-2 CAS: 64742-46-7, 64742-46-7	$\geq 50 - \leq 75$	Asp. Tox. 1, H304	[1]
Distillates (petroleum), hydrotreated light paraffinic	REACH #: 01-2119487077-29 EC: 265-158-7 CAS: 64742-55-8	$\geq 25 - \leq 50$	Asp. Tox. 1, H304	[1]
2,6-di-tert-butylphenol	REACH #: 01-2119490822-33 EC: 204-884-0 CAS: 128-39-2	<1	Skin Irrit. 2, H315 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
tris(methylphenyl) phosphate	REACH #: 01-2119531335-46 EC: 215-548-8 CAS: 1330-78-5	≤ 0.3	Repr. 2, H361 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)	[1]
naphthalene	EC: 202-049-5 CAS: 91-20-3 Index: 601-052-00-2	<0.1	Acute Tox. 4, H302 Carc. 2, H351 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1) See Section 16 for the full text of the H statements declared above.	[1] [2]

Additional information : Mineral oil of petroleum origin Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

**SECTION 3: Composition/information on ingredients**

The EC substance definition and related classification & labelling have been developed in the framework of the Regulation (EC) No 1907/2006 (REACH). The related CAS number* is used for the purpose of the international inventories present in section 15 of the SDS.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. The exposed person may need to be kept under medical surveillance for 48 hours.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed**Over-exposure signs/symptoms**

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
dryness
cracking
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : carbon monoxide
carbon dioxide
nitrogen oxides
phosphorus oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : Specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**SECTION 6: Accidental release measures**

Large spill : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limits**

Product/substance	Exposure limit values
naphthalene	EU OEL (Europe, 10/2019). Notes: list of indicative occupational exposure limit values TWA: 10 ppm 8 hours. TWA: 50 mg/m ³ 8 hours.



SECTION 8: Exposure controls/personal protection

Reportable hazardous constituent(s) contained in UVCB- and/or multi-constituent substance(s) complying with the classification criteria and/or with an exposure limit (OEL)

No exposure limit value known.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Advisory OEL : Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined)

DNELs/DMELs

Product/substance	Type	Exposure	Value	Population	Effects
Distillates (petroleum), hydrotreated light paraffinic	DNEL	Long term Inhalation	5.4 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	1.2 mg/m ³	General population	Local
	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m ³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
2,6-di-tert-butylphenol	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local
	DNEL	Long term Oral	6.75 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	11.25 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	20.9 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	70.61 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	6.75 mg/kg bw/day	General population	Systemic
tris(methylphenyl) phosphate	DNEL	Long term Dermal	6.75 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.47 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	3.33 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	1.11 mg/m ³	Workers	Systemic
	DNEL	Short term Dermal	74 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	16 mg/cm ²	Workers	Local
	DNEL	Long term Dermal	1.67 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.06 mg/m ³	General population	Systemic
DNEL	Long term Oral	0.03 mg/cm ²	General population	Systemic	



SECTION 8: Exposure controls/personal protection

naphthalene	DNEL	Short term Dermal	37 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	0.28 mg/m ³	General population	Systemic
	DNEL	Short term Oral	157.5 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	8 mg/cm ²	General population	Local
	DNEL	Long term Oral	0.02 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.03 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	0.15 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.18 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	0.41 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	3.57 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	25 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	25 mg/m ³	Workers	Systemic

PNECs

Product/substance	Compartment Detail	Value	Method Detail
2,6-di-tert-butylphenol	Fresh water	700 ng/l	-
	Marine water	70 ng/l	-
	Fresh water sediment	317 µg/kg dwt	-
	Marine water sediment	31.7 µg/kg dwt	-
	Soil	697 µg/kg dwt	-
	Sewage Treatment Plant	10 mg/l	-
	tris(methylphenyl) phosphate	Secondary Poisoning	60 mg/kg
Fresh water		0.000146 mg/l	-
Marine water		0.0000146 mg/l	-
Fresh water sediment		0.0404 mg/kg dwt	-
Marine water sediment		0.00404 mg/kg dwt	-
Soil		0.00000317 mg/kg dwt	-
Sewage Treatment Plant		100 mg/l	-

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**SECTION 8: Exposure controls/personal protection**

- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. EN 166
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Hydrocarbon-proof gloves
nitrile rubber
Fluorinated rubber
- Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
- In case of prolonged contact with the product, it is recommended to wear gloves complying with ISO 21420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Ensure adequate ventilation and check that a safe, breathable atmosphere is present before entry into confined spaces. In case of inadequate ventilation wear respiratory protection: Type A/P1. Warning! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature (20°C / 68°F) and pressure (1013 hPa) unless otherwise indicated

9.1 Information on basic physical and chemical properties**Appearance**

- Physical state** : Liquid.
- Colour** : Fluorescent yellowish-green
- Odour** : Characteristic.
- Odour threshold** : Not available.

**SECTION 9: Physical and chemical properties**

Melting point/freezing point	: <input checked="" type="checkbox"/> Technically not possible to measure
Initial boiling point and boiling range	: <input checked="" type="checkbox"/> 316°C (>600.8°F) [ISO 3405]
Flammability (solid, gas)	: <input checked="" type="checkbox"/> Not applicable.
Upper/lower flammability or explosive limits	: <input checked="" type="checkbox"/> Lower: 7% Upper: 9%
Flash point	: Open cup: 105°C (221°F) [ASTM D 93]
Auto-ignition temperature	: Not available.
Decomposition temperature	: <input checked="" type="checkbox"/> Not applicable.
pH	: Not applicable. <input checked="" type="checkbox"/> Product is non-soluble (in water).
Viscosity	: Kinematic (40°C): 18 mm ² /s [ISO 3104]
Solubility(ies)	:

Media	Result
<input checked="" type="checkbox"/> water	Not soluble

Miscible with water	: No.
Partition coefficient: n-octanol/ water	: Not applicable.
Vapour pressure	: <input checked="" type="checkbox"/> 0.013 kPa (<0.1 mm Hg) [room temperature] Not applicable. [50°C (122°F)]
Relative density	: <input checked="" type="checkbox"/> 0.831 to 0.841 [ISO EN 3675]
Density	: <input checked="" type="checkbox"/> 0.831 to 0.841 g/cm ³ [15°C (59°F)] [ISO EN 3675]
Vapour density	: <input checked="" type="checkbox"/> 2 [Air = 1]
Particle characteristics	
Median particle size	: Not applicable.

9.2 Other information

SECTION 10: Stability and reactivity

10.1 Reactivity	: <input checked="" type="checkbox"/> No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).
10.3 Possibility of hazardous reactions	: <input checked="" type="checkbox"/> Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: <input checked="" type="checkbox"/> Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
10.5 Incompatible materials	: <input checked="" type="checkbox"/> Strong oxidising agents
10.6 Hazardous decomposition products	: <input checked="" type="checkbox"/> carbon monoxide carbon dioxide nitrogen oxides phosphorus oxides

**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Product/substance	Result	Species	Dose	Exposure	Test
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	LC50 Inhalation Dusts and mists	Rat - Male, Female	>5266 mg/m ³	4 hours	OECD 403 Read across
	LD50 Dermal	Rabbit - Male, Female	>3160 mg/kg	-	OECD 402 Read across
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-	OECD 401 Read across
Distillates (petroleum), hydrotreated light paraffinic	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours	OECD 403
	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 420
2,6-di-tert-butylphenol	LD50 Dermal	Rabbit	>5000 mg/kg	-	-
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-	OECD 401 401
tris(methylphenyl) phosphate	LC50 Inhalation Dusts and mists	Rat	5.5 mg/l	4 hours	-
	LC50 Inhalation Vapour	Rat	21 mg/l	4 hours	-
	LD50 Dermal	Rabbit	10000 mg/kg	-	-
	LD50 Oral	Rat	3 g/kg	-	-
naphthalene	LD50 Oral	Rat	3700 mg/kg	-	-
	LD50 Dermal	Rat	16001 mg/kg	-	OECD 402
	LD50 Oral	Rat	533 mg/kg	-	OECD 401

Conclusion/Summary : Based on available data, the classification criteria are not met.

Acute toxicity estimates

Product/substance	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
tris(methylphenyl) phosphate	3000	10000	N/A	21	5.5
naphthalene	533	16001	N/A	N/A	N/A

Irritation/Corrosion

Product/substance	Result	Species	Score	Exposure	Test
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	Eyes - Oedema of the conjunctivae	Rabbit	0.3	24 hours	OECD 405 Read across
	Skin - Erythema/Eschar	Rabbit	0.3	-	404 Read across
2,6-di-tert-butylphenol	Eyes - Cornea opacity	Rabbit	0	-	OECD 405 405
	Skin - Moderate irritant	Rat	-	4 hours 0.5 MI	OECD 404 404
tris(methylphenyl) phosphate	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	495 mg	-

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Eyes : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

**SECTION 11: Toxicological information****Sensitisation**

Product/substance	Route of exposure	Species	Result
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics 2,6-di-tert-butylphenol	skin	Guinea pig	Not sensitizing
	skin	Guinea pig	Not sensitizing

Conclusion/Summary**Skin**

: Based on available data, the classification criteria are not met.

Respiratory

: Based on available data, the classification criteria are not met.

Mutagenicity

Product/substance	Test	Experiment	Result
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	OECD 471 Read across	Experiment: In vitro Subject: Bacteria	Negative
	OECD 473 Read across	Experiment: In vitro Subject: Mammalian-Animal	Negative
	OECD 476 Read across	Experiment: In vitro Subject: Mammalian-Animal	Negative
	OECD 474 Read across	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative
	OECD 475 Read across	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative
	OECD 483 Read across	Experiment: In vivo Subject: Mammalian-Animal Cell: Germ	Negative
2,6-di-tert-butylphenol	OECD 471 471	Experiment: In vitro Subject: Bacteria	Negative
	OECD 473	Experiment: In vitro Subject: Mammalian-Animal Cell: Somatic	Negative
	OECD 476	Experiment: In vitro Subject: Mammalian-Animal Cell: Somatic	Negative

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Carcinogenicity**Conclusion/Summary**

: Based on available data, the classification criteria are not met.

Reproductive toxicity

Product/substance	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
2,6-di-tert-butylphenol	-	Negative	Negative	Rat - Male, Female	Oral	-

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Teratogenicity**Conclusion/Summary**

: Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.



SECTION 11: Toxicological information

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Not available.

Conclusion/Summary : Based on available data, the classification criteria are not met.

Aspiration hazard

Product/substance	Result
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	ASPIRATION HAZARD - Category 1
Distillates (petroleum), hydrotreated light paraffinic	ASPIRATION HAZARD - Category 1

Conclusion/Summary : Based on available data, the classification criteria are met.

Information on likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation.
- Ingestion** : May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
dryness
cracking
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

**SECTION 11: Toxicological information**

Product/substance	Result	Species	Dose	Exposure
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics 2,6-di-tert-butylphenol	Sub-chronic NOAEL Oral	Rat - Male, Female	>5000 mg/kg	13 weeks; 7 days per week
	Sub-acute NOAEL Inhalation Vapour	Rat - Male, Female	>10400 mg/m ³	90 days; 5 days per week
	Sub-chronic NOAEL Oral	Rat - Male, Female	100 mg/kg NOAEL	5 days

Conclusion/Summary	: Not available.
General	: <input checked="" type="checkbox"/> No known significant effects or critical hazards.
Carcinogenicity	: <input checked="" type="checkbox"/> No known significant effects or critical hazards.
Mutagenicity	: <input checked="" type="checkbox"/> No known significant effects or critical hazards.
Reproductive toxicity	: <input checked="" type="checkbox"/> No known significant effects or critical hazards.

11.2 Information on other hazards**11.2.1 Endocrine disrupting properties**

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

Harmful to aquatic life with long lasting effects.

12.1 Toxicity

Product/substance	Result	Species	Exposure	Test
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	Acute EC50 10000 mg/l	Algae - Skeletonema costatum	72 hours	ISO 10253
	Acute EC50 3193 mg/l	Daphnia - Acartia tonsa	48 hours	ISO 14669
	Acute LC50 1028 mg/l	Fish	96 hours	-
	Chronic NOELR >1000 mg/l	Daphnia - Daphnia Magna	21 days	OECD 211
Distillates (petroleum), hydrotreated light paraffinic	Chronic NOELR >1000 mg/l	Fish - Oncorhynchus mykiss	28 days	-
	Acute EC50 >100 mg/l	Algae - Pseudokirchnerella subcapitata	48 hours	OECD 201
	Acute EC50 >10000 mg/l	Daphnia - Daphnia magna	48 hours	OECD 202
	Chronic NOEL 10 mg/l	Daphnia - Daphnia magna	21 days	OECD 211
2,6-di-tert-butylphenol	Chronic NOEL >1000 mg/l	Fish - Oncorhynchus mykiss	21 days	-
	Acute EC50 1.2 mg/l	Algae	72 hours	-
	Acute EC50 0.45 mg/l	Daphnia - Daphnia magna	48 hours	-
	Acute LC50 1 mg/l	Fish	96 hours	-
tris(methylphenyl) phosphate	Chronic NOEC 0.035 mg/l	Daphnia - Daphnia magna	21 days	-
	Chronic NOEC 0.3 mg/l	Fish	28 days	-
	Acute EC50 0.4 mg/l	Algae - Desmodesmus subspicatus	72 hours	-



SECTION 12: Ecological information

naphthalene	Acute EC50 290 µg/l Fresh water	Algae - Stephanodiscus hantzschii - Exponential growth phase	96 hours	-
	Acute EC50 170 µg/l Fresh water	Fish - Gasterosteus aculeatus	96 hours	-
	Acute LC50 0.09 mg/l Fresh water	Daphnia - Daphnia magna - Instar	48 hours	US EPA
	Acute LC50 0.14 mg/l Fresh water	Daphnia - Daphnia magna	48 hours	-
	Acute LC50 0.6 mg/l Fresh water	Fish	96 hours	-
	Chronic NOEC 3.2 µg/l Fresh water	Fish - Gasterosteus aculeatus - Egg	35 days	-
	Chronic NOEC 0.01 mg/l Fresh water	Fish - Oncorhynchus mykiss	28 days	-
	Acute EC50 1.6 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours	-
	Acute LC50 2350 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours	-
	Acute LC50 2160 µg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours	OECD 202
	Acute LC50 213 µg/l Fresh water	Fish - Melanotaenia fluviatilis - Larvae	96 hours	-
	Chronic NOEC 0.5 mg/l Marine water	Crustaceans - Uca pugnax - Adult	3 weeks	-
Chronic NOEC 0.37 mg/l Fresh water	Fish - Oncorhynchus kisutch	40 days	-	

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Product/substance	Test	Result	Dose	Inoculum
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	OECD 306	74 % - Readily - 28 days	-	-

Conclusion/Summary : Not available.

Product/substance	Aquatic half-life	Photolysis	Biodegradability
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	-	-	Readily
2,6-di-tert-butylphenol	-	-	Not readily
tris(methylphenyl) phosphate	-	-	Readily

12.3 Bioaccumulative potential

Product/substance	LogP _{ow}	BCF	Potential
2,6-di-tert-butylphenol	4.48	660	high
tris(methylphenyl) phosphate	5.93	144	low
naphthalene	3.4	36.5 to 168	low

12.4 Mobility in soil

**SECTION 12: Ecological information**

- Soil/water partition coefficient (K_{oc})** : Not available.
- Mobility** : Not available.
- Mobility in soil** : Given its physical and chemical characteristics, the product generally shows low soil mobility. The product is insoluble and floats on water. Loss by evaporation is limited.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods**Product**

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

- Hazardous waste** : Yes.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used. The following Waste Codes are only suggestions: 13 01 10*

Packaging

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

- Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	ICAO/IATA
14.1 UN number or ID number	Not regulated.	9006	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,6-di-tert-butylphenol, tris (methylphenyl) phosphate)	-	-
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	Yes.	No.	No.

Additional information

ADN : The product is only regulated as a dangerous good when transported in tank vessels.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****UK (GB) /REACH****Annex XIV - List of substances subject to authorisation****Annex XIV**

None of the components are listed.

Substances of very high concern

None of the components are listed.

Ozone depleting substances

Not listed.

Prior Informed Consent (PIC)

Not listed.

**SECTION 15: Regulatory information****Persistent Organic Pollutants**

Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Seveso Directive

This product is not controlled under the Seveso Directive.

EU regulations

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

DIRECTIVE 2008/68/EC related on the inland transport of dangerous goods

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

International regulations**Chemical Weapon Convention List Schedules I, II & III Chemicals**

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

- | | |
|---|--|
| Australia inventory (AIC) | : At least one component is not listed. |
| Canada inventory | : At least one component is not listed in DSL but all such components are listed in NDSL. |
| China inventory (IECSC) | : At least one component is not listed. |
| Europe inventory | : <input checked="" type="checkbox"/> All components are listed or exempted. |
| Japan inventory | : Japan inventory (CSCL) : At least one component is not listed.
Japan inventory (ISHL) : Not determined. |
| New Zealand Inventory of Chemicals (NZIoC) | : At least one component is not listed. |
| Philippines inventory (PICCS) | : At least one component is not listed. |
| Korea inventory (KECI) | : At least one component is not listed. |

**SECTION 15: Regulatory information**

Taiwan Chemical Substances Inventory (TCSI)	: At least one component is not listed.
Thailand inventory	: Not determined.
Turkey inventory	: Not determined.
United States inventory (TSCA 8b)	: All components are listed or exempted.
Vietnam inventory	: Not determined.

The information stated in this section relates solely to the conformity of the chemical product with the countries Inventories. The information used to confirm the inventory status of this product may be based on additional data to the chemical composition shown in Section 3. Other regulations may apply for importation or marketing authorizations.

15.2 Chemical safety assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms :

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DNEL = Derived No Effect Level
- DMEL = Derived Minimal Effect Level
- EUH statement = CLP-specific Hazard statement
- N/A = Not available
- PBT = Persistent, Bioaccumulative and Toxic
- vPvB = Very Persistent and Very Bioaccumulative
- PNEC = Predicted No Effect Concentration
- LC50 = Median lethal concentration
- LD50 = Median lethal dose
- OEL = Occupational Exposure Limit
- VOC = Volatile Organic Compound
- UVCB Substance of unknown or Variable composition, Complex reaction products or Biological material
- NOEC No Observed Effect Concentration
- QSAR = Quantitative Structure–Activity Relationship

Procedure used to derive the classification

Classification	Justification
Asp. Tox. 1, H304 Aquatic Chronic 3, H412	Calculation method Calculation method

Full text of abbreviated H statements

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications

**SECTION 16: Other information**

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Carc. 2	CARCINOGENICITY - Category 2
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2

Date of printing : 2023/03/06

Date of issue/ Date of revision : 2023/03/06

Date of previous issue : 2022/03/03

Version : 2

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition : Mixture
Code : 32897
Product name : LHM PLUS

Section 1 - Title

Short title of the exposure scenario : Formulation additives, lubricants and greases - Industrial
List of use descriptors : **Identified use name:** Formulation additives, lubricants and greases - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15
Sector of end use: SU03, SU10
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02
Environmental contributing scenarios :
Health Contributing scenarios :

Processes and activities covered by the exposure scenario	: Industrial formulation of lubricant additives, lubricants and greases. Includes material transfers, mixing, large and small scale packing, sampling, maintenance.
---	---

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1: ATIEL-ATC SPERC 2.Ai-I.v1	
Amounts used	: Volume manufactured/imported (tonnes/year) : 1.00E+04 Fraction of EU tonnage used in region : 0.1 Fraction of Regional tonnage used locally : 0.1
Frequency and duration of use	: Emission days (days per year) : 300
Environment factors not influenced by risk management	: Local freshwater dilution factor : 10 Local marine water dilution factor : 100
Other conditions affecting environmental exposure	: Negligible wastewater emissions as process operates without water contact. Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements) : 5.00E-05 Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant): 5.00E-12 Release fraction to soil from process (after typical onsite RMMs): 0
Technical conditions and measures at process level (source) to prevent release	: Common practices vary across sites thus conservative process release estimates used.
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil	: Treat air emission to provide a typical removal efficiency of (%) : 70 Prevent discharge of undissolved substance to or recover from onsite wastewater. User sites are assumed to be provided with oil/water separators and for waste water to be discharged via public sewer system.
Organisational measures to prevent/limit release from site	: Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.

Date of issue/Date of revision	: 3/22/2021
--------------------------------	-------------

21/26

Conditions and measures related to sewage treatment plant	: Estimated substance removal from wastewater via domestic sewage treatment (%): (%) : 0.10 Assumed domestic sewage treatment plant flow (m ³ /d) : 2.00E+03 Maximum allowable site tonnage (M _{safe}) based on release following total wastewater treatment removal (kg/day) : 210 932
Conditions and measures related to external treatment of waste for disposal	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Contributing scenario controlling worker exposure for 2:

No exposure assessment presented for human health.

Conditions and measures related to personal protection, hygiene and health evaluation

Section 3 - Exposure estimation and reference to its source

Website: : Not applicable.

Exposure estimation and reference to its source - Environment: 1:

Exposure assessment (environment): : Used ECETOC TRA model.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 2:

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction .
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction .

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition : Mixture
Code : 32897
Product name : LHM PLUS

Section 1 - Title

Short title of the exposure scenario : General use of lubricants and greases in vehicles or machinery - Industrial

List of use descriptors : **Identified use name:** General use of lubricants and greases in vehicles or machinery - Industrial
Process Category: PROC01, PROC02, PROC08b, PROC09
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC04, ERC07

Environmental contributing scenarios :

Health Contributing scenarios :

Processes and activities covered by the exposure scenario	: Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.
---	---

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

ATIEL-ATC SPERC 4.Bi.v1

Amounts used : Volume manufactured/imported (tonnes/year) : 2.63E+03

Fraction of EU tonnage used in region : 0.1
Fraction of Regional tonnage used locally : 0.1

Frequency and duration of use : Emission days (days per year) : 300

Environment factors not influenced by risk management : Local freshwater dilution factor : 10
Local marine water dilution factor : 100

Other conditions affecting environmental exposure : Negligible wastewater emissions as process operates without water contact.

Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements) : 5.00E-05
Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant): 5.00E-12
Release fraction to soil from process (after typical onsite RMMs): 0

Technical conditions and measures at process level (source) to prevent release : Common practices vary across sites thus conservative process release estimates used.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil : Prevent discharge of undissolved substance to or recover from onsite wastewater. User sites are assumed to be provided with oil/water separators and for waste water to be discharged via public sewer system.

Organisational measures to prevent/limit release from site : Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.

Date of issue/Date of revision : 3/22/2021

23/26

Conditions and measures related to sewage treatment plant	: Estimated substance removal from wastewater via domestic sewage treatment (%): (%) : 0.1 Assumed domestic sewage treatment plant flow (m ³ /d) : 2.00E+03 Maximum allowable site tonnage (M _{Safe}) based on release following total wastewater treatment removal (kg/day) : 55 500
Conditions and measures related to external treatment of waste for disposal	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Contributing scenario controlling worker exposure for 2:

No exposure assessment presented for human health.

Conditions and measures related to personal protection, hygiene and health evaluation

Section 3 - Exposure estimation and reference to its source

Website: : Not applicable.

Exposure estimation and reference to its source - Environment: 1:

Exposure assessment (environment): : Used ECETOC TRA model.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 2:

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction .
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction .

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.

Annex to the extended Safety Data Sheet (eSDS)

Professional

Identification of the substance or mixture

Product definition : Mixture
Code : 32897
Product name : LHM PLUS

Section 1 - Title

Short title of the exposure scenario : General use of lubricants and greases in vehicles or machinery - Professional

List of use descriptors : **Identified use name:** General use of lubricants and greases in vehicles or machinery - Professional
Process Category: PROC01, PROC02, PROC08a, PROC08b, PROC20
Sector of end use: SU22
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC09a, ERC09b

Environmental contributing scenarios :

Health Contributing scenarios :

Processes and activities covered by the exposure scenario	: Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.
---	---

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1: ATIEL-ATC SPERC 9.Bp.v1	
Amounts used	: Volume manufactured/imported (tonnes/year) : 5.39E+03 Fraction of EU tonnage used in region : 0.1 Fraction of Regional tonnage used locally : 0.1
Frequency and duration of use	: Emission days (days per year) : 365
Environment factors not influenced by risk management	: Local freshwater dilution factor : 10 Local marine water dilution factor : 100
Other conditions affecting environmental exposure	: Negligible wastewater emissions as process operates without water contact. Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements) : 5.00E-04 Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant): 5.00E-04 Release fraction to soil from process (after typical onsite RMMs): 1.00E-03
Technical conditions and measures at process level (source) to prevent release	: Common practices vary across sites thus conservative process release estimates used.
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil	: Prevent discharge of undissolved substance to or recover from onsite wastewater.
Organisational measures to prevent/limit release from site	: Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.
Date of issue/Date of revision	: 3/22/2021

Conditions and measures related to sewage treatment plant	: Estimated substance removal from wastewater via domestic sewage treatment (%): (%) : 0.10 Assumed domestic sewage treatment plant flow (m ³ /d) : 2.00E+03 Maximum allowable site tonnage (M _{Safe}) based on release following total wastewater treatment removal (kg/day) : 560
Conditions and measures related to external treatment of waste for disposal	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Contributing scenario controlling worker exposure for 2:

No exposure assessment presented for human health.

Conditions and measures related to personal protection, hygiene and health evaluation

Section 3 - Exposure estimation and reference to its source

Website:	: Not applicable.
-----------------	-------------------

Exposure estimation and reference to its source - Environment: 1:	
Exposure assessment (environment):	: Used ECETOC TRA model.
Exposure estimation and reference to its source	: Not available.

Exposure estimation and reference to its source - Workers: 2:	
Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction .
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction .

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.