

According to Regulation (EU) No 2015/830

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

: SHELL DIESEL ADDITIVE Product name

Product code : CRX724, BT82I

1.2. Relevant identified uses of the substance or mixture and uses advised against

Application : SU21 Consumer product. PC0 Other. Engine maintenance.

1.3. Details of the supplier of the safety data sheet

Supplier : Kemetyl Polska Sp. z o. o.

Al. Jerozolimskie 146

02-305 Warszawa, Poland

Telephone : +48 22 822 5390 E-mail : msds@kemetyl.com Website : www.kemetyl.com

1.4. Emergency telephone number

EMERGENCY TELEPHONE NUMBER, for DOCTORS/FIRE BRIGADE/POLICE only:

PL - Telephone : +48 22 822 5390 (During office hours only)

SECTION 2 HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP classification : Aspiration hazard, category 1. Hazardous to the aquatic environment — Chronic category 3.

(1272/2008/EC)

Human health hazards : May be fatal if swallowed and enters airways. Repeated exposure may cause skin dryness or

cracking.

Physical/chemical hazards : Not classified as dangerous according to statutory EC-Directives. Combustible.

Environmental hazards : Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements (1272/2008/EC):

Hazard pictograms



Signal word : Danger

H- and P-phrases : H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

P101 If medical advice is needed, have product container or label at hand.

Keep out of reach of children. P102

IF SWALLOWED: Immediately call a POISON CENTER/doctor. P301+P310

Do NOT induce vomiting. P331

P501 Dispose of contents/container to an official chemical waste depot.

Product name : Shell Diesel Additive Page 1/11 Date of issue : 2018-05-15 Replaces issue dated **INFO CARE SDS**



According to Regulation (EU) No 2015/830

Labelling of packagings where the contents do not exceed 125 ml and it is technically impossible to list all phrases:

Hazard pictograms

Signal word : Danger

H- and P-phrases : H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P501 Dispose of contents/container to an official chemical waste depot.

Additional labelling (for all packaging sizes)

: Contains: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics; Hydrocarbons,

C10, aromatics, <1% naphthalene.

Other information : According to regulation (EC) 1272/2008, Annex II, part 3, the packaging of this product shall carry a

tactile warning of danger and a child-resistant fastening.

2.3. Other hazards

Other information : Does not contain PBT or vPvB substances in concentrations higher than 0,1%.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.2. Mixtures

Product description : Mixture. Information on hazardous substances:

Substance name	Concentration (w/w) (%)	CAS nr.	EC number	Remark	REACH nr.
2-Ethylhexan-1-ol	0,1 - < 1	104-76-7	203-234-3		01-2119487289-20
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	> 75	<u></u>	918-481-9		01-2119457273-39
Hydrocarbons, C10, aromatics, <1% naphthalene	1 - < 2,5		918-811-1		01-2119463583-34
Naphthalene	0,1 - < 0,25	91-20-3	202-049-5	Ī	

Substance name	Hazard Class	H-phrases	Pictograms	
2-Ethylhexan-1-ol	Acute Tox. 4; Eye Irrit.	H315; H319; H332;	GHS07	
	2; STOT SE 3; Skin	H335		
	Irrit. 2			
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Asp. Tox. 1	H304; EUH066	GHS08	
Hydrocarbons, C10, aromatics, <1%	Aquatic Chronic 2; Asp.	H304; H336; H411;	GHS07; GHS08;	
naphthalene	Tox. 1; STOT SE 3	EUH066	GHS09	
Naphthalene	Acute Tox. 4; Aquatic	H302; H351; H400;	GHS07; GHS08;	M (acute) = 1
	Acute 1; Aquatic	H410	GHS09	
	Chronic 1; Carc. 2			

Occupational exposure limit(s), if relevant, are listed in section 8.

Product name : Shell Diesel Additive Page 2/11
Date of issue : 2018-05-15 Replaces issue dated : --- INFO CARE SDS



According to Regulation (EU) No 2015/830

Reference is made to chapter 16 for full text of each relevant H phrase.

SECTION 4 FIRST-AID MEASURES

4.1. Description of first aid measures

First aid measures

Inhalation : Move victim into fresh air. Consult a doctor if victim feels unwell.

Skin contact : Take off contaminated clothing. Wash off skin with plenty of water and soap before product dries up.

Consult a doctor if irritation persists.

Eye contact : Wash out with (lukewarm) water. Remove contact lenses. Consult a doctor if irritation persists. Ingestion : Do not induce vomiting. Give nothing to drink. Do rinse the mouth. As necessary give 1 or 2

soupspoons of laxative (sodium sulphate). Never give anything by mouth to an unconscious

person. Consult a doctor immediately if victim feels unwell.

4.2. Most important symptoms and effects, both acute and delayed

Effects and symptoms

Inhalation : May cause headache, dizziness and a feeling of sickness. Skin contact : Repeated exposure may cause skin dryness or cracking.

Eye contact : May cause stinging of eyes and redness.

Ingestion : May cause a feeling of sickness, vomiting and diarrhoea. May cause lung damage, sore throat and

lack of breath.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians : None known.

SECTION 5 FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Suitable : Carbondioxide (CO2). Foam. Dry chemical. Water fog.

Not suitable : Water jet.

5.2. Special hazards arising from the substance or mixture

Special exposure hazards : Will float on water and can be reignited.

Hazardous thermal : Carbon monoxide may be evolved if incomplete combustion occurs.

decomposition products

5.3. Advice for firefighters

Special protective : Use adequate respiratory equipment in case of insufficient ventilation.

equipment for fire-fighters

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions : Danger of slipping. Clean up spills immediately. Wear shoes with non-slip soles. Avoid contact with

spilled or released material. Vapours are heavier than air. Build up (of gasses) in low areas involves

risk of suffocation.

6.2. Environmental precautions

Product name : Shell Diesel Additive Page 3/11
Date of issue : 2018-05-15 Replaces issue dated : --- INFO CARE SDS



According to Regulation (EU) No 2015/830

Environmental precautions: Avoid release of product into sewers, surface water and/or ground water. In case of large spills:

contain with dike. Waste product should not be allowed to contaminate soil or water.

Other information : Notify authorities if any exposure to the general public or the environment occurs or is likely to

occur.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Collect spilled material in containers. Absorb residues in sand or other inert material. Dispose at an

authorised waste collection point. Wash away remainder with plenty of water and soap.

6.4. Reference to other sections

Reference to other sections: See also section 8.

SECTION 7 HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling : Handle in accordance with good occupational hygiene and safety practices in well-ventilated areas.

Keep away from sources of ignition — No smoking. Do not breathe vapour. Avoid contact with skin

and eyes. Avoid splashing. Wear protective clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage : Keep in a cool, dry and well-ventilated place (< 35 °C). Keep away from oxidizing agents. Keep

away from food, drink and animal feedingstuffs.

Recommended packaging : Keep only in the original container.

Non recommended

packaging

: PE and PP.

7.3. Specific end use(s)

Use : Use only as directed.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure

limits

: Occupational exposure limits have not been established for this product. Derived no-effect levels (DNEL) have not been established for this product. Predicted no-effect concentrations (PNEC) have

not been established for this product.

Workplace exposure limits (mg/m³):

Chemical name	Country	TWA 8 hour	STEL 15 min	Comments	Source
		(mg/m3)	(mg/m3)		
1,2,4-trimethylbenzene	EC	100	-	-	
1,2,4-trimethylbenzene	GB	125	-	-	
2-Ethylhexan-1-ol		5,42	-	SCOEL (2011)	
Hydrocarbons, C10-C13, n-alkanes,		1200	-	-	CEFIC-HSPA
isoalkanes, cyclics, < 2% aromatics					
Hydrocarbons, C10, aromatics, <1%		100	-	CEFIC-HSPA	
naphthalene					
Naphthalene	EC	50	-	-	

Derived no-effect level (DNEL) for workers:

Observational reservation	Davida af	DNEL -1		DNEL laws tawns	
Chemical name	Route of	DNEL, short-ter	m	DNEL, long-term	
	exposure				
		Local effect	Systemic effect	Local effect	Systemic effect

Product name : Shell Diesel Additive Page 4/11

Date of issue : 2018-05-15 Replaces issue dated : --- INFO CARE SDS



According to Regulation (EU) No 2015/830

Kemety

2-Ethylhexan-1-ol	Inhalation	106,4 mg/m3		53,2 mg/m3
	Dermal			23 mg/kg bw/day
Hydrocarbons, C10, aromatics, <1% naphthalene	Dermal			12,5 mg/kg bw/day
	Inhalation			151 mg/m3
Naphthalene	Dermal			3,57 mg/kg bw/day
	Inhalation		25 mg/m3	25 mg/m3

Derived no-effect level (DNEL) for consumers:

Chemical name	Route of	DNEL, short-term		DNEL, long-term	
	exposure				
	•	Local effect	Systemic effect	Local effect	Systemic effect
2-Ethylhexan-1-ol Hydrocarbons, C10, aromatics, <1% naphthalene	Inhalation Dermal Oral Oral	53,2 mg/m3			2,3 mg/m3 11,4 mg/kg bw/day 1,1 mg/kg bw/day 7,5 mg/kg bw/day
,	Inhalation Dermal				32 mg/m3 7,5 mg/kg bw/day

Predicted no-effect concentration (PNEC):

Chemical name	Route of exposure	Fresh water	Marine water	
2-Ethylhexan-1-ol	Water	0,017 mg/l	0,0017 mg/l	
	Sediment	0,28 mg/kg	0,028 mg/kg	
	Intermittent water			0,17 mg/l
	STP			10 mg/l
	Soil			0,047 mg/kg
	Oral			55 mg/kg food
Naphthalene	Water	0,0024 mg/l	0,0024 mg/l	
	Sediment	0,0672 mg/kg	0,0672 mg/kg	
	Intermittent water			0,02 mg/l
	STP			2,9 mg/l
	Soil			0,0533 mg/kg

8.2. Exposure controls

Engineering measures : Use only in well-ventilated areas. Comply with standard precautionary measures for working with

chemicals.

Hygienic measures : When using do not eat, drink or smoke.

Personal protective equipment:

The efficiency of personal protective equipment depends among other things on temperature and degree of ventilation. Always get professional advice for the particular local situation.

Body protection : Use of specific protective industrial clothing is not required under normal conditions of use. In

case of large scale exposure wear suitable protective clothing, overalls or suit, and similar boots.

Suitable material: nitril. Indication of permeation breakthrough time: 6 hours.

Respiratory protection : Take care of sufficient ventilation. Wear suitable respiratory protection in case of large scale

exposure. Suitable: gas filter type A (brown), class I or higher on e.g. a facemask in accordance

with EN 140.

Hand protection : Under normal conditions of use specific gloves are not required. Wear appropriate gloves in case of

frequent or prolonged use and in case of large scale exposure. Suitable material: nitril. \pm 0,5 mm.

Indication of permeation breakthrough time: 6 hours.

Eye protection : Wear appropriate safety glasses when there is danger of possible eye contact.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Product name : Shell Diesel Additive Page 5/11
Date of issue : 2018-05-15 Replaces issue dated : --- INFO CARE SDS



According to Regulation (EU) No 2015/830

Kemetyl

9.1. Information on basic physical and chemical properties

Appearance : Liquid.
Colour : Colourless.
Odour : Characteristic.
Odour threshold : Not known.

pH : Not applicable. Waterfree product.

Solubility in water : Not soluble. Partition coefficient (n-oc- : Not known.

tanol/water)

Flash point : 64 °C Closed Cup (ISO 2719, EN 11, DIN 51758, ASTM D 93)

Flammability (solid, gas) : Not applicable. Liquid. See flashpoint.

Auto ignition temperature : > 200 °C
Boiling point/boiling range : 179 °C
Melting point/melting range : < -20 °C

Explosive properties : None known. Does not contain explosives.

Explosion limits (% in air) : 0,7 - 6

Oxidising properties : Not applicable. Does not contain oxidizing substances.

Decomposition temperature : Not applicable. Viscosity (20°C) : Not known. Viscosity (40°C) : < 20 mm2/sec

Vapour pressure (20°C) : 90 Pa

Vapour density $(20^{\circ}C)$: > 1 (air = 1)

Relative density (20°C) : 0,8 g/ml

Evaporation rate : 0,04 (n-butyl acetate = 1)

SECTION 10 STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity : See sub-sections below.

10.2. Chemical stability

Stability : Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactivity : No other hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid : See section 7.

10.5. Incompatible materials

Materials to avoid : Keep away from oxidizing agents.

10.6. Hazardous decomposition products

Hazardous decomposition : Not known.

products

SECTION 11 TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

No toxicological research has been carried out on this product.

Product name : Shell Diesel Additive Page 6/11
Date of issue : 2018-05-15 Replaces issue dated : --- INFO CARE SDS



According to Regulation (EU) No 2015/830

Kemetyl

Inhalation

Acute toxicity : Calculated LC50: > 5,621 mg/l. Ingredients of unknown toxicity: < 1 %. ATE: > 5 mg/l. Low

toxicity. Not classified - based on available data, the classification criteria are not met. May cause

headache, dizziness and a feeling of sickness.

Corrosion/irritation : Not classified - based on available data, the classification criteria are not met.

The discount of the state of th

Sensitisation : Does not contain substances classified as respiratory sensitiser. Not classified - based on available

data, the classification criteria are not met.

Carcinogenicity : Not expected to be carcinogenic. Not classified - based on available data, the classification criteria

are not met.

Mutagenicity : Not expected to be mutagenic. Not classified - based on available data, the classification criteria

are not met.

Skin contact

Acute toxicity : Calculated LD50: > 5000 mg/kg.bw. Ingredients of unknown toxicity: < 1 %. ATE: > 2000 mg/kg.bw.

Low toxicity. Not classified - based on available data, the classification criteria are not met.

Corrosion/irritation : Slight irritation possible. Repeated exposure may cause skin dryness or cracking. Prolonged

contact may dry out and defat the skin. Not classified - based on available data, the classification

criteria are not met.

Sensitisation : Does not contain skin sensitisers. Not classified - based on available data, the classification criteria

are not met.

Mutagenicity : Does not contain mutagenic substances. Not classified - based on available data, the classification

criteria are not met.

Eye contact

Corrosion/irritation : Slight irritation possible. Not classified - based on available data, the classification criteria are not

met.

Ingestion

Acute toxicity : Calculated LD50: > 2000 mg/kg.bw. Ingredients of unknown toxicity: < 1 %. ATE: > 2000 mg/kg.bw.

Low toxicity. Not classified - based on available data, the classification criteria are not met.

Aspiration : Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can

be fatal. If swallowed, if any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 38.3° C, shortness of breath,

chest congestion or continued coughing or wheezing.

Corrosion/irritation : May cause a feeling of sickness, stomachache, vomiting and diarrhoea.

Carcinogenicity : Not expected to be carcinogenic. Not classified - based on available data, the classification criteria

are not met.

Mutagenicity : Not expected to be mutagenic. Not classified - based on available data, the classification criteria

are not met.

Reprotoxicity : Development: Not expected to be reprotoxic. Development: Not classified - Based on available

data, the classification criteria are not met. Fertility: not expected to be reprotoxic. Fertility: Not

classified - based on available data, the classification criteria are not met.

Toxicological information:

Chemical name	Property		Method	Test animal
Hydrocarbons, C10-C13, n-alkanes,	Eye irritation - estimate	Non-irritant		
isoalkanes, cyclics, < 2% aromatics				
	LD50 (oral) - estimate	> 5000 mg/kg bw	OECD 401	Rat
	LD50 (dermal) -	> 5000 mg/kg bw	OECD 402	Rabbit
	estimate			
	Skin irritation	Slightly irritant		
	Mutagenicity	Not mutagenic		
	NOEL (carcinogenicity)	Not carcinogenic		
	- estimate			
	Respiratory irritation -	Non-irritant		
	estimate			

Product name : Shell Diesel Additive Page 7/11

Date of issue : 2018-05-15 Replaces issue dated : --- INFO CARE SDS



According to Regulation (EU) No 2015/830

Kemetyl

			_	-
	NOAEL (development)	Not teratogenic		
	- estimate			
	NOAEL (fertility) -	Not reprotoxic		
	estimate			
	LC50 (inhalation)	> 5610 mg/m3	OECD 403	Rat
	NOAEL (oral) -	> 5000 mg/kg bw/d	Read across	Rat
	estimate			
	NOAEL (inhalation) -	> 1160 mg/m3	Read across	Rat
	estimate			
	Skin sensitisation -	Not sensitizing	Read across	Guinea pig
	estimate			
Hydrocarbons, C10, aromatics, <1%	LD50 (oral)	> 2000 mg/kg bw		Rat
naphthalene				
	LD50 (dermal)	> 2000 mg/kg bw		Rat
	Skin sensitisation	Not sensitizing		
	Skin irritation	Moderately irritant		
	Eye irritation	Moderately irritant		
	Skin irritation	Irritant		
	LC50 (inhalation) -	> 5000 mg/m3		
	estimate			
	Mutagenicity - estimate	Not mutagenic	Read across	Salmonella typhimurium

SECTION 12 ECOLOGICAL INFORMATION

12.1. Toxicity

No ecotoxicological research has been carried out on this product.

Ecotoxicity : Harmful to aquatic organisms. Calcu

: Harmful to aquatic organisms. Calculated LC50 (fish): 43 mg/l. Calculated EC50 (waterflea): 45 mg/l. Contains 0 % of components with unknown hazards to the aquatic environment. May form an oil film on the water surface causing a decline in oxygen content with possible adverse effects for

aquatic organisms.

12.2. Persistence and degradability

Persistence – degradability: May cause long-term adverse effects in the aquatic environment.

12.3. Bioaccumulative potential

 $\label{eq:bioaccumulative potential} \quad \hbox{i. No specific information known.}$

12.4. Mobility in soil

Mobility : Adsorbs to soil and has low mobility. Floats on water.

12.5. Results of PBT and vPvB assessment

PBT/vPvB assessment : Does not contain PBT or vPvB substances in concentrations higher than 0,1%.

12.6. Other adverse effects

Other information : Not applicable.

Ecological information:

Chemical name	Property		Method	Test animal
Hydrocarbons, C10, aromatics, <1%	LC50 (fish)	> 1 mg/l		
naphthalene				
	EC50 (waterflea)	> 1 mg/l		

Product name : Shell Diesel Additive Page 8/11
Date of issue : 2018-05-15 Replaces issue dated : --- INFO CARE SDS



According to Regulation (EU) No 2015/830

Kemetyl

Ultimate aerobic 49,6 % OECD 301 F biodegradation (%) Hydrocarbons, C10, aromatics, <1% Log P(ow) naphthalene Hydrocarbons, C10, aromatics, <1% BCF < 100 naphthalene Naphthalene EC50 (waterflea) 2,16 mg/l Daphnia magna _C50 (fish) 0,51 mg/l NOEC (fish) 0,12 mg/l.d Naphthalene Log P(ow) 3,4000 Naphthalene 427

SECTION 13 DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product residues : Do not dispose empty pack with waste produced by households. Containers may be recycled. Treat

product residues and non-empty pack as hazardous waste.

Additional warning : None.

Waste water discharge : Do not dispose into the environment, in drains or in water courses.

European waste catalogue : Dispose hazardous waste in accordance with Directive 91/689/EEC under acknowledgement of a

waste code according to Commission Decision 2000/532/EC to an official chemical waste depot.

Local legislation : Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be

complied with.

SECTION 14 TRANSPORT INFORMATION

14.1. UN number

UN nr. : None.

14.2. UN proper shipping name

Transport name : Not regulated.

14.3/14.4/14.5. Transport hazard class(es)/Packing group/Environmental hazards

ADR/RID/ADN (road/railway/inland waterways)

Class : This product is not classified according to ADR/RID/ADN.

IMDG (sea)

Class : This product is not classified according to IMDG.

Marine pollutant : No

IATA (air)

Class : This product is not classified according to IATA.

14.6. Special precautions for user

Other information : Country specific variations may apply.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Marpol : Not intended to be carried in bulk according to International Maritime Organisation (IMO)

instruments. Packaged liquids are not considered bulk.

Product name : Shell Diesel Additive Page 9/11
Date of issue : 2018-05-15 Replaces issue dated : --- INFO CARE SDS



According to Regulation (EU) No 2015/830

SECTION 15 REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Community regulations : Regulation (EU) No 2015/830 (REACH), Regulation (EC) No 1272/2008 (CLP) and other

regulations.

15.2. Chemical safety assessment

Chemical safety : Not applicable.

assessment

SECTION 16 OTHER INFORMATION

16.1. Other information

The information in this safety data sheet is compiled in compliance with Regulation (EU) No 2015/830 dated 28 May 2015 and accurate to the best of our knowledge and experience at the date of issue specified. It is the user's obligation to use this product safely and to comply with all applicable laws and regulations concerning the use of the product. This safety data sheet complements the technical information sheets but does not replace them and offers no warranty with regard to product properties.

Users are also forewarned for any hazards involved when the product is used for other purposes than those for which it is designed.

Changed or new information with regard to the previous release is indicated with an asterisk (*).

List of abbreviations and acronyms that could be (but not necessarily are) used in this safety data sheet:

ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE : Acute Toxicity Estimate

CLP : Classification, Labeling & Packaging

CMR : Carcinogenic, Mutagenic or toxic for Reproduction

EEC : European Economic Community

GHS : Globally Harmonized System of Classification and Labelling of Chemicals

IATA : International Air Transport Association IBC code : International Bulk Chemical Code

IMDG : International Maritime Dangerous Goods Code LD50/LC50 : Lethal Dose/Concentration for 50% of a population

MAC : Maximum Allowable Concentration

MARPOL : International Convention for the Prevention of Pollution From Ships

NO(A)EL : No Observed (Adverse) Effect Level

OECD : Organisation for Economic Co-operation and Development

PBT : Persistent, Bioaccumulative and Toxic

PC : Chemical product category

PT : Product type

REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals

RID : Regulations concerning the International Carriage of Dangerous Goods by Rail

STP : Sewage Treatment Plant

SU : Sector of Use

TWA/STEL : Time-Weighted Average/Short Term Exposure Limit

UN : United Nations

VOC : Volatile Organic Compounds

vPvB : Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008:

Asp. Tox. 1 : On basis of test data. Calculation method.

Aquatic Chronic 3 : Calculation method.

Product name : Shell Diesel Additive Page 10/11
Date of issue : 2018-05-15 Replaces issue dated : --- INFO CARE SDS



According to Regulation (EU) No 2015/830

Kemetyl

Full text of hazard classes mentioned in section 3:

Acute Tox. 4 : Acute toxicity, category 4. Skin Irrit. 2 : Skin irritation, category 2. Eye Irrit. 2 : Eye irritation, category 2. Carc. 2 : Carcinogen, category 2.

STOT SE 3 : Specific target organ toxicity after single exposure, category 3.

Asp. Tox. 1 : Aspiration hazard, category 1.

Aquatic Chronic 1 : Hazardous to the aquatic environment — Chronic category 1.

Aquatic Chronic 2 : Hazardous to the aquatic environment — Chronic category 2.

Aquatic Acute 1 : Hazardous to the aquatic environment — Acute category 1.

Full text of H-phrases mentioned in section 3:

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Number format : "," used as decimal separator.

End of safety data sheet.

Print date : 2020-09-10

Product name : Shell Diesel Additive Page 11/11
Date of issue : 2018-05-15 Replaces issue dated : --- INFO CARE SDS