Printing date 19.12.2018 Version number 8 Revision: 21.09.2018

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Cartechnic Unterboden-Schutz
- · Article number: 278150
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC9a Coatings and paints, thinners, paint removers
- · Process category

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC7 Industrial spraying

- · Application of the substance / the mixture Coating compound/ Surface coating/ paint
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Auto-Teile-Ring GmbH

Otto-Hirsch-Brücken 17

D-70329 Stuttgart

*Tel.*:+49 (0) 711/91 89 79-99 *Fax*:+49 (0) 711/91 89 79-30

E-Mail: info@cartechnic.de

- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:

Notfallauskunft bei Vergiftungen: Giftinformationszentrum Mainz – Tel.: +49 (6131) 19240

# SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

 ${\it The product is classified and labelled according to the CLP\ regulation}.$ 

· Hazard pictograms





GHS02

GHS07

· Signal word Warning

(Contd. on page 2)

Printing date 19.12.2018 Version number 8 Revision: 21.09.2018

Trade name: Cartechnic Unterboden-Schutz.

(Contd. of page 1)

#### · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P312 Call a POISON CENTER/doctor if you feel unwell.

P403 Store in a well-ventilated place.

P501 Dispose of contents / container in accordance with regional regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components:  |   |         |
|--|---|---------|
| EC number: 927-241-2   | Naphtha (petroleum), hydrotreated light   | 25-<50% |
| Reg.nr.: 01-2119471843-32  | <ul> <li>Flam. Liq. 3, H226</li> <li>Asp. Tox. 1, H304</li> <li>STOT SE 3, H336</li> <li>Aquatic Chronic 3, H412</li> </ul> |         |
| CAS: 8052-42-4<br>EINECS: 232-490-9                              | Asphalt substance with a Community workplace exposure limit   | 25-<50% |
| CAS: 108-32-7<br>EINECS: 203-572-1<br>Index number: 607-194-00-1 | propylene carbonate  © Eye Irrit. 2, H319   | <2.5%   |

#### · Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.

For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

GB

Printing date 19.12.2018 Version number 8 Revision: 21.09.2018

Trade name: Cartechnic Unterboden-Schutz

(Contd. of page 2)

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

No further relevant information available.

- · 5.3 Advice for firefighters -
- · Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

No special precautions are necessary if used correctly.

No special precautions are necessary if used correctly.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- $\cdot$  7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

#### 8052-42-4 Asphalt

WEL Short-term value: 10 mg/m<sup>3</sup> Long-term value: 5 mg/m<sup>3</sup>

(Contd. on page 4)

Printing date 19.12.2018 Version number 8 Revision: 21.09.2018

Trade name: Cartechnic Unterboden-Schutz

(Contd. of page 3)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection:

Filter AX

Not necessary if room is well-ventilated.

#### · Protection of hands:

In case of contact with spray dust protective gloves made of butyl shoul be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products

Solvent resistant gloves

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

#### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 143 °C (289.4 °F)

• Flash point:  $30 \, ^{\circ}C \, (86 \, ^{\circ}F)$ 

· Flammability (solid, gas): Not applicable.

· Ignition temperature: ~490 °C (~914 °F)

(Contd. on page 5)

Printing date 19.12.2018 Version number 8 Revision: 21.09.2018

Trade name: Cartechnic Unterboden-Schutz.

|   | (Contd. of pag  |
|---|---|
| Decomposition temperature:              | Not determined.   |
| · Explosive properties:                 | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · Explosion limits:                     |   |
| Lower:                                  | 0.7 Vol %   |
| Upper:                                  | 7.5 Vol %   |
| · Vapour pressure at 20 °C (68 °F):     | 5 hPa (3.8 mm Hg)   |
| Density at 20 °C (68 °F):               | 0.78 g/cm³ (6.51 lbs/gal)   |
| Relative density                        | Not determined.   |
| Vapour density                          | Not determined.   |
| Evaporation rate                        | Not determined.   |
| Solubility in / Miscibility with        |   |
| water:                                  | Not miscible or difficult to mix.   |
| Partition coefficient: n-octanol/water: | Not determined.   |
| Viscosity:                              |   |
| Dynamic:                                | Not determined.   |
| Kinematic:                              | Not determined.   |
| Solvent content:                        |   |
| Organic solvents:                       | 59.9 %  |
| VOC (EC)                                |   |
|   | 467.2 g/l   |
| · VOC-EU%                               | 59.90 %   |
| Solids content:                         | 69.9 %  |
| · 9.2 Other information                 | No further relevant information available.  |

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

| · LD/LC5                                | · LD/LC50 values relevant for classification: |   |  |  |
|---|---|---|--|--|
| Naphtha (petroleum), hydrotreated light |   |   |  |  |
| Oral                                    | LD50  | 5,000 mg/kg (rat)                             |  |  |
| Dermal                                  | LD50  | >5,000 mg/kg (rabbit)                         |  |  |
|   | LC50 / 72 h                                   | >1,000 mg/l (Pseudokirchneriella Subcapitata) |  |  |
| Hydroce                                 | Hydrocarbons, C9, aromatics                   |   |  |  |
| Oral                                    | LD50  | 3,592 mg/kg (rat)                             |  |  |
| Dermal                                  | LD50  | 3,160 mg/kg (rabbit)                          |  |  |

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date 19.12.2018 Version number 8 Revision: 21.09.2018

Trade name: Cartechnic Unterboden-Schutz

(Contd. of page 5)

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

### Naphtha (petroleum), hydrotreated light

EC50 34 mg/l (daphnia magna / Wasserfloh)

LC50 / 96 h | 20 mg/l (Regenbogenforelle)

#### Hydrocarbons, C9, aromatics

EC50 / 48 h 3.2 mg/l (Daphnia magna)

EC50 / 72 h | 2.75 mg/l (Pseudokirchneriella Subcapitata)

EC50 / 96 h 9.2 mg/l (Regenbogenforelle)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

13 02 08\* other engine, gear and lubricating oils

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

GB

Printing date 19.12.2018 Version number 8 Revision: 21.09.2018

Trade name: Cartechnic Unterboden-Schutz

(Contd. of page 6)

| 14.1 UN-Number<br>ADR, IMDG, IATA  | UN1139   |
|--|--|
| 14.2 UN proper shipping name<br>ADR<br>IMDG, IATA  | 1139 COATING SOLUTION<br>COATING SOLUTION  |
| 14.3 Transport hazard class(es)  |  |
| ADR  |  |
| Class  | 3 (F1) Flammable liquids.  |
| Label  | 3  |
| MDG, IATA  |  |
| Class  | 3 Flammable liquids.   |
| Label  | 3  |
| 14.4 Packing group<br>ADR, IMDG, IATA  | III  |
| 4.5 Environmental hazards:   | Not applicable.  |
| 4.6 Special precautions for user<br>Danger code (Kemler):<br>EMS Number:<br>Stowage Category | Warning: Flammable liquids.<br>30<br>F-E, <u>S-E</u><br>A  |
| 4.7 Transport in bulk according to Anne  | ex II of   |
| Marpol and the IBC Code  | Not applicable.  |
| Transport/Additional information:  |  |
| ADR<br>Limited quantities (LQ)<br>Excepted quantities (EQ)                                   | 5L<br>Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| Transport category<br>Tunnel restriction code  | 3 D/E  |
| MDG<br>Limited quantities (LQ)<br>Excepted quantities (EQ)                                   | 5L<br>Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| UN ''Model Regulation'':   | UN 1139 COATING SOLUTION, 3, III   |

Printing date 19.12.2018 Version number 8 Revision: 21.09.2018

Trade name: Cartechnic Unterboden-Schutz

(Contd. of page 7)

# SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

 $A quatic\ Chronic\ 3:\ Hazardous\ to\ the\ aquatic\ environment\ -\ long-term\ aquatic\ hazard\ -\ Category\ 3$ 

\* \* Data compared to the previous version altered.

GB