

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 12.01.2024

Version number 8 (replaces version 7)

Revision: 12.01.2024

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1 Product identifier

Trade name: Cartechnic Steinschlag Unterboden-Schutz Schwarz 1.000 ml

Article number: 278198, 278211alt, 4027289013268

##### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

##### Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers

##### Process category

PROC10 Roller application or brushing

PROC7 Industrial spraying

PROC11 Non industrial spraying

Application of the substance / the mixture Coating

##### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

Auto-Teile-Ring GmbH

Marie-Curie-Str. 3

73770 Denkendorf, Germany

Tel.: +49 (0) 711/91 89 79-99

E-Mail: info@cartechnic.de

Further information obtainable from: Department Product Safety

##### 1.4 Emergency telephone number:

Emergency information in the event of poisoning: Giftinformationszentrum Mainz – Tel.: +49 (6131) 19240

#### SECTION 2: Hazards identification

##### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 2

H225 Highly flammable liquid and vapour.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2

H315 Causes skin irritation.

STOT SE 3

H336 May cause drowsiness or dizziness.

##### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 12.01.2024

Version number 8 (replaces version 7)

Revision: 12.01.2024

Trade name: Cartechnic Steinschlag Unterboden-Schutz Schwarz 1.000 ml

(Contd. of page 1)

## · Hazard pictograms



GHS02 GHS07 GHS09

## · Signal word Danger

## · Hazard-determining components of labelling:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane ethyl acetate

## · Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

## · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves / eye protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P501 Dispose of contents / container in accordance with regional regulations.

## · 2.3 Other hazards

## · Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

## · 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

## · Dangerous components:

CAS: 8052-42-4 EINECS: 232-490-9	Asphalt substance with a Community workplace exposure limit	50-<75%
EC number: 927-510-4 Reg.nr.: 01-2119475515-33	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	12.5-<20%
EC number: 920-750-0 Reg.nr.: 01-2119473851-33	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336 EUH066	12.5-<20%
EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	10-<12.5%

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 12.01.2024

Version number 8 (replaces version 7)

Revision: 12.01.2024

**Trade name: Cartechnic Steinschlag Unterboden-Schutz Schwarz 1.000 ml**

(Contd. of page 2)

CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46	ethyl acetate Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	5-<10%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336 EUH066	2.5-<5%

**Additional information:**

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.  
For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
No further relevant information available.  
No further relevant information available.
- **5.3 Advice for firefighters -**
- **Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.  
Keep away from ignition sources.
- **6.2 Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 12.01.2024

Version number 8 (replaces version 7)

Revision: 12.01.2024

**Trade name: Cartechnic Steinschlag Unterboden-Schutz Schwarz 1.000 ml**

See Section 13 for disposal information.

(Contd. of page 3)

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

##### · **Ingredients with limit values that require monitoring at the workplace:**

##### **8052-42-4 Asphalt**

WEL Short-term value: 10 mg/m<sup>3</sup>  
Long-term value: 5 mg/m<sup>3</sup>

##### **141-78-6 ethyl acetate**

WEL Short-term value: 1468 mg/m<sup>3</sup>, 400 ppm  
Long-term value: 734 mg/m<sup>3</sup>, 200 ppm

#### · **DNELs**

##### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

Oral	DNEL	1301 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	13964 mg/kg /per day (Worker, longterm systemic)
	DNEL	1377 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	5306 mg/m <sup>3</sup> (Worker, longterm systemic)
	DNEL	1131 mg/m <sup>3</sup> (Consumer, longterm systemic)

##### **141-78-6 ethyl acetate**

Oral	DNEL	4.5 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	63 mg/kg /per day (Worker, longterm systemic)
	DNEL	37 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	734 mg/m <sup>3</sup> /200 ppm (Worker, longterm systemic)
	DNEL	1468 mg/m <sup>3</sup> /400 ppm (Worker, acute systemic)
	DNEL	734 mg/m <sup>3</sup> /200 ppm (Worker, longterm local)
	DNEL	1468 mg/m <sup>3</sup> /400 ppm (Worker, acute local)
	DNEL	367 mg/m <sup>3</sup> /100 ppm (Consumer, longterm systemic)
	DNEL	734 mg/m <sup>3</sup> /200 ppm (Consumer; acute systemic)
	DNEL	367 mg/m <sup>3</sup> /100 ppm (Consumer, longterm local)
	DNEL	734 mg/m <sup>3</sup> /200 ppm (Consumer, acute local)

##### **Hydrocarbons, C9, aromatics**

Oral	DNEL	11 mg/kg /per day (Consumer, longterm systemic)
------	------	---

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 12.01.2024

Version number 8 (replaces version 7)

Revision: 12.01.2024

**Trade name: Cartechnic Steinschlag Unterboden-Schutz Schwarz 1.000 ml**

(Contd. of page 4)

Dermal	DNEL	25 mg/kg /per day (Worker, longterm systemic)
	DNEL	11 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	150 mg/m <sup>3</sup> (Worker, longterm systemic)
	DNEL	32 mg/m <sup>3</sup> (Consumer, longterm systemic)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· **Hand protection**



Protective gloves

· **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· **Eye/face protection**



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Fluid

· **Colour:**

According to product specification

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

(Contd. on page 6)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 12.01.2024

Version number 8 (replaces version 7)

Revision: 12.01.2024

Trade name: Cartechnic Steinschlag Unterboden-Schutz Schwarz 1.000 ml

(Contd. of page 5)

· <b>Melting point/freezing point:</b>	Undetermined.
· <b>Boiling point or initial boiling point and boiling range</b>	77 °C (170.6 °F) (141-78-6 ethyl acetate)
· <b>Flammability</b>	Highly flammable.
· <b>Lower and upper explosion limit</b>	
· <b>Lower:</b>	0.6 Vol % (Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics)
· <b>Upper:</b>	7.4 Vol % (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)
· <b>Flash point:</b>	-4 °C (24.8 °F) (141-78-6 ethyl acetate)
· <b>Auto-ignition temperature:</b>	>200 °C (>392 °F) (Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics)
· <b>Decomposition temperature:</b>	Not determined.
· <b>pH</b>	Mixture is non-soluble (in water).
· <b>Viscosity:</b>	
· <b>Kinematic viscosity at 20 °C (68 °F)</b>	690 mm <sup>2</sup> /s
· <b>Kinematic viscosity at 40 °C (104 °F)</b>	>21 mm <sup>2</sup> /s
· <b>Dynamic:</b>	Not determined.
· <b>Solubility</b>	
· <b>water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
· <b>Vapour pressure at 20 °C (68 °F):</b>	60 hPa (45 mm Hg) (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)
· <b>Density and/or relative density</b>	
· <b>Density at 20 °C (68 °F):</b>	1 g/cm <sup>3</sup> (8.3 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.

· **9.2 Other information**

· <b>Appearance:</b>	
· <b>Form:</b>	Fluid
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Solvent content:</b>	
· <b>Organic solvents:</b>	48.0 %
· <b>VOC (EC)</b>	---
	499.2 g/l
· <b>VOC-EU%</b>	48.00 %
· <b>Solids content:</b>	52.0 %
· <b>Change in condition</b>	
· <b>Evaporation rate</b>	Not determined.

· **Information with regard to physical hazard classes**

· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Void
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Highly flammable liquid and vapour.
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void

(Contd. on page 7)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 12.01.2024

Version number 8 (replaces version 7)

Revision: 12.01.2024

Trade name: Cartechnic Steinschlag Unterboden-Schutz Schwarz 1.000 ml

(Contd. of page 6)

· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

##### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50 / 4 h	>20 mg/m <sup>3</sup> (rat)

##### 141-78-6 ethyl acetate

Oral	LD50	>18000 mg/kg (rab)
Dermal	LD50	5620 mg/kg (rat)
Inhalative	LC50 / 4 h	1600 mg/m <sup>3</sup> (rat)

##### Hydrocarbons, C9, aromatics

Oral	LD50	>5000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2000 mg/kg (rab) (OECD 402)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

#### · Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

#### · 12.1 Toxicity

##### · Aquatic toxicity:

##### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

EC50 / 48 h	3 mg/l (daphnia magna / Wasserfloh)
EC50 / 72 h	30 mg/l (Pseudokirchneriella subcapitata)
LC50 / 96 h	11.4 mg/l (oncorhynchus mykiss)

##### Hydrocarbons, C9, aromatics

EC50 / 48 h	302 mg/l (daphnia magna)
-------------	--------------------------

(Contd. on page 8)

Safety data sheet  
according to 1907/2006/EC, Article 31

Printing date 12.01.2024

Version number 8 (replaces version 7)

Revision: 12.01.2024

Trade name: Cartechnic Steinschlag Unterboden-Schutz Schwarz 1.000 ml

(Contd. of page 7)

EC50 / 72 h 2.75 mg/l (Pseudokirchneriella subcapitata)

EC50 / 96 h 9.2 mg/l (Regenbogenforelle)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Remark:** Toxic for fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

**SECTION 13: Disposal considerations**

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:**

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

**SECTION 14: Transport information**

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA**

UN1139

· **14.2 UN proper shipping name**

· **ADR**

1139 COATING SOLUTION, special provision 640D,  
MARINE POLLUTANT/ENVIRONMENTALLY  
HAZARDOUS

· **IMDG**

COATING SOLUTION, MARINE POLLUTANT

· **IATA**

COATING SOLUTION

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class**

3 (F1) Flammable liquids.

· **Label**

3

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 12.01.2024

Version number 8 (replaces version 7)

Revision: 12.01.2024

**Trade name: Cartechnic Steinschlag Unterboden-Schutz Schwarz 1.000 ml**

(Contd. of page 8)

· **IMDG**

· **Class** 3 Flammable liquids.  
· **Label** 3

· **IATA**

· **Class** 3 Flammable liquids.  
· **Label** 3

· **14.4 Packing group**

· **ADR, IMDG, IATA** II

· **14.5 Environmental hazards:**

· **Marine pollutant:** Yes  
Symbol (fish and tree)  
· **Special marking (ADR):** Symbol (fish and tree)

· **14.6 Special precautions for user**

· **Hazard identification number (Kemler code):** 33  
· **EMS Number:** F-E, S-E  
· **Stowage Category** B

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**· **ADR**

· **Limited quantities (LQ)** 5L  
· **Excepted quantities (EQ)** Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml  
· **Transport category** 2  
· **Tunnel restriction code** D/E

· **IMDG**

· **Limited quantities (LQ)** 5L  
· **Excepted quantities (EQ)** Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN 1139 COATING SOLUTION, 3, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS

\*

**SECTION 15: Regulatory information**· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Directive 2012/18/EU**· **Named dangerous substances - ANNEX I** None of the ingredients is listed.· **Seveso category**

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

(Contd. on page 10)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 12.01.2024

Version number 8 (replaces version 7)

Revision: 12.01.2024

**Trade name: Cartechnic Steinschlag Unterboden-Schutz Schwarz 1.000 ml**

(Contd. of page 9)

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

#### · **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

#### · **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (UK REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

- **\* Data compared to the previous version altered.**

GB