

POWER KLEBER GEL

Page: 1 Compilation date: 31/07/2008 Revision date: 31/01/2017 Revision No: 4a

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: Power Kleber Gel

Index number: 01-005-408

Product code: 93620, 93720

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Cyanoacrylate adhesive

1.3. Details of the supplier of the safety data sheet

Company name: PETEC Verbindungstechnik GmbH Wüstenbuch 16

96132 Schlüsselfeld

DEUTSCHLAND

- **Tel:** +49 (0) 9555 80994-0
- Fax: +49 (0) 9555-80994-25
- Email: sdb@chemiebuero.de
- Web: www.petec.de

1.4. Emergency telephone number

Emergency tel: +49 (0)89-19240 (24h) (English and German)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

| Classification under CLP: | STOT SE 3: H335; Eye Irrit. 2: H319; Skin Irrit. 2: H315; -: EUH202 |
|---------------------------------|------------------------------------------------------------------------------------------|
| Most important adverse effects: | Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. |
| | Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of |
| | children. |

2.2. Label elements

| Label elements: | |
|--------------------|--------------------------------------------------------------------------------|
| Hazard statements: | * H315: Causes skin irritation. |
| | H319: Causes serious eye irritation. |
| | H335: May cause respiratory irritation. |
| | EUH202: Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the |
| | reach of children. |

POWER KLEBER GEL

Signal words:* WarningHazard pictograms:* GHS07: Exclamation markPrecautionary statements:* P261: Avoid breathing vapours.P271: Use only outdoors or in a well-ventilated area.P271: Use only outdoors or in a well-ventilated area.P280: Wear protective gloves.P302+352: IF ON SKIN: Wash with plenty of water/.P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove
contact lenses, if present and easy to do. Continue rinsing.P37+313: If eye irritation persists: Get medical attention.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

Hazardous ingredients:

ETHYL-2-CYANOACRYLATE - REACH registered number(s): 01-2119527766-29-...

| EINECS | CAS | PBT / WEL | CLP Classification | Percent |
|-----------|-----------|-----------|-------------------------------------------------------------|---------|
| 230-391-5 | 7085-85-0 | - | Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315 | |

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Do not pull bonded skin apart. Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Any bonded skin should be gently peeled apart, preferably after soaking in warm, soapy water. In the case of large spills on the skin, superficial burns may occur - treat accordingly. If irritation persists, obtain medical attention.

- **Eye contact:** Bathe the eye with running water for 15 minutes. If the eyelid is bonded closed, do not force open. Cover with wet pad soaked in warm water. Get prompt medical attention, in case solid particles of cured cyanoacrylate trapped behind the eye cause any abrasive damage. Keep eye covered with wet pad until debonding is complete, usually 1-3 days. (Cyanoacrylate will bond to eye protein, causing a lachrymatory effect that aids debonding).
 - **Ingestion:** The product will polymerise immediately in the mouth, making it almost impossible to swallow, but beware of possible choking hazard. Ensure breathing passages are not obstructed. Saliva will separate the solidified product from the mouth over a period of hours. Consult a doctor.

Page: 2

POWER KLEBER GEL

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If symptoms persist, Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Cyanoacrylates bond skin in seconds. In the case of large spills on the skin, superficial burns may occur - treat accordingly. There may be irritation and redness at the site of contact.

- **Eye contact:** Cyanoacrylates bond eyelids in seconds. There may be irritation and redness. The eyes may water profusely.
 - Ingestion: There may be soreness and redness of the mouth and throat. The product will polymerise immediately in the mouth, making it almost impossible to swallow, but beware of possible choking hazard.
 - **Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Dry chemical powder. Carbon dioxide. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. In combustion emits toxic fumes of nitrogen oxides. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

 Personal precautions:
 Evacuate the area immediately. Refer to section 8 of SDS for personal protection details.

 Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. (do not use cloths). Transfer to a closable, labelled

POWER KLEBER GEL

Page: 4

salvage container for disposal by an appropriate method. Or polymerise slowly with

water (~10:1, adhesive : water) and then scrape up.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements:Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.Do not handle in a confined space. Avoid the formation or spread of mists in the air.Ambient humidity should be >35% to minimise discomfort.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from direct sunlight. Keep container tightly closed. Keep away from sources of ignition. Refrigerated storage (2 - 8oC) is recommended for optimum shelf-life.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): Adhesive

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

ETHYL-2-CYANOACRYLATE

Workplace exposure limits:

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|------------|--------------|------------|--------------|
| UK | - | 1.5 mg/m3 | - | - |

Respirable dust

DNEL/PNEC Values

DNEL / PNEC No data available.

| 8.2. Exposure controls | |
|-------------------------|-------------------------------------------------------------------------------------|
| Engineering measures: | Ensure there is sufficient ventilation of the area. Ensure all engineering measures |
| | mentioned in section 7 of SDS are in place. |
| Respiratory protection: | If WEL is likely to be exceeded, respiratory protective equipment will be needed. |
| | Gas/vapour filter, type A: organic vapours (EN141). |
| Hand protection: | Nitrile gloves. Viton gloves. |
| Eye protection: | Safety glasses with side-shields. Ensure eye bath is to hand. |
| Skin protection: | Protective clothing. |

POWER KLEBER GEL

Page: 5

Section 9: Physical and chemical properties

| 9.1. Information on basic physical and chemical properties | | | |
|------------------------------------------------------------|---------------------------------------|-------------------|-------|
| State: | Gel | | |
| Colour: | Colourless | | |
| Odour: | Acrid | | |
| Evaporation rate: | Negligible | | |
| Oxidising: | Non-oxidising (by EC criteria) | | |
| Solubility in water: | Reacts with water. | | |
| Also soluble in: | Acetone. | | |
| Viscosity: | * Highly viscous | | |
| Kinematic viscosity: | * 50K-90KcPs | | |
| Viscosity test method: | Brookfield RVT, 'T'-spindle C, 2.5rpm | | |
| Boiling point/range°C: | >150 | Flash point°C: | >85 |
| Vapour pressure: | ~0.04mmHg @25°C | Relative density: | ~1.10 |
| pH: | ~6-7 | | |

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Polymerises rapidly with water.

10.3. Possibility of hazardous reactions

 Hazardous reactions:
 Hazardous reactions will not occur under normal transport or storage conditions.

 Polymerisation may occur on exposure to conditions or materials listed below.

 Polymerisation can be rapid.

10.4. Conditions to avoid

Conditions to avoid: Heat. Direct sunlight. Moist air. Humidity.

10.5. Incompatible materials

Materials to avoid: Water. Alkalis. Amines. Alcohols. Strong oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. In combustion emits toxic fumes of nitrogen oxides.

POWER KLEBER GEL

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ETHYL-2-CYANOACRYLATE

| ORL RAT LD50 | >5 | ml/kg |
|--------------|----|-------|
|--------------|----|-------|

Relevant hazards for substance:

| Hazard | Route | Basis |
|-------------------------------|-------|-----------------------|
| Skin corrosion/irritation | DRM | Hazardous: calculated |
| Serious eye damage/irritation | OPT | Hazardous: calculated |
| STOT-single exposure | INH | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: Cyanoacrylates bond skin in seconds. In the case of large spills on the skin, superficial burns may occur - treat accordingly. There may be irritation and redness at the site of contact.

Eye contact: Cyanoacrylates bond eyelids in seconds. There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. The product will polymerise immediately in the mouth, making it almost impossible to swallow, but beware of possible choking hazard.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Considered to be very low due to rapid polymerisation with water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

POWER KLEBER GEL

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

| Disposal operations: | Transfer to a suitable container and arrange for collection by specialised disposal | | |
|------------------------|----------------------------------------------------------------------------------------|--|--|
| | company. Or polymerise slowly with water (10:1, adhesive : water). Hardened product | | |
| | can be disposed of in land-fill sites by licensed contractors. | | |
| Waste code number: | 08 04 09 | | |
| Disposal of packaging: | Dispose of in a regulated landfill site or other method for hazardous or toxic wastes. | | |
| NB: | The user's attention is drawn to the possible existence of regional or national | | |
| | regulations regarding disposal. | | |

Section 14: Transport information

14.1. UN number

UN number: UN3334

14.2. UN proper shipping name

Shipping name: AVIATION REGULATED LIQUID, N.O.S.

(ETHYL-2-CYANOACRYLATE)

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

POWER KLEBER GEL

Phrases used in s.2 and s.3: EUH202: Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the

reach of children.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. PETEC Verbindungstechnik GmbH and/or its agents cannot accept any liability for the use of information contained in this data sheet or for the use, applicationor processing of the product described in this data sheet. Users should note the possibility of hazards occurring due to improper uses of the product.