

According to 1907/2006/EC (REACH), 2015/830/EU

ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH SPRAY

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH SPRAY

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: The protection measure for closed profiles in constructions. Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Agencja Handlowa "BOLL" Wojciech Dalewski Spólka Jawna

ul. Chemiczna 3

65-713 Zielona Góra - Polska

Phone.: 68 451 99 99 - Fax: 68 451 99 00

technolog@boll.pl

1.4 Emergency telephone number:

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aerosol 1: Flammable aerosols, Category 1, H222

Aerosol 1: Pressurised container: May burst if heated., H229

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411

Skin Irrit. 2: Skin irritation, Category 2, H315

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger







Hazard statements:

H222 - Extremely flammable aerosol

H229 - Pressurised container: May burst if heated

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H411 - Toxic to aquatic life with long lasting effects

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand

P102: Keep out of reach of children

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P211: Do not spray on an open flame or other ignition source

P251: Do not pierce or burn, even after use

P260: Do not breathe spray

P271: Use only outdoors or in a well-ventilated area

P273: Avoid release to the environment P280: Wear protective gloves/eye protection

P302+P352: IF ON SKIN: Wash with plenty of water

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing

P403: Store in a well-ventilated place

P410+P412: Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122°F

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking

2.3 Other hazards:

BOLL

Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH SPRAY

SECTION 2: HAZARDS IDENTIFICATION (continued)

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: active ingredient mixture with a propellant

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	Concentration		
	106-97-8	Butane ⁽¹⁾	ATP CLP00			
Index:	203-448-7 601-004-00-0 01-2119474691-32-XXXX	Regulation 1272/2008	Flam. Gas 1: H220; Press. Gas: H280 - Danger			
	Non-applicable 921-024-6	Hydrocarbons, C6-C2	7, n-alkanes, isoalkanes, cyclics, <5% n-hexane(1) Self-classified			
Index:	921-024-6 Non-applicable 01-2119475514-35-XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336 - Danger	25 - <50 %		
	74-98-6 200-827-9	Propane ⁽¹⁾	ATP CLP00			
Index:	200-827-9 601-003-00-5 01-2119486944-21-XXXX	Regulation 1272/2008	Flam. Gas 1: H220; Press. Gas: H280 - Danger	10 - <25 %		
	64742-48-9 919-857-5	Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics(1) Self-classified				
Index:	919-857-5 Non-applicable 01-2119463258-33-XXXX	Regulation 1272/2008	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Danger			
	68608-26-4 271-781-5	Sulfonic acids, petro	leum, sodium salts(1) Self-classified			
Index:	271-781-5 Non-applicable 01-2119527859-22-XXXX	Regulation 1272/2008	Eye Irrit. 2: H319 - Warning	1 - <2,5 %		
	64742-95-6	Hydrocarbons, C9, a	romatics (EC 200-753-7 <0,1%)(1) Self-classified			
Index:	918-668-5 Non-applicable 01-2119455851-35-XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336; EUH066 - Danger	1 - <2,5 %		
	111-76-2	2-butoxyethanol ⁽¹⁾ ATP CLP00				
Index:	203-905-0 603-014-00-0 :01-2119475108-36-XXXX	Regulation 1272/2008	Acute Tox. 4: H302+H312+H332; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning	<1 %		

 $^{^{(1)}}$ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 8, 11, 12, 15 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

- CONTINUED ON NEXT PAGE -



ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH SPRAY

SECTION 4: FIRST AID MEASURES (continued)

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

- CONTINUED ON NEXT PAGE -



ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH SPRAY

SECTION 7: HANDLING AND STORAGE (continued)

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Avoid splashes and pulverizations. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 20 °C

Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

Identification	Environmental limits			
2-butoxyethanol	IOELV (8h)	20 ppm	98 mg/m ³	
CAS: 111-76-2	IOELV (STEL)	50 ppm	246 mg/m ³	

DNEL (Workers):

		Short e	xposure	Long exposure	
Identification	Systemic	Local	Systemic	Local	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	758 - 788 mg/kg	Non-applicable
EC: 921-024-6	Inhalation	Non-applicable	Non-applicable	2020 - 2050 mg/m ³	Non-applicable
Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, $<2\%$ aromatics	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 64742-48-9	Dermal	Non-applicable	Non-applicable	285 - 315 mg/kg	Non-applicable
EC: 919-857-5	Inhalation	Non-applicable	Non-applicable	1485 - 1515 mg/m ³	Non-applicable
Sulfonic acids, petroleum, sodium salts	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 68608-26-4	Dermal	Non-applicable	Non-applicable	-11,67 - 18,33 mg/kg	Non-applicable
EC: 271-781-5	Inhalation	Non-applicable	Non-applicable	-14,34 - 15,66 mg/m ³	Non-applicable
Hydrocarbons, C9, aromatics (EC 200-753-7 <0,1%)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 64742-95-6	Dermal	Non-applicable	Non-applicable	10 - 40 mg/kg	Non-applicable
EC: 918-668-5	Inhalation	Non-applicable	Non-applicable	135 - 165 mg/m ³	Non-applicable

- CONTINUED ON NEXT PAGE -



ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH SPRAY

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
2-butoxyethanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 111-76-2	Dermal	74 - 104 mg/kg	Non-applicable	60 - 90 mg/kg	Non-applicable
EC: 203-905-0	Inhalation	648 - 678 mg/m ³	231 - 261 mg/m ³	83 - 113 mg/m ³	Non-applicable

DNEL (General population):

	a				
		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Oral	Non-applicable	Non-applicable	684 - 714 mg/kg	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	684 - 714 mg/kg	Non-applicable
EC: 921-024-6	Inhalation	Non-applicable	Non-applicable	593 - 623 mg/m ³	Non-applicable
Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics	Oral	Non-applicable	Non-applicable	285 - 315 mg/kg	Non-applicable
CAS: 64742-48-9	Dermal	Non-applicable	Non-applicable	285 - 315 mg/kg	Non-applicable
EC: 919-857-5	Inhalation	Non-applicable	Non-applicable	885 - 915 mg/m ³	Non-applicable
Sulfonic acids, petroleum, sodium salts	Oral	Non-applicable	Non-applicable	-14,17 - 15,83 mg/kg	Non-applicable
CAS: 68608-26-4	Dermal	Non-applicable	Non-applicable	-13,33 - 16,67 mg/kg	Non-applicable
EC: 271-781-5	Inhalation	Non-applicable	Non-applicable	-14,67 - 15,33 mg/m³	Non-applicable
Hydrocarbons, C9, aromatics (EC 200-753-7 <0,1%)	Oral	Non-applicable	Non-applicable	-4 - 26 mg/kg	Non-applicable
CAS: 64742-95-6	Dermal	Non-applicable	Non-applicable	-4 - 26 mg/kg	Non-applicable
EC: 918-668-5	Inhalation	Non-applicable	Non-applicable	17 - 47 mg/m ³	Non-applicable
2-butoxyethanol	Oral	-1,6 - 28,4 mg/kg	Non-applicable	-11,8 - 18,2 mg/kg	Non-applicable
CAS: 111-76-2	Dermal	29,5 - 59,5 mg/kg	Non-applicable	23 - 53 mg/kg	Non-applicable
EC: 203-905-0	Inhalation	411 - 441 mg/m³	108 - 138 mg/m ³	34 - 64 mg/m ³	Non-applicable

PNEC:

Identification							
Sulfonic acids, petroleum, sodium salts	STP	85 - 115 mg/L	Fresh water	-14 - 16 mg/L			
CAS: 68608-26-4	Soil	868699985 - 868700015 mg/kg	Marine water	-14 - 16 mg/L			
EC: 271-781-5	Intermittent	-5 - 25 mg/L	Sediment (Fresh water)	723499985 - 723500015 mg/kg			
	Oral	1,67 - 31,67 g/kg	Sediment (Marine water)	723499985 - 723500015 mg/kg			
2-butoxyethanol	STP	448 - 478 mg/L	Fresh water	-6,2 - 23,8 mg/L			
CAS: 111-76-2	Soil	-11,87 - 18,13 mg/kg	Marine water	-14,12 - 15,88 mg/L			
EC: 203-905-0	Intermittent	-5,9 - 24,1 mg/L	Sediment (Fresh water)	19,6 - 49,6 mg/kg			
	Oral	5 - 35 g/kg	Sediment (Marine water)	Non-applicable			

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

- CONTINUED ON NEXT PAGE -



According to 1907/2006/EC (REACH), 2015/830/EU

ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH SPRAY

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CAT III	EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves	CAT III	EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

[&]quot;As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield	CATII	EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	CATIII	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2001 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
•	ANSI Z358-1 ISO 3864-1:2002	⊢	DIN 12 899 ISO 3864-1:2002
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 98 % weight

V.O.C. density at 20 °C: 545,1 kg/m³ (545,1 g/L)

Average carbon number: 7,95

Average molecular weight: 113,59 g/mol

SECTION Q: DHYSICAL AND CHEMICAL DDODEDTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH SPRAY

SECTION 9:	DHACIUVI	VND	CHEMICAL	DDOD	PEDTIES /	continued)
SECTION 5.	FILIDICAL	AND	CHILITOAL	FIVOR	FLIIFS (continueu /

Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Odour:

Characteristic

Non-applicable *

Volatility:

Boiling point at atmospheric pressure: -44 °C

Vapour pressure at 20 °C: 830000 Pa

Vapour pressure at 50 °C: Non-applicable *

Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: 660 kg/m³
Relative density at 20 °C: 0,66

Dynamic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 40 °C: Non-applicable * Concentration: Non-applicable * pH: Non-applicable * Vapour density at 20 °C: Non-applicable * Partition coefficient n-octanol/water 20 °C: Non-applicable * Solubility in water at 20 °C: Non-applicable * Solubility properties: Immiscible Decomposition temperature: Non-applicable * Non-applicable * Melting point/freezing point: Explosive properties: Non-applicable * Oxidising properties: Non-applicable *

Flammability:

Flash Point: -97 °C

Flammability (solid, gas): Non-applicable *

Autoignition temperature: 200 °C

Lower flammability limit: 0,6 % Volume
Upper flammability limit: 10,9 % Volume

Explosive:

Lower explosive limit: Non-applicable * Upper explosive limit: Non-applicable *

9.2 Other information:

Surface tension at 20 °C: Non-applicable *
Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

- CONTINUED ON NEXT PAGE -



According to 1907/2006/EC (REACH), 2015/830/EU

ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH SPRAY

SECTION 10: STABILITY AND REACTIVITY (continued)

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids Water		Combustive materials	Combustible materials	Others	
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases	

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.

 IARC: 2-butoxyethanol (3)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:



ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH SPRAY

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Skin: Repeated exposure may cause skin dryness or cracking
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	A	Acute toxicity	
Butane	LD50 oral	>2000 mg/kg	
CAS: 106-97-8	LD50 dermal	>2000 mg/kg	
EC: 203-448-7	LC50 inhalation	658 mg/L (4 h)	Rat
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	LD50 oral	5840 mg/kg	Rat
CAS: Non-applicable	LD50 dermal	2920 mg/kg	Rat
EC: 921-024-6	LC50 inhalation	>20 mg/L (4 h)	
Propane	LD50 oral	>2000 mg/kg	
CAS: 74-98-6	LD50 dermal	>2000 mg/kg	
EC: 200-827-9	LC50 inhalation	>5 mg/L (4 h)	
Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics	LD50 oral	5100 mg/kg	Rat
CAS: 64742-48-9	LD50 dermal	>2000 mg/kg	
EC: 919-857-5	LC50 inhalation	>20 mg/L (4 h)	
Sulfonic acids, petroleum, sodium salts	LD50 oral	5500 mg/kg	Rat
CAS: 68608-26-4	LD50 dermal	5500 mg/kg	Rabbit
EC: 271-781-5	LC50 inhalation	>20 mg/L (4 h)	
Hydrocarbons, C9, aromatics (EC 200-753-7 <0,1%)	LD50 oral	>2000 mg/kg	
CAS: 64742-95-6	LD50 dermal	>2000 mg/kg	
EC: 918-668-5	LC50 inhalation	>20 mg/L (4 h)	
2-butoxyethanol	LD50 oral	1414 mg/kg	Rat
CAS: 111-76-2	LD50 dermal	1060 mg/kg	Rabbit
EC: 203-905-0	LC50 inhalation	11 mg/L (4 h)	Rat

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	LC50	5.1 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: Non-applicable		Non-applicable		
EC: 921-024-6	EC50	Non-applicable		



According to 1907/2006/EC (REACH), 2015/830/EU

ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH SPRAY

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Species	Genus
Hydrocarbons, C9, aromatics (EC 200-753-7 <0,1%)	LC50	1 - 10 mg/L (96 h)		Fish
CAS: 64742-95-6	EC50	1 - 10 mg/L		Crustacean
EC: 918-668-5	EC50	1 - 10 mg/L		Algae
2-butoxyethanol	LC50	1490 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 111-76-2	EC50	1815 mg/L (48 h)	Daphnia magna	Crustacean
EC: 203-905-0	EC50	911 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae

12.2 Persistence and degradability:

Identification	Degradability		Biodegradab	ility
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	BOD5	Non-applicable	Concentration	Non-applicable
CAS: Non-applicable	COD	Non-applicable	Period	28 days
EC: 921-024-6	BOD5/COD	Non-applicable	% Biodegradable	98 %
Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 64742-48-9	COD	Non-applicable	Period	28 days
EC: 919-857-5	BOD5/COD	Non-applicable	% Biodegradable	80 %
2-butoxyethanol	BOD5	0.71 g O2/g	Concentration	100 mg/L
CAS: 111-76-2	COD	2.2 g O2/g	Period	14 days
EC: 203-905-0	BOD5/COD	0.32	% Biodegradable	96 %

12.3 Bioaccumulative potential:

Id	Bioaccumulation potential		
Butane		BCF	33
CAS: 106-97-8	CAS: 106-97-8 Pov		2.89
EC: 203-448-7 Po		Potential	Moderate
Propane		BCF	13
-		Pow Log	2.86
		Potential	Low
2-butoxyethanol		BCF	3
· ·		Pow Log	0.83
		Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volat	ility
Butane	Koc	900	Henry	96258,75 Pa·m³/mol
CAS: 106-97-8	Conclusion	Low	Dry soil	Yes
EC: 203-448-7	Surface tension	1,187E-2 N/m (25 °C)	Moist soil	Yes
Propane	Koc	460	Henry	71636,78 Pa·m³/mol
CAS: 74-98-6	Conclusion	Moderate	Dry soil	Yes
EC: 200-827-9	Surface tension	7,02E-3 N/m (25 °C)	Moist soil	Yes
2-butoxyethanol	Koc	8	Henry	1,621E-1 Pa·m³/mol
CAS: 111-76-2	Conclusion	Very High	Dry soil	No
EC: 203-905-0	Surface tension	2,729E-2 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS 13.1 Waste treatment methods: Code Description Waste class (Regulation (EU) No 1357/2014)

- CONTINUED ON NEXT PAGE -



According to 1907/2006/EC (REACH), 2015/830/EU

ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH SPRAY

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

gases in pressure containers (including halons) containing hazardous substances

Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP14 Ecotoxic, HP4 Irritant — skin irritation and eye damage, HP5 Specific Target Organ Toxicity (STOT) /Aspiration Toxicity

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

Transport of dangerous goods by land:

With regard to ADR 2017 and RID 2017:



UN1950 14.1 UN number:

14.2 UN proper shipping name: AEROSOLS, flammable

14.3 Transport hazard class(es):

Labels: 2.1 14.4 Packing group: N/A

14.5 Environmental hazards: Yes

14.6 Special precautions for user

190, 327, 344, 625 Special regulations:

Tunnel restriction code:

Physico-Chemical properties: see section 9

Limited quantities: 1 L

14.7 Transport in bulk according

to Annex II of Marpol and

the IBC Code:

Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 38-16:

14.1 UN number: UN1950

14.2 UN proper shipping name: AEROSOLS, flammable

14.3 Transport hazard class(es): 2 Labels: 2.1

14.4 Packing group: N/A

14.5 Environmental hazards: Yes

14.6 Special precautions for user

Special regulations: 190, 277, 327, 344, 63, 959

FmS Codes: F-D, S-U Physico-Chemical properties: see section 9

Limited quantities: 1 I

Segregation group: Non-applicable Non-applicable 14.7 Transport in bulk according

to Annex II of Marpol and the IBC Code:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2018:

- CONTINUED ON NEXT PAGE -

Revised: 13/07/2018 Date of compilation: 06/02/2014 Version: 3 (Replaced 2)



According to 1907/2006/EC (REACH), 2015/830/EU

ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH SPRAY

SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number: UN1950

14.2 UN proper shipping name: AEROSOLS, flammable

14.3 Transport hazard class(es): 2

Labels: 2.1

14.4 Packing group: N/A **14.5 Environmental hazards:** Yes

14.6 Special precautions for user

Physico-Chemical properties: see section 9

14.7 Transport in bulk according to Annex II of Marpol and

the IBC Code:

Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P3a		150	500
E2		200	500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16. OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H222: Extremely flammable aerosol

H315: Causes skin irritation

H336: May cause drowsiness or dizziness

H411: Toxic to aquatic life with long lasting effects

H229: Pressurised container: May burst if heated

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

- CONTINUED ON NEXT PAGE -



According to 1907/2006/EC (REACH), 2015/830/EU

ŚRODEK DO KONSERWACJI PROFILI ZAMKNIĘTYCH SPRAY

SECTION 16: OTHER INFORMATION (continued)

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways

Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Gas 1: H220 - Extremely flammable gas

Flam. Liq. 2: H225 - Highly flammable liquid and vapour Flam. Liq. 3: H226 - Flammable liquid and vapour

Press. Gas: H280 - Contains gas under pressure, may explode if heated

Skin Irrit. 2: H315 - Causes skin irritation

STOT SE 3: H335 - May cause respiratory irritation STOT SE 3: H336 - May cause drowsiness or dizziness

Classification procedure:

Aerosol 1: Calculation method Skin Irrit. 2: Calculation method STOT SE 3: Calculation method Aquatic Chronic 2: Calculation method Aerosol 1: Calculation method

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.