

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.04.2024

Version: 4.01 (replaces version 4.00)

Revision: 19.01.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX PROFILINE ActiFoam Energy

Article number:

06180000, 06183000, 06185050

UFI: U940-G096-W00Y-WFQG

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Car care product

Cleaning material/ Detergent

Consumer uses: Private households / general public / consumers

Professional uses

Uses advised against There is currently no information available on this.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk

1.4 Emergency telephone number:

European Union: +49 (0) 89 19240 (Poison Centre Munich)

United Kingdom: 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1A H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS05 GHS07

Signal word Danger

Hazard-determining components of labelling:

Sodium Laureth Sulfate

2-methylisothiazol-3(2H)-one

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.04.2024

Version: 4.01 (replaces version 4.00)

Revision: 19.01.2022

Trade name: SONAX PROFILINE ActiFoam Energy

(Contd. of page 1)

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P280 Wear protective gloves/eye protection.
P302+P352 IF ON SKIN: Wash with plenty of water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Aqueous tenside solution.

Dangerous components:

CAS: 68891-38-3 NLP: 500-234-8 Reg.nr.: 01-2119488639-16-xxxx	alcohols, C12-14, ethoxylated, sulfates, sodium salts ☠ Eye Dam. 1, H318; ☠ Skin Irrit. 2, H315; Aquatic Chronic 3, H412 Specific concentration limits: Eye Dam. 1; H318: C ≥ 10% Eye Irrit. 2; H319: 5 % ≤ C < 10 %	15-<20%
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35-xxxx	1-Methoxy-2-propanol ☠ Flam. Liq. 3, H226; ☠ STOT SE 3, H336	3-<5%
CAS: 308062-28-4 EC No 931-292-6 Reg.nr.: 01-2119490061-47-xxxx	Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides Alternative CAS number: 70592-80-2 ☠ Eye Dam. 1, H318; ☠ Aquatic Acute 1, H400 (M=1); Aquatic Chronic 2, H411; ☠ Skin Irrit. 2, H315	<1%
CAS: 2682-20-4 EINECS: 220-239-6 Reg.nr.: 01-2120764690-50-xxxx	2-methylisothiazol-3(2H)-one ☠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; ☠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ☠ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); ☠ Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %	>0.0015-<0.01%
CAS: 3811-73-2 EINECS: 223-296-5 Reg.nr.: 01-2119493385-28-xxxx	pyridine-2-thiol 1-oxide, sodium salt ☠ Acute Tox. 3, H311; Acute Tox. 3, H331; ☠ STOT RE 1, H372; ☠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 2, H411; ☠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH070	<0.01%

Regulation (EC) No 648/2004 on detergents / Labelling for contents

anionic surfactants	≥15 - <30%
amphoteric surfactants	<5%

(Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.04.2024

Version: 4.01 (replaces version 4.00)

Revision: 19.01.2022

Trade name: SONAX PROFILINE ActiFoam Energy

(Contd. of page 2)

perfumes (LINALOOL, CITRONELLOL), methylisothiazolinone, sodium pyrrithione, benzisothiazolinone

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Remove soiled clothing

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Wash the areas of skin affected with water and a mild detergent.

If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Eye irritation / Eye damage

Skin irritation

sensitization

Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

The normal measures for firefighting are to be taken.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

For non-emergency personnel Wear protective clothing.

For emergency responders Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Use only in well ventilated areas.

Information about fire - and explosion protection: No special measures required.

(Contd. on page 4)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.04.2024

Version: 4.01 (replaces version 4.00)

Revision: 19.01.2022

Trade name: SONAX PROFILINE ActiFoam Energy

(Contd. of page 3)

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.

Information about storage in one common storage facility:

Store away from foodstuffs.

Observe local/state/federal regulations.

Further information about storage conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

Protect from frost.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:
CAS: 107-98-2 1-Methoxy-2-propanol

WEL (Great Britain)	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm Sk
IOELV (EU)	Short-term value: 568 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm Skin
OEL (Ireland)	Short-term value: 568 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm IOELV

Regulatory information

WEL (Great Britain): EH40/2020

IOELV (EU): (EU) 2019/1831

OEL (Ireland): 2021 CoP for the Safety, Health and Welfare at Work

DNELs

CAS: 68891-38-3 alcohols, C12-14, ethoxylated, sulfates, sodium salts

Oral	DNEL	15 mg/kg (VL)
Dermal	DNEL	1,650 mg/kg (VL) 2,750 mg/kg (worker long-term)
Inhalative	DNEL	52 mg/m ³ (VL) 175 mg/m ³ (worker long-term)

CAS: 107-98-2 1-Methoxy-2-propanol

Oral	DNEL	3.3 mg/kg (consumer) (long-term / systemic effects)
Dermal	DNEL	18.1 mg/kg (consumer) (long-term / systemic effects) 50.6 mg/kg (worker) (long-term / systemic effects)
Inhalative	DNEL	43.9 mg/m ³ (consumer) (long-term / systemic effects) 553.5 mg/m ³ (worker) (short-term / local effects) 369 mg/m ³ (worker) (long-term / systemic effects)

CAS: 308062-28-4 Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides

Oral	DNEL	0.44 mg/kg bw/day (consumer) (acute systematic effects)
Dermal	DNEL	5.5 mg/kg bw/day (consumer) (longterm systematic effects) 11 mg/kg bw/day (worker) (longterm systematic effects)
Inhalative	DNEL	3.8 mg/m ³ (consumer) (longterm systematic effects) 15.5 mg/m ³ (worker) (longterm systematic effects)

PNECs

CAS: 68891-38-3 alcohols, C12-14, ethoxylated, sulfates, sodium salts

PNEC	10,000 mg/l (sewage plant)
------	----------------------------

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.04.2024

Version: 4.01 (replaces version 4.00)

Revision: 19.01.2022

Trade name: SONAX PROFILINE ActiFoam Energy

(Contd. of page 4)

	PNEC	0.24 mg/l (water (fresh water)) 0.024 mg/l (water (sea water)) 7.5 mg/kg (gro) 0.9168 mg/kg (sediment (fresh water)) 0.09168 mg/kg (sediment (sea water))
CAS: 107-98-2 1-Methoxy-2-propanol		
	PNEC	100 mg/l (STP) 100 mg/l (water (intermittent release)) 10 mg/l (water (fresh water)) 1 mg/l (water (sea water))
	PNEC	2.47 mg/kg (gro) 41.6 mg/kg (sediment (fresh water)) 4.17 mg/kg (sediment (sea water))
CAS: 308062-28-4 Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides		
Oral	PNEC	11.1 mg/kg (food)
	PNEC	24 mg/l (sewage plant) 335 mg/l (water (intermittent release)) 0.0335 mg/l (water (fresh water)) 0.00335 mg/l (water (sea water))
	PNEC	5.24 mg/kg (sediment (fresh water)) 0.524 mg/kg (sediment (sea water)) 1.02 mg/kg (soil)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection:

Not required in normal cases

Ensure good ventilation/exhaustion at the workplace.

Hand protection Protective gloves

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

[EN 374]

Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min)

Eye/face protection

Safety glasses

[EN 166]

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state

Fluid

Colour:

Brown

Odour:

Fruit-like

(Contd. on page 6)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.04.2024

Version: 4.01 (replaces version 4.00)

Revision: 19.01.2022

Trade name: SONAX PROFILINE ActiFoam Energy

(Contd. of page 5)

Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	100 °C (CAS: 7732-18-5 water)
Flammability	Product is not flammable.
Lower and upper explosion limit	
Lower:	Not applicable
Upper:	Not applicable
Flash point:	Not applicable.
Decomposition temperature:	Not determined.
pH at 20 °C	6.5 - 7.5
Viscosity:	
Kinematic viscosity at 40 °C	<20.5 mm²/s
Solubility	
water:	Fully miscible.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	23 hPa (CAS: 7732-18-5 water)
Density and/or relative density	
Density at 20 °C:	1.04-1.05 g/cm³
Vapour density	Not determined.

9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health and environment, and on safety.	
Ignition temperature:	Not applicable
Explosive properties:	Product does not present an explosion hazard.
Change in condition	
Evaporation rate	Not determined.

Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity** No dangerous reactions known.
- 10.2 Chemical stability** Stable under normal conditions.
- 10.3 Possibility of hazardous reactions** No dangerous reactions known.
- 10.4 Conditions to avoid** See Section 7 for information on safe handling.
- 10.5 Incompatible materials:** No known incompatible materials.
- 10.6 Hazardous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.04.2024

Version: 4.01 (replaces version 4.00)

Revision: 19.01.2022

Trade name: SONAX PROFILINE ActiFoam Energy

(Contd. of page 6)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

CAS: 68891-38-3 alcohols, C12-14, ethoxylated, sulfates, sodium salts

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD 50	>5,000 mg/kg (rat)

CAS: 107-98-2 1-Methoxy-2-propanol

Oral	LD50	4,016 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC0 / 6h	>7,000 ppm (rat)

CAS: 308062-28-4 Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides

Oral	LD50	1,064 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat)
	LC50 / 96 h	2.67 mg/l (Pimephales promelas)

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye damage.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Additional toxicological information:

Repeated dose toxicity

CAS: 308062-28-4 Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides

Oral	NOAEL 90 d	2,000 mg/kg (rat) (OECD 451)
	NOAEL	2,000 mg/kg (rat) (OECD 451)
		88 mg/kg (rabbit) (OECD 408)
		25 mg/kg (Ratte)

11.2 Information on other hazards

Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture.

Aquatic toxicity:

CAS: 68891-38-3 alcohols, C12-14, ethoxylated, sulfates, sodium salts

LC 50	>10-100 mg/l (Leuciscus idus)
EC0	>100 mg/l (Pseudomonas putida)
EC50	>100 mg/l (Scenedesmus subspicatus)
	>10-100 mg/l (Daphnia magna)
NOEC	>1-10 mg/l (Leuciscus idus)
	>0.1-1 mg/l (Daphnia magna)

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.04.2024

Version: 4.01 (replaces version 4.00)

Revision: 19.01.2022

Trade name: SONAX PROFILINE ActiFoam Energy

(Contd. of page 7)

CAS: 107-98-2 1-Methoxy-2-propanol

LC50 / 96h	>6,800 mg/l (<i>Leuciscus idus</i>) (DIN38412)
LC50 / 48h	23,300 mg/l (<i>Daphnia magna</i>)
EC50	>1,000 mg/l (<i>Pseudokirchneriella subcapitata</i>) (7d)
EC50/3h	>1,000 mg/l (activated sludge) (OECD 209)

CAS: 308062-28-4 Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides

NOEC 302 d	0.42 mg/l (<i>Pimephales promelas</i>)
EC10 / 18h	24 mg/l (<i>Pseudomonas putida</i>)
EC50 / 48h	3.1 mg/l (<i>Daphnia magna</i>)
EC50 / 72h	0.143 mg/l (<i>Pseudokirchneriella subcapitata</i>) (OECD 201)
NOEC / 21 d	0.7 mg/l (<i>Daphnia magna</i>) (OECD 211)
NOEC / 28d	0.067 mg/l (algae)

CAS: 2682-20-4 2-methylisothiazol-3(2H)-one

EC 20 / 3h	2.8 mg/l (activated sludge) (DIN 38412-3 (TTC-Test))
EC50/3h	34.6 mg/l (activated sludge) (DIN 38412-3 (TTC-Test))

CAS: 3811-73-2 pyridine-2-thiol 1-oxide, sodium salt

LC50 / 96h	0.00767 mg/l (<i>Zebrabärbling</i>)
EC 20 / 3h	0.48 mg/l (KS) (OECD 209)
EC50/3h	1.81 mg/l (KS) (OECD 209)
EC50 / 48h	0.022 mg/l (<i>daphnia</i>)
EC50 / 72h	0.46 mg/l (<i>Selenastrum capricornutum</i>)
NOEC / 72 h	0.08 mg/l (<i>Selenastrum capricornutum</i>) (OECD 201)

12.2 Persistence and degradability

The surface-active substances contained in the product meet the requirement of the EU Detergent Regulation (EC/648/2004) for ultimate biodegradability for surfactants in detergents.

CAS: 107-98-2 1-Methoxy-2-propanol

Biodegradation	90-100 % (OECD 301E)
----------------	----------------------

CAS: 308062-28-4 Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides

Biodegradation	90 %
----------------	------

CAS: 3811-73-2 pyridine-2-thiol 1-oxide, sodium salt

Biodegradation	>70 % (activated sludge) (OECD 301 B)
----------------	---------------------------------------

12.3 Bioaccumulative potential**CAS: 107-98-2 1-Methoxy-2-propanol**

log Kow	0.37 (25°C)
---------	-------------

CAS: 308062-28-4 Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides

log POW	2.7
---------	-----

CAS: 2682-20-4 2-methylisothiazol-3(2H)-one

BCF	3.16
log Kow	≤0.32

CAS: 3811-73-2 pyridine-2-thiol 1-oxide, sodium salt

log Kow	<-1.09 ((n-Octanol/Wasser) OECD 107)
---------	--------------------------------------

12.4 Mobility in soil No further relevant information available.**12.5 Results of PBT and vPvB assessment****PBT:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB

12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

(Contd. on page 9)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.04.2024

Version: 4.01 (replaces version 4.00)

Revision: 19.01.2022

Trade name: SONAX PROFILINE ActiFoam Energy

(Contd. of page 8)

12.7 Other adverse effects

Additional ecological information:

General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

The product does not contain organically bounded halogens (AOX-free).

The product does not contain organic complexing agents.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.

European waste catalogue

1) Disposal / product

2) Disposal / contaminated packaging

20 01 29* detergents containing hazardous substances

15 01 10* packaging containing residues of or contaminated by hazardous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN, IMDG, IATA Void

14.2 UN proper shipping name

ADR/RID/ADN, IMDG, IATA Void

14.3 Transport hazard class(es)

ADR/RID/ADN, ADN, IMDG, IATA
Class Void

14.4 Packing group

ADR/RID/ADN, IMDG, IATA Void

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user Not applicable.

14.7 Maritime transport in bulk according to IMO instruments Not applicable.

UN "Model Regulation": Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

European Directives:

Directive 2010/75/EU (VOC) 7.34 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU) not subject to
REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

(Contd. on page 10)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.04.2024

Version: 4.01 (replaces version 4.00)

Revision: 19.01.2022

Trade name: SONAX PROFILINE ActiFoam Energy

(Contd. of page 9)

National regulations:

Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

Employment restrictions concerning juveniles must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

H226 Flammable liquid and vapour.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H331 Toxic if inhaled.
H336 May cause drowsiness or dizziness.
H372 Causes damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH070 Toxic by eye contact.
EUH071 Corrosive to the respiratory tract.

Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation Serious eye damage/irritation Skin sensitisation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
--	--

Date of previous version: 22.04.2021

Version number of previous version: 4.00

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = Lethal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.04.2024

Version: 4.01 (replaces version 4.00)

Revision: 19.01.2022

Trade name: SONAX PROFILINE ActiFoam Energy

(Contd. of page 10)

*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**Skin Sens. 1: Skin sensitisation – Category 1**Skin Sens. 1A: Skin sensitisation – Category 1A**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1**Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1**Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3**** Data compared to the previous version altered.**

GB