

According to Regulation EC No 1907/2006 - REACH and Regulation EC No 1272/2008 - CLP and its later amendments

REPSOL PREMIUM GTI/TDI 10W40

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

REPSOL PREMIUM GTI/TDI 10W40 Lubricating oil. N/A
N/A N/A
N/A
N/A
N/A
N/A
RP080X

1.2 Relevant identified uses of the substance or mixture and uses advised against

Automotive applications.

1.3 Details of the supplier of the safety data sheet

Company	REPSOL LUBRICANTES Y ESPECIALIDADES, S.A.
Address	Méndez Álvaro, 44 28045 - MADRID, Spain
Phone	+34 917538000 /+34 917538100
Fax	+34 902303145
e-mail address	FDSRLESA@repsol.com

1.4 Emergency telephone number Carechem 24: +44 (0) 1235 239 670 Carechem 24: +1 215 207 0061 Carechem 24: 001866 928 0789

SECTION 2. Hazards identification

2.1 Classification of the substance or mixture	2.2 Label elements
CLASSIFICATION Reg.(CE)1272/2008(CLP)	LABELLING



Eye Irrit. 2; Eye irritation Category 2 Aquatic Chronic 3; Hazardous to the aquatic environment - chronic Category 3	Pictograms GHS07	
	Signal word	Warning
	Hazard statements	H319: Causes serious eye irritation. H412: Harmful to aquatic life with long lasting effects.
	Supplemental information	EUH 208: Contains Molybdenum polysulphide long chain alkyl dithiocarbamate complex. May produce an allergic reaction.
	Precautionary statements	 P264: Wash thoroughly after handling. P273: Avoid release to the environment. P280: Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313: If eye irritation persists: Get medical advice/attention. P501: Dispose of the container supplied for that purpose in accordance with current guidelines.

- Supplementary elements which must be displayed on the labels

N/A

- Special packaging requirements

Containers which must be provided with a child safety seal: Not applicable Tactile hazzard warning: Not applicable

2.3 Other hazards

Results of the assessment of PBT and vPvB in the product, in accordance with the criteria set out in Annex XIII of REACH, can be found in Section 12.5 of this MSDS.

Please refer to Sections 5, 6 and 7 of this MSDS for information on other dangers, different from classification dangers but which may contribute to the overall hazards of the product.

SECTION 3. Composition/information on ingredients



3.1. Substances

- Not applicable
- 3.2. Mixtures

Motor oil.

Dangerous components Reg. (CE) 1272/2008 (CLP)	Concentration (%)	Hazard statements
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) CAS: 93819-94-4 EC (EINECS): 298-577-9 Registration Number: 01-2119543726-33-XXXX	>=1,53 <=2,46	H315, H318, H411
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased CAS: 68784-26-9 EC (EINECS): 272-234-3 Registration Number: 01-2119524004-56-XXXX	>=0,30 <=1,23	H413
Branched dodecylphenol CAS: 121158-58-5 EC (EINECS): 310-154-3 Registration Number: 01-2119513207-49-XXXX	>=0,03 <=0,12	H314, H318, H360F, H400, H410, (Acute and chronic factor M = 10)
Molybdenum polysulphide long chain alkyl dithiocarbamate complex EC (EINECS): 457-320-2 Registration Number: 01-0000019337-66-XXXX	>=0,03 <=0,12	H315, H317, H412

SECTION 4. First aid measures

4.1. Description of first aid measures

Inhalation: In case of inhalation, move the affected person to an area of fresh air. Administer oxygen if necessary. Seek medical care.

Ingestion/Aspiration: Do not induce vomiting. Seek medical care.

Contact skin: Wash with soap and plenty of water. Call for medical attention.

Contact eyes: In case of contact with eyes, wash with plenty of water for at least 15 minutes. Call for medical attention.



4.2. Most important symptoms and effects, both acute and delayed

Inhalation: Repeated and prolonged exposures to high concentrations of vapor result in central nervous system damage and may cause cardiac irregularities. In low areas or confined spaces, vapors may cause asphyxia.

Ingestion/Aspiration: Intestinal absorption is very limited. Accidental intake of large amounts causes irritation of the gastrointestinal tract, nausea, vomiting and diarrhea.

Contact skin: Skin toxicity is very low in short contacts. Prolonged contact with eyes may produce stinging, irritation, and dermatitis due removal of natural fats from skin.

Contact eyes: Causes serious eye irritation. Skin toxicity is very low in short contacts.

4.3. Indication of any immediate medical attention and special treatment needed Seek medical care.

SECTION 5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Water spray, CO2, foam and dry chemical powder.

Unsuitable extinguishing media: WATER SHOULD NEVER BE USED DIRECTLY.

5.2. Special hazards arising from the substance or mixture

Combustion products: CO2, H2O, CO (in the absence of air), SO2, zinc oxides.

Special measures: Not required.

Special hazards: N/A

5.3. Advice for firefighters: Clothing and gloves resistant to fire and SCBA.

SECTION 6. Accidental release measures



6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Avoid prolonged contact with product or contaminated clothes, and avoid inhalation of vapors.

Contaminated clothing should be discarded.

Personal protection: During cleaning operation, one must use appropriate protective clothing, respiratory protection, gloves and goggles.

6.2. Environmental precautions

Serious physical contamination hazard if released (coasts, soils, etc.) Due to its floating capacity and oily consistency, which may cause damage to fauna and flora upon contact. Prevent flow into drainages, waterways or water sources.

6.3. Methods and material for containment and cleaning up

Treat as an accidental oil spill. Avoid dispersion using mechanical barriers and eliminate using physical or chemical means.

6.4. Reference to other sections

Section 8 contains more detailed advice on personal protective equipment and section 13 on waste disposal.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

General precautions: Avoid prolonged contact with the product and prolonged inhalation of vapors or mists from the product.

During transfer avoid contact with air, use properly grounded pumps and connections to prevent generation of electrostatic charges.

In case of air pollution in the place of production or work, air must be filtered before discharge. Ensure safe systems of work.

Specific conditions: Safety goggles or face-shield and gloves are recommended to protect from splashes.

Do not cut nor weld in areas close to filled tanks.

Follow similar precautions with empty containers.

Before making any repairs to a tank, make sure it is properly drained and washed and check inside for explosive atmosphere.

7.2. Conditions for safe storage, including any incompatibilities

Temperature and decomposition products: The incomplete combustion of the product can produce CO and other asphyxiating substances.



Dangerous reactions: N/A

Storage conditions: Drums properly sealed in cool and ventilated places. Do not smoke, weld or do any work that can produce flames or sparks in storage area. This product should be stored below 45°C.

Incompatible materials: Strong oxidizing substances.

7.3. Specific end use(s)

See section 1 or exposure scenario

SECTION 8. Exposure controls/personal protection

8.1 Control parameters

Mineral oil mists INSHT (Spain):VLA-ED: 5 mg/m3 / VLA-EC: 10 mg/m3 ACGIH(USA): TLV-TWA:5 mg/m3. Työterveyslaitos, Sosiaali- ja terveysministeriö (Finland): TWA:5 mg/m3. Lijst Grenswaarden / Valeurs Limites (Belgium):TWA: 5 mg/m³/ STEL: 10 mg/m³. РБ МТСП и МЗ Наредба №13/2003 (Bulgaria): limit value 5 mg/m3. 178/2001 (Czech Republic):TWA: 5 mg/m3 / CEIL: 10 mg/m3. Arbeidstilsynet (Denmark): GV: 1 mg/m³. PD 90/1999 (Greece): TWA: 5 mg/m³. EüM-SzCsM (Hungary): CEIL: 5 mg/m³. NAOSH (Ireland): OELV: 5 mg/m3. Ministero della Salute (Italy): TWA: 5 mg/m³. LV Nat. Standardisation and Meterological Centre (Latvia):TWA: 5 mg/m³. Del Lietuvos Higienos Normos (Lithuania): TWA: 1 mg/m³/ STEL: 3 mg/m³. Nationale MAC-lijst (Holland): TGG: 5 mg/m3. Arbeidstilsynet (Norway): AN: 1 mg/m³. Rozporządzenie Ministra Pracy i Polityki Społecznej (Poland): TWA: 5 mg/m3 / STEL: 10 ma/m³. Instituto Português da Qualidade (Portugal): TLV-TWA: 5 mg/m³/ STEL: 10 mg/m³. Ministerul Muncii, Solidarității Sociale și Familiei, și Ministerul Sănătății Publice (Romania): VLA: 5 mg/m³ / Termen scurt: 10 mg/m³. Nariadenie Vlády Slovenskej republiky (Slovakia): TWA: 5 mg/m³. AFS 2005:17 (Sweden): NGV: 1 mg/m3 / KTV: 3 mg/m3. EH40-MEL (United Kingdom, 2002): TWA: 5 mg/m³.

DNEL

CAS: 93819-94-4 DNELs for workers Long term exposure, systemic effects, dermal (mg/kg/day): 0,58 Long term exposure, systemic effects, inhalation (mg/m3): 8,31



DNELs for consumers Long term exposure, systemic effects, dermal (mg/kg/day): 0,29 Long term exposure, systemic effects, inhalation (mg/m3): 2,11 Long term exposure, systemic effects, oral (mg/kg/day): 0,24

CAS: 68784-26-9 DNELs for workers: Dermal, short term systemic effects: 80 mg / kg Inhalation, short term systemic effects: 167 mg / m3 Dermal, long-term systemic effects: 20,8 mg / kg Inhalation, systemic long term effects: 70.52 mg / m3

DNELs for consumers: Dermal, short term systemic effects: 40 mg / kg Inhalation, short term systemic effects: 0.167 mg / m3 Oral, short term systemic effects: 50 mg / kg Dermal, long-term systemic effects: 10.42 mg / kg Inhalation, systemic long term effects: 52.6 mg / m3 Oral long-term systemic effects: 5 mg / kg

PNEC

CAS: 93819-94-4 PNEC water PNEC aqua - freshwater (mg/L): 0,004 PNEC aqua - marine water (mg/L): 0,0046

PNEC sediments PNEC sediment - freshwater (mg/kg): 0,0116 PNEC sediment - marine water (mg/kg): 0,0116

PNEC soil PNEC soil (mg/kg): 0,00528

PNEC Sewage treatment plant PNEC STP (mg/l): 100

PNEC oral (secondary poisoning) PNEC oral (mg/kg): 10,67

CAS: 68784-26-9 PNEC water Freshwater PNEC (mg / L): 0.5 Seawater PNEC (mg / L): 0.04

PNEC sediment PNEC freshwater sediments (mg / kg): 43500 PNEC marine sediment water (mg / kg): 3480

PNEC soil PNEC soil (mg / kg): 8850



8.2 Exposure controls

Avoid contact with the product and inhalation of product mists and vapors. Local exhaust ventilation (LEV) close to generation point.

Individual protection measures, such as personal protective equipment

Respiratory protection: Low vapor pressure; the product is slightly volatile at room temperature and does not have special risks. In presence of heated oils, wear respiratory protection to avoid inhalation of vapors or mists.

Skin protection: Gloves (polyethylene, polyvinyl chloride and neoprene; do not use natural rubber or butyl).

Eye/face protection: Goggles to protect from splashes.

Other protective equipment: Showers and eye-washers in the work area.

Specific hygiene measures: Contaminated footwear should be discarded. Contaminated clothing should not be taken home for laundering with other clothing. Regular changing of underwear is also important to avoid possible penetration from outer clothing. Washing/Showering facilities with a non-solvent based skin cleanser, hot water and soap must be provided and used. Use skin reconditioning cream after work.

Medical Conditions Aggravated by Exposure: Respiratory tract deficiencies and dermatological problems.

Environmental exposure controls:

Product should not reach the environment through wastewater or sewage. Measures to take in case of accidental release can be found in Section 6 of this MSDS.

SECTION 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: N/A (*) Odour: N/A (*) Odour threshold: N/A (*) Colour: 3.0 max. (ASTM D-1500) pH: N/A (*) Melting point/freezing point: -39°C typical (ASTM D-97) Initial boiling point and boiling range: N/A (*) Flash point: 230°C (ASTM D-92) Evaporation rate: N/A (*) Flammability (solid, gas): N/A (*) Upper/lower flammability or explosive limits: N/A (*) Vapour pressure: N/A (*) Vapour density: N/A (*) Density: 0,877 g/cm³ (15 °C). ASTM D-4052 Typical Solubility(ies: N/A (*)



Partition coefficient: n-octanol/water: N/A (*) Auto-ignition temperature: N/A (*) Decomposition temperature: N/A (*) Viscosity: (100 °C) 14 cSt (40 °C) 93 cSt Typical (ASTM D-445) Explosive properties: N/A (*) Oxidising properties: N/A (*)

9.2 Other information

N/A (*)

(*) No data available at the time of writing or because it is not applicable due to the nature and danger of the product.

SECTION 10. Stability and reactivity

- 10.1. Reactivity: N/A
- **10.2.** Chemical stability: Stable product at room temperature.
- **10.3. Possibility of hazardous reactions:** The strong oxidants react in contact with oils and organic matter in general.
- **10.4.** Conditions to avoid: Exposure to open flames.
- **10.5.** Incompatible materials: N/A
- **10.6. Hazardous decomposition products:** The incomplete combustion of the product can produce CO and other asphyxiating substances.

SECTION 11. Toxicological information

11.1. Information on toxicological effects

The provided toxicological information results from the application of Annexes VII to XI of Regulation 1907/2006 (REACH).

Acute toxicity:

CAS: 93819-94-4. Oral LD50: 2,600 mg/kg; Dermal LD50: > 3,160 mg/kg. CAS 68784-26-9. Rat oral LD50: >5000 mg/kg; Rabbit dermal LD50: >4000 mg/kg; Rat inhalation LC50: >1,67 mg/l (1h).

Skin corrosion/irritation: N/A

Serious eye damage/irritation: Causes serious eye irritation.

Respiratory or skin sensitisation: N/A



Germ cell mutagenicity: N/A

Carcinogenicity: Lubricant base oil. IARC classification: Group 3 (not classifiable as to carcinogenicity in humans)

Product rating corresponds to the comparison of the results from the toxicological studies with the criteria set out in Regulation (EC) No 1272/2008 for CMR, categories 1A and 1B.

Reproductive toxicity: No evidence exists.

STOT-single exposure: N/A

STOT-repeated exposure: N/A

Aspiration hazard: N/A

SECTION 12. Ecological information

- 12.1. Toxicity: Harmful to aquatic life with long lasting effects.
 CAS: 93819-94-4. LC50: 4,5 mg/l (96h) (Fish-Trout. Oncorhynchus mykiss).
 CAS 68784-26-9. NOEC: 1000 mg/l; (96 h.); Pimephales promelas; OECD 203.
 CE: 457-320-2. LC50:94,8 mg/l (96h) (Fish-Trout. Oncorhynchus mykiss).
- **12.2. Persistence and degradability:** The material is oily and viscous and floats on water. It presents a high physical contamination potential, mainly in sea-spills; destroys small aquatic organisms upon contact and makes living difficult for lower organisms, not allowing the sunlight to reach underlying marine ecosystems, affecting its normal development. Not readily biodegradable.
- **12.3. Bioaccumulative potential:** There are no data to indicate that the product is significantly bioaccumulated by aquatic organisms or incidence in the trophic food web, although it may cause long-term adverse effects in the aquatic environment, due to its high physical contamination potential.
- **12.4.** Mobility in soil: N/A
- **12.5. Results of PBT and vPvB assessment:** This mixture contains no substance considered to be PBT or vPvB.
- **12.6.** Other adverse effects: N/A

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Disposal: Recycle and recover base oils when possible. In landfills and incineration managed by authorized agents. Avoid releasing waste oils to sewers because they can destroy water



treatment plant microorganisms.

Handling: Sealed containers. Avoid direct contact with waste.

Provisions: Establishments and companies which recover, dispose, store, transport or handle waste should comply with Dir. 2008/98/EC on waste, or other local, national or community provisions.

SECTION 14. Transport information

- 14.1. UN number: N/A
- 14.2. UN proper shipping name: N/A
- 14.3. Hazard classes for transportation: N/A
- 14.4. Packing group

ADR/RID: N/A

IATA-DGR: N/A

IMDG: N/A

14.5. Environmental hazards

ADR/RID: N/A

IATA-DGR: N/A

IMDG: N/A

- **14.6.** Special precautions for user Stable at room temperature and during transport. Store in cool areas.
- 14.7. Transport in bulk in accordance with appendix II of the Marpol agreement and the IBC code

No category assigned for the IBC code.

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

COMMISSION REGULATION (EU) No 2015/830. Globally Harmonized System of Classification and Labelling of Chemicals (GHS). Regulation (EC) No 1272/2008 of the European Parliament and the Council of 16 December 2008 on classification, labeling and packaging of substances and mixtures (CLP). Regulation (EC) No 1907/2006 concerning Registration, Evaluation, Authorization and



Restriction of Chemicals (REACH). European Agreement concerning the international carriage of dangerous goods by road (ADR). Regulation on the international transport of dangerous goods on the railway. (RID) International maritime code of dangerous goods. (IMDG) International Air Transport Association (IATA) regulation pertaining to air shipment. International Bulk Chemical Code (IMSBC Code), MARPOL 73/78.

 $\begin{array}{l} \mbox{Commission Regulation Other hazards} \\ \mbox{N/A} \end{array}$

15.2. Chemical safety assessment A chemical safety assessment has not been carried out.

SECTION 16. Other information

Glossary

MSDS: Material safety data sheet CAS: Chemical Abstract Service IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists. TLV: Threshold Limit Value TWA: Time Weighted Average STEL: Short-term Exposure Level **REL: Recommendable Exposure Limit** PEL: Permissible Exposure Limit INSHT: Instituto Nacional de Seguridad e Higiene en el Trabajo. VLA-ED: Environmental limit value - daily exposure VLA-EC: Limit environmental value - short exposure DNEL/DMEL: Derived no-effect level / Derivation of minimal effects levels PNEC: Predicted No Effect Concentration LD50: Lethal Dose Medium LC50: Lethal Concentration Medium EC50: Effective Concentration Medium IC50: Inhibitory Concentration Medium BOD: Biological Oxygen Demand. NOAEL: No observable adverse effect level NOEL: No observed effect level NOAEC: No observed adverse effect concentration NOEC: No observed effect concentration N/A: Not applicable || - | : Changes from the last revision

Data Bases consulted

EINECS: European Inventory of Existing Commercial Substances. TSCA: Toxic Substances Control Act, US Environmental Protection Agency. HSDB: US National Library of Medicine. RTECS: US Dept. of Health & Human Services.



Hazard Class-and-Category shown in the document

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H360F: May damage fertility.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

H413: May cause long lasting harmful effects to aquatic life.

Purchasing companies have an obligation to ensure that their employees are properly trained on the safe handling and use of the product in accordance with the guidelines contained in this MSDS.

Furthermore, companies purchasing this product are required to inform their employees, and individuals who could manipulate or use it within their facilities, about all indications included in the MSDS, in particular those relating to the product's risks to the health and safety of people and to the environment.

The information given in this document has been compiled based on the best existing information sources, latest available knowledge and according to the current requirements on classification, packaging and labelling of hazardous substances. It does not imply the information is exhaustive or accurate in all cases. It is the user's responsibility to determine the validity of the information contained in this Material Safety Data Sheet to apply depending on the case.