

SAFETY DATA SHEET STP® Power Steering Fluid

According to Regulation (EC) No 1907/2006, Annex II, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name STP® Power Steering Fluid

Product number 00204, 17699

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Power steering fluid.

Uses advised againstNo specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Energizer Trading Ltd

Sword House Totteridge Road High Wycombe HP13 6DG

UK

Tel: +44 845 602 1995 euregulatory@energizer.com

1.4. Emergency telephone number

Emergency telephone +44 1495 350234

Monday - Thursday: 0830 - 1700

Friday: 0830 - 1530

National emergency telephone Product information has been submitted to the UK National Poisons Information Service

number (NPIS) and is accessible to medical health professionals.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Hazard statements NC Not Classified

Precautionary statements P102 Keep out of reach of children.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

STP® Power Steering Fluid

Distillates (petroleum), hydrotreated heavy paraffinic

CAS number: 64742-54-7 EC number: 265-157-1 REACH registration number: 01-

2119484627-25-XXXX

50 - 100%

Classification
Not Classified

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing.

Inhalation If throat irritation or coughing persists, proceed as follows. Remove person to fresh air and

keep comfortable for breathing. Get medical attention if symptoms are severe or persist.

Ingestion Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person.

Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if

symptoms are severe or persist.

Skin contact Remove contaminated clothing and rinse skin thoroughly with water. Continue to rinse for at

least 15 minutes. Get medical attention if symptoms are severe or persist after washing.

Eye contact Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do.

Continue rinsing. Get medical attention if symptoms are severe or persist after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Prolonged or repeated exposure to vapours in high concentrations may cause the following

adverse effects: Drowsiness. Dizziness.

Ingestion May cause discomfort if swallowed.

Skin contact Prolonged skin contact may cause redness and irritation.

Eye contact May cause irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically. Keep affected person under observation.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-

extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances: Oxides

of carbon. Toxic gases or vapours.

STP® Power Steering Fluid

5.3. Advice for firefighters

Protective actions during

firefighting

Use water to keep fire exposed containers cool and disperse vapours.

Special protective equipment

for firefighters

Use protective equipment appropriate for surrounding materials. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Eliminate all

ignition sources if safe to do so. Avoid contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage. Eliminate all ignition sources if safe to do so. Do not touch or walk into spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Use only non-sparking tools. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Reference to other sections

See Section 11 for additional information on health hazards. For waste disposal, see Section

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Ground/bond container and receiving equipment. Take precautionary measures against static discharges. Keep away from heat, sparks and open flame. Provide adequate ventilation.

Advice on general occupational hygiene

Avoid contact with eyes and prolonged skin contact. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in a cool and well-ventilated place. Keep away from heat, sparks and open flame. Take

precautionary measures against static discharges.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Distillates (petroleum), hydrotreated heavy paraffinic

Long-term exposure limit (8-hour TWA): 5 mg/m³

Distillates (petroleum), hydrotreated heavy paraffinic (CAS: 64742-54-7)

STP® Power Steering Fluid

DNEL Workers - Inhalation; Long term local effects: 5.6 mg/m³

General population - Inhalation; Long term local effects: 1.2 mg/m³

PNEC Oral; 9.33 mg/kg

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts (CAS: 68442-22-8)

DNEL Workers - Inhalation; Long term systemic effects: 8.05 mg/m³

Workers - Dermal; Long term systemic effects: 11.4 mg/kg/day

General population - Inhalation; Long term systemic effects: 1.98 mg/m³ General population - Dermal; Long term systemic effects: 5.71 mg/kg/day General population - Oral; Long term systemic effects: 0.24 mg/kg/day

PNEC Fresh water; 4 μg/l

marine water; 4.6 µg/l

STP; 100 mg/l

Sediment (Freshwater); 0.045 mg/kg Sediment (Marinewater); 0.005 mg/kg

Soil; 0.007 mg/kg Oral; 10.67 mg/kg

8.2. Exposure controls

Protective equipment





Appropriate engineering controls

Provide adequate ventilation. All handling should only take place in well-ventilated areas. Avoid inhalation of vapours and spray/mists. Use explosion-proof electrical, ventilating and

lighting equipment.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Wear tight-fitting, chemical splash goggles

or face shield.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Frequent changes are recommended.

Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures

Do not smoke in work area. Wash promptly with soap and water if skin becomes

contaminated. Wash at the end of each work shift and before eating, smoking and using the

toilet.

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective

equipment is suitable for its intended use and is 'CE'-marked.

Environmental exposure

controls

Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

STP® Power Steering Fluid

Appearance Coloured liquid.

Colour Yellow.

Odour Petroleum.

Odour threshold Not determined.

pH Not determined.

Melting point Not relevant.

Initial boiling point and range Not determined.

Flash point 220°C Open cup.

Evaporation rate Not determined.

Evaporation factor Not determined.

Flammability (solid, gas) Not relevant.

Upper/lower flammability or

explosive limits

Not relevant.

Vapour pressure Not determined.

Vapour density Not determined.

Relative density 0.86 @ 15°C

Bulk density

Not determined.

Solubility(ies)

Insoluble in water.

Partition coefficient

Not determined.

Auto-ignition temperature >270°C

Decomposition Temperature Not relevant.

Viscosity 44 cSt @ 40°C

7 cSt @ 100°C

Explosive properties Not considered to be explosive.

Oxidising properties The mixture itself has not been tested but none of the ingredient substances meet the criteria

for classification as oxidising.

9.2. Other information

Other information No information required.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

Will not polymerise.

reactions

10.4. Conditions to avoid

STP® Power Steering Fluid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Keep away from oxidising materials, heat and flames.

10.6. Hazardous decomposition products

Hazardous decomposition

None at ambient temperatures. Thermal decomposition or combustion products may include

the following substances: Oxides of the following substances: Carbon. Nitrogen. Zinc.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

products

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Genotoxicity - in vivoBased on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Not anticipated to present an aspiration hazard, based on chemical structure.

SECTION 12: Ecological information

12.1. Toxicity

Toxicity Not considered toxic to fish. However, large or frequent spills may have hazardous effects on

the environment.

STP® Power Steering Fluid

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

12.4. Mobility in soil

Mobility The product is soluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.

STP® Power Steering Fluid

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Commission Regulation (EU) No 2015/830 of 28 May 2015.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet ADR: European Agreement concerning the International Carriage of Dangerous Goods by

RID: European Agreement concerning the International Carriage of Dangerous Goods by

Rail.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association.

ADN: European Agreement concerning the International Carriage of Dangerous Goods by

Inland Waterways.

ATE: Acute Toxicity Estimate. DNEL: Derived No Effect Level.

LC₅o: Lethal Concentration to 50 % of a test population.

LD₅o: Lethal Dose to 50% of a test population (Median Lethal Dose).

PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative.

BCF: Bioconcentration Factor.

Classification procedures according to Regulation (EC)

1272/2008

Revision comments

Not classified.: Calculation method.

Section 1: Identification of the substance/mixture and of the company/undertaking // 1.3.

Details of the supplier of the safety data sheet.

Revision date 19/03/2020

Revision 11

Supersedes date 03/07/2018

SDS number 637

The information supplied here is accurate to the best knowledge and belief of Energizer Trading Ltd, it is however, not intended as a warranty or representation, and should not be construed as such, for which Energizer Trading Ltd assumes any legal responsibility. Any information or advice obtained from Energizer Trading Ltd other than by means of this publication, and whether relating to Energizer Trading Ltd's products or other materials is also given in good faith. It remains at all times the responsibility of the customer, and user, to ensure that the materials are suitable for the particular purpose intended. Materials not manufactured, or supplied, by Energizer Trading Ltd when used instead of, or in conjunction with materials supplied by Energizer Trading Ltd, it is the customer's responsibility to ensure that all technical, and other information related to such materials is obtained from the manufacturer or supplier. Energizer Trading Ltd accepts no liability for the data contained within this document, as the information herein may be applied under conditions beyond our control, and in situations with which we may be unfamiliar. The information contained within this document is furnished upon condition that the customer and user of this product makes his own determination of the suitability of the product for his particular purpose.