

# **PROTECTIVE 50 HEAVY DUTY Ready to use (820893, 820894)**

Revision nr. 2

Dated 19/01/2021 First compilation

Printed on 19/01/2021

Page n. 1/15

# Safety Data Sheet According to Annex II to REACH - Regulation 2015/830

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product name

PROTECTIVE 50 HEAVY DUTY Ready to use - 820893, 820894

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

PREDILUTED COOLANT (for B2C) Intended use

Identified Uses	Industrial	Professional	Consumer
De-icing and anti-icing applications	~	<b>~</b>	<b>~</b>
1.3. Details of the supplier of the safety data shee	t		
Name	Valeo Service UK Limited		
Full address	Heming Road, Washford	00.007	
District and Country	Redditch, Worcestershire BS ENGLAND	98 002	
	Tel. +44 1527 838 300		
	Fax +44 1527 523 732		
e-mail address of the competent person			
responsible for the Safety Data Sheet	vsa.uk.technical.mailbox@v	aleo.com	
1.4. Emergency telephone number	. 444507020200 (business b	1	
For urgent inquiries refer to	+441527838300 (business he 844 892 0111 (24 hrs)	ours)	
	· · · · · · · · · · · · · · · · · · ·		

# **SECTION 2. Hazards identification**

### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Acute toxicity, category 4 H302 Specific target organ toxicity - repeated exposure, category 2 H373 Harmful if swallowed.

May cause damage to organs through prolonged or repeated

exposure.

### 2.2. Label elements



# PROTECTIVE 50 HEAVY DUTY Ready to use (820893, 820894)

Revision nr. 2

Dated 19/01/2021 First compilation

Printed on 19/01/2021

Page n. 2/15

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

### Hazard pictograms:





Signal words: Warning

Hazard statements:

H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

**P501** Dispose of contents/container in accordance with local/regional/national/international regulations.

P314 Get medical advice / attention if you feel unwell.
P270 Do not eat, drink or smoke when using this product.

P264 Wash hands thoroughly after handling.

Contains: ETHANEDIOL

SODIUM NITRITE

## 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

# **SECTION 3. Composition/information on ingredients**

### 3.2. Mixtures

### Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

**ETHANEDIOL** 

CAS 107-21-1  $45 \le x < 50$  Acute Tox. 4 H302, STOT RE 2 H373

EC 203-473-3 INDEX 603-027-00-1

Reg. no. 01-2119456816-28-xxxx

**SODIUM NITRITE** 

CAS 7632-00-0 0,1 ≤ x < 0.25 Ox. Sol. 2 H272, Acute Tox. 3 H301, Aquatic Acute 1 H400 M=1

EC 231-555-9 INDEX 007-010-00-4



# PROTECTIVE 50 HEAVY DUTY Ready to use (820893, 820894)

Revision nr. 2

Dated 19/01/2021

First compilation

Printed on 19/01/2021

Page n. 3/15

The full wording of hazard (H) phrases is given in section 16 of the sheet.

# **SECTION 4. First aid measures**

### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

# **SECTION 5. Firefighting measures**

### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

### 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

### 5.3. Advice for firefighters

### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

# **SECTION 6. Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.



# PROTECTIVE 50 HEAVY DUTY Ready to use (820893, 820894)

Revision nr. 2

Dated 19/01/2021 First compilation

Printed on 19/01/2021

Page n. 4/15

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

# 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Information not available

# **SECTION 8. Exposure controls/personal protection**

### 8.1. Control parameters

### Regulatory References:

BGR	България	МИНИСТЕРСТВО НА ТРУДА И СОЦИАЛНАТА ПОЛИТИКА МИНИСТЕРСТВО НА
075	×	ЗДРАВЕОПАЗВАНЕТО НАРЕДБА No 13 от 30 декември 2003 г (4 Септември 2018г)
CZE	Česká Republika	Nařízení vlády č. 246/2018 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
DNK	Danmark	Bekendtgørelse om ændring af bekendtgørelse om grænseværdier for stoffer og materialer1- BEK nr 655
		af 31/05/2018
ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
EST	Eesti	Töökeskkonna keemiliste ohutegurite piirnormid. Vastu võetud Vabariigi Valitsuse 18. septembri 2001. a
		määrusega nr 293 (RT I 2001, 77, 460), jõustunud 29.09.2001. Muudetud järgmise määrusega (kuupäev,
		number, avaldamine Riigi Teatajas, jõustumise aeg): 11.10.2007 nr 223 (RT I 2007, 55, 369) 1.01.2008
CINI	0:	
FIN	Suomi	HTP-VÄRDEN 2018. Koncentrationer som befunnits skadliga. SOCIAL- OCH
		HÄLSOVÅRDSMINISTERIETS PUBLIKATIONER 10/2018
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition published 2018)
GRC	Ελλάδα	ΕΦΗΜΕΡΙΔΑ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 152 - 21 Αυγούστου 2018
HRV	Hrvatska	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti
THIN	HValona	
		i biološkim graničnim vrijednostima (NN 91/18)



OEL EU

I VA

NLD

SVK

SWE

TUR

ΕU

ETHANEDIO

# **PROTECTIVE 50 HEAVY DUTY Ready to use (820893, 820894)**

Revision nr. 2

Dated 19/01/2021 First compilation

Printed on 19/01/2021

Page n. 5/15

HUN Magyarország A pénzügyminiszter 7/2018. (VIII. 29.) PM rendelete a munkahelyek kémiai biztonságáról szóló 25/2000.

(IX. 30.) EüM-

SZCSM együttes rendelet módosításáról

Italia DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017 LTU Lietuva

LIETŲVOS HIGIENOS NORMA HN 23:2011 "CHEMINIŲ MEDŽIAGŲ PROFESINIO POVEIKIO RIBINIAI

DYDŽIAI. MATAVIMO IR POVEIKIO VERTINIMO BENDRIEJI REIKALAVIMAI. Nr. V-695/A1-272, 2018-

06-12, paskelbta TAR 2018-06-15, i. k. 2018-09988

Ķīmisko vielu aroda ekspozīcijas robežvērtības (AER) darba vides gaisā 2018 Latviia Nederland

Regeling van de Staatssecretaris van Sociale Zaken en Werkgelegenheid van 13 juli 2018. 2018-

0000118517 tot wijziging van de Arbeidsomstandighedenregeling in verband met de implementatie van

Richtlijn 2017/164 in Bijlage XIII

NOR Norge Fastsatt av Arbeids- og sosialdepartementet 21. august 2018 med hjemmel i lov 17. juni 2005 nr. 62 om

arbeidsmiljø, arbeidstid, stillingsvern mv. (arbeidsmiljøloven) § 1-3, § 1-4 og § 4-5

Slovensko

Nariadenie vlády Š. 33/2018 Z. z. Nariadenie vlády Slovenskej republiky, ktorým sa mení a dopíňa nariadenie vlády Slovenskej republiky č. 355/2006 Z. z. o ochrane zamestnancov pred rizikami súvisiacimi s expozíciou chemickým faktorom pri práci v znení neskorších predpisov

Sverige Hygieniska gränsvärden, AFS 2018:1 Türkiye

KİMYASAL MADDELERLE ÇALIŞMALARDA SAĞLIK VE GÜVENLİK ÖNLEMLERİ HAKKINDA

YÖNETMELİK - Resmi Gazete Tarihi: 12.08.2013 Resmi Gazete Sayısı: 28733

Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive

2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.

TLV-ACGIH **ACGIH 2019** 

Туре	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	52		104		SKIN
TLV	CZE	50		100		SKIN
AGW	DEU	26	10	52	20	SKIN
MAK	DEU	26	10	52	20	SKIN
TLV	DNK	26	10			SKIN
VLA	ESP	52	20	104	40	SKIN
TLV	EST	52	20	104	40	SKIN
HTP	FIN	50	20	100	40	SKIN
VLEP	FRA	52	20	104	40	SKIN
WEL	GBR	52	20	104	40	
TLV	GRC	125	50	125	50	
GVI/KGVI	HRV	52	20	104	40	SKIN
AK	HUN	52		104		
VLEP	ITA	52	20	104	40	SKIN
RD	LTU	25	10	50	20	SKIN
RV	LVA	52	20	104	40	SKIN
TGG	NLD	52		104		SKIN
TLV	NOR		25			SKIN
NPEL	SVK	52	20	104		SKIN
NGV/KGV	SWE	25	10	50	20	SKIN
ESD	TUR	52	20	104	40	SKIN
OEL	EU	52	20	104	40	SKIN
TLV-ACGIH				100 (C)		

Predicted no-effect concentration - PNEC



VALEO SERVICE Revision nr. 2

Dated 19/01/2021

First compilation

Printed on 19/01/2021



# PROTECTIVE 50 HEAVY DUTY Ready to use (820893, 820894)

Page n. 6/15

Normal value in fresh water	10	mg/l	
Normal value in marine water	1	mg/l	_
Normal value for fresh water sediment	20,9	mg/kg	_
Normal value for water, intermittent release	10	mg/l	
Normal value of STP microorganisms	199,5	mg/l	
Normal value for the terrestrial compartment	1,53	mg/kg	

Health - Derived no-effe	ct level - DNEL / D	OMEL						
	Effects on				Effects on			
	consumers				workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic
				systemic		systemic		systemic
Inhalation			7 mg/m3	VND			35 mg/m3	VND
Skin			VND	53 mg/kg/d			VND	106 mg/kg/d

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

# HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with



# PROTECTIVE 50 HEAVY DUTY Ready to use (820893, 820894)

Revision nr. 2

Dated 19/01/2021 First compilation

Printed on 19/01/2021

Page n. 7/15

standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

### **ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

# **SECTION 9. Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Appearance liquid Colour pink

Odour characteristic Odour threshold Not available 7,5 - 10 °C -37 Melting point / freezing point Initial boiling point > 100 °C Boiling range Not available > 125 °C Flash point **Evaporation Rate** Not available Flammability of solids and gases Not available Lower inflammability limit Not available Upper inflammability limit Not available Lower explosive limit 4,9 % (V/V) Upper explosive limit 14,6 % (V/V) Vapour pressure Not available Vapour density Not available 1,050 - 1,080 Relative density Solubility soluble Partition coefficient: n-octanol/water -1,93 > 400 °C Auto-ignition temperature Decomposition temperature Not available Viscosity Not available Explosive properties Not available

Not available

# 9.2. Other information

Oxidising properties

VOC (Directive 2010/75/EC): 0
VOC (volatile carbon): 0

# **SECTION 10. Stability and reactivity**

# 10.1. Reactivity



# PROTECTIVE 50 HEAVY DUTY Ready to use (820893, 820894)

Revision nr. 2

Dated 19/01/2021

First compilation

Printed on 19/01/2021

Page n. 8/15

The product may react exothermically on contact with strong oxidising or reducing agents, strong acids or bases.

### 10.2. Chemical stability

Excessively high temperatures can cause thermal decomposition.

ETHANEDIOL

Reacts with strong oxidising agents.

### 10.3. Possibility of hazardous reactions

See paragraph 10.1.

#### 10.4. Conditions to avoid

Avoid overheating.

ETHANEDIOL

ETHANEDIOL: avoid exposure to sources of heat and naked flames.

# 10.5. Incompatible materials

Oxidising or reducing agents. Strong acids or bases.

Do not store in zinc-coated.

# 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHANEDIOL

ETHANEDIOL: hydroxyacetaldehyde, glyoxal, acetaldehyde, methane, formaldehyde, carbon monoxide, hydrogen.

# **SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

### 11.1. Information on toxicological effects

ETHANEDIOL



# **PROTECTIVE 50** HEAVY DUTY Ready to use (820893, 820894)

Revision nr. 2

Dated 19/01/2021

First compilation

Printed on 19/01/2021

Page n. 9/15

ETHANEDIOL: following ingestion it initially stimulates the CNS; later on depression results. Renal damage with anuria and uremia may occur. Symptoms of over exposure are: vomiting, somnolence, difficulty in breathing, convulsions. The lethal dose in man is approximately 1.4 l/kg. The way of

entry is inhalation and ingestion.

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

### **ACUTE TOXICITY**

LC50 (Inhalation) of the mixture: Not classified (no significant component) LD50 (Oral) of the mixture: 595,24 mg/kg LD50 (Dermal) of the mixture: Not classified (no significant component)

SODIUM NITRITE

LD50 (Oral) 180 mg/kg Rat

ETHANEDIOL

LD50 (Oral) > 300 mg/kg

LD50 (Dermal) > 5000 mg/kg Rabbit

# SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

# SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION



# PROTECTIVE 50 HEAVY DUTY Ready to use (820893, 820894)

Revision nr. 2

Dated 19/01/2021 First compilation

Printed on 19/01/2021

Page n. 10/15

Does not meet the classification criteria for this hazard class

### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

# REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

### STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

### STOT - REPEATED EXPOSURE

May cause damage to organs

### **ASPIRATION HAZARD**

Does not meet the classification criteria for this hazard class

# **SECTION 12. Ecological information**

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

## 12.1. Toxicity

### SODIUM NITRITE

LC50 - for Fish0,79 mg/l/96h Oncorhynchus mykissEC50 - for Crustacea23,31 mg/l/48h Penaeus monodonEC50 - for Algae / Aquatic Plants159 mg/l/72h Tetraseimis chui

### **ETHANEDIOL**

### 12.2. Persistence and degradability



# **PROTECTIVE 50 HEAVY DUTY Ready to use (820893, 820894)**

Revision nr. 2

Dated 19/01/2021

First compilation Printed on 19/01/2021

Page n. 11/15

#### SODIUM NITRITE

Solubility in water 848000 mg/l

Degradability: information not available

FTHANEDIOL

Rapidly degradable

12.3. Bioaccumulative potential

SODIUM NITRITE

Partition coefficient: n-octanol/water -3,7

FTHANEDIOL

Partition coefficient: n-octanol/water -1,93

12.4. Mobility in soil

ETHANEDIOL

ETHANEDIOL: very mobile in soil.

12.5. Results of PBT and vPvB assessment

ETHANEDIOL

ETHANEDIOL: is not considered to be PBT or vPvB.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### 12.6. Other adverse effects

Information not available

# **SECTION 13. Disposal considerations**

### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# **SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

## 14.1. UN number



# PROTECTIVE 50 HEAVY DUTY Ready to use (820893, 820894)

Revision nr. 2

Dated 19/01/2021

First compilation
Printed on 19/01/2021

Page n. 12/15

Not applicable
14.2. UN proper shipping name
Not applicable
14.3. Transport hazard class(es)
Not applicable
14.4. Packing group
Not applicable
14.5. Environmental hazards
Not applicable
14.6. Special precautions for user
Not applicable
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code
Information not relevant
SECTION 15. Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Seveso Category - Directive 2012/18/EC: None
Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006
Product Point 3



# PROTECTIVE 50 HEAVY DUTY Ready to use (820893, 820894)

Revision nr. 2

Dated 19/01/2021 First compilation

Printed on 19/01/2021

Page n. 13/15

### Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

### 15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

ETHANEDIOL

# **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Ox. Sol. 2 Oxidising solid, category 2

Acute Tox. 3 Acute toxicity, category 3

Acute Tox. 4 Acute toxicity, category 4

STOT RE 2 Specific target organ toxicity - repeated exposure, category 2

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1

H272 May intensify fire; oxidiser.

H301 Toxic if swallowed.H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road



# **PROTECTIVE 50** HEAVY DUTY Ready to use (820893, 820894)

Revision nr. 2

Dated 19/01/2021

First compilation

Printed on 19/01/2021

Page n. 14/15

CAS NUMBER: Chemical Abstract Service Number

- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

# GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
- 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. 10th Edition Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

# Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.



# PROTECTIVE 50 HEAVY DUTY Ready to use (820893, 820894)

Revision nr. 2

Dated 19/01/2021

First compilation

Printed on 19/01/2021

Page n. 15/15