



## SAFETY DATA SHEET

### STP® Ultra Diesel

According to Regulation (EC) No 1907/2006, Annex II, as amended.

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product name STP® Ultra Diesel

Product number 77400

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Fuel additive.

Uses advised against No specific uses advised against are identified.

##### 1.3. Details of the supplier of the safety data sheet

Supplier Energizer Trading Ltd  
Sword House  
Totteridge Road  
High Wycombe  
HP13 6DG  
UK  
Tel: +44 845 602 1995  
euregulatory@energizer.com

##### 1.4. Emergency telephone number

Emergency telephone +44 1495 350234  
Monday - Thursday: 0830 - 1700  
Friday: 0830 - 1530

National emergency telephone number Product information has been submitted to the UK National Poisons Information Service (NPIS) and is accessible to medical health professionals.

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Asp. Tox. 1 - H304

Environmental hazards Aquatic Chronic 3 - H412

Human health Pneumonia may be the result if vomited material containing solvents reaches the lungs.

##### 2.2. Label elements

Hazard pictograms



## STP® Ultra Diesel

<b>Signal word</b>	Danger
<b>Hazard statements</b>	H412 Harmful to aquatic life with long lasting effects. H304 May be fatal if swallowed and enters airways.
<b>Precautionary statements</b>	P102 Keep out of reach of children. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P331 Do NOT induce vomiting. P501 Dispose of contents/ container in accordance with national regulations.
<b>Supplemental label information</b>	EUH066 Repeated exposure may cause skin dryness or cracking.
<b>Contains</b>	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics, Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics, Distillates (petroleum), hydrotreated heavy paraffinic
<b>Supplementary precautionary statements</b>	P405 Store locked up.

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics			50 - 100%
CAS number: 64742-47-8	EC number: 926-141-6	REACH registration number: 01-2119456620-43-XXXX	
Classification Asp. Tox. 1 - H304			
2-ethylhexyl nitrate			10 - <25%
CAS number: 27247-96-7	EC number: 248-363-6	REACH registration number: 01-2119539586-27-XXXX	
Classification Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Aquatic Chronic 2 - H411			
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics			5 - <10%
CAS number: —	EC number: 918-481-9		
Classification Flam. Liq. 3 - H226 Asp. Tox. 1 - H304			

## STP® Ultra Diesel

2-ethylhexan-1-ol			2 - <3%
CAS number: 104-76-7	EC number: 203-234-3	REACH registration number: 01-2119487289-20-XXXX	
<b>Classification</b> Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335			
Distillates (petroleum), hydrotreated heavy paraffinic			1 - <2.5%
CAS number: 64742-54-7	EC number: 265-157-1	REACH registration number: 01-2119484627-25-XXXX	
<b>Classification</b> Asp. Tox. 1 - H304			

The full text for all hazard statements is displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
<b>Inhalation</b>	If throat irritation or coughing persists, proceed as follows. Remove person to fresh air and keep comfortable for breathing. Get medical attention if symptoms are severe or persist.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if symptoms are severe or persist.
<b>Skin contact</b>	Remove contaminated clothing and rinse skin thoroughly with water. Continue to rinse for at least 15 minutes. Get medical attention if symptoms are severe or persist after washing.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if symptoms are severe or persist after washing.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	Prolonged or repeated exposure to vapours in high concentrations may cause the following adverse effects: Drowsiness. Dizziness.
<b>Ingestion</b>	May cause discomfort if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
<b>Skin contact</b>	Prolonged skin contact may cause redness and irritation.
<b>Eye contact</b>	May cause irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Treat symptomatically. Keep affected person under observation.
-----------------------------	--

### SECTION 5: Firefighting measures

## STP® Ultra Diesel

### 5.1. Extinguishing media

**Suitable extinguishing media** Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up.

**Hazardous combustion products** Thermal decomposition or combustion products may include the following substances: Oxides of carbon. Toxic gases or vapours.

### 5.3. Advice for firefighters

**Protective actions during firefighting** Use water to keep fire exposed containers cool and disperse vapours.

**Special protective equipment for firefighters** Use protective equipment appropriate for surrounding materials. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet. Eliminate all ignition sources if safe to do so. Avoid contact with skin and eyes.

### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains or watercourses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage. Eliminate all ignition sources if safe to do so. Do not touch or walk into spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Use only non-sparking tools. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

### 6.4. Reference to other sections

**Reference to other sections** See Section 11 for additional information on health hazards. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Ground/bond container and receiving equipment. Take precautionary measures against static discharges. Keep away from heat, sparks and open flame. Provide adequate ventilation.

**Advice on general occupational hygiene** Avoid contact with eyes and prolonged skin contact. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in a cool and well-ventilated place. Keep away from heat, sparks and open flame. Take precautionary measures against static discharges.

## STP® Ultra Diesel

### 7.3. Specific end use(s)

#### Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

#### Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (CAS: 64742-47-8)

**DNEL** Not determined.

**PNEC** Not determined.

#### 2-ethylhexyl nitrate (CAS: 27247-96-7)

**DNEL** Workers - Inhalation; Long term systemic effects: 0.35 mg/m<sup>3</sup>  
 Workers - Dermal; Long term systemic effects: 1 mg/kg/day  
 Workers - Dermal; Long term local effects: 44 µg/cm<sup>2</sup>  
 General population - Inhalation; Long term systemic effects: 87 µg/m<sup>3</sup>  
 General population - Dermal; Long term systemic effects: 0.52 mg/kg/day  
 General population - Dermal; Long term local effects: 22 µg/cm<sup>2</sup>  
 General population - Oral; Long term systemic effects: 0.025 mg/kg/day

**PNEC** Fresh water; 0.0008 mg/l  
 marine water; 0.00008 mg/l  
 STP; 10 mg/l  
 Sediment (Freshwater); 0.00074 mg/kg  
 Sediment (Marinewater); 0.00074 mg/kg  
 Soil; 0.000191 mg/kg

#### 2-ethylhexan-1-ol (CAS: 104-76-7)

**DNEL** Workers - Inhalation; Long term systemic effects: 12.8 mg/m<sup>3</sup>  
 Workers - Inhalation; Long term local effects: 53.2 mg/m<sup>3</sup>  
 Workers - Inhalation; Short term local effects: 53.2 mg/m<sup>3</sup>  
 Workers - Dermal; Long term systemic effects: 23 mg/kg/day  
 General population - Inhalation; Long term systemic effects: 2.3 mg/m<sup>3</sup>  
 General population - Inhalation; Long term local effects: 26.6 mg/m<sup>3</sup>  
 General population - Inhalation; Short term local effects: 26.6 mg/m<sup>3</sup>  
 General population - Dermal; Long term systemic effects: 11.4 mg/kg/day  
 General population - Oral; Long term systemic effects: 1.1 mg/kg/day

**PNEC** Fresh water; 0.017 mg/l  
 Fresh water, Intermittent release; 0.17 mg/l  
 marine water; 0.002 mg/l  
 STP; 10 mg/l  
 Sediment (Freshwater); 0.284 mg/kg  
 Sediment (Marinewater); 0.028 mg/kg  
 Soil; 0.047 mg/kg  
 Oral; 55 mg/kg

#### Distillates (petroleum), hydrotreated heavy paraffinic (CAS: 64742-54-7)

**PNEC** - Oral; 9.33 mg/kg

### 8.2. Exposure controls

## STP® Ultra Diesel

### Protective equipment



### Appropriate engineering controls

Provide adequate ventilation. All handling should only take place in well-ventilated areas. Avoid inhalation of vapours and spray/mists. Use explosion-proof electrical, ventilating and lighting equipment.

### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Wear tight-fitting, chemical splash goggles or face shield.

### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacture, who can provide information about the breakthrough time of the glove material. Frequent changes are recommended.

### Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

### Hygiene measures

Do not smoke in work area. Wash promptly with soap and water if skin becomes contaminated. Wash at the end of each work shift and before eating, smoking and using the toilet.

### Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked.

### Environmental exposure controls

Keep container tightly sealed when not in use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Dark brown.
Odour	Characteristic.
Odour threshold	Not determined.
pH	Not determined.
Melting point	Not relevant.
Initial boiling point and range	Not determined.
Flash point	72°C
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	Not relevant.
Upper/lower flammability or explosive limits	Not relevant.
Vapour pressure	Not determined.
Vapour density	Not determined.

## STP® Ultra Diesel

Relative density	0.8399
Bulk density	838.3 kg/m <sup>3</sup>
Partition coefficient	Not determined.
Auto-ignition temperature	Not relevant.
Decomposition Temperature	Not relevant.
Viscosity	2.762 cSt @ 40°C
Explosive properties	Not considered to be explosive.
Oxidising properties	The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.

### 9.2. Other information

Other information	No information required.
-------------------	--------------------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
------------	---

### 10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
-----------	---

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Will not polymerise.
------------------------------------	----------------------

### 10.4. Conditions to avoid

Conditions to avoid	Avoid excessive heat for prolonged periods of time.
---------------------	---

### 10.5. Incompatible materials

Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
--------------------	--

### 10.6. Hazardous decomposition products

Hazardous decomposition products	None at ambient temperatures. Thermal decomposition or combustion products may include the following substances: Oxides of carbon. Oxides of nitrogen.
----------------------------------	--

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - oral

Notes (oral LD <sub>50</sub> )	Based on available data the classification criteria are not met.
--------------------------------	--

ATE oral (mg/kg)	6,469.0
------------------	---------

#### Acute toxicity - dermal

Notes (dermal LD <sub>50</sub> )	Based on available data the classification criteria are not met.
----------------------------------	--

ATE dermal (mg/kg)	7,412.4
--------------------	---------

#### Acute toxicity - inhalation

Notes (inhalation LC <sub>50</sub> )	Based on available data the classification criteria are not met.
--------------------------------------	--

ATE inhalation (vapours mg/l)	61.82
-------------------------------	-------

## STP® Ultra Diesel

### Skin corrosion/irritation

**Skin corrosion/irritation** Based on available data the classification criteria are not met.

### Serious eye damage/irritation

**Serious eye damage/irritation** Based on available data the classification criteria are not met.

### Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

### Skin sensitisation

**Skin sensitisation** Based on available data the classification criteria are not met.

### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

**Genotoxicity - in vivo** Based on available data the classification criteria are not met.

### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

### Reproductive toxicity

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

### Specific target organ toxicity - single exposure

**STOT - single exposure** Based on available data the classification criteria are not met.

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Based on available data the classification criteria are not met.

### Aspiration hazard

**Aspiration hazard** Kinematic viscosity  $\leq 20.5 \text{ mm}^2/\text{s}$ . May be fatal if swallowed and enters airways.

### Skin contact

Repeated exposure may cause skin dryness or cracking.

### Toxicological information on ingredients.

#### Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

##### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 15,000.0

**Species** Rat

**Notes (oral LD<sub>50</sub>)** REACH dossier information. Read-across data.

**ATE oral (mg/kg)** 15,000.0

##### Acute toxicity - dermal

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 3,160.0

**Species** Rabbit

**Notes (dermal LD<sub>50</sub>)** REACH dossier information. Read-across data.

**ATE dermal (mg/kg)** 3,160.0

##### Acute toxicity - inhalation



## STP® Ultra Diesel

**Acute toxicity inhalation**  
(LC<sub>50</sub> vapours mg/l)

4,951.0

**Species**

Rat

**Notes (inhalation LC<sub>50</sub>)**

REACH dossier information. Read-across data.

**ATE inhalation (vapours mg/l)**

4,951.0

### Skin corrosion/irritation

**Animal data**

Dose: 0.5 ml, 4 hours, Rabbit Erythema/eschar score: Well defined erythema (2). Oedema score: Very slight oedema - barely perceptible (1). REACH dossier information. Read-across data.

### Serious eye damage/irritation

**Serious eye damage/irritation**

Dose: 0.1 ml, 1 second, Rabbit Not irritating. REACH dossier information. Read-across data.

### Skin sensitisation

**Skin sensitisation**

Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. REACH dossier information. Read-across data.

### Germ cell mutagenicity

**Genotoxicity - in vitro**

Gene mutation: Negative. REACH dossier information. Read-across data.

**Genotoxicity - in vivo**

Chromosome aberration: Negative. REACH dossier information. Read-across data.

### Carcinogenicity

**Carcinogenicity**

NOAEC 1100 mg/m<sup>3</sup>, Inhalation, Mouse REACH dossier information. Read-across data.

### Reproductive toxicity

**Reproductive toxicity - fertility**

Fertility, One-generation study - NOAEL 750 mg/kg/day, Oral, Rat F1 REACH dossier information. Read-across data.

**Reproductive toxicity - development**

Maternal toxicity: - NOAEL: >= 5220 mg/m<sup>3</sup>, Inhalation, Rat REACH dossier information.

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure**

NOAEC > 10400 mg/m<sup>3</sup>, Inhalation, Rat REACH dossier information. Read-across data.

### Aspiration hazard

**Aspiration hazard**

2.4 cSt @ 20°C Asp. Tox. 1 - H304

### 2-ethylhexyl nitrate

#### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)**

960.0

**Species**

Rat

**ATE oral (mg/kg)**

960.0

#### Acute toxicity - dermal

**ATE dermal (mg/kg)**

1,100.0

## STP® Ultra Diesel

### Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 11.0

### Skin corrosion/irritation

Animal data Dose: 0.5 ml, 4 hours, Rabbit Erythema/eschar score: No erythema (0). Oedema score: No oedema (0). REACH dossier information.

### Serious eye damage/irritation

Serious eye damage/irritation Dose: 0.1 ml, 1 second, Rabbit REACH dossier information. Not irritating.

### Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. REACH dossier information.

### Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative. REACH dossier information.

### Reproductive toxicity

Reproductive toxicity - fertility Screening - NOAEL 100 mg/kg/day, Oral, Rat F1 REACH dossier information.

### Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 500 mg/kg/day, Dermal, Rabbit REACH dossier information.

### Aspiration hazard

Aspiration hazard 1.7 mPa s @ 20°C/68°F REACH dossier information.

### Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

### Acute toxicity - oral

Notes (oral LD<sub>50</sub>) LD<sub>50</sub> >5000 mg/kg, Oral, Rat REACH dossier information. Read-across data.

### Acute toxicity - dermal

Notes (dermal LD<sub>50</sub>) LD<sub>50</sub> >2000 mg/kg, Dermal, Rat REACH dossier information. Read-across data.

### Acute toxicity - inhalation

Notes (inhalation LC<sub>50</sub>) LC<sub>50</sub> >4951 mg/m<sup>3</sup>, Inhalation, Rat REACH dossier information. Read-across data.

### Skin corrosion/irritation

Animal data Dose: 0.5 ml, 4 hours, Rabbit Erythema/eschar score: Well defined erythema (2). Oedema score: No oedema (0). REACH dossier information. Read-across data.

### Serious eye damage/irritation

Serious eye damage/irritation Dose: 0.1 ml, 1 second, Rabbit REACH dossier information. Read-across data. Not irritating.

### Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. REACH dossier information. Read-across data.

### Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative. REACH dossier information. Read-across data.

## STP® Ultra Diesel

<b>Genotoxicity - in vivo</b>	Chromosome aberration: Negative. REACH dossier information. Read-across data.
<b><u>Carcinogenicity</u></b>	
<b>Carcinogenicity</b>	NOAEC $\geq$ 138 mg/m <sup>3</sup> , Inhalation, Rat REACH dossier information. Read-across data.
<b><u>Reproductive toxicity</u></b>	
<b>Reproductive toxicity - fertility</b>	Fertility - NOAEC $\geq$ 2200 mg/m <sup>3</sup> , Inhalation, Rat P REACH dossier information. Read-across data.
<b>Reproductive toxicity - development</b>	Developmental toxicity: - NOAEL: $\geq$ 5220 mg/m <sup>3</sup> , Inhalation, Rat REACH dossier information.
<b><u>Aspiration hazard</u></b>	
<b>Aspiration hazard</b>	1.8 cSt @ 20°C/68°F REACH dossier information.

### 2-ethylhexan-1-ol

<b><u>Acute toxicity - oral</u></b>	
<b>Acute toxicity oral (LD<sub>50</sub> mg/kg)</b>	3,290.0
<b>Species</b>	Rat
<b>Notes (oral LD<sub>50</sub>)</b>	REACH dossier information.
<b>ATE oral (mg/kg)</b>	3,290.0
<b><u>Acute toxicity - dermal</u></b>	
<b>Acute toxicity dermal (LD<sub>50</sub> mg/kg)</b>	3,000.0
<b>Species</b>	Rat
<b>Notes (dermal LD<sub>50</sub>)</b>	REACH dossier information.
<b>ATE dermal (mg/kg)</b>	3,000.0
<b><u>Acute toxicity - inhalation</u></b>	
<b>ATE inhalation (vapours mg/l)</b>	11.0
<b><u>Skin corrosion/irritation</u></b>	
<b>Animal data</b>	Primary dermal irritation index: 6.75 Dose: 0.5 ml, 4 hours, Rabbit REACH dossier information. Highly irritating.
<b><u>Serious eye damage/irritation</u></b>	
<b>Serious eye damage/irritation</b>	Dose: 0.1 ml, 1 second, Rabbit REACH dossier information. Irritating.
<b><u>Germ cell mutagenicity</u></b>	
<b>Genotoxicity - in vitro</b>	Gene mutation: Negative. REACH dossier information.
<b><u>Carcinogenicity</u></b>	
<b>Carcinogenicity</b>	NOAEL 500 mg/kg/day, Oral, Rat REACH dossier information.
<b><u>Reproductive toxicity</u></b>	

## STP® Ultra Diesel

**Reproductive toxicity - development** Developmental toxicity: - NOAEL: 2520 mg/kg/day, Dermal, Rat REACH dossier information.

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** NOAEL 250 mg/kg/day, Oral, Rat REACH dossier information.

### Aspiration hazard

**Aspiration hazard** 4.3 mPa s @ 40°C/104°F REACH dossier information.

### Distillates (petroleum), hydrotreated heavy paraffinic

### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** LD<sub>50</sub> > 5000 mg/kg, Rat, REACH dossier information.

### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** LD<sub>50</sub> > 2000 mg/kg, Rabbit, REACH dossier information.

### Skin corrosion/irritation

**Animal data** Dose: 0.5 ml, 24 hours, Rabbit Erythema/eschar score: Very slight erythema - barely perceptible (1). Oedema score: Very slight oedema - barely perceptible (1). REACH dossier information. Not irritating.

### Serious eye damage/irritation

**Serious eye damage/irritation** Dose: 0.1 ml, 1 second, Rabbit REACH dossier information. Not irritating.

### Skin sensitisation

**Skin sensitisation** Buehler test - Guinea pig: Not sensitising. REACH dossier information.

### Germ cell mutagenicity

**Genotoxicity - in vitro** Chromosome aberration: Negative. REACH dossier information.

**Genotoxicity - in vivo** Chromosome aberration: Negative. REACH dossier information.

### Carcinogenicity

**Carcinogenicity** REACH dossier information. No evidence of carcinogenicity in animal studies.

### Reproductive toxicity

**Reproductive toxicity - fertility** Screening - NOAEL ≥ 1000 mg/kg/day, Dermal, Mouse P REACH dossier information.

**Reproductive toxicity - development** Maternal toxicity: - LOAEL: 125 mg/kg/day, Dermal, Rat REACH dossier information.

### Aspiration hazard

**Aspiration hazard** 1.99 - 847 cSt @ 40°C REACH dossier information.

## SECTION 12: Ecological information

### 12.1. Toxicity

**Toxicity** Harmful to aquatic life with long lasting effects.

### Ecological information on ingredients.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

### Acute aquatic toxicity

## STP® Ultra Diesel

<b>Acute toxicity - fish</b>	LL <sub>50</sub> , 96 hours: > 1000 mg/l, Oncorhynchus mykiss (Rainbow trout) REACH dossier information.
<b>Acute toxicity - aquatic invertebrates</b>	EL <sub>50</sub> , 48 hours: > 1000 mg/l, Daphnia magna REACH dossier information.
<b>Acute toxicity - aquatic plants</b>	EL <sub>50</sub> , 72 hours: > 1000 mg/l, Pseudokirchneriella subcapitata REACH dossier information.
<b><u>Chronic aquatic toxicity</u></b>	
<b>Chronic toxicity - fish early life stage</b>	NOELR, 28 days: 0.173 mg/l, Oncorhynchus mykiss (Rainbow trout) QSAR REACH dossier information.
<b>Chronic toxicity - aquatic invertebrates</b>	NOELR, 21 days: 1.22 mg/l, Daphnia magna QSAR REACH dossier information.

### 2-ethylhexyl nitrate

#### Acute aquatic toxicity

<b>Acute toxicity - fish</b>	LC <sub>50</sub> , 96 hours: 2 mg/l, Brachydanio rerio (Zebra Fish) REACH dossier information.
<b>Acute toxicity - aquatic invertebrates</b>	EC <sub>50</sub> , 48 hours: > 12.6 mg/l, Daphnia magna REACH dossier information.
<b>Acute toxicity - aquatic plants</b>	EC <sub>50</sub> , 48 hours: 3.26 mg/l, Pseudokirchneriella subcapitata REACH dossier information.
<b>Acute toxicity - microorganisms</b>	EC <sub>50</sub> , 3 hours: > 1000 mg/l, Activated sludge REACH dossier information.

### Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

#### Acute aquatic toxicity

<b>Acute toxicity - fish</b>	LL <sub>50</sub> , 96 hours: > 1000 mg/l, Oncorhynchus mykiss (Rainbow trout) REACH dossier information.
<b>Acute toxicity - aquatic invertebrates</b>	EL <sub>50</sub> , 48 hours: > 1000 mg/l, Daphnia magna REACH dossier information.
<b>Acute toxicity - aquatic plants</b>	EL <sub>50</sub> , 72 hours: > 1000 mg/l, Pseudokirchneriella subcapitata REACH dossier information.
<b>Acute toxicity - microorganisms</b>	EL <sub>50</sub> , 48 hours: > 1000 mg/l, Tetrahymena pyriformis REACH dossier information. QSAR

#### Chronic aquatic toxicity

<b>Chronic toxicity - fish early life stage</b>	NOELR, 28 days: 0.101 mg/l, Oncorhynchus mykiss (Rainbow trout) REACH dossier information. QSAR
<b>Chronic toxicity - aquatic invertebrates</b>	NOELR, 21 days: 0.176 mg/l, Daphnia magna REACH dossier information. QSAR

## STP® Ultra Diesel

### 2-ethylhexan-1-ol

#### Acute aquatic toxicity

<b>Acute toxicity - fish</b>	LC <sub>50</sub> , 96 hours: 17.1 mg/l, <i>Leuciscus idus</i> (Golden orfe) REACH dossier information.
<b>Acute toxicity - aquatic invertebrates</b>	EC <sub>50</sub> , 48 hours: 39 mg/l, <i>Daphnia magna</i> REACH dossier information.
<b>Acute toxicity - aquatic plants</b>	EC <sub>50</sub> , 72 hours: 11.5 mg/l, <i>Scenedesmus subspicatus</i> REACH dossier information.

### Distillates (petroleum), hydrotreated heavy paraffinic

#### Acute aquatic toxicity

<b>Acute toxicity - fish</b>	LL <sub>50</sub> , 96 hours: > 100 mg/l, <i>Pimephales promelas</i> (Fat-head Minnow) NOEL, 96 hours: ≥ 100 mg/l, <i>Pimephales promelas</i> (Fat-head Minnow) REACH dossier information.
<b>Acute toxicity - aquatic invertebrates</b>	LL <sub>50</sub> , 24, 48, 72, 96 hours: > 10000 mg/l, <i>Gammarus pulex</i> REACH dossier information.
<b>Acute toxicity - aquatic plants</b>	NOEL, 72 hours: ≥ 100 mg/l, <i>Pseudokirchneriella subcapitata</i> REACH dossier information.
<b>Acute toxicity - microorganisms</b>	NOEL, 10 minutes: > 1.93 mg/l, <i>Photobacterium phosphoreum</i> REACH dossier information.
<b><u>Chronic aquatic toxicity</u></b>	
<b>Chronic toxicity - aquatic invertebrates</b>	NOEL, 21 days: 10 mg/l, <i>Daphnia magna</i> REACH dossier information.

## 12.2. Persistence and degradability

**Persistence and degradability** No data available.

### Ecological information on ingredients.

#### Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

<b>Biodegradation</b>	Water - Degradation ~ 5%: 3 days Water - Degradation 69: 28 days REACH dossier information. Readily biodegradable but failing the 10-day window.
-----------------------	---

### 2-ethylhexyl nitrate

<b>Stability (hydrolysis)</b>	pH4 - DT <sub>50</sub> : 1225 minutes @ 50°C/122°F pH7 - DT <sub>50</sub> : 1475 minutes @ 50°C/122°F pH9 - DT <sub>50</sub> : 1702 minutes @ 50°C/122°F REACH dossier information.
<b>Biodegradation</b>	Water - Degradation 0%: 28 days REACH dossier information. No biodegradation observed under test conditions.

#### Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

## STP® Ultra Diesel

**Biodegradation** Water - Degradation 80%: 28 days  
REACH dossier information.  
Read-across data.  
Readily biodegradable but failing the 10-day window.

### 2-ethylhexan-1-ol

**Biodegradation** Water - Degradation 79 - 99.9%: 2 weeks  
REACH dossier information.  
The substance is readily biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** Not determined.

### Ecological information on ingredients.

#### Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

**Partition coefficient** Scientifically unjustified. REACH dossier information.

### 2-ethylhexyl nitrate

**Partition coefficient** log Pow: 5.24 REACH dossier information.

#### Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

**Bioaccumulative potential** Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

### 2-ethylhexan-1-ol

**Bioaccumulative potential** BCF: 25.33, REACH dossier information.

**Partition coefficient** log Pow: 2.9 REACH dossier information.

### 12.4. Mobility in soil

**Mobility** The product is soluble in water.

### Ecological information on ingredients.

#### Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

**Mobility** The product has poor water-solubility.

**Surface tension** 26.4 mN/m @ 25°C

### 2-ethylhexyl nitrate

**Adsorption/desorption coefficient** Water - log Koc: 3.75 @ 22°C/72°F REACH dossier information.

#### Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

**Mobility** The product contains organic solvents which will evaporate easily from all surfaces.  
The product contains substances which are insoluble in water and which sediment in water systems.

## STP® Ultra Diesel

**Surface tension** 25.3 mN/m @ 25°C/77°F REACH dossier information.

### 2-ethylhexan-1-ol

**Surface tension** 47 mN/m @ 20°C/68°F REACH dossier information.

#### **12.5. Results of PBT and vPvB assessment**

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

#### **Ecological information on ingredients.**

**Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics**

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current EU criteria.

#### **12.6. Other adverse effects**

**Other adverse effects** Not determined.

### **SECTION 13: Disposal considerations**

#### **13.1. Waste treatment methods**

**General information** Dispose of waste product or used containers in accordance with local regulations

### **SECTION 14: Transport information**

**General** The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

#### **14.1. UN number**

Not applicable.

#### **14.2. UN proper shipping name**

Not applicable.

#### **14.3. Transport hazard class(es)**

No transport warning sign required.

#### **14.4. Packing group**

Not applicable.

#### **14.5. Environmental hazards**

**Environmentally hazardous substance/marine pollutant**  
No.

#### **14.6. Special precautions for user**

Not applicable.

#### **14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

### **SECTION 15: Regulatory information**

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**



## STP® Ultra Diesel

<b>National regulations</b>	EH40/2005 Workplace exposure limits.
<b>EU legislation</b>	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Commission Regulation (EU) No 2015/830 of 28 May 2015.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## SECTION 16: Other information

<b>Abbreviations and acronyms used in the safety data sheet</b>	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail. IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways. ATE: Acute Toxicity Estimate. DNEL: Derived No Effect Level. LC <sub>50</sub> : Lethal Concentration to 50 % of a test population. LD <sub>50</sub> : Lethal Dose to 50% of a test population (Median Lethal Dose). PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative. BCF: Bioconcentration Factor.
<b>Classification procedures according to Regulation (EC) 1272/2008</b>	Asp. Tox. 1 - H304: Calculation method., On basis of test data. Aquatic Chronic 3 - H412: Calculation method.
<b>Revision comments</b>	Section 1: Identification of the substance/mixture and of the company/undertaking // 1.3. Details of the supplier of the safety data sheet.
<b>Revision date</b>	19/03/2020
<b>Revision</b>	4
<b>Supersedes date</b>	26/06/2017
<b>SDS number</b>	163
<b>Hazard statements in full</b>	H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

## STP® Ultra Diesel

The information supplied here is accurate to the best knowledge and belief of Energizer Trading Ltd, it is however, not intended as a warranty or representation, and should not be construed as such, for which Energizer Trading Ltd assumes any legal responsibility. Any information or advice obtained from Energizer Trading Ltd other than by means of this publication, and whether relating to Energizer Trading Ltd's products or other materials is also given in good faith. It remains at all times the responsibility of the customer, and user, to ensure that the materials are suitable for the particular purpose intended. Materials not manufactured, or supplied, by Energizer Trading Ltd when used instead of, or in conjunction with materials supplied by Energizer Trading Ltd, it is the customer's responsibility to ensure that all technical, and other information related to such materials is obtained from the manufacturer or supplier. Energizer Trading Ltd accepts no liability for the data contained within this document, as the information herein may be applied under conditions beyond our control, and in situations with which we may be unfamiliar. The information contained within this document is furnished upon condition that the customer and user of this product makes his own determination of the suitability of the product for his particular purpose.