	Page: 1
SAFETY DATA SHEET	Revision Date: 06.02.2019
	Print Date: 13.05.2020
	SDS Number: 000000274854
Valvoline™ CARBURETTOR CLEANER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887082	Version: 3.1

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_DE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Valvoline™ CARBURETTOR CLEANER

™ Trademark, Valvoline or its subsidiaries, registered in various countries

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Cleaner.

1.3 Details of the supplier of the safety data sheet Ellis Enterprises B.V., an affiliate of Valvoline Wieldrechtseweg 39 3316 BG Dordrecht Netherlands +31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person SDS@valvoline.com	1.4 Emergency telephone number 00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number at 0 30-1 92 40 Product Information +31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person
---	---

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Skin irritation, Category 2


H315: Causes skin irritation.

Eye irritation, Category 2

H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness.

	Page: 2
SAFETY DATA SHEET	Revision Date: 06.02.2019
	Print Date: 13.05.2020
	SDS Number: 000000274854
Valvoline™ CARBURETTOR CLEANER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887082	Version: 3.1

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
Prevention:
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
Storage:
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Disposal:
P501 Dispose of contents/container in accordance with local regulation.

Hazardous components which must be listed on the label:

Butanone
propan-2-ol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional advice

No information available.

SECTION 3: Composition/information on ingredients



SAFETY DATA SHEET

Revision Date: 06.02.2019

Print Date: 13.05.2020

SDS Number: 000000274854

Version: 3.1

Valvoline™ CARBURETTOR CLEANER
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 887082

3.2 Mixtures

Hazardous components


Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
xylene	1330-20-7	Flam. Liq.3; H226 Acute Tox.4; H332 Acute Tox.4; H312 Skin Irrit.2; H315	>= 40,00 - < 50,00
Butanone	78-93-3 201-159-0 01-2119457290-43-xxxx	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336	>= 15,00 - < 20,00
propan-2-ol	67-63-0 200-661-7 01-2119457558-25-xxxx	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336	>= 10,00 - < 15,00
Substances with a workplace exposure limit :			
Propane	74-98-6 200-827-9 01-2119486944-21-xxxx	Flam. Gas1; H220 Press. GasLiquefied gas; H280	>= 15,00 - < 25,00
Butane	106-97-8 203-448-7 01-2119474691-32-xxxx	Flam. Gas1; H220 Press. GasLiquefied gas; H280	>= 5,00 - < 10,00
Isobutane	75-28-5 200-857-2 01-2119485395-27-xxxx	Flam. Gas1; H220 Press. GasLiquefied gas; H280	>= 5,00 - < 10,00

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.
 Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.

	Page: 4
SAFETY DATA SHEET	Revision Date: 06.02.2019
	Print Date: 13.05.2020
	SDS Number: 000000274854
Valvoline™ CARBURETTOR CLEANER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887082	Version: 3.1

- | | |
|-------------------------|---|
| If inhaled | : Move to fresh air.
If unconscious, place in recovery position and seek medical advice.
Consult a physician after significant exposure. |
| In case of skin contact | : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use. |
| In case of eye contact | : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye. |
| If swallowed | : IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician. |

4.2 Most important symptoms and effects, both acute and delayed

- | | |
|----------|---|
| Symptoms | : No symptoms known or expected. |
| Risks | : Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness. |


4.3 Indication of any immediate medical attention and special treatment needed

- | | |
|-----------|--|
| Treatment | : No hazards which require special first aid measures. |
|-----------|--|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | |
|--------------------------------|---|
| Suitable extinguishing media | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : High volume water jet |

	Page: 5
SAFETY DATA SHEET	Revision Date: 06.02.2019
	Print Date: 13.05.2020
	SDS Number: 000000274854
Valvoline™ CARBURETTOR CLEANER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887082	Version: 3.1

5.2 Special hazards arising from the substance or mixture

- | | |
|--------------------------------------|---|
| Specific hazards during firefighting | : Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : carbon dioxide and carbon monoxide
Hydrocarbons |

5.3 Advice for firefighters

- | | |
|---|---|
| Special protective equipment for firefighters | : In the event of fire, wear self-contained breathing apparatus. |
| Specific extinguishing methods | : Product is compatible with standard fire-fighting agents. |
| Further information | : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers. |


SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- | | |
|----------------------|---|
| Personal precautions | : Evacuate personnel to safe areas.
Remove all sources of ignition.
Use personal protective equipment.
Ensure adequate ventilation.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Comply with all applicable federal, state, and local regulations. |
|----------------------|---|

6.2 Environmental precautions

- | | |
|---------------------------|---|
| Environmental precautions | : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities. |
|---------------------------|---|

	Page: 6
SAFETY DATA SHEET	Revision Date: 06.02.2019
	Print Date: 13.05.2020
	SDS Number: 000000274854
Valvoline™ CARBURETTOR CLEANER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887082	Version: 3.1

6.3 Methods and material for containment and cleaning up

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- | | |
|---|--|
| Advice on safe handling | : Open drum carefully as content may be under pressure.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Take precautionary measures against static discharges.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.
Container may be opened only under exhaust ventilation hood. |
| Advice on protection against fire and explosion | : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition. Use only explosion-proof equipment. |
| Hygiene measures | : Wash hands before breaks and at the end of workday. When using do not eat or drink. When using do not smoke. |

7.2 Conditions for safe storage, including any incompatibilities

- | | |
|---|---|
| Requirements for storage areas and containers | : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. No smoking. |
| Storage class (TRGS 510) | : 2B, Aerosol cans and lighters |
| Other data | : No decomposition if stored and applied as directed. |

7.3 Specific end use(s)



SAFETY DATA SHEET

Revision Date: 06.02.2019

Print Date: 13.05.2020

SDS Number: 000000274854

Version: 3.1

Valvoline™ CARBURETTOR CLEANER
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 887082

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection


8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
xylene	1330-20-7	TWA	50 ppm 221 mg/m ³	2000/39/EC
		STEL	100 ppm 442 mg/m ³	2000/39/EC
		AGW	100 ppm 440 mg/m ³	DE TRGS 900
Butanone	78-93-3	TWA	200 ppm 600 mg/m ³	2000/39/EC
		STEL	300 ppm 900 mg/m ³	2000/39/EC
		AGW	200 ppm 600 mg/m ³	DE TRGS 900
Propane	74-98-6	AGW	1.000 ppm 1.800 mg/m ³	DE TRGS 900
propan-2-ol	67-63-0	AGW	200 ppm 500 mg/m ³	DE TRGS 900
Butane	106-97-8	AGW	1.000 ppm 2.400 mg/m ³	DE TRGS 900
Isobutane	75-28-5	AGW	1.000 ppm 2.400 mg/m ³	DE TRGS 900

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Xylene	1330-20-7	xylene: 1,5 mg/l (Blood)	Immediately after exposure or after working hours	TRGS 903
		methylhippuric acid (all isomers): 2 g/l (Urine)	Immediately after exposure or after working hours	TRGS 903
METHYL ETHYL KETONE	78-93-3	2-butanone: 2 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
ISOPROPANOL	67-63-0	Acetone: 25 mg/l (Blood)	Immediately after exposure or after working hours	TRGS 903
		Acetone: 25 mg/l	Immediately after	TRGS 903

	Page: 8
SAFETY DATA SHEET	Revision Date: 06.02.2019
	Print Date: 13.05.2020
	SDS Number: 000000274854
Valvoline™ CARBURETTOR CLEANER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887082	Version: 3.1

		(Urine)	exposure or after working hours	
--	--	---------	---------------------------------	--

8.2 Exposure controls

Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Wear as appropriate:
Impervious clothing
Safety shoes
Flame-resistant clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
In the case of dust or aerosol formation use respirator with an approved filter.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : aerosol

Colour : clear

Odour : solvent-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

**SAFETY DATA SHEET**

Revision Date: 06.02.2019

Print Date: 13.05.2020

SDS Number: 000000274854

Version: 3.1

Valvoline™ CARBURETTOR CLEANER
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 887082

Initial boiling point and boiling range : Not applicable

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper flammability limit : 11,5 %(V)

Lower explosion limit / Lower flammability limit : 1 %(V)

Vapour pressure : 105 hPa (20 °C)

Relative vapour density : No data available

Relative density : No data available

Density : 0,72 g/cm³ (20 °C)

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Ignition temperature : 500 °C

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available


Viscosity, kinematic : No data available

Oxidizing properties : No data available

9.2 Other information

Self-ignition : not auto-flammable

SECTION 10: Stability and reactivity

	Page: 10
SAFETY DATA SHEET	Revision Date: 06.02.2019
	Print Date: 13.05.2020
	SDS Number: 000000274854
Valvoline™ CARBURETTOR CLEANER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887082	Version: 3.1

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : None known.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids
Aldehydes
alkalis
Amines
Copper
Copper alloys
Ethylene oxide
halogens
isocyanates
strong alkalis
Strong oxidizing agents
Do not use with aluminum equipment at temperatures above 49C or 120 degrees F.


10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

	Page: 11
SAFETY DATA SHEET	Revision Date: 06.02.2019
	Print Date: 13.05.2020
	SDS Number: 000000274854
Valvoline™ CARBURETTOR CLEANER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887082	Version: 3.1

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate : > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 2.000 mg/kg
Method: Calculation method

Components:

Xylene:

Acute oral toxicity : LD50 (Rat, male): 3.523 mg/kg

Acute inhalation toxicity : LC50 (Rat, male): 29 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 2.000 mg/kg

Components:

METHYL ETHYL KETONE:

Acute oral toxicity : LD50 (Rat): 2.300 - 3.500 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Components:

ISOPROPANOL:

Acute oral toxicity : LD50 (Rat): 5,84 g/kg


Acute inhalation toxicity : LC50 (Rat): 16000 ppm
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12.800 mg/kg

Components:

PROPANE:

Acute inhalation toxicity : LC50 (Rat): 1.237 mg/l
Exposure time: 2 h
Test atmosphere: gas
Assessment: Not classified as acutely toxic by inhalation under GHS.

	Page: 12
SAFETY DATA SHEET	Revision Date: 06.02.2019
	Print Date: 13.05.2020
	SDS Number: 000000274854
Valvoline™ CARBURETTOR CLEANER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887082	Version: 3.1

Remarks: Information given is based on data obtained from similar substances.

Components:

BUTANE NORMAL:

Acute inhalation toxicity : LC50 (Mouse): 680 mg/l
Exposure time: 2 h

LC50 (Rat): > 50000 ppm
Exposure time: 2 h
Test atmosphere: gas

Components:

ISOBUTANE:

Acute inhalation toxicity : LC50 (Mouse, male): 520400 ppm
Exposure time: 2 h
Test atmosphere: gas

Skin corrosion/irritation

Causes skin irritation.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation and/or dermatitis.

Components:

Xylene:

Result: Irritating to skin.

METHYL ETHYL KETONE:

Result: No skin irritation

ISOPROPANOL:

Result: Slight, transient irritation

ISOBUTANE:


Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

	Page: 13
SAFETY DATA SHEET	Revision Date: 06.02.2019
	Print Date: 13.05.2020
	SDS Number: 000000274854
Valvoline™ CARBURETTOR CLEANER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887082	Version: 3.1

Components:

METHYL ETHYL KETONE:

Result: Irritating to eyes.

ISOPROPANOL:

Result: Irritating to eyes.

ISOBUTANE:

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Components:

PROPANE:

Genotoxicity in vitro : Test Type: Ames test
Test species: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative
Remarks: Information given is based on data obtained from similar substances.

BUTANE NORMAL:


Genotoxicity in vitro : Test Type: Ames test
Test species: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

ISOBUTANE:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Test species: Human lymphocytes
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative
GLP: yes

: Test Type: Ames test
Metabolic activation: with and without metabolic activation
Result: negative

Genotoxicity in vivo : Test Type: in vivo assay
Test species: Drosophila melanogaster (vinegar fly)

	Page: 14
SAFETY DATA SHEET	Revision Date: 06.02.2019
	Print Date: 13.05.2020
	SDS Number: 000000274854
Valvoline™ CARBURETTOR CLEANER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887082	Version: 3.1

Result: negative
Remarks: Information given is based on data obtained from similar substances.

Test Type: In vivo micronucleus test
Test species: Rat
Method: OECD Test Guideline 474
Result: negative
Remarks: Information given is based on data obtained from similar substances.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Product:

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

Components:

METHYL ETHYL KETONE:

Assessment: May cause drowsiness or dizziness.

ISOPROPANOL:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Product:

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.


Aspiration toxicity

Not classified based on available information.

Components:

METHYL ETHYL KETONE:

May be harmful if swallowed and enters airways.

	Page: 15
SAFETY DATA SHEET	Revision Date: 06.02.2019
	Print Date: 13.05.2020
	SDS Number: 000000274854
Valvoline™ CARBURETTOR CLEANER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887082	Version: 3.1

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Components:

METHYL ETHYL KETONE:

Remarks: Central nervous system

ISOPROPANOL:

Remarks: Central nervous system

SECTION 12: Ecological information

12.1 Toxicity

Components:

xylene

Toxicity to fish : LC50 (Fish): 13,5 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 7,4 mg/l
Exposure time: 48 h

Butanone


Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 3.130 - 3.320 mg/l
Exposure time: 96 h
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.025 - 6.440 mg/l
Exposure time: 48 h
Test Type: static test
Remarks: Intoxication

propan-2-ol

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 5.770 - 7.450 mg/l
Exposure time: 96 h
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10.000 mg/l
Exposure time: 24 h

	Page: 16
SAFETY DATA SHEET	Revision Date: 06.02.2019
	Print Date: 13.05.2020
	SDS Number: 000000274854
Valvoline™ CARBURETTOR CLEANER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887082	Version: 3.1

Test Type: static test

Butane

Toxicity to fish

: Remarks: No toxicity at the limit of solubility
QSAR

Toxicity to daphnia and other aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): Expected > 10 - < 100 mg/l
Exposure time: 48 h
Remarks: QSAR

Toxicity to algae

: EC50 (green algae): Expected 7,7 mg/l
Exposure time: 96 h
Remarks: QSAR

12.2 Persistence and degradability

Components:

xylene

Biodegradability

: Result: Readily biodegradable.

Butane

Biodegradability

: Result: Readily biodegradable.
Remarks: Information given is based on data obtained from similar substances.

12.3 Bioaccumulative potential

Components:

xylene

Partition coefficient: n-octanol/water

: log Pow: 3,16

Butanone

Partition coefficient: n-octanol/water

: log Pow: 0,29

propan-2-ol

Partition coefficient: n-octanol/water

: log Pow: 0,05

Propane


Partition coefficient: n-octanol/water

: log Pow: 2,36

Butane

Partition coefficient: n-

: log Pow: 2,89

	Page: 17
SAFETY DATA SHEET	Revision Date: 06.02.2019
	Print Date: 13.05.2020
	SDS Number: 000000274854
Valvoline™ CARBURETTOR CLEANER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887082	Version: 3.1

octanol/water

Isobutane

Partition coefficient: n-
octanol/water : log Pow: 2,76

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life.

SECTION 13: Disposal considerations

13.1 Waste treatment methods


Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1950

	Page: 18
SAFETY DATA SHEET	Revision Date: 06.02.2019
	Print Date: 13.05.2020
	SDS Number: 000000274854
Valvoline™ CARBURETTOR CLEANER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887082	Version: 3.1

ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS
IATA : AEROSOLS

14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group


ADN
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1

ADR
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

RID
Packing group : Not assigned by regulation
Classification Code : 5F
Hazard Identification Number : 23
Labels : 2.1

IMDG
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)

	Page: 19
SAFETY DATA SHEET	Revision Date: 06.02.2019
	Print Date: 13.05.2020
	SDS Number: 000000274854
Valvoline™ CARBURETTOR CLEANER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887082	Version: 3.1

Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.


Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

	Page: 20
SAFETY DATA SHEET	Revision Date: 06.02.2019
	Print Date: 13.05.2020
	SDS Number: 000000274854
Valvoline™ CARBURETTOR CLEANER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887082	Version: 3.1

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t
18	Liquefied extremely flammable gases (including LPG) and natural gas	50 t	200 t

Water contaminating class (Germany) : WGK 3 highly hazardous to water

TA Luft List (Germany) : Total dust, Not applicable

: Inorganic substances in powdered form, Not applicable

: Inorganic substances in vapour or gaseous form, Not applicable

: Organic Substances, Not applicable


: Carcinogenic substances, Not applicable

: Mutagenic, Not applicable

: Toxic to reproduction, Not applicable

Other regulations : Young people under 18 years old are not allowed to work with this product according to the EU Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

	Page: 21
SAFETY DATA SHEET	Revision Date: 06.02.2019
	Print Date: 13.05.2020
	SDS Number: 000000274854
Valvoline™ CARBURETTOR CLEANER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887082	Version: 3.1

DSL : This product contains one or several components that are not on the Canadian DSL and have annual quantity limits.

AICS Not in compliance with the inventory

ENCS Not in compliance with the inventory

KECI Not in compliance with the inventory

PICCS Not in compliance with the inventory

IECSC Not in compliance with the inventory

TCSI Not in compliance with the inventory

TSCA Not On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information


Further information

Revision Date: 06.02.2019

Full text of H-Statements

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance

	Page: 22
SAFETY DATA SHEET	Revision Date: 06.02.2019
	Print Date: 13.05.2020
	SDS Number: 000000274854
Valvoline™ CARBURETTOR CLEANER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887082	Version: 3.1

of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit


STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

	Page: 23
SAFETY DATA SHEET	Revision Date: 06.02.2019
	Print Date: 13.05.2020
	SDS Number: 000000274854
Valvoline™ CARBURETTOR CLEANER ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887082	Version: 3.1

ABM : Water Hazard Class for the Netherlands
ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.
ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine
CLP : Classification, Labelling and Packaging
CSA : Chemical Safety Assessment
CSR : Chemical Safety Report
DNEL : Derived No Effect Level.
EINECS : European Inventory of Existing Commercial Chemical Substances.
ELINCS : European List of Notified Chemical Substances
PEC : Predicted Effect Concentration
PEL : Permissible Exposure Limits
PNEC : Predicted No Effect Concentration
R-phrase : Risk phrase
REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals
RID : Regulation Concerning the International Transport of Dangerous Goods by Rail
S-phrase: Safety phrase
WGK : German Water Hazard Class