

SAFETY DATA SHEET

LUB ENGRENAGE

Version:3

Review date:10/03/2015

RE EC/453/2010 - ISO 11014-1

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1. 1. Product identifier: LUB ENGRENAGE
1. 2. Relevant identified uses of the substance or mixture and uses advised against: For more information, to consult the chart.
1. 3. Details of the supplier of the safety data sheet: SELD
6 rue Jules Guesde – ZI du Pontet
F-69360 Saint Symphorien d'Ozon
France
Phone: +33 (0)4 37 25 16 16
Fax: +33 (0)4 78 21 80 70
E-mail: contact@mecatech-performances.com
1. 4. Product code nr: 438012
1. 5. Emergency telephone number: UK - National Poisons Information Service Phone: 44 / 191 22 5131

2. HAZARDS IDENTIFICATION

2. 1. Classification of the substance or mixture: * Flam. Aerosol 1 / SGH02 - H222 *
* STOT SE 3 / SGH07 - H336 *
2. 2. EC number: Not applicable.
2. 3. Contains: • Naphta lourd (pétrole), hydrotraité
2. 4. Label elements (R - S):
- 
2. 4. 1. Symbol(s): F+ - Extremely flammable
2. 4. 2. R-pharse(s): 12 Extremely flammable.
66 Repeated exposure may cause skin dryness or cracking
2. 4. 3. S-pharse(s): 2 Keep out of the reach of children.
16 Keep away from sources of ignition - No smoking.
23 Do not breathe gas / fumes / vapour / spray.
38 In case of insufficient ventilation, wear suitable respiratory equipment.
51 Use only in well-ventilated areas.
62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.
2. 5. Label elements (CLP - SGH):
-  
- Danger
2. 5. 1. Symbol(s) and signal word: .
2. 5. 2. Hazard statement: H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H336 May cause drowsiness or dizziness.
2. 5. 3. Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing dust / fume / gas / mist / vapours / spray.
P271 Use only outdoors or in a well-ventilated area.
2. 5. 4. Response: P304 IF INHALED:
P340 Remove person to fresh air and keep comfortable for breathing.

SAFETY DATA SHEET

LUB ENGRENAGE

Version:3

Review date:10/03/2015

RE EC/453/2010 - ISO 11014-1

2. 5. 5. Storage: P312a Call a POISON CENTER / doctor if you feel unwell.
P410 Protect from sunlight.
P412 Do not expose to temperatures exceeding 50 °C / 122°F.
P403 Store in a well-ventilated place.
P233 Keep container tightly closed.
P405 Store locked up.
2. 5. 6. Disposal: P501a Dispose of contents / container in accordance with local / regional / national / international regulation
2. 6. Further information(s): EUH 066 - Repeated exposure may cause skin dryness or cracking.
56.92 % by mass of the contents are flammable.
2. 7. Most important hazards: Case aerosol under pressure
Aerosols
2. 8. Other hazards: Frequent or prolonged contacts may defat and dry the skin, leading to discomfort and dermatitis.
Extremely flammable.

3. COMPOSITION / INFORMATION ON INGREDIENTS

3. 1. Component(s) contributing to the health hazard:

- Dioxyde de carbone
 - CE nr: 204-696-9 - CAS nr: 124-38-9
 - Conc. (w eight %) : 1 < C <= 5
 - SGH :
 - * SGH04 - Gas cylinder - Warning - Compressed gases - H280
 - VME ppm = 5000 - VME mg/m³ = 9000 - VLE ppm = 30000 - VLE mg/m³ = 54000
- Naphta lourd (pétrole), hydrotraité
 - CE nr: 918-481-9
 - REACH registration number : 01-2119457273-39xxx
 - Conc. (w eight %) : 20 < C <= 25
 - R-S :
Symbol(s): Xn - R-phrased(s): 10-65-66-67
 - SGH :
 - * SGH02 - Flame - Warning - Flam. Liq. 3 - H226
 - * SGH07 - Exclamation mark - Warning - STOT SE 3 - H336 * SGH08 - Health hazard - Danger - Asp. Tox. 1 - H304
 - Miscellaneous :
LD50 / Dermal / Rabbit = >5000 mg/kg
LD50 / Oral / Rat = >5000 mg/kg
LC50 / 96h / Oncorhynchus mykiss = >1000 mg/l
CE50 / 48h / Daphnia magna = >1000 mg/l
CEr50 / 72h / Algae = >1000 mg/l
 - Additional phrase(s)
EUH 066 - Repeated exposure may cause skin dryness or cracking.

The wording of the sentences are mentioned at heading 16.

4. FIRST AID MEASURES

4. 1. Description of first aid measures:

4. 1. 1. General advice: In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.
For symptom description, see item 11.
4. 1. 2. Inhalation: Take victim to fresh air, in a quiet place and if necessary take medical advice.

SAFETY DATA SHEET

LUB ENGRENAGE

Version:3

Review date:10/03/2015

RE EC/453/2010 - ISO 11014-1

4. 1. 3. Skin contact:	Take off contaminated clothes, wash skin with plenty of water or have a shower (during minimum 15 minutes) and if necessary take medical advice.
4. 1. 4. Eye contact:	Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart, and seek medical advice.
4. 1. 5. Ingestion:	Rinse mouth, drink a lot of water, do not vomit, keep quiet, and go immediately to hospital or to a doctor.
4. 2. Most important symptoms and effects, both acute and delayed:	
4. 2. 1. Inhalation:	In the event of massive fume vapor inhalation /, can cause nausea, an irritation of the respiratory tracts
4. 2. 2. Skin contact:	Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin.
4. 2. 3. Eyes contact:	Splashes in the eyes may cause irritation and reversible local damage.
4. 2. 4. Ingestion:	May cause nausea, vomiting, sore throat, stomach-ache and eventually a perforation of the intestine.
4. 3. Indication of any immediate medical attention and special treatment needed :	In all cases of doubt, or when symptoms persist, seek medical attention.

5. FIREFIGHTING MEASURES

- | | |
|--|--|
| 5. 1. Extinguishing media: | alcohol-resistant foam, carbon dioxide (CO ₂), powder, water spray. |
| 5. 2. Special hazards arising from the substance or mixture: | Be careful of explosion risk.
Decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. |
| 5. 3. Advice for firefighters: | Use a self-contained breathing apparatus and also a protective suit. |
| 5. 4. Specific method(s): | Cool closed containers exposed to fire with water spray. |
| 5. 5. Extinguishing media which must NOT be used for safety reasons: | Do not use water jet. |

6. ACCIDENTAL RELEASE MEASURES

- | | |
|--|--|
| 6. 1. Personal precautions, protective equipment and emergency procedures: | Exclude sources of ignition and ventilate the area. Exclude non-essential personnel. Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8. |
| 6. 2. Environmental precautions: | Prevent liquid from entering sewers, watercourses, underground or low areas. |
| 6. 3. Methods and material for containment and cleaning up: | Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth
Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). |
| 6. 4. Reference to other sections: | Concerning disposal elimination after cleaning, see item 13.
Concerning personal protective equipment to use, see item 8. |

7. HANDLING AND STORAGE

- | | |
|---|--|
| 7. 1. Handling: | |
| 7. 1. 1. Precautions for safe handling: | Smoking, eating and drinking is prohibited in areas of storage and use.
Avoid contact with skin and eyes.
For personal protection, see Section 8.
The Manual Handling Operations Regulations may apply to the handling of containers of this product. Refer to the guide weight indicated on the container when carrying out assessments. |
| 7. 1. 2. Technical condition(s): | The product should only be used in areas from which all naked lights and other sources of |

SAFETY DATA SHEET

LUB ENGRENAGE

Version:3

Review date:10/03/2015

RE EC/453/2010 - ISO 11014-1

ignition have been excluded. Avoid skin and eyes contact. Avoid inhalation of vapour and spray mist.	
7. 2. Storage:	
7. 2. 1. Conditions for safe storage, including any incompatibilities:	No smoking. Prevent unauthorised access.
7. 2. 2. Storage condition(s):	Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Recommended storage temperature: 5 à 50°C
7. 2. 3. Packaging / tank material:	made of the same material as the supply container.
7. 3. Specific end use(s):	None reasonably foreseeable.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8. 1. Control parameters:	
8. 1. 1. Exposure limit(s):	• Dioxyde de carbone : VME ppm = 5000 - VME mg/m³ = 9000 - VLE ppm = 30000 - VLE mg/m³ = 54000
8. 1. 2. Engineering measure(s):	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and/or solvent vapours below the relevant occupational exposure limits, suitable respiratory protective equipment should be worn.
8. 2. Exposure controls:	
8. 2. 1. Respiratory protection:	Not necessary with sufficient ventilation.
8. 2. 2. Hand protection:	When skin exposure may occur, advice should be sought from glove suppliers on appropriate types. nitrile rubber gloves
8. 2. 3. Skin and body protection:	Wear suitable protective clothing
8. 2. 4. Eye protection:	Eye protection designed to protect against exposure to dusts should be worn when there is a likelihood of exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

9. 1. Information on basic physical and chemical properties:	
9. 1. 1. Appearance:	aerosol: . + propellant gas no flammable
9. 1. 2. Colour:	black
9. 1. 3. Odour:	characteristic
9. 1. 4. PH:	Not applicable.
9. 1. 5. Boiling point/range:	Not determined.
9. 1. 6. Flash point:	< 21 °C
9. 1. 7. Explosion limits:	0,6 -12 volume %
9. 1. 8. Relative density (water = 1):	0.865 kg/m³
9. 1. 9. Viscosity:	Not determined.
9. 2. Other information:	
9. 2. 1. Water solubility:	immiscible
9. 2. 2. Fat solubility:	partly miscible
9. 2. 3. Solvent solubility:	soluble in most organic solvents

SAFETY DATA SHEET

LUB ENGRENAGE

Version:3

Review date: 10/03/2015

RE EC/453/2010 - ISO 11014-1

10. STABILITY AND REACTIVITY

- | | |
|--|--|
| 10. 1. Reactivity: | No decomposition if stored and applied as directed. |
| 10. 2. Chemical stability: | Stable under the recommended storage and handling conditions. (See Section 7). |
| 10. 3. Possibility of hazardous reactions: | Not waited |
| 10. 4. Conditions to avoid: | Avoid temperature above 50 °C
Heating will cause rise in pressure with risk of bursting. |
| 10. 5. Incompatible materials: | Keep away from oxidising agents and strongly alkaline and strongly acidic materials to prevent the possibility of exothermic reaction. |
| 10. 6. Hazardous decomposition products: | Hazardous decomposition products may be released during prolonged heating like smokes, carbon monoxide and dioxide... |

11. TOXICOLOGICAL INFORMATION

- | | |
|--|--|
| 11. 1. Information on toxicological effects: | No available information on preparation. |
| 11. 2. Acute toxicity: | |
| 11. 2. 1. Inhalation: | see item nr 3 |
| 11. 2. 2. Skin contact: | see item nr 3 |
| 11. 2. 3. Eyes contact: | see item nr 3 |
| 11. 2. 4. Ingestion: | see item nr 3 |

12. ECOLOGICAL INFORMATION

- | | |
|--|---|
| 12. 1. Toxicity: | Ecological problems are not known or expected under normal use. |
| 12. 2. Persistence and degradability: | Product has only a limited biodegradability in soil and water. |
| 12. 3. Bioaccumulative potential: | None bioaccumulation. |
| 12. 4. Mobility in soil: | . |
| 12. 5. Results of PBT and vPvB assessment: | This product n' is not a substance PBT or vPvB, or n' in does not contain. |
| 12. 6. Other adverse effects: | No expected harmful effects. |
| 12. 7. General information(s): | There is no data available on the product itself.
The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters. |

13. DISPOSAL CONSIDERATIONS

- | | |
|---------------------------------|--|
| 13. 1. Waste treatment methods: | Do not allow into drains or water courses or dispose of where ground or surface waters may be affected.
Collect all waste in suitable and labelled containers and dispose according to local legislation. |
| 13. 2. Contaminated packaging: | Empty containers should be taken for recycle, recovery or waste in accordance with local regulation. |

14. TRANSPORT INFORMATION

- | | |
|--------------------------------|------------------------------------|
| 14. 1. General information(s): | Transport followed ADR, IMDG, IATA |
|--------------------------------|------------------------------------|

SAFETY DATA SHEET

LUB ENGRENAGE

Version:3

Review date:10/03/2015

RE EC/453/2010 - ISO 11014-1

- | | |
|---|--|
| 14. 2. UN number: | 1950 |
| 14. 3. Land (Road / Rail way: ADR/RID): | |
| 14. 3. 1. Transport hazard class(es): | 2 |
| 14. 3. 2. ADR/RID-Labels: | 2.1 |
| 14. 3. 3. Classification code: | 5F |
| 14. 3. 4. Packing instructions: | P204 |
| 14. 4. Sea (IMDG): | |
| 14. 5. Air (ICAO/IATA): | |
| 14. 6. Environmental hazards: | No special environmental precautions required. |
| 14. 7. Special precautions for user: | Concerning personal protective equipment to use, see item 8. |
| 14. 8. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: | Not applicable. |

15. REGULATORY INFORMATION

- | | |
|--|--|
| 15. 1. Safety, health and environmental regulations/legislation specific for the substance or mixture: | Payment 1907/2006 concerning I recording, I evaluation and I authorization of chemical substances, as well as the restrictions applicable to these substances.... as modified. |
| 15. 2. Chemical safety assessment: | Not applicable. |

16. OTHER INFORMATION

- | | |
|---|--|
| 16. 1. Text of the phrases listed in section 3: | R10 Flammable.
R65 Harmful: may cause lung damage if swallowed.
R66 Repeated exposure may cause skin dryness or cracking
R67 Vapours may cause drowsiness and dizziness
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H225 Highly flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H304 May be fatal if swallowed and enters airways. |
| 16. 2. Important remarks: | As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.
The user is always responsible for ensuring that the requirements of relevant legislation are complied with.
The information contained in this safety data sheet is based on the present state of knowledge and current national legislation it provides guidance on health safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. |
| 16. 3. Restrictions: | This information relates to the specific material designated and may not be valid in combination with other product(s). |
| 16. 4. History: | |
| 16. 4. 1. First edition date: | 20/12/2005 |
| 16. 4. 2. Previous revision date: | 11/06/2010 |
| 16. 4. 3. Review date: | 10/03/2015 |
| 16. 4. 4. Version: | 3 |
| 16. 4. 5. Review chapter(s) n°: | CLP |

SAFETY DATA SHEET

LUB ENGRENAGE

Version:3

Review date:10/03/2015

RE EC/453/2010 - ISO 11014-1

16. 5. Written by:	SELD