

Safety Data Sheet dated 4/7/2019, version 5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: WIZZY SMACCHIA TESSUTI (con impregnante)

Trade code: 1939

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Cloth impregnated with fabric stain remover

1.3. Details of the supplier of the safety data sheet

Supplier:

Arexons S.p.A.

via Antica di Cassano, 23, 20063

Cernusco sul Naviglio (MI), Italy

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Competent person responsible for the safety data sheet:

arexons@arexons.it

1.4. Emergency telephone number

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Centro Antiveleni di Pavia IRCCS- Fondazione Maugeri tel. +39 (0)382 24444 (h24; it, en)

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

In Ireland: Beaumont Hospital - National Poisons Information Centre 01 809 2166 (7days, 8:00 -

22:00)

In South Africa: Poison Information Helpline 0861 555 777

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Hazard pictograms:

None

Hazard statements:

None

Precautionary statements:

None

Special Provisions:

None

Special provisions according to Annex XVII of REACH and subsequent amendments:

. None

Regulation (EC) nr 648/2004 (detergents).

Product contents:

Phosphates, Non-ionic surfactants

< 5 %

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

1939/5

Page n. 1 of 9



Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

>= 3% - < 5% Dipropylen glycol methyl ether

REACH No.: 01-2119450011-60, CAS: 34590-94-8, EC: 252-104-2

Substance with a Union workplace exposure limit.

>= 1% - < 2% 1-methoxy-2-propanol

REACH No.: 01-2119457435-35, Index number: 603-064-00-3, CAS: 107-98-2, EC: 203-539-1

2.6/3 Flam. Liq. 3 H226

◆ 3.8/3 STOT SÉ 3 H336

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Appropriate Extinguishing Media:

To carbon dioxide.

To dust.

Foam

Water spray.

Not Recommended Extinguishing Media:

Do not use direct water jets.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains

Move undamaged containers from immediate hazard area if it can be done safely.



SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Dipropylen glycol methyl ether - CAS: 34590-94-8

20101.10 - TWA(8h): 308 mg/m3, 50 ppm

EU - TWA(8h): 308 mg/m3, 50 ppm - Notes: Skin

ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: Skin - Eye and URT irr, CNS impair

1-methoxy-2-propanol - CAS: 107-98-2

EÚ - TWÁ(8h): 375 mg/m3, 100 ppm - STEL: 563 mg/m3, 150 ppm - Notes: Skin ACGIH - TWA(8h): 50 ppm - STEL: 100 ppm - Notes: A4 - Eye and URT irr

DNEL Exposure Limit Values

Dipropylen glycol methyl ether - CAS: 34590-94-8

Consumer: 36 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects Worker Professional: 308 mg/m3 - Consumer: 37.2 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Professional: 283 mg/kg - Consumer: 121 mg/kg - Exposure: Human Dermal -Frequency: Long Term, systemic effects

1-methoxy-2-propanol - CAS: 107-98-2

Consumer: 33 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects Worker Industry: 369 mg/m3 - Worker Professional: 369 mg/m3 - Consumer: 43.9 mg/m3

- Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 183 mg/kg - Worker Professional: 183 mg/kg - Consumer: 78 mg/kg -

Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 553.5 mg/m3 - Worker Professional: 553.5 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, local effects



Worker Industry: 553.5 mg/m3 - Worker Professional: 553.5 mg/m3 - Exposure: Human

Inhalation - Frequency: Short Term, systemic effects

PNEC Exposure Limit Values

Dipropylen glycol methyl ether - CAS: 34590-94-8

Target: Fresh Water - Value: 19 mg/l Target: Marine water - Value: 1.9 mg/l

Target: Marine water sediments - Value: 7.02 mg/kg Target: Freshwater sediments - Value: 70.2 mg/kg

Target: 09 - Value: 4168 mg/l 1-methoxy-2-propanol - CAS: 107-98-2 Target: Fresh Water - Value: 10 mg/l

Target: Freshwater sediments - Value: 52.3 mg/kg Target: Marine water sediments - Value: 5.2 mg/kg

Target: Marine water - Value: 1 mg/l

Target: 09 - Value: 100 mg/l

8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Not needed for normal use.

Respiratory protection:

Not needed for normal use.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Appearance and colour:	Panno impregnato		
Odour:	Characteristic		
Odour threshold:	N.A.		
pH:	11		
Melting point / freezing point:	N.A.		
Initial boiling point and boiling range:	N.A.		
Flash point:	N.A.		
Evaporation rate:	N.A.		
Solid/gas flammability:	N.A.		
Upper/lower flammability	N.A.		



or explosive limits:		
Vapour pressure:	N.A.	
Vapour density:	N.A.	
Relative density:	N.A.	
Solubility in water:	N.A.	
Solubility in oil:	N.A.	
Partition coefficient (n-octanol/water):	N.A.	
Auto-ignition temperature:	N.A.	
Decomposition temperature:	N.A.	
Viscosity:	N.A.	
Explosive properties:	N.A.	
Oxidizing properties:	N.A.	

9.2. Other information

Properties	Value	Method:	Notes:
Miscibility:	N.A.		
Fat Solubility:	N.A.		
Conductivity:	N.A.		
Substance Groups relevant properties	N.A.		

NA=not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

- 10.3. Possibility of hazardous reactions None
- 10.4. Conditions to avoid

Stable under normal conditions.

- 10.5. Incompatible materials

 None in particular.
- 10.6. Hazardous decomposition products None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

1939/5

Page n. 5 of 9



Toxicological information of the product:
WIZZY SMACCHIA TESSUTI (con impregnante)
a) acute toxicity

Based on available data, the classification criteria are not met b) skin corrosion/irritation

Based on available data, the classification criteria are not met c) serious eye damage/irritation

Based on available data, the classification criteria are not met d) respiratory or skin sensitisation

Based on available data, the classification criteria are not met e) germ cell mutagenicity

Based on available data, the classification criteria are not met f) carcinogenicity

Based on available data, the classification criteria are not met g) reproductive toxicity

Based on available data, the classification criteria are not met h) STOT-single exposure

Based on available data, the classification criteria are not met i) STOT-repeated exposure

Based on available data, the classification criteria are not met j) aspiration hazard

Based on available data, the classification criteria are not met Toxicological information of the main substances found in the product:

Dipropylen glycol methyl ether - CAS: 34590-94-8

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg Test: LD50 - Route: Skin - Species: Rabbit > 9510 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat 275 Ppm - Duration: 7h

1-methoxy-2-propanol - CAS: 107-98-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 4016 mg/kg Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 7000 Ppm - Duration: 8h

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment. Dipropylen glycol methyl ether - CAS: 34590-94-8

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96 Endpoint: LC50 - Species: Daphnia 1919 mg/l - Duration h: 48 Endpoint: CE5 - Species: Algae > 969 mg/l - Duration h: 72

1-methoxy-2-propanol - CAS: 107-98-2

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 72

Endpoint: EC50 - Species: Daphnia > 21100 mg/l - Duration h: 48 - Notes: 21100-25900



mg/

Endpoint: EC50 - Species: Fish = 20800 mg/l - Duration h: 96

12.2. Persistence and degradability

None

N.A.

12.3. Bioaccumulative potential

1-methoxy-2-propanol - CAS: 107-98-2

Test: Kow - Partition coefficient -0.43

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

14.1. UN number

Not classified as dangerous in the meaning of transport regulations.

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

N.A.

14.4. Packing group

N.A.

14.5. Environmental hazards

ADR-Enviromental Pollutant: No IMDG-Marine pollutant: No

14.6. Special precautions for user

ŃΑ

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) 2015/830

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)



Regulation (EU) n. 2017/776 (ATP 10 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 40

Restrictions related to the substances contained:

Restriction 30

Volatile Organic compounds - VOCs = 5.45~%

Volatile Organic compounds - VOCs = 54.50 g/Kg

Volatile Organic compounds - VOCs = 55.05 g/l

Where applicable, refer to the following regulatory provisions:

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

None

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture. Substances for which a Chemical Safety Assessment has been carried out:

None

SECTION 16: Other information

Text of phrases referred to under heading 3:

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Hazard class and hazard category	Code	Description
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3

Paragraphs modified from the previous revision:

SECTION 7: Handling and storage

SECTION 8: Exposure controls/personal protection

SECTION 11: Toxicological information SECTION 12: Ecological information

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

1939/5



This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

CAS: Chemical Abstracts Service (division of the American Chemical

Society)

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of

Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

(ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

NA: Not applicable

PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods

by Rail.

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWA: Time-weighted average
WGK: German Water Hazard Class.