Printing date 20.11.2019

Safety data sheet according to 1907/2006/EC, Article 31

Version number 3

Revision: 20.11.2019

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- Trade name: MANNOL 4015 Antifreeze AF13++ (-40)
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Technical function Antifreeze agent
- · Application of the substance / the mixture Heat transfer fluid
- · 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: UAB "SCT Lubricants" Silutes PI. 119 LIT-95112 KLAIPEDA LITHUANIA renata@sct.lt

- · Further information obtainable from: Product safety department.
- 1.4 Emergency telephone number: During normal opening times: +370/615 313 68

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008
 - GHS08 health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Eye Irrit. 2 H319 Causes serious eye irritation.

2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labelling:
- ethanediol • Hazard statements

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

- Precautionary statements
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.

(Contd. on page 2)

⁻ GB

Trade name: MANNOL 4015 Antifreeze AF13++ (-40)

	(Contd. of page 1)
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P280	Wear eye protection / face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing.
P314	Get medical advice/attention if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
· 2.3 Other hazards	5

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:						
CAS: 107-21-1 EINECS: 203-473-3	ethanediol	STOT RE 2, H373; Acute Tox. 4, H30)2 <52.25%			
EINECS. 203-473-3						
· Not dangerous substances						
	sodium hydroxide		<0.275%			
EINECS: 215-185-5	Skin Corr. 1A, H314; Acute Tox. 4, H302					
	methyl-1H-benzotriazole		0.0055–0.22%			
EINECS: 249-596-6	Acute Tox. 4, H302					

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

Use fire extinguishing methods suitable to surrounding conditions.

(Contd. on page 3)



Printing date 20.11.2019

Version number 3

Revision: 20.11.2019

Printing date 20.11.2019

Version number 3

Revision: 20.11.2019

Trade name: MANNOL 4015 Antifreeze AF13++ (-40)

(Contd. of page 2)

Foam Fire-extinguishing powder Sand

- 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Ensure adequate ventilation Particular danger of slipping on leaked/spilled product. Wear protective clothing. · 6.2 Environmental precautions: Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

- GB



Version number 3

Revision: 20.11.2019

Trade name: MANNOL 4015 Antifreeze AF13++ (-40)

(Contd. of page 3)

· Ingredients with limit values that require monitoring at the workplace:

107-21-1 ethanediol (52.25%)

· 8.1 Control parameters

WEL Short-term value: 104** mg/m³, 40** ppm Long-term value: 10* 52** mg/m³, 20** ppm Sk *particulate **vapour

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eve protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties • 9.1 Information on basic physical and chemical properties

- · General Information
- Appearance:
- Form:
 - Colour:

Liquid Violet

(Contd. on page 5)



Printing date 20.11.2019

Printing date 20.11.2019

Version number 3

Revision: 20.11.2019

Trade name: MANNOL 4015 Antifreeze AF13++ (-40)

	(Contd. of page 4)
· Odour:	Product specific
· Odour threshold:	Not determined.
· pH-value:	Not determined.
 Change in condition Melting point/freezing point: Initial boiling point and boiling range 	Undetermined. e: >160 °C
· Flash point:	Not applicable.
· Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapour pressure:	Not determined.
 Density at 20 °C: Relative density Vapour density Evaporation rate 	1.075 g/cm ³ Not determined. Not determined. Not determined.
 Solubility in / Miscibility with water: 	Fully miscible.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
 Solvent content: VOC (EC) 9.2 Other information 	0.00 % No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- · 10.6 Hazardous decomposition products:
- Carbon monoxide
- Aldehyde

Poisonous gases/vapours

(Contd. on page 6)

[–] GB



Printing date 20.11.2019

Version number 3

Revision: 20.11.2019

Trade name: MANNOL 4015 Antifreeze AF13++ (-40)

Carbon dioxide

(Contd. of page 5)

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

107-21-1 ethanediol

Oral LD50 5,840 mg/kg (rat)

Dermal LD50 9,530 mg/kg (rabbit)

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation
- Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure
- May cause damage to organs through prolonged or repeated exposure.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Version number 3

Revision: 20.11.2019

(Contd. of page 6)

Trade name: MANNOL 4015 Antifreeze AF13++ (-40)

· European waste catalogue

HP 5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

· Uncleaned packaging:

HP 6 Acute Toxicity

· Recommendation: Disposal must be made according to official regulations.

• Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, ADN, IMDG, IATA	not regulated			
 14.2 UN proper shipping name ADR, ADN, IMDG, IATA 	not regulated			
 14.3 Transport hazard class(es) 				
· ADR, ADN, IMDG, IATA · Class	not regulated			
· 14.4 Packing group · ADR, IMDG, IATA	not regulated			
· 14.5 Environmental hazards:	Not applicable.			
 14.6 Special precautions for user 	Not applicable.			
• 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.				
· UN "Model Regulation":	not regulated			

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H373 May cause damage to organs through prolonged or repeated exposure.

· Department issuing SDS: Product safety department.

(Contd. on page 8)



Printing date 20.11.2019

Revision: 20.11.2019

Trade name: MANNOL 4015 Antifreeze AF13++ (-40)

(Contd. of page 7) · Contact: Mrs. Zubaite · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - oral - Category 4 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 * * Data compared to the previous version altered. GB



Printing date 20.11.2019

Version number 3