

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.06.2023

Version number 2306 (replaces version 2205)

Revision: 01.06.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** **MANNOL 9668 Tar Remover 450ml**
- **UFI:** 51SU-S0NS-A000-R87X
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Cleaning agent/ Cleaner
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SCT-Vertriebs GmbH
Feldstrasse 154
22880 WEDEL
DEUTSCHLAND
+49 (0)4103 1211 0
info@sct-germany.de
- **Further information obtainable from:** Product safety department.
- **1.4 Emergency telephone number:**
Members of the public seeking specific information on poisons should contact:
In England and Wales: NHS 111 - dial 111
In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger

(Contd. on page 2)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.06.2023

Version number 2306 (replaces version 2205)

Revision: 01.06.2023

Trade name: MANNOL 9668 Tar Remover 450ml

(Contd. of page 1)

· Hazard-determining components of labelling:

xylene

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards**· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures**· Description:** Mixture of substances listed below with nonhazardous additions.**· Dangerous components:**

| | | |
|--------------------------------------|---|--------|
| CAS: 1330-20-7 EINECS: 215-535-7 | xylene Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 | 40–60% |
| CAS: 68476-86-8 EINECS: 270-705-8 | Petroleum gases, liquefied, sweetened Flam. Gas 1A, H220; Press. Gas (Comp.), H280 | 10–24% |
| CAS: 108-67-8 EINECS: 203-604-4 | mesitylene Flam. Liq. 3, H226; Aquatic Chronic 2, H411; STOT SE 3, H335 Specific concentration limit: STOT SE 3; H335: C ≥ 25 % | 1–4% |

· Not dangerous substances

| | | | |
|-------------------------------------|----------------------|-------------------|------|
| CAS: 8008-20-6 EINECS: 232-366-4 | Kerosine (petroleum) | Asp. Tox. 1, H304 | 1–8% |
|-------------------------------------|----------------------|-------------------|------|

(Contd. on page 3)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.06.2023

Version number 2306 (replaces version 2205)

Revision: 01.06.2023

Trade name: MANNOL 9668 Tar Remover 450ml

(Contd. of page 2)

CAS: 67254-74-4

EC number: 614-042-8

Naphthenic oils

1–4%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· **Suitable extinguishing agents:**

CO₂. Do not use water.

Use fire extinguishing methods suitable to surrounding conditions.

Foam

Fire-extinguishing powder

Sand

· **For safety reasons unsuitable extinguishing agents:** Water

· 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

· 5.3 Advice for firefighters

· **Protective equipment:** Mouth respiratory protective device.

· **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Particular danger of slipping on leaked/spilled product.

Wear protective clothing.

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.06.2023

Version number 2306 (replaces version 2205)

Revision: 01.06.2023

Trade name: MANNOL 9668 Tar Remover 450ml

(Contd. of page 3)

- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 xylene (60.0%)

| | |
|-----|---|
| OEL | Short-term value: 442 mg/m ³ , 100 ppm |
| | Long-term value: 221 mg/m ³ , 50 ppm |
| | Sk, IOELV |

108-67-8 mesitylene (4.0%)

| | |
|-----|---|
| OEL | Long-term value: 100 mg/m ³ , 20 ppm |
| | IOELV |

- **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.06.2023

Version number 2306 (replaces version 2205)

Revision: 01.06.2023

Trade name: MANNOL 9668 Tar Remover 450ml

(Contd. of page 4)

- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye/face protection**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

| | |
|---|-----------------------------|
| · Colour: | Clear |
| · Odour: | Characteristic |
| · Odour threshold: | Not determined. |
| · Melting point/freezing point: | Undetermined. |
| · Boiling point or initial boiling point and boiling range | Not applicable, as aerosol. |
| · Flammability | Not applicable. |
| · Lower and upper explosion limit | |
| · Lower: | Not determined. |
| · Upper: | Not determined. |
| · Flash point: | Not applicable, as aerosol. |
| · Decomposition temperature: | Not determined. |
| · pH | Not determined. |
| · Viscosity: | |
| · Kinematic viscosity | Not determined. |
| · Dynamic: | Not determined. |
| · Solubility | |
| · water: | Fully miscible. |

(Contd. on page 6)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.06.2023

Version number 2306 (replaces version 2205)

Revision: 01.06.2023

Trade name: MANNOL 9668 Tar Remover 450ml

(Contd. of page 5)

- **Partition coefficient n-octanol/water (log value)** Not determined.
- **Vapour pressure:** Not determined.
- **Density and/or relative density**
- **Density:** Not determined.
- **Relative density** Not determined.
- **Vapour density** Not determined.

9.2 Other information

- **Appearance:**
- **Form:** Liquid
- **Important information on protection of health and environment, and on safety.**
- **Ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Not determined.
- **Solvent content:**
- **Organic solvents:** 30–60 %
- **VOC (EC)** 41–64 %
- **Solids content:** 0.0 %
- **Change in condition**
- **Evaporation rate** Not applicable.

Information with regard to physical hazard classes

- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Extremely flammable aerosol. Pressurised container: May burst if heated.
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Void
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.

(Contd. on page 7)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.06.2023

Version number 2306 (replaces version 2205)

Revision: 01.06.2023

Trade name: MANNOL 9668 Tar Remover 450ml

(Contd. of page 6)

- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
 - Carbon monoxide
 - Aldehyde
 - Poisonous gases/vapours
 - Carbon dioxide

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**
Harmful if inhaled.

| | | |
|--|----------|----------------------------|
| · LD/LC50 values relevant for classification: | | |
| ATE (Acute Toxicity Estimates) | | |
| Dermal | LD50 | 3,333–5,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 18.3–27.5 mg/l |

| | | |
|------------|----------|----------------------------|
| Dermal | LD50 | 3,333–5,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 18.3–27.5 mg/l |

| | | |
|-------------------------|------|----------------------|
| 1330-20-7 xylene | | |
| Oral | LD50 | 4,300 mg/kg (rat) |
| Dermal | LD50 | 2,000 mg/kg (rabbit) |

| | | |
|--------|------|----------------------|
| Oral | LD50 | 4,300 mg/kg (rat) |
| Dermal | LD50 | 2,000 mg/kg (rabbit) |

- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

| |
|--|
| · Endocrine disrupting properties |
| None of the ingredients is listed. |

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
For information on endocrine disrupting properties see section 11.

(Contd. on page 8)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.06.2023

Version number 2306 (replaces version 2205)

Revision: 01.06.2023

Trade name: MANNOL 9668 Tar Remover 450ml

(Contd. of page 7)

12.7 Other adverse effects**Additional ecological information:****General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

13.1 Waste treatment methods**Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

| | |
|------|---|
| HP3 | Flammable |
| HP4 | Irritant - skin irritation and eye damage |
| HP6 | Acute Toxicity |
| HP14 | Ecotoxic |

Uncleaned packaging:**Recommendation:** Disposal must be made according to official regulations.**Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

14.1 UN number or ID number**ADR, IMDG, IATA**

UN1950

14.2 UN proper shipping name**ADR**

1950 AEROSOLS

IMDG

AEROSOLS

IATA

AEROSOLS, flammable, containing substances in Division 6.1, Packing Group III

14.3 Transport hazard class(es)**ADR****Class**

2 5TF Gases.

Label

2.1+6.1

IMDG**Class**

2.1 Gases.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 01.06.2023

Version number 2306 (replaces version 2205)

Revision: 01.06.2023

Trade name: MANNOL 9668 Tar Remover 450ml

(Contd. of page 8)

| | |
|--|---|
| · Label | 2.1/6.1 |
| · IATA | |
|  | |
| · Class | 2.1 Gases. |
| · Label | 2.1 (6.1) |
| · 14.4 Packing group · ADR, IMDG, IATA | not regulated |
| · 14.5 Environmental hazards: | Not applicable. |
| · 14.6 Special precautions for user · Hazard identification number (Kemler code): - · EMS Number: · Stowage Code · Segregation Code | Warning: Gases. F-D,S-U SW1 Protected from sources of heat. SW2 Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. |
| · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| · Transport/Additional information: | |
| · ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code | 120 ml Code: E0 Not permitted as Excepted Quantity 1 D |
| · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | 1L Code: E0 Not permitted as Excepted Quantity |
| · UN "Model Regulation": | UN 1950 AEROSOLS, 2.1 |

(Contd. on page 10)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.06.2023

Version number 2306 (replaces version 2205)

Revision: 01.06.2023

Trade name: MANNOL 9668 Tar Remover 450ml

(Contd. of page 9)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H220 Extremely flammable gas.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS: Product safety department.

Date of previous version: 03.10.2022

Version number of previous version: 2205

Abbreviations and acronyms:

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association

(Contd. on page 11)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.06.2023

Version number 2306 (replaces version 2205)

Revision: 01.06.2023

Trade name: MANNOL 9668 Tar Remover 450ml

(Contd. of page 10)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * **Data compared to the previous version altered.**

IE