Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SAFETY DATA SHEET



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier		
Product name	Castrol Magnatec Stop-Start 5W-30 S1	
Product code	469559-BE02	
SDS #	469559	
Product type	Liquid.	
1.2 Relevant identified uses	s of the substance or mixture and uses advised against	
Use of the substance/ mixture	Engine Oils. For specific application advice see appropriate Technical Data Sheet or consult our company representative.	
1.3 Details of the supplier o	of the safety data sheet	
Supplier	Lubricants UK Limited, Chertsey Road, Sunbury On Thames, Middlesex, TW16 7BP	
	+44 (0)345 600 8125	
E-mail address	MSDSadvice@bp.com	

 1.4 Emergency telephone number

 EMERGENCY
 Carechem: +44 (0) 1235 239 670 (24/7)

 TELEPHONE NUMBER

SECTION 2: Hazards identification

 2.1 Classification of the substance or mixture

 Product definition
 Mixture

 Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

 Not classified.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements

2.2 Laber elements						
Signal word	No signal word.					
Hazard statements	No known significant effects or critical	hazards	i.			
Precautionary statements						
Prevention	Not applicable.					
Response	Not applicable.					
Storage	Not applicable.					
Disposal	Not applicable.					
Hazardous ingredients	Not applicable.					
Supplemental label elements	Contains C14-16-18 Alkyl phenol. May produce an allergic reaction. Safety data sheet available on request.					
EU Regulation (EC) No. 1907/2	006 (REACH)					
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Not applicable.					
Special packaging requirement	<u>ts</u>					
Product name Castrol Magnatec	Stop-Start 5W-30 S1	P	Product code	469559-B	E02	Page: 1/11
Version 3.02 Date of issue 11	September 2023 Fo		Inited (ingdom UK)		Language	ENGLISH
Date of previous issue 17	November 2022.	(i	United Kingdo	om)		

SECTION 2: Hazards identification

Containers to be fitted with child-resistant fastenings	Not applicable.
Tactile warning of danger	Not applicable.
2.3 Other hazards	
Results of PBT and vPvB assessment	Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	Defatting to the skin. USED ENGINE OILS Used engine oil may contain hazardous components which have the potential to cause skin cancer. See Toxicological Information, section 11 of this Safety Data Sheet.

SECTION 3: Composition/information on ingredients

Mixture

3.2 Mixtures

Product definition

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	REACH #: 01-2119474889-13 EC: 276-738-4 CAS: 72623-87-1 Index: 649-483-00-5	≥25 - ≤50	Asp. Tox. 1, H304	-	[1]
C14-16-18 Alkyl phenol	REACH #: 01-2119498288-19	≤0.3	Skin Sens. 1B, H317 STOT RE 2, H373	-	[1]

See Section 16 for the full text of the H statements declared above.

Type

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.
Inhalation	If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Potential acute health effects

Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
No known significant effects or critical hazards.
Defatting to the skin. May cause skin dryness and irritation.
No known significant effects or critical hazards.

Product name Castrol Magnatec Stop-Start 5W-30 S1			Product code 469559-	3E02	Page: 2/11
Version 3.02 Date of issue	11 September 2023	Format	United Kingdom (UK)	Language	ENGLISH
Date of previous issue	17 November 2022.		(United Kingdom)		

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SECTION 4: First aid measures

-	e effects as well as chronic effects from short and long-term exposure
Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet. The use of a water jet may cause the fire to spread by splashing the burning product.
5.2 Special hazards arising fro	om the substance or mixture
Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	Combustion products may include the following: carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide) metal oxide/oxides nitrogen oxides (NO, NO ₂ etc.)
5.3 Advice for firefighters	
Special precautions for fire-fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, prot	ective equipment and emergency procedures
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Put on appropriate personal protective equipment.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for c	containment and cleaning up
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Product name Castrol Magnatec Stop-Start 5W-30 S1	Product code 469559-BE02 Page: 3/11
Version 3.02 Date of issue 11 September 2023	Format United Language ENGLISH Kingdom (UK)
Date of previous issue 17 November 2022.	(United Kingdom)

SECTION 6: Accidental release measures

6.4 Reference to other	See Section 1 for emergency contact information.
sections	See Section 5 for firefighting measures.
	See Section 8 for information on appropriate personal protective equipment.
	See Section 12 for environmental precautions.
	See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe han	ıdling
Protective measures	Put on appropriate personal protective equipment.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/ containers designed for use with this product. Do not store in unlabelled containers.
Not suitable	Prolonged exposure to elevated temperature.
7.3 Specific end use(s)	
Recommendations	See section 1.2 and Exposure scenarios in annex, if applicable.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Recommended monitoring procedures

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived No Effect Level

No DNELs/DMELs available.

Predicted No Effect Concentration

No PNECs available

8.2 Exposure controls	
Appropriate engineering controls	Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.
Respiratory protection	

Product name Castrol Magnatec Stop-Start 5W-30 S1	Product code 469559-BE02	Page: 4/11
Version 3.02 Date of issue 11 September 2023	Format United Language I Kingdom (UK)	ENGLISH
Date of previous issue 17 November 2022.	(United Kingdom)	

SECTION 8: Exposure controls/personal protection

	In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.
Eye/face protection	Safety glasses with side shields.
Skin protection	
Hand protection	General Information:
	Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).
	Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.
	Recommended: Nitrile gloves. Breakthrough time:
	Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:
	Continuous contact:
	Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained. If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.
	Short-term / splash protection:
	Recommended breakthrough times as above. It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.
	Glove Thickness:
	For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.
	It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.
	Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:
	• Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
	• Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

Product name	Castrol Magnat	ec Stop-Start 5W-30 S1		Product code 469559-	BE02	Page: 5/11
Version 3.02	Date of issue	11 September 2023	Format	United Kingdom (UK)	Language	ENGLISH
Date of previo	ous issue	17 November 2022.		(United Kingdom)		

SECTION 8: Exposure controls/personal protection

Skin and body	Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
<u>Refer to standards:</u>	Respiratory protection: EN 529 Gloves: EN 420, EN 374 Eye protection: EN 166 Filtering half-mask: EN 149 Filtering half-mask with valve: EN 405 Half-mask: EN 140 plus filter Full-face mask: EN 136 plus filter Particulate filters: EN 143 Gas/combined filters: EN 14387
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

	ind chemical proper							
Physical state	Liquid.							
Colour	Amber. [Light]							
Odour	Not available.							
Odour threshold	Not available.							
Melting point/freezing point	Not available.							
Initial boiling point and boiling range	Not available.							
Flammability	Not available.							
Lower and upper explosion limit	Not available.							
Flash point	Closed cup: 209°C ((408.2°F) [Pensky	y-Martens]				
Auto-ignition temperature	Ingredient name		°C	°F	Ν	lethod		
	bis(nonylphenyl)amine		440	824	E	U A.15		
Decomposition temperature	Not available.							_1
pH	Not applicable.							
Kinematic viscosity	Kinematic: 59.9 mm Kinematic: 10.3 mm							
Solubility		,	,					
	Media		Result					1
	water	N	ot soluble)				
Partition coefficient n-octanol/ water (log value)	Not applicable.	I						J
Vapour pressure		Vapo	ur Press	ure at 20°C	Vapo	ur press	ure at 50°C	1
	Ingredient name	mm Hç	g kPa	Method	mm	kPa	Method	Ī
					Hg			
	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based	<0.08	<0.011	ASTM D 5191	Hg			
	(petroleum), C20-50, hydrotreated neutral oil-	<0.08	<0.011	ASTM D 5191 ASTM D 5191	Hg			
Product name Castrol Magnatec Stop	(petroleum), C20-50, hydrotreated neutral oil- based Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based			ASTM D 5191		9559-BEC)2 Pag	ge: 6/11
Product name Castrol Magnatec Stop Version 3.02 Date of issue 11 Se	(petroleum), C20-50, hydrotreated neutral oil- based Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based		<0.011	ASTM D 5191 Product mat United	code 46			ge: 6/11 GLISH
	(petroleum), C20-50, hydrotreated neutral oil- based Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based		<0.011	ASTM D 5191 Product	code 46			

Conforms to Regulation (EC) N	o. 1907/2006 (REACH), Annex II, as amended by C	ommissio	n Regula	ition (EU) 20	20/878
SECTION 9: Physical a	nd chemical properties				
	bis(nonylphenyl)amine <0.01 <0.0013 EU A.4	0.0019	0.00025	EU A.4	
	Distillates (petroleum), <0.08 <0.011 ASTM D 519 solvent-dewaxed heavy paraffinic	91			
	Distillates (petroleum), <0.08 <0.011 ASTM D 519 hydrotreated heavy paraffinic	91			
Density and/or Relative densit	<1000 kg/m³ (<1 g/cm³) at 15°C				_
Relative vapour density	Not available.				
Particle characteristics					
Median particle size	Not applicable.				
9.2 Other information					
Evaporation rate	Not available.				
Explosive properties	Not available.				
Oxidising properties	Not available.				
Pour point	-46 °C				
SECTION 10: Stability	and reactivity				
10.1 Reactivity	No specific test data available for this product. Reference materials for additional information.	er to Condi	tions to a	void and Inco	ompatible
10.2 Chemical stability	The product is stable.				
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.				
10.4 Conditions to avoid	Avoid all possible sources of ignition (spark or flame).				
10.5 Incompatible materials	Reactive or incompatible with the following materials	: oxidising	materials	S.	
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazard produced.	ous decon	nposition	products sho	uld not be

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity estimates

Product/ingredient name		Oral (mg/ kg)		Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)	
		2500	N/A	N/A	N/A	N/A
Information on likely Routes of entry antici routes of exposure		ipated: Derm	al, Inhalatio	n, Eyes.		
Potential acute health effect	<u>cts</u>					
Inhalation Exposure to decomposition pro delayed following exposure.		•	cts may cau	ise a health ha	azard. Seriou	is effects may
Ingestion	No known significant	No known significant effects or critical hazards.				
Skin contact	May cause s	skin dryness	and irritation.			
Eye contact No known significant		effects or cri	tical hazard	S.		
Symptoms related to the p	hysical, chemical and to	xicological o	haracteris	<u>tics</u>		
Inhalation	No specific data.					
Ingestion	No specific data.					
Skin contact Adverse symptoms irritation dryness cracking		nay include th	ne following:			
Eye contact	No specific data.	No specific data.				
Delayed and immediate eff	ects as well as chronic e	effects from	short and I	ong-term exp	<u>osure</u>	
Product name Castrol Magna	atec Stop-Start 5W-30 S1			Product code	469559-BE02	Page:
Version 3.02 Date of issu	e 11 September 2023			United Kingdom (UK)	La	nguage ENGL
Date of previous issue 17 November 2022. (United Kingdom)						

SECTION 11: Toxicological information

Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.
Potential chronic health eff	ects
General	USED ENGINE OILS Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties				
Not available.				
Remarks - Endocrine disruptor - Health 11.2.2 Other information	Not available.			
Not available.				

SECTION 12: Ecological information

12.1 Toxicity

Environmental hazards

Not classified as dangerous

12.2 Persistence and degradability

Expected to be biodegradable.

12.3 Bioaccumulative potential

Date of previous issue

This product is not expected to bioaccumulate through food chains in the environment.

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	Not available.
Mobility	Spillages may penetrate the soil causing ground water contamination.

12.5 Results of PBT and vPvB assessment

Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.

12.6 Endocrine disrupting properties	Not available.
Remarks - Endocrine disruptor - Environment	Not available.
Other ecological information	Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.
12.7 Other adverse effects	No known significant effects or critical hazards.

SECTION 13: Disposal considerations

17 November 2022.

13.1 Waste treatment meth	ods				
Product					
Methods of disposal	Where possible, arrange fo licensed waste disposal co				d person/
Hazardous waste	Yes.				
European waste catalog	ue (EWC)				
Product name Castrol Magr	natec Stop-Start 5W-30 S1		Product code	469559-BE02	Page: 8/11
Version 3.02 Date of iss	ue 11 September 2023	Format	United Kingdom	Language	ENGLISH

(UK)

(United Kingdom)

SECTION 13: Disposal considerations

	Waste code Waste designation				
	13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils			
	However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.				
P	ackaging				
	Methods of disposal	Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.			
S	pecial precautions	This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.			
R	eferences	Commission 2014/955/EU			

SECTION 14: Transport information

Directive 2008/98/EC

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

14.6 Special precautions for Not available. user

14.7 Maritime transport in	Not available.
bulk according to IMO	
instruments	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture	
EU Regulation (EC) No. 1907/2006 (REACH)	

Annex XIV - List of substances subject to authorisation

Not applicable.

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other regulations REACH Status

The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

Product name Castro	ol Magnatec Stop-Start 5W-30 S1		Product code 469559-E	3E02	Page: 9/11
Version 3.02 Date	e of issue 11 September 2023	Format	United Kingdom (UK)	Language	ENGLISH
Date of previous is	SSUE 17 November 2022.		(United Kingdom)		

SECTION 15: Regulatory information

· · · · · · · · · · · · · · · · · · ·				
United States inventory (TSCA 8b)	All components are active or exempted.			
Australia inventory (AIIC)	All components are listed or exempted.			
Canada inventory	All components are listed or exempted.			
China inventory (IECSC)	All components are listed or exempted.			
Japan inventory (CSCL)	All components are listed or exempted.			
Korea inventory (KECI)	All components are listed or exempted.			
Philippines inventory (PICCS)	At least one component is not listed.			
Taiwan Chemical Substances Inventory (TCSI)	All components are listed or exempted.			
Ozone depleting substances (1005/2009/EU)				
Not listed.				
Prior Informed Consent (PIC) (649/2012/EU) Not listed.				
Persistent Organic Pollutants Not listed.				
EU - Water framework directive - Priority substances				

EU - Water framework directive - Priority substances

None of the components are listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

15.2 Chemical safety	A Chemical Safety Assessment has been carried out for one or more of the substances within
assessment	this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

SECTION 16: Other information

Abbreviations and acronyms	ADN = European Provisions concern Inland Waterway	ning the	nternational Ca	arriage of	Dangerous	Goods by
	ADR = The European Agreement co	oncerning	the Internatior	al Carria	ge of Dange	rous Goods by
	Road ATE = Acute Toxicity Estimate					
	BCF = Bioconcentration Factor					
	CAS = Chemical Abstracts Service					
	CLP = Classification, Labelling and I	Packagin	a Regulation [F	Regulation	n (FC) No. 1	272/20081
	CSA = Chemical Safety Assessmen		g rogalation [i	togalatio	(20)110.1	212/2000]
	CSR = Chemical Safety Report	•				
	DMEL = Derived Minimal Effect Lev	el				
	DNEL = Derived No Effect Level					
	EINECS = European Inventory of Ex	kisting Co	ommercial chen	nical Sub	stances	
	ES = Exposure Scenario	•				
	EUH statement = CLP-specific Haza	ard stater	nent			
	EWC = European Waste Catalogue					
	GHS = Globally Harmonized System			abelling o	f Chemicals	
	IATA = International Air Transport A	ssociatio	n			
	IBC = Intermediate Bulk Container	-				
	IMDG = International Maritime Dang					
	LogPow = logarithm of the octanol/w					4070
	MARPOL = International Convention				rom Snips,	1973 as
	modified by the Protocol of 1978. ("N					
	OECD = Organisation for Economic PBT = Persistent, Bioaccumulative a			lopment		
	PNEC = Predicted No Effect Concer					
	REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation					
	[Regulation (EC) No. 1907/2006]					egulation
	RID = The Regulations concerning t	he Intern	ational Carriad	e of Dano	nerous Good	ls by Rail
	RRN = REACH Registration Numbe		allonial ournag	o or Darig		lo by Hall
	SADT = Self-Accelerating Decompo		mperature			
	SVHC = Substances of Very High C					
	STOT-RE = Specific Target Organ 1		Repeated Expo	osure		
	STOT-SE = Specific Target Organ 1					
Product name Castrol Magnate	ec Stop-Start 5W-30 S1		Product code	469559-1	3E02	Page: 10/11
Version 3.02 Date of issue	11 September 2023	Format	United Kingdom (UK)		Language	ENGLISH
Date of previous issue	17 November 2022.		(United Kingde	om)		

SECTION 16: Other information

TWA = Time weighted average UN = United Nations UVCB = Complex hydrocarbon substance VOC = Volatile Organic Compound vPvB = Very Persistent and Very Bioaccumulative Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4/ RRN 01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN 01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN 01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN 01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN 01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8, 64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 / RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN 01-2119474889-13

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classif	ication	Justification
Not classified.		
Full text of abbreviated H statements	H304	May be fatal if swallowed and enters airways.
Full text of classifications [CLP/GHS]	Asp. Tox. 1	ASPIRATION HAZARD - Category 1
<u>History</u>		
Date of issue/ Date of revision	11/09/2023.	
Date of previous issue	17/11/2022.	
Prepared by	Product Stewardship	
Indicates information that	has showned from monther	

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Castrol Magnatec Stop-Start 5W-30 S1		Product code 469559-BE02		Page: 11/11	
Version 3.02 Date of issu	e 11 September 2023	Format	United Kingdom (UK)	Language	ENGLISH
Date of previous issue	17 November 2022.		(United Kingdom)		