

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 1-10-2019 Revision date: 1-3-2023 Supersedes: 1-10-2019 Version: 2.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture

Product name : Eurol Fluence DXS 5W-30

Product code : E100076
Product group : Trade product

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Intended for general public

Main use category : Industrial use, professional use, Consumer use

Use of the substance/mixture : Lubricant

Function or use category : Lubricants and additives

### 1.2.2. Uses advised against

No additional information available

## 1.3. Details of the supplier of the safety data sheet

Eurol B.V. Energiestraat 12 NL-7442 DA Nijverdal The Netherlands Tel: +31 548 615 165

reach@eurol.com - www.eurol.com

## 1.4. Emergency telephone number

Emergency number : For Transport Emergency Call +31 6 26 71 27 43 (24hr/day 7days/week)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital Msida MSD 2090 Msida	+356 2545 6508	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements (CLP) : P102 - Keep out of reach of children.

EUH-statements : EUH208 - Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs,

calcium salts, Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated. May produce an

allergic reaction.

EUH210 - Safety data sheet available on request.

Child-resistant fastening : Not applicable Tactile warning : Not applicable

### 2.3. Other hazards

Other hazards not contributing to the classification

This product floats on water and may affect the oxygen-balance in the water. The base oil contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT classified as H350: May cause cancer" (Note L).". USED ENGINE OILS: Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0.1 %

## **SECTION 3: Composition/information on ingredients**

## 3.1. Substances

Not applicable

## 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.]	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627- 25	35 – 50	Asp. Tox. 1, H304
Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based	CAS-No.: 72623-87-1 EC-No.: 276-738-4 REACH-no: 01-2119474889- 13	35 – 50	Asp. Tox. 1, H304
Highly refined mineral oil (C15 -C50) substance with a Community workplace exposure limit	REACH-no: 01-2119484627- 25; 01-2119487077-29: 01- 2119471299-27	5 – 10	Not classified
Benzenesulfonic acid, methyl-, mono-C20-24- branched alkyl derivs., calcium salts	CAS-No.: 722503-68-6 EC-No.: 682-816-2	0,1 – 1	Skin Sens. 1B, H317
Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated	EC-No.: 953-650-0 EC Index-No.: 953-650-0	0,1 – 1	Skin Sens. 1B, H317 Repr. 2, H361d

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements: see section 16

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

First-aid measures general

First-aid measures after inhalation

First-aid measures after skin contact

First-aid measures after eye contact

First-aid measures after ingestion

: Seek medical attention if ill effect develops.

: Take victim to fresh air, in a quiet place, in an half laying position and if necessary take  ${\sf res}$ 

medical advice. Allow the victim to rest.

: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. High-pressure injection under skin may cause serious

damage. Seek medical attention if ill effect or irritation develops.

: Remove contact lenses, if present and easy to do. Continue rinsing. Ensure adequate flushing of eyes by separating eyelids with the fingers. Obtain medical attention if pain,

blinking, tears or redness persist.

Consult a doctor/medical service if you feel unwell. If vomiting occurs spontaneously, keep

head below the hips to prevent aspiration. Do not induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation

: At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.

Symptoms/effects after skin contact

: Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis. High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Symptoms/effects after eye contact Symptoms/effects after ingestion

 $: \ \ \mbox{Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.}$ 

: Bad taste. Unlikely to cause harm if accidentally swallowed in small doses, though larger

quantities may cause nausea and diarrhoea.

Symptoms/effects upon intravenous administration : Unknown.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Suitable extinguishing media : carbon dioxide (CO2), dry chemical powder, foam. Water fog.

Unsuitable extinguishing media : Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustion generates: CO, CO2, POx, NOx, SOx, H2S. Metallic oxides.

Explosion hazard : Not expected to be a fire/explosion hazard under normal conditions of use.

## 5.3. Advice for firefighters

Precautionary measures fire

Firefighting instructions

: Use water spray or fog for cooling exposed containers.

Protection during firefighting

: Use self-contained breathing apparatus and chemically protective clothing.

: Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : Prevent fire fighting water from entering the environment. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Spill area may be slippery. Prevent soil and water pollution. Prevent entry to sewers and

public waters.

1-3-2023 (Revision date) EN (English) 3/12

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 6.1.1. For non-emergency personnel

Protective equipment : When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of

splashing) then chemical resistant aprons and/or impervious chemical suits and boots will

be required. Use protective clothing.

**Emergency procedures** 

6.1.2. For emergency responders

Protective equipment When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of

splashing) then chemical resistant aprons and/or impervious chemical suits and boots will

be required.

Consider evacuation.

**Emergency procedures** : No specific measures are necessary.

### 6.2. Environmental precautions

Dike for recovery or absorb with appropriate material. Notify authorities if product enters sewers or public waters. Prevent soil and water pollution. Prevent liquid from entering sewers, watercourses, underground or low areas. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

## 6.3. Methods and material for containment and cleaning up

For containment : Large quantities: Contain large spillage with sand or earth.

Methods for cleaning up : Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders,

sawdust). Take up large spills with pump or vacuum and finish with dry chemical absorbent.

: Use suitable disposal containers. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations. On water, recover/skim from surface and pour out in disposal container.

## 6.4. Reference to other sections

Other information

For further information refer to section 13.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Additional hazards when processed : Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat,

flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and

promptly returned to a drum reconditioner or disposed of properly.

Precautions for safe handling Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or

smoke during use. Remove contaminated clothing and shoes.

Hygiene measures Take all necessary measures to avoid accidental discharge of products into drains and

waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before

reuse.

## 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep container tightly closed and in well ventilated place.

Storage conditions Keep only in original container.

Incompatible products Reacts vigorously with strong oxidizers and acids.

Maximum storage period : 5 year Storage temperature : ≤ 40 °C

Information on mixed storage : Keep away from : Oxidizing materials. Strong acids.

Storage area : Store at ambient temperature.

Special rules on packaging : Keep container tightly closed and dry.

### 7.3. Specific end use(s)

No additional information available

1-3-2023 (Revision date) EN (English) 4/12

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

### Highly refined mineral oil (C15 -C50)

### **EU - Indicative Occupational Exposure Limit (IOEL)**

IOELV TWA (mg/m³)

5 mg/m<sup>3</sup>

#### 8.1.2. Recommended monitoring procedures

No additional information available

## 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

Exposure-value for oil mist

: 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours).

#### 8.1.5. Control banding

No additional information available

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

### Appropriate engineering controls:

Large quantities: Contain large spillage with sand or earth.

#### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Gloves. In case of splash hazard: safety glasses. Eye protection should only be necessary where liquid could be splashed or sprayed.

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

#### Eye protection:

Eye protection should only be necessary where liquid could be splashed or sprayed

## 8.2.2.2. Skin protection

## Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use. Avoid repeated or prolonged skin contact. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn. Equipment should conform to EN 166.

## Hand protection:

In case of repeated or prolonged contact wear gloves. The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream). The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

#### Other skin protection

#### Materials for protective clothing:

PVC gloves. Neoprene or nitrile rubber gloves

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 8.2.2.3. Respiratory protection

#### Respiratory protection:

Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn. Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point >65°C) may be required if vapour or abnormal odour is also present due to high product temperature. Use filter type AP or comparable standard.

#### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

## Environmental exposure controls:

See Heading 12. See Heading 6.

#### Consumer exposure controls:

PVC gloves. Neoprene or nitrile rubber gloves.

#### Other information:

Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour brown. Appearance Oily. Liquid. Odour : characteristic. Odour threshold : Not available Melting point : -36 °C ASTM D 97 Freezing point Not available Boiling point Not available Flammability (solid, gas) : Not available **Explosive limits** : 0.6 - 7 vol %Lower explosive limit (LEL) : 0,6 vol % Upper explosive limit (UEL) : 7 vol %

Flash point : 237 °C ASTM D 92
Auto-ignition temperature : Not available
Decomposition temperature : Not available
pH : Not available

Viscosity, kinematic : 50 – 100 mm²/s at 40 °C, ASTM D 445

Solubility : insoluble in water.

Log Kow : Not available

Vapour Pressure 20°C : Not available

Vapour pressure at 50°C : Not available

Density : 0,85 – 0,86 kg/l ASTM D 4052

Relative density : Not available

Relative vapour density at 20°C

Particle characteristics : Not applicable

## 9.2. Other information

## 9.2.1. Information with regard to physical hazard classes

Explosion limits : 0,6 – 7 vol %

9.2.2. Other safety characteristics

VOC content : 0 %

Other properties : Gas/vapour heavier than air at 20°C

1-3-2023 (Revision date) EN (English) 6/12

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Stable under normal conditions of use.

## 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

### 10.4. Conditions to avoid

Moisture. Overheating.

### 10.5. Incompatible materials

Strong oxidizing agents. Strong acids.

### 10.6. Hazardous decomposition products

CO, CO2, POx, NOx, SOx, H2S. Metallic oxides.

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	> 5,53 mg/l

Skin corrosion/irritation : Not classified Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : The mixture contains a substance with skin sensitization potential, but allergic skin reactions

are not expected.

Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

## **Eurol Fluence DXS 5W-30**

Viscosity, kinematic 50 – 100 mm²/s at 40 °C, ASTM D 445

## Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based (72623-87-1)

Viscosity, kinematic 10000 – 12000 mm²/s

## 11.2. Information on other hazards

## 11.2.1. Endocrine disrupting properties

No additional information available

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 11.2.2. Other information

Other information

: Toxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the toxicology of similar products, Likely route of exposure: ingestion, skin and eye.

## **SECTION 12: Ecological information**

### 12.1. Toxicity

Ecology - general : Ecotoxicological data have not been determined specifically for this product. Information

given is based on a knowledge of the components and the ecotoxicology of similar

Ecology - water

This product floats on water and may affect the oxygen-balance in the water.

Hazardous to the aquatic environment, short-term

(acute)

: Not classified

Hazardous to the aquatic environment, long-term

: Not classified

(chronic)

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

LC50 fish 1	100 mg/l
EC50 Daphnia 1	10000 mg/l
EC50 72h - Algae [1]	> 100 mg/l
Highly refined mineral oil (C15 -C50)	
EC50 other aquatic organisms 1 ≈ 1,2 mg/l	

## 12.2. Persistence and degradability

Eurol Fluence DXS 5W-30	
Persistence and degradability	Not readily biodegradable.

#### 12.3. Bioaccumulative potential

Eurol Fluence DXS 5W-30	
Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.

## 12.4. Mobility in soil

Eurol Fluence DXS 5W-30	
Ecology - soil	Not miscible with water. Spillages may penetrate the soil causing ground water contamination. This product floats on water and may affect the oxygen-balance in the water.

### 12.5. Results of PBT and vPvB assessment

No additional information available

## 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

1-3-2023 (Revision date) EN (English) 8/12

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not discharge

into drains or the environment.

Additional information : Hazardous waste.

Ecology - waste materials : Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden. Empty containers retain product residue (solid, liquid, and/or vapor) and can be

dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. When not

empty dispose of this container at hazardous or special waste collection point.

European List of Waste (LoW) code : 13 02 06\* - Synthetic engine, gear and lubricating oils

## **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID n	umber			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shippin	g name			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard	class(es)			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group	14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information	on available			

## 14.6. Special precautions for user

## Overland transport

Not applicable

### Transport by sea

Not applicable

## Air transport

Not applicable

## Inland waterway transport

Not applicable

## Rail transport

Not applicable

## 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

### **REACH Annex XVII (Restriction List)**

EU restriction list (REACH Annex XVII)	
Reference code	Applicable on
3(b)	Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based; Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.]; Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts; Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

#### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

## VOC Directive (2004/42)

VOC content : 0 %

## **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### **Drug Precursors Regulation (273/2004)**

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

No additional information available

## 15.2. Chemical safety assessment

No additional information available

### **SECTION 16: Other information**

Abbreviations and acr	Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008	

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
CAS-No.	Chemical Abstract Service number
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
ED	Endocrine disrupting properties
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
N.O.S.	Not Otherwise Specified
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and

amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:	
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs, calcium salts, Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated. May produce an allergic reaction.

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
EUH210	Safety data sheet available on request.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H361d	Suspected of damaging the unborn child.
Repr. 2	Reproductive toxicity, Category 2
Skin Sens. 1B	Skin sensitisation, category 1B

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.