



SAFETY DATA SHEET
SynPower™ SAE 0W-40 Synthetic Motor Oil

Version: 5.0

Revision Date: 02.11.2020

Print Date: 16/09/2022

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SynPower™ SAE 0W-40
Synthetic Motor Oil

Product code : 872587

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Ellis Enterprises B.V., an affiliate of Valvoline
Wieldrechtseweg 39
3316 BG Dordrecht
Netherlands
+31 (0)78 654 3500 (in the Netherlands), or
contact your local CSR contact person

SDS@valvoline.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact
your local emergency telephone number at 112

Product Information

+31 (0)78 654 3500 (in the Netherlands), or
contact your local CSR contact person

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling:

EUH210 Safety data sheet available on request.

EUH208 Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.



SAFETY DATA SHEET

SynPower™ SAE 0W-40 Synthetic Motor Oil

Version: 5.0

Revision Date: 02.11.2020

Print Date: 16/09/2022

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional advice

No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : organic

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
DECENE-1 HOMOPOLYMER HYDROGENATED	68037-01-4 01-2119486452-34-xxxx	Asp. Tox.1; H304	>= 40,00 - < 50,00
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based	72623-87-1 276-738-4 01-2119474889-13-xxxx	Asp. Tox.1; H304	>= 2,50 - < 5,00
bis(nonylphenyl)amine	36878-20-3 253-249-4 01-2119488911-28-xxxx	Aquatic Chronic4; H413	>= 1,00 - < 2,50
Zinc bis[O-(6- methylheptyl)] bis[O- (sec-butyl)] bis(dithiophosphate)	93819-94-4 298-577-9 01-2119543726-33-xxxx	Skin Irrit.2; H315 Eye Dam.1; H318 Aquatic Chronic2; H411	>= 1,00 - < 2,50
C14-16-18 Alkyl phenol	931-468-2 01-2119498288-19-xxxx	Skin Sens.1B; H317 STOT RE2; H373	>= 0,50 - < 1,00

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Do not leave the victim unattended.



SAFETY DATA SHEET

SynPower™ SAE 0W-40 Synthetic Motor Oil

Version: 5.0

Revision Date: 02.11.2020

Print Date: 16/09/2022

Show this safety data sheet to the doctor in attendance.
Move out of dangerous area.

- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash contaminated clothing before re-use.
If on skin, rinse well with water.
Remove contaminated clothing. If irritation develops, get medical attention.
- In case of eye contact : Protect unharmed eye.
Remove contact lenses.
Immediately flush eye(s) with plenty of water.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet



SAFETY DATA SHEET

SynPower™ SAE 0W-40 Synthetic Motor Oil

Version: 5.0

Revision Date: 02.11.2020

Print Date: 16/09/2022

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
Nitrogen oxides (NOx)

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Use personal protective equipment.
Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

- Environmental precautions : Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Dispose of rinse water in accordance with local and national regulations.



SAFETY DATA SHEET

SynPower™ SAE 0W-40 Synthetic Motor Oil

Version: 5.0

Revision Date: 02.11.2020

Print Date: 16/09/2022

For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Avoid contact with skin and eyes.
Container hazardous when empty.
Do not smoke.
Do not breathe vapours/dust.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not smoke. When using do not eat or drink.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Zinc bis[O-(6-methylheptyl)]bis[O-(sec-butyl)]bis(dithiophosphate)	: End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 8,31 mg/m3RD TOX - Repeated dose toxicity
	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 0,58 mg/kgRD TOX - Repeated dose toxicity
	End Use: Consumer use Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 2,11 mg/m3RD TOX - Repeated dose toxicity
	End Use: Consumer use Exposure routes: Dermal



SAFETY DATA SHEET

SynPower™ SAE 0W-40 Synthetic Motor Oil

Version: 5.0

Revision Date: 02.11.2020

Print Date: 16/09/2022

Potential health effects: Long-term systemic effects Value: 0,29 mg/kgRD TOX - Repeated dose toxicity End Use: Consumer use Exposure routes: Oral Potential health effects: Long-term systemic effects Value: 0,24 mg/kgRD TOX - Repeated dose toxicity

8.2 Exposure controls

Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Hand protection

Remarks : Nitrile rubber butyl-rubber

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Safety shoes
Impervious clothing
Wear as appropriate:

Respiratory protection : No personal respiratory protective equipment normally required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : amber
Odour : oily
Odour Threshold : No data available
pH : Not applicable



SAFETY DATA SHEET

SynPower™ SAE 0W-40 Synthetic Motor Oil

Version: 5.0

Revision Date: 02.11.2020

Print Date: 16/09/2022

Pour point	:	< -42 °C
Boiling point/boiling range	:	> 225,00 °C
Flash point	:	203 °C Method: Pensky-Martens closed cup
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	ca. 0,843 (15,6 °C)
Density	:	ca. 0,843 g/cm ³ (15 °C)
Bulk density	:	Not applicable
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	ca. 77 mm ² /s (40 °C)
Oxidizing properties	:	No data available

9.2 Other information

Self-ignition	:	No data available
		No data available



SAFETY DATA SHEET

SynPower™ SAE 0W-40 Synthetic Motor Oil

Version: 5.0

Revision Date: 02.11.2020

Print Date: 16/09/2022

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Product will not undergo hazardous polymerization.

10.4 Conditions to avoid

Conditions to avoid : excessive heat

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

DECENE-1 HOMOPOLYMER HYDROGENATED:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 5,2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.



SAFETY DATA SHEET

SynPower™ SAE 0W-40 Synthetic Motor Oil

Version: 5.0

Revision Date: 02.11.2020

Print Date: 16/09/2022

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Not classified as acutely toxic by inhalation under GHS.
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Remarks: No mortality observed at this dose.

Components:

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.
Remarks: Information given is based on data obtained from similar substances.

Components:

ZINC DIALKYL DITHIOPHOSPHATE:

Acute oral toxicity : LD50 (Rat): 2.600 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3.160 mg/kg
Method: OECD Test Guideline 402
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

Components:

C14-16-18 Alkyl phenol:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Assessment: Not classified as acutely toxic by ingestion under GHS.

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg



SAFETY DATA SHEET

SynPower™ SAE 0W-40 Synthetic Motor Oil

Version: 5.0

Revision Date: 02.11.2020

Print Date: 16/09/2022

Assessment: **Not classified as acutely toxic by dermal absorption under GHS.**
Remarks: **No mortality observed at this dose.**

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:

DECENE-1 HOMOPOLYMER HYDROGENATED:

Species: **Rabbit**
Result: **No skin irritation**

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Species: **Rabbit**
Result: **No skin irritation**

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: **Rabbit**
Result: **Mild skin irritation**
Remarks: **Information given is based on data obtained from similar substances.**

ZINC DIALKYLDITHIOPHOSPHATE:

Species: **Guinea pig**
Method: **OECD Test Guideline 404**
Result: **Irritating to skin.**
Remarks: **Information given is based on data obtained from similar substances.**

C14-16-18 Alkyl phenol:

Method: **OECD Test Guideline 431**
Result: **No skin irritation**

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Causes serious eye irritation., Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

DECENE-1 HOMOPOLYMER HYDROGENATED:

Species: **Rabbit**
Result: **Slight, transient irritation**



SAFETY DATA SHEET
SynPower™ SAE 0W-40 Synthetic Motor Oil

Version: 5.0

Revision Date: 02.11.2020

Print Date: 16/09/2022

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Species: Rabbit

Result: No eye irritation

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Rabbit

Result: Slight, transient irritation

Remarks: Information given is based on data obtained from similar substances.

ZINC DIALKYL DITHIOPHOSPHATE:

Species: Rabbit

Result: Corrosive

Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol:

Species: Rabbit

Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitisation.

Remarks: Based on similar product.

Components:

DECENE-1 HOMOPOLYMER HYDROGENATED:

Test Type: Maximisation Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol:



SAFETY DATA SHEET

SynPower™ SAE 0W-40 Synthetic Motor Oil

Version: 5.0

Revision Date: 02.11.2020

Print Date: 16/09/2022

Test Type: **Local lymph node assay**
Species: **Mouse**
Assessment: **The product is a skin sensitiser, sub-category 1B.**
Method: **OECD Test Guideline 429**

Germ cell mutagenicity

Not classified based on available information.

Components:

DECENE-1 HOMOPOLYMER HYDROGENATED:

Genotoxicity in vitro : Test Type: **Ames test**
Test species: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Result: **negative**

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Genotoxicity in vitro : Test Type: **Ames test**
Test species: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Result: **negative**

ZINC DIALKYL DITHIOPHOSPHATE:

Genotoxicity in vitro : Test Type: **Ames test**
Test species: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Method: **OECD Test Guideline 471**
Result: **negative**
Remarks: **Information given is based on data obtained from similar substances.**

Genotoxicity in vivo : Test Type: **Micronucleus test**
Test species: **Mouse**
Method: **OECD Test Guideline 474**
Result: **negative**
Remarks: **Information given is based on data obtained from similar substances.**

C14-16-18 Alkyl phenol:

Genotoxicity in vitro : Test Type: **Ames test**
Test species: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Result: **negative**

Carcinogenicity

Not classified based on available information.

Components:



SAFETY DATA SHEET

SynPower™ SAE 0W-40 Synthetic Motor Oil

Version: 5.0

Revision Date: 02.11.2020

Print Date: 16/09/2022

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

C14-16-18 Alkyl phenol:

Target Organs: Liver

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Aspiration toxicity

Not classified based on available information.

Components:

DECENE-1 HOMOPOLYMER HYDROGENATED:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

DECENE-1 HOMOPOLYMER HYDROGENATED

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l
Exposure time: 96 h



SAFETY DATA SHEET

SynPower™ SAE 0W-40 Synthetic Motor Oil

Version: 5.0

Revision Date: 02.11.2020

Print Date: 16/09/2022

	Test Type: semi-static test Test substance: WAF
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 1.000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae	: EL50 (Scenedesmus capricornutum (fresh water algae)): > 1.000 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOELR: 125 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Test Type: semi-static test Test substance: WAF Method: OECD Test Guideline 211

Ecotoxicology Assessment

Short-term (acute) aquatic hazard	: Not classified based on available information.
Long-term (chronic) aquatic hazard	: Not classified based on available information.

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Toxicity to fish	: LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 10.000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae	: NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition



SAFETY DATA SHEET

SynPower™ SAE 0W-40 Synthetic Motor Oil

Version: 5.0

Revision Date: 02.11.2020

Print Date: 16/09/2022

	Exposure time: 72 h
	Test Type: static test
	Test substance: WAF
	Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOELR: ≥ 1.000 mg/l
	Exposure time: 14 d
	Species: <i>Oncorhynchus mykiss</i> (rainbow trout)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEL: 10 mg/l
	Exposure time: 21 d
	Species: <i>Daphnia</i> (water flea)
	Test substance: WAF
	Method: OECD Test Guideline 211

bis(nonylphenyl)amine

Toxicity to fish	: LC50 (<i>Danio rerio</i> (zebra fish)): > 100 mg/l
	Exposure time: 96 h
	Test Type: static test
	Remarks: Information given is based on data obtained from similar substances.
Toxicity to daphnia and other aquatic invertebrates	: EC50 (<i>Daphnia magna</i> (Water flea)): > 100 mg/l
	Exposure time: 48 h
	Test Type: static test
	Test substance: WAF
Toxicity to algae	: EC50 (<i>Pseudokirchneriella subcapitata</i> (algae)): 600 mg/l
	End point: Growth inhibition
	Exposure time: 72 h
	Test Type: static test

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Toxicity to fish	: LL50 (<i>Oncorhynchus mykiss</i> (rainbow trout)): 4,5 mg/l
	Exposure time: 96 h
	Test Type: semi-static test
Toxicity to daphnia and other aquatic invertebrates	: EC50 (<i>Daphnia magna</i> (Water flea)): 5,4 mg/l
	Exposure time: 48 h
	Test Type: static test
Toxicity to algae	: EC50 (<i>Selenastrum capricornutum</i> (green algae)): 2,1 mg/l
	End point: Growth inhibition
	Exposure time: 72 h
	Test Type: static test

C14-16-18 Alkyl phenol

Toxicity to fish	: LC50 (<i>Cyprinus carpio</i> (Carp)): > 100 mg/l
------------------	-------------------------------------------------------



SAFETY DATA SHEET

SynPower™ SAE 0W-40 Synthetic Motor Oil

Version: 5.0

Revision Date: 02.11.2020

Print Date: 16/09/2022

	Exposure time: 96 h
	Test Type: static test
	Test substance: WAF
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l
	Exposure time: 48 h
	Test Type: static test
	Method: OECD Test Guideline 202
Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l
	End point: Growth inhibition
	Exposure time: 72 h
	Test Type: static test
	Test substance: WAF

12.2 Persistence and degradability

Components:

DECENE-1 HOMOPOLYMER HYDROGENATED

Biodegradability : Result: Inherently biodegradable

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

bis(nonylphenyl)amine

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1,5 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

C14-16-18 Alkyl phenol

Biodegradability : Result: Readily biodegradable.
Remarks: Expert judgement

12.3 Bioaccumulative potential

Components:

DECENE-1 HOMOPOLYMER HYDROGENATED



SAFETY DATA SHEET

SynPower™ SAE 0W-40 Synthetic Motor Oil

Version: 5.0

Revision Date: 02.11.2020

Print Date: 16/09/2022

Partition coefficient: n-octanol/water : log Pow: > 6,5

bis(nonylphenyl)amine

Partition coefficient: n-octanol/water : log Pow: > 7,5

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Partition coefficient: n-octanol/water : log Pow: 0,59 - 1,2 (23 °C)

C14-16-18 Alkyl phenol

Partition coefficient: n-octanol/water : log Pow: > 7,2

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Send to a licensed waste management company.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not dispose of waste into sewer.

Contaminated packaging : Do not re-use empty containers.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Dispose of as unused product.
Empty remaining contents.



SAFETY DATA SHEET

SynPower™ SAE 0W-40 Synthetic Motor Oil

Version: 5.0

Revision Date: 02.11.2020

Print Date: 16/09/2022

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable



SAFETY DATA SHEET
SynPower™ SAE 0W-40 Synthetic Motor Oil

Version: 5.0

Revision Date: 02.11.2020

Print Date: 16/09/2022

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

Directive 96/82/EC does not apply

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : Not in compliance with the inventory

TSCA : On TSCA Inventory

Inventories

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available



SAFETY DATA SHEET

SynPower™ SAE 0W-40 Synthetic Motor Oil

Version: 5.0

Revision Date: 02.11.2020

Print Date: 16/09/2022

SECTION 16: Other information

Further information

Internal information : R0517098

Full text of H-Statements

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO : International Civil Aviation Organization



SAFETY DATA SHEET

SynPower™ SAE 0W-40 Synthetic Motor Oil

Version: 5.0

Revision Date: 02.11.2020

Print Date: 16/09/2022

ICAO-TI (ICAO) : Technical Instructions by the “International Civil Aviation Organization”

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

ABM : Water Hazard Class for the Netherlands

ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.

ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine

CLP : Classification, Labelling and Packaging

CSA : Chemical Safety Assessment

CSR : Chemical Safety Report

DNEL : Derived No Effect Level.

EINECS : European Inventory of Existing Commercial Chemical Substances.

ELINCS : European List of Notified Chemical Substances

PEC : Predicted Effect Concentration

PEL : Permissible Exposure Limits

PNEC : Predicted No Effect Concentration

R-phrase : Risk phrase

REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals

RID : Regulation Concerning the International Transport of Dangerous Goods by Rail

S-phrase: Safety phrase

WGK : German Water Hazard Class