

Revision Date: 22.08.2019

Print Date: 26.09.2022

SDS Number: 000000126048 Version: 8.0

SynPower[™] SAE 0W-30 FE Synthetic Motor Oil [™] Trademark, Valvoline or its subsidiaries, registered in various countries 872559

:

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_GB SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

SynPower™ SAE 0W-30 FE Synthetic Motor Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries

1.2 Relevant identified uses of the substance or mixture and uses advised against Recommended use : Engine, gear & lubricating oil.

| 1.3 Details of the supplier of the safety data sheet Ellis Enterprises B.V., an affiliate of Valvoline Wieldrechtseweg 39 3316 BG Dordrecht | 1.4 Emergency telephone number 00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number at 112 |
|---|---|
| Netherlands +31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person | Product Information +31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person |
| SDS@valvoline.com | |

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling:

| EUH208 | Contains C14-16-18 Alkyl phenol. May produce an allergic reaction. |
|--------|--|
| EUH210 | Safety data sheet available on request. |



Revision Date: 22.08.2019

Print Date: 26.09.2022

SDS Number: 000000126048 Version: 8.0

SynPower[™] SAE 0W-30 FE Synthetic Motor Oil [™] Trademark, Valvoline or its subsidiaries, registered in various countries 872559

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher. **Additional advice**

No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

| Chemical name | CAS-No. EC-No. Registration number | Classification (REGULATION (EC) No 1272/2008) | Concentration (%) |
|---|--|--|--------------------|
| Distillates (petroleum), hydrotreated heavy paraffinic | 64742-54-7 265-157-1 01-2119484627-25-xxxx | Asp. Tox.1; H304 | >= 70,00 - < 80,00 |
| Reaction products of Benzeneamine, N- phenyl- with nonene (branched) | 36878-20-3 253-249-4 01-2119488911-28-xxxx | Aquatic Chronic4; H413 | >= 1,00 - < 2,50 |
| Zinc bis[O-(6- methylheptyl)] bis[O- (sec-butyl)] bis(dithiophosphate) | 93819-94-4 298-577-9 01-2119543726-33-xxxx | Skin Irrit.2; H315 Eye Dam.1; H318 Aquatic Chronic2; H411 | >= 1,00 - < 2,50 |
| C14-16-18 Alkyl phenol | 931-468-2 01-2119498288-19-xxxx | Skin Sens.1B; H317 STOT RE2; H373 | >= 0,50 - < 1,00 |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

| General advice | : No hazards which require special first aid measures. |
|----------------|--|
| If inhaled | If breathed in, move person into fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician. |

Version: 8.0



Revision Date: 22.08.2019

Print Date: 26.09.2022 SDS Number: 000000126048

SynPower[™] SAE 0W-30 FE Synthetic Motor Oil [™] Trademark, Valvoline or its subsidiaries, registered in various countries 872559

| In case of skin contact : | First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water. |
|---------------------------|--|
| In case of eye contact : | Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. If eye irritation persists, consult a specialist. |
| If swallowed : | IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. |

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

- : No symptoms known or expected.
- 4.3 Indication of any immediate medical attention and special treatment needed
 - Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures

5.1 Extinguishing media

| Suitabl | e extinguishing media | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical |
|---------|-----------------------|--|
| | | |

Unsuitable extinguishing : High volume water jet media

5.2 Special hazards arising from the substance or mixture

| Specific hazards during firefighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
|---|--|
| Hazardous combustion products | carbon dioxide and carbon monoxide Hydrocarbons Nitrogen oxides (NOx) zinc oxide |



Revision Date: 22.08.2019

Print Date: 26.09.2022

SDS Number: 000000126048 Version: 8.0

SynPower™ SAE 0W-30 FE Synthetic Motor Oil [™] Trademark, Valvoline or its subsidiaries, registered in various countries 872559

> Sulphur oxides hydrogen sulfide mercaptans

5.3 Advice for firefighters

| Special protective equipment for firefighters | : In the event of fire, wear self-contained breathing apparatus. |
|---|--|
| Specific extinguishing methods | : Product is compatible with standard fire-fighting agents. |
| Further information | : Standard procedure for chemical fires. |

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

| Personal precautions | : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Comply with all applicable federal, state, and local regulations. | | |
|--|---|--|--|
| 6.2 Environmental precautions | | | |
| Environmental precautions | : Prevent further leakage or spillage if safe to do so. | | |
| 6.3 Methods and material for containment and cleaning up | | | |
| Methods for cleaning up | : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. | | |

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

| Advice on safe handling | Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. Dispose of rinse water in accordance with local and national regulations. |
|------------------------------|---|
| Advice on protection against | : Normal measures for preventive fire protection. |



Revision Date: 22.08.2019

Print Date: 26.09.2022

SDS Number: 000000126048 Version: 8.0

SynPower[™] SAE 0W-30 FE Synthetic Motor Oil [™] Trademark, Valvoline or its subsidiaries, registered in various countries 872559

fire and explosion

Hygiene measures : Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

| Requirements for storage areas and containers | : Keep container tightly closed in a dry and well-ventilated place. |
|---|---|
| Other data | : No decomposition if stored and applied as directed. |
| 7.3 Specific end use(s) Specific use(s) | : No data available |

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Zinc bis[O-(6-methylheptyl)] : | End Use: Workers | |
|--------------------------------|--|--|
| bis[O-(sec-butyl)] | Exposure routes: Inhalation | |
| bis(dithiophosphate) | Potential health effects: Long-term systemic effects | |
| | Value: 8,31 mg/m3RD TOX - Repeated dose toxicity | |
| | End Use: Workers | |
| | Exposure routes: Dermal | |
| | Potential health effects: Long-term systemic effects | |
| | Value: 0,58 mg/kgRD TOX - Repeated dose toxicity | |
| | End Use: Consumer use | |
| | Exposure routes: Inhalation | |
| | Potential health effects: Long-term systemic effects | |
| | Value: 2,11 mg/m3RD TOX - Repeated dose toxicity | |
| | End Use: Consumer use | |
| | Exposure routes: Dermal | |
| | Potential health effects: Long-term systemic effects | |
| | Value: 0,29 mg/kgRD TOX - Repeated dose toxicity | |
| | End Use: Consumer use | |
| | Exposure routes: Oral | |
| | Potential health effects: Long-term systemic effects | |
| | Value: 0,24 mg/kgRD TOX - Repeated dose toxicity | |
| | | |

8.2 Exposure controls

Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below



Revision Date: 22.08.2019

Print Date: 26.09.2022 SDS Number: 000000126048

Version: 8.0

SynPower[™] SAE 0W-30 FE Synthetic Motor Oil [™] Trademark, Valvoline or its subsidiaries, registered in various countries 872559

exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

| Personal protective equipmer | t |
|------------------------------|---|
| Eye protection | : Not required under normal conditions of use. Wear splash- proof safety goggles if material could be misted or splashed into eyes. |
| Hand protection | |
| Remarks | : Nitrile rubber butyl-rubber |
| | The suitability for a specific workplace should be discussed with the producers of the protective gloves. |
| Skin and body protection | : Wear as appropriate: Impervious clothing Safety shoes Choose body protection according to the amount and concentration of the dangerous substance at the work place. Discard gloves that show tears, pinholes, or signs of wear. |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| Appearance | : | liquid |
|-----------------------------|---|--------------------------------------|
| Colour | : | amber |
| Odour | : | oily |
| Odour Threshold | : | No data available |
| рН | : | Not applicable |
| Pour point | : | < -45 °C |
| Boiling point/boiling range | : | > 350 °C |
| Flash point | : | 232 °C Method: Cleveland open cup |
| Evaporation rate | : | No data available |
| Flammability (solid, gas) | : | No data available |



Revision Date: 22.08.2019

Print Date: 26.09.2022

SDS Number: 000000126048 Version: 8.0

SynPower[™] SAE 0W-30 FE Synthetic Motor Oil [™] Trademark, Valvoline or its subsidiaries, registered in various countries 872559

| Upper explosion limit / Upper flammability limit | : | No data available |
|--|---|-------------------------|
| Lower explosion limit / Lower flammability limit | : | No data available |
| Vapour pressure | : | No data available |
| Relative vapour density | : | No data available |
| Relative density | : | No data available |
| Density | : | ca. 0,842 g/cm3 (15 °C) |
| Solubility(ies) Water solubility | : | insoluble |
| Solubility in other solvents | : | No data available |
| Partition coefficient: n- octanol/water | : | No data available |
| Decomposition temperature | : | No data available |
| Viscosity Viscosity, dynamic | : | No data available |
| Viscosity, kinematic | : | ca. 51,9 mm2/s (40 °C) |
| Oxidizing properties | : | No data available |
| 9.2 Other information | | |
| Self-ignition | : | No data available |

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Product will not undergo hazardous polymerization.



| SAFETY DATA SHEET | Revision Date: 22.08.20 |)19 |
|---|-------------------------|-----|
| | Print Date: 26.09.20 |)22 |
| | SDS Number: 0000001260 |)48 |
| SynPower™ SAE 0W-30 FE Synthetic Motor Oil | Version: | 8.0 |
| ™ Trademark, Valvoline or its subsidiaries, registered in various | | |
| countries | | |
| 872559 | | |

10.4 Conditions to avoid

| Conditions to avoid : ex | cessive heat |
|--------------------------|--------------|
|--------------------------|--------------|

10.5 Incompatible materials

Materials to avoid

: Strong oxidizing agents

10.6 Hazardous decomposition products

| Hazardous decomposition | : No hazardous decomposition products are known. |
|-------------------------|--|
| products | |

SECTION 11: Toxicological information

| 11.1 Information on toxicological | effects |
|--|--|
| Information on likely routes of exposure | : Inhalation Skin contact Eye Contact Ingestion |
| Acute toxicity | |
| Not classified based on availab | le information. |
| Product: | |
| Acute oral toxicity | : LD50 (Rat): > 2.000 mg/kg |
| Acute dermal toxicity | : LD50 (Rabbit): > 2.000 mg/kg |
| Components: | |
| HEAVY PARAFFINIC DISTILI | |
| Acute oral toxicity | : LD50 (Rat): > 15 g/kg |
| Acute dermal toxicity | : LD50 (Rabbit): > 5 g/kg |
| Components: | |
| | ENEAMINE, N-PHENYL- W/ NONENE (BRANCHED): |
| Acute oral toxicity | : LD50 (Rat): > 5.000 mg/kg Remarks: No mortality observed at this dose. |
| Acute dermal toxicity | LD50 (Rat): > 2.000 mg/kg Assessment: Not classified as acutely toxic by dermal absorption under GHS. Remarks: Information given is based on data obtained from similar substances. |



Revision Date: 22.08.2019

Print Date: 26.09.2022 SDS Number: 000000126048

Version: 8.0

SynPower[™] SAE 0W-30 FE Synthetic Motor Oil [™] Trademark, Valvoline or its subsidiaries, registered in various countries 872559

Components:

ш

ZINC DIALKYLDITHIOPHOSPHATE:

| Acute oral toxicity | : LD50 (Rat): 2.600 mg/kg |
|-----------------------|---|
| Acute dermal toxicity | : LD50 (Rabbit): > 3.160 mg/kg Method: OECD Test Guideline 402 Assessment: Not classified as acutely toxic by dermal absorption under GHS. |

Components:

| C14-16-18 Alkyl phenol: | |
|-------------------------|---|
| Acute oral toxicity | : LD50 (Rat): > 2.000 mg/kg Assessment: Not classified as acutely toxic by ingestion under GHS. |
| Acute dermal toxicity | LD50 (Rat): > 2.000 mg/kg Assessment: Not classified as acutely toxic by dermal absorption under GHS. Remarks: No mortality observed at this dose. |

Skin corrosion/irritation

Not classified based on available information.

Components:

HEAVY PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Rabbit Result: Mild skin irritation

Remarks: Information given is based on data obtained from similar substances.

ZINC DIALKYLDITHIOPHOSPHATE:

Species: Guinea pig Method: OECD Test Guideline 404 Result: Irritating to skin. Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol:

Method: OECD Test Guideline 431 Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Version: 8.0



Revision Date: 22.08.2019 Print Date: 26.09.2022

SDS Number: 000000126048

SynPower™ SAE 0W-30 FE Synthetic Motor Oil [™] Trademark. Valvoline or its subsidiaries, registered in various countries 872559

Product:

Result: Slight, transient irritation Remarks: Expected based on components.

Remarks: Unlikely to cause eye irritation or injury.

Components:

HEAVY PARAFFINIC DISTILLATE:

Result: No eye irritation

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Rabbit Result: Slight, transient irritation Remarks: Information given is based on data obtained from similar substances.

ZINC DIALKYLDITHIOPHOSPHATE:

Species: Rabbit Result: Corrosive Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol:

Species: Rabbit Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitisation. Remarks: Based on similar product.

Components:

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Guinea pig Assessment: Does not cause skin sensitisation. Method: OECD Test Guideline 406 Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol:

Test Type: Local lymph node assay Species: Mouse Assessment: The product is a skin sensitiser, sub-category 1B. Method: OECD Test Guideline 429



Revision Date: 22.08.2019

Print Date: 26.09.2022

SDS Number: 000000126048 Version: 8.0

SynPower[™] SAE 0W-30 FE Synthetic Motor Oil [™] Trademark, Valvoline or its subsidiaries, registered in various countries 872559

Germ cell mutagenicity

Not classified based on available information.

Components:

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED): Genotoxicity in vitro : Test Type: Ames test Test species: Salmonella typhimurium

Test species: Salmonella typhimurium Metabolic activation: with and without metabolic activation Result: negative

ZINC DIALKYLDITHIOPHOSPHATE:

| Genotoxicity in vitro | : Test Type: Ames test Test species: Salmonella typhimurium Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative Remarks: Information given is based on data obtained from similar substances. |
|-------------------------|--|
| Genotoxicity in vivo | : Test Type: Micronucleus test Test species: Mouse Method: OECD Test Guideline 474 Result: negative Remarks: Information given is based on data obtained from similar substances. |
| C14 16 19 Alkul phonoli | |

C14-16-18 Alkyl phenol:

| Genotoxicity in vitro | : | Test Type: Ames test Test species: Salmonella typhimurium |
|-----------------------|---|---|
| | | Metabolic activation: with and without metabolic activation Result: negative |

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

C14-16-18 Alkyl phenol:

Target Organs: Liver Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Version: 8.0



Revision Date: 22.08.2019 Print Date: 26.09.2022

SDS Number: 000000126048

SynPower[™] SAE 0W-30 FE Synthetic Motor Oil [™] Trademark, Valvoline or its subsidiaries, registered in various countries 872559

Aspiration toxicity

Not classified based on available information.

Components:

HEAVY PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

| eempenenton | |
|--|--|
| Distillates (petroleum), hydrotreat | ted heavy paraffinic |
| Toxicity to fish : | LL50 (Fish): > 100 mg/l Exposure time: 96 h |
| Toxicity to daphnia and other : aquatic invertebrates | EL50 (Aquatic invertebrates): > 10.000 mg/l Exposure time: 48 h |
| Toxicity to algae : | EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h |
| Toxicity to fish (Chronic : toxicity) | NOEC: 10 mg/l Species: Fish |
| Toxicity to daphnia and other : aquatic invertebrates (Chronic toxicity) | NOEC: 10 mg/l Species: Aquatic invertebrates |
| Reaction products of Benzeneam | nine, N-phenyl- with nonene (branched) |
| | LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h Test Type: static test Remarks: Information given is based on data obtained from similar substances. |
| Toxicity to daphnia and other : aquatic invertebrates | EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h |

Version: 8.0



Revision Date: 22.08.2019

Print Date: 26.09.2022 SDS Number: 000000126048

SynPower[™] SAE 0W-30 FE Synthetic Motor Oil [™] Trademark, Valvoline or its subsidiaries, registered in various countries 872559

| Toxicity to algae | Test Type: static test Test substance: WAF EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test |
|--|--|
| Zinc bis[O-(6-methylheptyl)] bis Toxicity to fish | [O-(sec-butyl)] bis(dithiophosphate) : LL50 (Oncorhynchus mykiss (rainbow trout)): 4,5 mg/l |
| | Exposure time: 96 h Test Type: semi-static test |
| Toxicity to daphnia and other aquatic invertebrates | : EC50 (Daphnia magna (Water flea)): 5,4 mg/l Exposure time: 48 h Test Type: static test |
| Toxicity to algae | : EC50 (Selenastrum capricornutum (green algae)): 2,1 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test |
| C14-16-18 Alkyl phenol | |
| Toxicity to fish | : LC50 (Cyprinus carpio (Carp)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF |
| Toxicity to daphnia and other aquatic invertebrates | : EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202 |
| Toxicity to algae | : EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF |

12.2 Persistence and degradability

Components:

| Reaction products of Benze | neamine, N-phenyl- with nonene (branched) |
|----------------------------|---|
| Biodegradability | : Result: Not readily biodegradable. |
| | Biodegradation: 0% |
| | Exposure time: 28 d |
| | Method: OECD Test Guideline 301B |
| | |



Revision Date: 22.08.2019 Print Date: 26.09.2022 SDS Number: 000000126048 SynPower™ SAE 0W-30 FE Synthetic Motor Oil Version: 8.0 [™] Trademark, Valvoline or its subsidiaries, registered in various

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

| Biodegradability | : Result: Not readily biodegradable. Biodegradation: 1,5 % Exposure time: 28 d Method: OECD Test Guideline 301B |
|------------------------|--|
| C14-16-18 Alkyl phenol | |
| Biodegradability | : Result: Readily biodegradable. Remarks: Expert judgement |

12.3 Bioaccumulative potential

Components:

countries 872559

> Reaction products of Benzeneamine, N-phenyl- with nonene (branched) Partition coefficient: n-: $\log Pow: > 7,5$ octanol/water Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) Partition coefficient: n-: log Pow: 0,59 - 1,2 (23 °C) octanol/water C14-16-18 Alkyl phenol Partition coefficient: n-: log Pow: > 7,2 octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

| Assessment | : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher |
|---------------------------|--|
| 2.6 Other adverse effects | |

12

Product:

| Additional ecological | : | No data available |
|-----------------------|---|-------------------|
| information | | |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Version: 8.0



Revision Date: 22.08.2019

Print Date: 26.09.2022 SDS Number: 000000126048

SynPower[™] SAE 0W-30 FE Synthetic Motor Oil [™] Trademark, Valvoline or its subsidiaries, registered in various countries 872559

| Product | Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company. |
|------------------------|---|
| Contaminated packaging | Empty remaining contents. Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. |

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that : Not applicable deplete the ozone layer

Regulation (EC) No 850/2004 on persistent organic : Not applicable

Version: 8.0



Revision Date: 22.08.2019

Print Date: 26.09.2022 SDS Number: 000000126048

| SynPower™ SAE 0W-30 FE Synthetic Motor Oil | |
|---|--|
| ™ Trademark, Valvoline or its subsidiaries, registered in various | |
| countries | |
| 872559 | |

pollutants

| REACH - List of substances subject to authorisation (Annex XIV) | : Not applicable |
|--|------------------|
| REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) | : Not applicable |
| REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). | : Not applicable |
| Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals | : Not applicable |

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable

| The components of this product are reported in the following inventories:DSL: All components of this product are on the Canadian DSL | | |
|--|---|--|
| AICS | On the inventory, or in compliance with the inventory | |
| ENCS | On the inventory, or in compliance with the inventory | |
| KECI | On the inventory, or in compliance with the inventory | |
| PICCS | On the inventory, or in compliance with the inventory | |
| IECSC | On the inventory, or in compliance with the inventory | |
| TCSI | On the inventory, or in compliance with the inventory | |
| TSCA | On TSCA Inventory | |

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment No data available

Version: 8.0



Revision Date: 22.08.2019

Print Date: 26.09.2022 SDS Number: 000000126048

SynPower[™] SAE 0W-30 FE Synthetic Motor Oil [™] Trademark, Valvoline or its subsidiaries, registered in various countries 872559

SECTION 16: Other information

Further information

Revision Date: 22.08.2019

| Full text of H-Staten | nents |
|-----------------------|--|
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H413 | May cause long lasting harmful effects to aquatic life. |
| Other information | : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department |

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

(+31 (0)78 654 3500).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA). ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

Version: 8.0



Print Date: 26.09.2022 SDS Number: 000000126048

SynPower™ SAE 0W-30 FE Synthetic Motor Oil [™] Trademark. Valvoline or its subsidiaries, registered in various countries 872559

IMDG : International Maritime Code for Dangerous Goods ISO : International Organization for Standardization logPow : octanol-water partition coefficient LCxx : Lethal Concentration, for xx percent of test population LDxx : Lethal Dose, for xx percent of test population. ICxx : Inhibitory Concentration for xx of a substance Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified OECD : Organization for Economic Co-operation and Development **OEL** : Occupational Exposure Limit P-Statement : Precautionary Statement PBT : Persistent, Bioaccumulative and Toxic **PPE : Personal Protective Equipment** STEL : Short-term exposure limit STOT : Specific Target Organ Toxicity TLV : Threshold Limit Value TWA : Time-weighted average vPvB : Very Persistent and Very Bioaccumulative WEL : Workplace Exposure Level

ABM : Water Hazard Class for the Netherlands ADR : Agreement concerning the International Carriage of Dangerous Goods by Road. ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine CLP : Classification, Labelling and Packaging CSA : Chemical Safety Assessment CSR : Chemical Safety Report DNEL : Derived No Effect Level. EINECS : European Inventory of Existing Commercial Chemical Substances. ELINCS : European List of Notified Chemical Substances PEC : Predicted Effect Concentration **PEL : Permissible Exposure Limits PNEC : Predicted No Effect Concentration** R-phrase : Risk phrase REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals RID : Regulation Concerning the International Transport of Dangerous Goods by Rail S-phrase: Safety phrase WGK : German Water Hazard Class