

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 3.00

Revision: 01.04.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX Wheel rim coating

Article number:

04363000

UFI: 33F0-50YF-U00D-AD4U

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers

Application of the substance / the mixture Car care product

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

1.4 Emergency telephone number: Emergency Phone Munich Tel.: +49 (0)89 19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02

Signal word Danger

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT:

CAS: 541-02-6	decamethylcyclopentasiloxane
CAS: 540-97-6	Dodecamethylcyclohexasiloxane

vPvB:

CAS: 541-02-6	decamethylcyclopentasiloxane
---------------	------------------------------

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 3.00

Revision: 01.04.2020

Trade name: SONAX Wheel rim coating

(Contd. of page 1)

CAS: 540-97-6 Dodecamethylcyclohexasiloxane

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 541-02-6 EINECS: 208-764-9 Reg.nr.: 01-2119511367-43-xxxx	decamethylcyclopentasiloxane Non-classified vPvB substance. Non-classified PBT substance.	50-<75%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	15-<20%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<15%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	3-<5%
CAS: 540-97-6 EINECS: 208-762-8 Reg.nr.: 01-2119517435-42-xxxx	Dodecamethylcyclohexasiloxane Non-classified vPvB substance. Non-classified PBT substance.	1-<3%
	polymer ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315	1-<3%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Remove soiled clothing

After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

After skin contact:

Generally the product does not irritate the skin.

Wash the areas of skin affected with water and a mild detergent.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Water haze

Foam

Carbon dioxide

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO₂)

Silicon oxides

(Contd. on page 3)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 3.00

Revision: 01.04.2020

Trade name: SONAX Wheel rim coating

(Contd. of page 2)

5.3 Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.



Keep ignition sources away - Do not smoke.

Highly volatile, flammable constituents are released during processing.

Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Prevent any seepage into the ground.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Protect from heat and direct sunlight.

Protect from frost.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s)

 No further relevant information available.

GB

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 3.00

Revision: 01.04.2020

Trade name: SONAX Wheel rim coating

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 106-97-8 butane

WEL (Great Britain)	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
---------------------	---

Regulatory information WEL (Great Britain): EH40/2018

DNELs

polymer

Dermal	DNEL	9.1 mg/bw/day (worker) (longterm systematic effects)
	DNEL	9.1 mg/kg bw/day (worker) (akut systematic effects)
Inhalative	DNEL	16 mg/m ³ (worker) (longterm lokale effects)
	DNEL	16 mg/m ³ (worker) (lontime systematic effects)

PNECs

polymer

PNEC	0.0058 mg/l (freshwater (Süßwasser)) 0.00058 mg/l (water (sea water))
PNEC	2.3 mg/kg (sediment (fresh water)) 0.23 mg/kg (sediment (sea water))

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Respiratory protection:

Not required in normal cases

If the occupational exposure limit is exceeded:

The following breathing protection is recommended:

Respiratory filter for organic gases and vapours (Type A)

Identification colour: Brown

[DIN EN 14387]

Protection of hands: Not required in normal cases.

Eye protection: Not required in normal cases

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Aerosol
Colour:	Whitish
Odour:	Odourless
Odour threshold:	Not determined.

pH-value:	Not determined.
-----------	-----------------

(Contd. on page 5)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 3.00

Revision: 01.04.2020

Trade name: SONAX Wheel rim coating

(Contd. of page 4)

Change in condition**Melting point/freezing point:** Undetermined.**Initial boiling point and boiling range:** 211 °C**Flash point:** 76 °C
(Active ingredient data)**Flammability (solid, gas):** Not applicable.**Decomposition temperature:** Not determined.**Auto-ignition temperature:** Not determined.**Explosive properties:** Not determined.
In use, may form flammable/explosive vapour-air mixture.**Explosion limits:****Lower:** 1,5 Vol.% (Propellant data)**Upper:** 10,9 Vol.% (Propellant data)**Vapour pressure:** Not determined.**Density at 20 °C:** 0.95-0.97 g/cm³
(Active ingredient data)**Relative density** Not determined.**Vapour density** Not determined.**Evaporation rate** Not applicable.**Solubility in / Miscibility with water:** Not miscible or difficult to mix.**Partition coefficient: n-octanol/water:** Not determined.**Viscosity:****Flow time at 20 °C** 10 - 15 s (DIN EN ISO 2431/4mm)
(Active ingredient data)**9.2 Other information** No further relevant information available.**SECTION 10: Stability and reactivity****10.1 Reactivity** No dangerous reactions known.**10.2 Chemical stability** Stable under normal conditions.**10.3 Possibility of hazardous reactions** Develops readily flammable gases/fumes.**10.4 Conditions to avoid**

Protect from heat and direct sunlight.

An increase in pressure may lead to bursting.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

10.5 Incompatible materials: No further relevant information available.**10.6 Hazardous decomposition products:**

In case of fire, the following can be released:

Silicon oxides

Carbon monoxide

Carbon dioxide (CO₂)

Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C through oxidation.

SECTION 11: Toxicological information**11.1 Information on toxicological effects** There are no toxicological findings on this mixture.**Acute toxicity** Based on available data, the classification criteria are not met.**LD/LC50 values relevant for classification:**

Oral	ATE	>5,000-<10,000 mg/kg
------	-----	----------------------

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 3.00

Revision: 01.04.2020

Trade name: SONAX Wheel rim coating

(Contd. of page 5)

polymer

Oral	LD50	>5,110 mg/kg (rat)
Dermal	LD50	6,730 mg/kg (rabbit) (OECD TG 402)
Inhalative	LC0/4h	22 ppm (rat) (OECD TG 403)

Primary irritant effect:**Skin corrosion/irritation** Based on available data, the classification criteria are not met.**Serious eye damage/irritation** Based on available data, the classification criteria are not met.**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.**Repeated dose toxicity****polymer**

Oral	NOAEL	3,000 mg/kg (rat) (OECD TG 422)
		300 mg/kg (Ratte) (OECD TG 422)

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

None of the ingredients are known to have effects which are carcinogenic, mutagenic or harmful to reproduction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure** Based on available data, the classification criteria are not met.**STOT-repeated exposure** Based on available data, the classification criteria are not met.**Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture.**Aquatic toxicity:****CAS: 106-97-8 butane**

LC50 / 96 h	27.98 mg/l (fish)
EC50 / 4 d	7.71 mg/l (algae)

CAS: 74-98-6 propane

LC50 / 96 h	27.98 mg/l (fish)
EC50 / 96 h	7.71 mg/l (algae)

CAS: 75-28-5 isobutane

LC50 / 96 h	27.98 mg/l (fish)
EC50 / 4 d	7.71 mg/l (algae)

polymer

EC50/3h	>1,000 mg/l (activated sludge) (OECD TG 209)
NOEC/ 3 h	≥1,000 mg/l (activated sludge) (OECD TG 209)

12.2 Persistence and degradability No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**Additional ecological information:****General notes:** The product may not be released into the environment without control.**12.5 Results of PBT and vPvB assessment****PBT:**

CAS: 541-02-6	decamethylcyclopentasiloxane
CAS: 540-97-6	Dodecamethylcyclohexasiloxane

vPvB:

CAS: 541-02-6	decamethylcyclopentasiloxane
CAS: 540-97-6	Dodecamethylcyclohexasiloxane

(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 3.00

Revision: 01.04.2020

Trade name: SONAX Wheel rim coating

12.6 Other adverse effects No further relevant information available.

(Contd. of page 6)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

Recommendation

Waste must be disposed of while observing the local, official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

Disposal / product + Disposal / contaminated packaging

15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA

UN1950

14.2 UN proper shipping name

ADR

1950 AEROSOLS

IMDG

AEROSOLS

IATA

AEROSOLS, flammable

14.3 Transport hazard class(es)

ADR



Class

2 5F Gases.

Label

2.1

IMDG, IATA



Class

2.1

Label

2.1

14.4 Packing group

ADR, IMDG, IATA

Void

14.5 Environmental hazards:

Marine pollutant:

No

14.6 Special precautions for user

Warning: Gases.

14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code

Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ)

1L

Transport category

2

Tunnel restriction code

D

UN "Model Regulation":

UN1950, AEROSOLS, 2.1

GB

(Contd. on page 8)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2020

Version: 3.00

Revision: 01.04.2020

Trade name: SONAX Wheel rim coating

(Contd. of page 7)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

European Directives:

EC/1907/2006 (REACH)

EC/1272/2008 (CLP)

EC/648/2004

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H411 Toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

Aerosols On basis of test data

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = Lethal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Version history and indication of changes: Replaces version 2.01.

*** Data compared to the previous version altered.**