

Page 1/15

Revision: 10.02.2023

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.02.2023

Version number 9 (replaces version 8)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

- Trade name: BRUNOX® epoxy® AEROSOL
- · UFI: EWGA-0VAJ-U206-EKTX

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category

PC9a Coatings and paints, thinners, paint removers

PC14 Metal surface treatment products

Process category

PROC5 Mixing or blending in batch processes

PROC7 Industrial spraying

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC13 Treatment of articles by dipping and pouring

Environmental release category

ERC8c Widespread use leading to inclusion into/onto article (indoor)

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

· Application of the substance / the mixture Coating material

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

BRUNOX Korrosionsschutz GmbH Adlzreiterstrasse 13, 85051 Ingolstadt Postfach 100127, 85001 Ingolstadt

Tel. + 49/ (0) 841 961 29 04 Fax + 49/ (0) 841 961 29 13 E-mail: office@brunox.com

UFI info / E-mail: ufi@brunox.com

www.brunox.de

BRUNOX AG
Tunnelstrasse 6
CH - 8732 Neuhaus/SG

Tel. +41/ (0)55 285 80 80 Fax +41/ (0)55 285 80 81

E-mail: office@brunox.com

www.brunox.swiss

UFI info / E-mail: ufi@brunox.com



Page 2/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.02.2023 Version number 9 (replaces version 8) Revision: 10.02.2023

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 1)

· Further information obtainable from:

Abteilung Produktsicherheit / Product Safety Department:

Tel. - Switzerland: +41/ (0)55 285 80 80 Tel. - Germany: +49 / (0)841 961 29 04

Mo - Do / Mon - Thu: 08:00 - 16:00 Uhr

Fr / Fri: 08:00 - 12:00 Uhr

· 1.4 Emergency telephone number:

Toxikologisches Informationszentrum CH - 8030 Zürich, Freiestrasse 16

Tel. +41/ 044 251 51 51

Notruf - CH, STIZ : 145 Notruf - D - : Giftnotrufzentrale 030 19240 Notruf - BE - : 070 -245 245 EUROPÄISCHE NOTRUFNR. : 112

Notruf - GB -: 844 892 0111

Notruf - IE -: + 353 1 837 9964 (medical professionals); + 353 1 809 2166 (public)

Notruf - IS - : + 354 543 22 22

Notruf - JP - : + 81 72 727 2499; + 81 29 852 9999

Notruf - NZ -: 0800 764 766

Notruf - PK -: + 92 21 9920509; + 92 21 35686535

Notruf - PH -: +632 524 10 78; +632 544 84 00; local 2311

Notruf - SA -: + 966 146 77 353, + 966 3 8155 646; Ext. 280, 282, 283

Notruf - TH - : + 66 201 1086 Notruf - UAE - : 800 424

Notruf - ZA -: + 27 824 910 160

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 3)



Page 3/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.02.2023 Version number 9 (replaces version 8) Revision: 10.02.2023

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 2)

Hazard pictograms





GHS02 GHS07

Signal word Danger

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Causes serious eye irritation. H319 May cause drowsiness or dizziness. H336

· Precautionary statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. P271

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 115-10-6 dimethyl ether 25-50%

EINECS: 204-065-8 Flam. Gas 1A, H220 Index number: 603-019-00-8 Press. Gas (Comp.), H280 Reg.nr.: 01-2119472128-37-

XXXX

CAS: 67-64-1 >10-<20% acetone

EINECS: 200-662-2

 Flam. Liq. 2, H225
 Eye Irrit. 2, H319; STOT SE 3, H336 Index number: 606-001-00-8

Reg.nr.: 01-2119471330-49-**EUH066**

XXXX

(Contd. on page 4)



Page 4/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.02.2023 Version number 9 (replaces version 8) Revision: 10.02.2023

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 3) CAS: 107-98-2 2.5-10% 1-methoxy-2-propanol EINECS: 203-539-1 Flam. Liq. 3, H226

Index number: 603-064-00-3 ♠ STOT SÉ 3, H336

Reg.nr.: 01-2119457435-35-

XXXX

CAS: 108-65-6 2.5-10% 2-methoxy-1-methylethyl acetate

EINECS: 203-603-9 Flam. Liq. 3, H226 Index number: 607-195-00-7

XXXX

Reg.nr.: 01-2119475791-29-

CAS: 67-63-0 >2.5-<10% propan-2-ol

EINECS: 200-661-7 Flam. Liq. 2, H225
 Eye Irrit. 2, H319; STOT SE 3, H336 Index number: 603-117-00-0

Reg.nr.: 01-2119457558-25-

XXXX

CAS: 112-34-5 2-(2-butoxyethoxy)ethanol ≥2.5-<10%

EINECS: 203-961-6 Eye Irrit. 2, H319 Index number: 603-096-00-8

Reg.nr.: 01-2119475104-44-XXXX

CAS: 64-18-6 formic acid <2%

EINECS: 200-579-1 Acute Tox. 3, H331 Skin Corr. 1C, H314 Index number: 607-001-00-0

Reg.nr.: 01-2119491174-37-(x) Acute Tox. 4, H302 XXXX Specific concentration limits:

Skin Corr. 1A; H314: C≥ 90 % Skin Corr. 1B; H314: 10 % ≤ C < 90 %

Skin Irrit. 2; H315: 2 $\% \le C < 10 \%$ Eye Irrit. 2; H319: 2 % \leq C < 10 %

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information:

Take affected persons out into the fresh air. Do not leave affected persons unattended.

Position and transport stably in side position.

Seek medical treatment.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

A person vomiting while laying on their back should be turned onto their side.

(Contd. on page 5)



Page 5/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.02.2023 Version number 9 (replaces version 8) Revision: 10.02.2023

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 4)

· 4.2 Most important symptoms and effects, both acute and delayed

Dizziness Dizziness

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

- 5.3 Advice for firefighters
- · Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

· Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Use only in well ventilated areas.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

(Contd. on page 6)



Page 6/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.02.2023 Version number 9 (replaces version 8) Revision: 10.02.2023

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 5)

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

• Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Keep container tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

CAS: 115-10-6 dimethyl ether

IOELV Long-term value: 1920 mg/m³, 1000 ppm

CAS: 67-64-1 acetone

IOELV Long-term value: 1210 mg/m³, 500 ppm

CAS: 107-98-2 1-methoxy-2-propanol

IOELV Short-term value: 568 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm

Skin

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

IOELV Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm

Skin

CAS: 112-34-5 2-(2-butoxyethoxy)ethanol

IOELV Short-term value: 101.2 mg/m³, 15 ppm Long-term value: 67.5 mg/m³, 10 ppm

CAS: 64-18-6 formic acid

IOELV Long-term value: 9 mg/m³, 5 ppm

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 7)



Page 7/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.02.2023 Version number 9 (replaces version 8) Revision: 10.02.2023

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 6)

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

Short term filter device:

Filter A/P2

Filter AX

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Check the permeability prior to each anewed use of the glove.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR


Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection





Page 8/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.02.2023 Version number 9 (replaces version 8) Revision: 10.02.2023

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 7)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

General Information

Colour:
 Odour:
 Odour threshold:
 Melting point/freezing point:

Amber coloured
Characteristic
Not determined.
Undetermined.

· Boiling point or initial boiling point and

boiling range 82 °C

· Flammability Not applicable.

· Lower and upper explosion limit

. <u>Lower:</u> 2.6 Vol % . <u>Upper:</u> 18.6 Vol %

· Flash point: Not applicable, as aerosol.

Ignition temperature: 235 °C

· **Decomposition temperature:** Not determined.

• **pH at 20 °C** 4.8

· Viscosity:

• Kinematic viscosity Not determined.
• Dynamic: Not determined.

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value)
Not determined.
Vapour pressure at 20 °C:
5,200 hPa

Density and/or relative density

· Density at 20 °C: 1 g/cm³

Relative densityVapour densityNot determined.Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health

and environment, and on safety.

· <u>Auto-ignition temperature:</u> Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

 · Organic solvents:
 67.5 %

 · Water:
 16.4 %

 · VOC (EC)
 67.54 %

 · Solids content:
 1.5 %

(Contd. on page 9)



Page 9/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.02.2023 Version number 9 (replaces version 8) Revision: 10.02.2023

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 8)

· Change in condition

· Evaporation rate Not applicable.

· Information with regard to physical hazard

classes

· Explosives Void · Flammable gases Void

· Aerosols

Extremely flammable aerosol. Pressurised container: May burst if heated.

Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void Oxidising solids Void · Organic peroxides Void Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral LD50 61,315 mg/kg (rat)

Inhalative LC50/4 h 167 mg/l

(Contd. on page 10)



Page 10/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.02.2023 Version number 9 (replaces version 8) Revision: 10.02.2023

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 9)

CAS: 67-64-1 acetone

Oral LD50 5,800 mg/kg (rat)
Dermal LD50 >15,800 mg/kg (rat)

20,000 mg/kg (rabbit)

Inhalative LC50/4 h 76 mg/l (rat)

CAS: 107-98-2 1-methoxy-2-propanol

Oral LD50 5,660 mg/kg (rat)
Dermal LD50 13,000 mg/kg (rabbit)

Inhalative LC50/4 h 6 mg/l (rat)

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

Oral LD50 8,532 mg/kg (rat)

Dermal LD50 >5,000 mg/kg (rat)

Inhalative LC50/4 h 35.7 mg/l (rat)

CAS: 67-63-0 propan-2-ol

Oral LD50 5,045 mg/kg (rat)
Dermal LD50 12,800 mg/kg (rabbit)

Inhalative LC50/4 h 30 mg/l (rat)

CAS: 112-34-5 2-(2-butoxyethoxy)ethanol

Oral LD50 5,660 mg/kg (rat)

Dermal LD50 4,000 mg/kg (rabbit)

CAS: 64-18-6 formic acid

Oral LD50 1,100 mg/kg (rat) Inhalative LC50/4 h 3 mg/l (ATE)

Skin corrosion/irritation

Bei längeren und/oder häufigem Hautkontakt sind Reizerscheinungen möglich.

Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 11)



Page 11/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.02.2023 Version number 9 (replaces version 8) Revision: 10.02.2023

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 10)

- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity:

CAS: 115-10-6 dimethyl ether

EC50 154.92 mg/kg (algae) (QSAR)

>4,400 mg/kg (daphnia)

LC50/96 h >4,100 mg/l (fish)

EC10 >1,600 mg/l (pseudomonas putida)

CAS: 67-64-1 acetone

LC50/48 h 8,800 mg/l (daphnia)

CAS: 107-98-2 1-methoxy-2-propanol

EC50 >500 mg/kg (daphnia)

LC50/96 h 4,600-10,000 mg/l (leuciscus idus)

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

EC50 >500 mg/kg (daphnia)

LC50/96 h 160 mg/l (pimephales promelas)

CAS: 64-18-6 formic acid

EC50 120 mg/kg (daphnia) LC50/48 h 122 mg/l (leuciscus idus)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

EU



Page 12/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.02.2023 Version number 9 (replaces version 8) Revision: 10.02.2023

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 11)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

HP3 Flammable

HP4 Irritant - skin irritation and eye damage

- · Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR/RID/ADN, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR/RID/ADN 1950 AEROSOLS · IMDG AEROSOLS

· IATA AEROSOLS, flammable

- · 14.3 Transport hazard class(es)
- · ADR/RID/ADN



· Class 2 5F Gases.

· Label 2.1

· IMDG, IATA



· Class 2.1 Gases.

· Label 2.1

· 14.4 Packing group

· ADR/RID/ADN, IMDG, IATA Void

(Contd. on page 13)



Page 13/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.02.2023 Version number 9 (replaces version 8) Revision: 10.02.2023

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 12)

· 14.5 Environmental hazards:

· Marine pollutant: No

· 14.6 Special precautions for user Warning: Gases.

Hazard identification number (Kemler code): -

• **EMS Number:** F-D,S-U

· **Stowage Code** SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

• Segregation Code SG69 For AEROSOLS with a maximum capacity

of 1 litre:

Segregation as for class 9. Stow "separated from"

class 1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of

class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of

class 2.

· 14.7 Maritime transport in bulk according to

IMO instruments Not applicable.

· Transport/Additional information:

· ADR/RID/ADN

· <u>Limited quantities (LQ)</u> 1L · Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· Transport category 2 · Tunnel restriction code D

· IMDG

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· <u>UN "Model Regulation":</u> UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS

(Contd. on page 14)



Page 14/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.02.2023 Version number 9 (replaces version 8) Revision: 10.02.2023

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 13)

3

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

CAS: 67-64-1 acetone

· Regulation (EC) No 273/2004 on drug precursors

CAS: 67-64-1 acetone

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

CAS: 67-64-1 acetone 3

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

- · Date of previous version: 16.03.2021
- · Version number of previous version: 8

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 15)



Page 15/15

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.02.2023 Version number 9 (replaces version 8) Revision: 10.02.2023

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 14)

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1C: Skin corrosion/irritation - Category 1C Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

* Data compared to the previous version altered.