

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.05.2023

Version: 4.00 (replaces version 3.00)

Revision: 05.05.2023

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name:** SONAX Soft Top+Fabric Water Proof Impregnation

**Article number:**

03101410

**UFI:** 8XW1-F0JF-D00N-JPA9

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Application of the substance / the mixture

Car care product

Textile dyes, and impregnating products

Consumer uses: Private households / general public / consumers

Professional uses

**Uses advised against** None

### 1.3 Details of the supplier of the safety data sheet

#### Manufacturer/Supplier:

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

#### Further information obtainable from:

Product safety

E-mail: [erp@sonax.de](mailto:erp@sonax.de)

Phone: + +49 (0) 8431 53 217

#### United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: [info@aaoil.co.uk](mailto:info@aaoil.co.uk)

### 1.4 Emergency telephone number:

**European Union:** +49 (0) 89 19240 (Poison Centre Munich)

**United Kingdom:** 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

#### Hazard pictograms



GHS02

GHS07

GHS08

GHS09

**Signal word** Danger

#### Hazard-determining components of labelling:

C10-12-Isoalkanes

#### Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

(Contd. on page 2)

GB

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 16.05.2023

Version: 4.00 (replaces version 3.00)

Revision: 05.05.2023

**Trade name: SONAX Soft Top+Fabric Water Proof Impregnation**

(Contd. of page 1)

H319 Causes serious eye irritation.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapours.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/eye protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

Buildup of explosive mixtures possible without sufficient ventilation.

**2.3 Other hazards****Results of PBT and vPvB assessment****PBT:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

**vPvB:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

**Determination of endocrine-disrupting properties**

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures****Description:** Additives in solvent**Dangerous components:**

CAS: 90622-57-4 EC No 923-037-2 Reg.nr.: 01-2119471991-29-xxxx	Hydrocarbons, C10-C12, isoalkanes, < 2%aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411, EUH066	75-100%
CAS: 540-84-1 EINECS: 208-759-1 Reg.nr.: 01-2119457965-22-xxxx	2,2,4-trimethylpentane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Acute 1, H400 (M=1); ⚠ Aquatic Chronic 1, H410 (M=1); ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	5-<10%
CAS: 1071-76-7 EINECS: 213-995-3	Zirconium tetrabutanolate ⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; STOT SE 3, H335; STOT SE 3, H336	1-<3%

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

**4.1 Description of first aid measures****General information:**

Take affected persons out of danger area and lay down.

Remove soiled clothing

**After inhalation:**

Supply fresh air.

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.05.2023

Version: 4.00 (replaces version 3.00)

Revision: 05.05.2023

**Trade name: SONAX Soft Top+Fabric Water Proof Impregnation**

(Contd. of page 2)

*In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately.*

*In case of unconsciousness place patient stably in side position for transportation.*

**After skin contact:**

*Wash the areas of skin affected with water and a mild detergent.*

*If skin irritation continues, consult a doctor.*

**After eye contact:**

*Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.*

**After swallowing:** *Do not induce vomiting; call for medical help immediately.*

**4.2 Most important symptoms and effects, both acute and delayed**

Headache

Dizziness

Drowsiness

Nausea

Reddening, drying and crack formation of the skin

Skin irritation

Eye irritation

**4.3 Indication of any immediate medical attention and special treatment needed**

*If swallowed or in case of vomiting, danger of entering the lungs.*

*Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.*

## SECTION 5: Firefighting measures

**5.1 Extinguishing media****Suitable extinguishing agents:**

Foam

Carbon dioxide

Fire-extinguishing powder

Water haze

**For safety reasons unsuitable extinguishing agents:** *Water with full jet*

**5.2 Special hazards arising from the substance or mixture**

*In case of fire, the following can be released:*

Carbon monoxide (CO)

Carbon dioxide (CO<sub>2</sub>)

**5.3 Advice for firefighters****Protective equipment:**

*Do not inhale explosion gases or combustion gases.*

*Wear fully protective suit.*

*Do not enter the hazardous area without a self-contained breathing apparatus.*

*See Section 8 for information on personal protection equipment.*

**Additional information**

*Cool endangered receptacles with water spray.*

*Collect contaminated fire fighting water separately. It must not enter the sewage system.*

## SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures**

*Keep away from ignition sources.*

**For non-emergency personnel**

*Ensure adequate ventilation*

*Wear protective clothing.*

**For emergency responders**

*Do not inhale gases / fumes / aerosols.*

*Wear protective equipment. Keep unprotected persons away.*

**6.2 Environmental precautions:**

*Do not allow to penetrate the ground/soil.*

*Inform respective authorities in case of seepage into water course or sewage system.*

*Do not allow to enter sewers/ surface or ground water.*

**6.3 Methods and material for containment and cleaning up:**

*Ensure adequate ventilation.*

(Contd. on page 4)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2023

Version: 4.00 (replaces version 3.00)

Revision: 05.05.2023

**Trade name: SONAX Soft Top+Fabric Water Proof Impregnation**

(Contd. of page 3)

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.

### 6.4 Reference to other sections

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## SECTION 7: Handling and storage

**7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

**Information about fire - and explosion protection:**



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Highly volatile, flammable constituents are released during processing.

Fumes can combine with air to form an explosive mixture.

**7.2 Conditions for safe storage, including any incompatibilities**

**Storage:**

**Requirements to be met by storerooms and receptacles:** Provide solvent resistant, sealed floor.

**Information about storage in one common storage facility:**

Store away from foodstuffs.

Observe local/state/federal regulations.

**Further information about storage conditions:**

Store receptacle in a well ventilated area.

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from frost.

**7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

**8.1 Control parameters**

**Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

### DNELs

**CAS: 540-84-1 2,2,4-trimethylpentane**

Oral	DNEL	699 mg/kg (consumer) (longterm systematic effects)
Dermal	DNEL	699 mg/kg (consumer) (longterm systematic effects)
		773 mg/kg (worker) (longterm systematic effects)
Inhalative	DNEL	608 mg/m <sup>3</sup> (consumer) (longterm systematic effects)
		2,035 mg/m <sup>3</sup> (worker) (longterm systematic effects)

**Additional information:** The lists valid during the making were used as basis.

**8.2 Exposure controls**

**Suitable technical control devices**

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

**Individual protection measures, such as personal protective equipment**

**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

(Contd. on page 5)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 16.05.2023

Version: 4.00 (replaces version 3.00)

Revision: 05.05.2023

**Trade name: SONAX Soft Top+Fabric Water Proof Impregnation**

(Contd. of page 4)

**Respiratory protection:**

If inhalative exposure above the occupational exposure limit cannot be excluded, adequate respiratory protection equipment must be used. Suitable respiratory equipment: Respirator with a full face mask, according to acknowledged standards such as EN 136.

Recommended Filter type: Gas filter type ABEK (certain inorganic, organic and acidic gases and vapors; ammonia/amines), according to acknowledged standards such as EN 14387

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. Suitable respiratory equipment: Respirator with a full face mask, according to acknowledged standards such as EN 136.

Recommended Filter type: Combined filter type ABEK-P2 (certain inorganic, organic and acidic gases and vapors; ammonia/amines; particles), according to acknowledged standards such as EN 14387

Observe the equipment manufacturer's information and wear time limits for respirators.

**Hand protection** Protective gloves**Material of gloves**

Butyl rubber, BR

Recommended thickness of the material:  $\geq 0.3$  mm

Penetration time of glove material &gt;480min.

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.4$  mm

Penetration time of glove material: 10-30min

[EN 374]

**Penetration time of glove material**

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

**Eye/face protection**

Safety glasses

[EN 166]

## SECTION 9: Physical and chemical properties

**9.1 Information on basic physical and chemical properties****General Information****Physical state**

Fluid

**Colour:**

Colourless

**Odour:**

Solvent-like

**Melting point/freezing point:**

Undetermined.

**Boiling point or initial boiling point and boiling range**

138-174 °C (CAS: 90622-57-4 Hydrocarbons, C10-C12, isoalkanes, &lt; 2%aromatics)

Flammable liquid and vapour.

**Flammability****Lower and upper explosion limit****Lower:**

0.7 Vol % (CAS: 90622-57-4 Hydrocarbons, C10-C12, isoalkanes, &lt; 2%aromatics)

**Upper:**

6 Vol % (CAS: 90622-57-4 Hydrocarbons, C10-C12, isoalkanes, &lt; 2%aromatics)

**Flash point:**

29 °C (DIN 51755)

**Decomposition temperature:**

Not determined.

**pH**

Not applicable.

**Viscosity:****Kinematic viscosity at 40 °C**<20.5 mm<sup>2</sup>/s**Solubility****water:**

Not miscible or difficult to mix.

**Partition coefficient n-octanol/water (log value)**

Not determined.

**Vapour pressure at 20 °C:**

~3 hPa (CAS: 90622-57-4 Hydrocarbons, C10-C12, isoalkanes, &lt; 2%aromatics)

**Density and/or relative density****Density at 20 °C:**0.75-0.77 g/cm<sup>3</sup>**Vapour density**

Not determined.

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.05.2023

Version: 4.00 (replaces version 3.00)

Revision: 05.05.2023

Trade name: SONAX Soft Top+Fabric Water Proof Impregnation

(Contd. of page 5)

**9.2 Other information****Appearance:****Form:**

Fluid

**Important information on protection of health and environment, and on safety.****Ignition temperature:**

Not determined.

**Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

**Change in condition****Evaporation rate**

Not determined.

**Information with regard to physical hazard classes****Explosives**

Void

**Flammable gases**

Void

**Aerosols**

Void

**Oxidising gases**

Void

**Gases under pressure**

Void

**Flammable liquids**

Flammable liquid and vapour.

**Flammable solids**

Void

**Self-reactive substances and mixtures**

Void

**Pyrophoric liquids**

Void

**Pyrophoric solids**

Void

**Self-heating substances and mixtures**

Void

**Substances and mixtures, which emit flammable**

gases in contact with water

Void

**Oxidising liquids**

Void

**Oxidising solids**

Void

**Organic peroxides**

Void

**Corrosive to metals**

Void

**Desensitised explosives**

Void

**SECTION 10: Stability and reactivity****10.1 Reactivity** No dangerous reactions known.**10.2 Chemical stability** Stable under normal conditions.**10.3 Possibility of hazardous reactions** No dangerous reactions known.**10.4 Conditions to avoid**

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

**10.5 Incompatible materials:**

acids

caustic solutions

strong oxidizing agents

**10.6 Hazardous decomposition products:**

Ethanol

Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C through oxidation.

**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity** Based on available data, the classification criteria are not met.**LD/LC50 values relevant for classification:****CAS: 90622-57-4 Hydrocarbons, C10-C12, isoalkanes, < 2%aromatics**

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50 / 4h	>5.6 mg/l (rat) (OECD 403)

(Contd. on page 7)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.05.2023

Version: 4.00 (replaces version 3.00)

Revision: 05.05.2023

Trade name: SONAX Soft Top+Fabric Water Proof Impregnation

(Contd. of page 6)

**CAS: 540-84-1 2,2,4-trimethylpentane**

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50 / 4h	>33.52 mg/l (rat) (OECD 403)

**Skin corrosion/irritation** Causes skin irritation.**Serious eye damage/irritation** Causes serious eye irritation.**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.**Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure** Based on available data, the classification criteria are not met.**STOT-repeated exposure** Based on available data, the classification criteria are not met.**Aspiration hazard**Viscosity: < 20,5mm<sup>2</sup>/s (40°C)

May be fatal if swallowed and enters airways.

**11.2 Information on other hazards****Endocrine disrupting properties**

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

None of the ingredients is listed.

**SECTION 12: Ecological information****12.1 Toxicity**

Product is considered to be harmful to aquatic organisms. May have long-term harmful effects in aquatic environments.

**Aquatic toxicity:****CAS: 90622-57-4 Hydrocarbons, C10-C12, isoalkanes, < 2%aromatics**

LC50 / 2 d	>1,000 mg/l (Daphnia magna) (OECD 202)
NOEC / 3 d	1,000 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
LC50 / 4 d	>1,000 mg/l (Oncorhynchus mykiss) (OECD 203)
NOEC / 21 d	<1 mg/l (Daphnia magna) (OECD 211)
NOEC / 28d	0.192 mg/l (Oncorhynchus mykiss)
EC50 / 3 d	>1,000 mg/l (Pseudokirchneriella subcapitata) (OECD 201)

**CAS: 540-84-1 2,2,4-trimethylpentane**

NOEC / 3 d	0.658 mg/l (Pseudokirchneriella subcapitata)
LC50 / 4 d	18.4 mg/l (Oncorhynchus mykiss) (OECD 203)
NOEC / 21 d	0.17 mg/l (Daphnia magna) (OECD 211)
NOEC / 28d	0.82 mg/l (Oncorhynchus mykiss)
EC50 / 2 d	0.4 mg/l (Daphnia magna)
EC50 / 3 d	2,943 mg/l (Pseudokirchneriella subcapitata)

**12.2 Persistence and degradability****CAS: 90622-57-4 Hydrocarbons, C10-C12, isoalkanes, < 2%aromatics**

Biodegradation 31.3 %

**CAS: 540-84-1 2,2,4-trimethylpentane**

Biodegradation 22 %

**12.3 Bioaccumulative potential****CAS: 540-84-1 2,2,4-trimethylpentane**

log Kow 4.08

**12.4 Mobility in soil** No further relevant information available.

(Contd. on page 8)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2023

Version: 4.00 (replaces version 3.00)

Revision: 05.05.2023

**Trade name: SONAX Soft Top+Fabric Water Proof Impregnation**

(Contd. of page 7)

### 12.5 Results of PBT and vPvB assessment

#### PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

#### vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB

### 12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

### 12.7 Other adverse effects

#### Additional ecological information:

**General notes:** Do not allow product to reach ground water, water course or sewage system.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

**Recommendation** Waste must be disposed of while observing the local, official regulations.

#### European waste catalogue

- 1) Disposal / product
- 2) Disposal / contaminated packaging

20 01 13*	solvents
15 01 10*	packaging containing residues of or contaminated by hazardous substances
HP3	Flammable
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP14	Ecotoxic

#### Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR/RID/ADN, IMDG, IATA UN3295

### 14.2 UN proper shipping name

ADR/RID/ADN 3295 HYDROCARBONS, LIQUID, N.O.S.  
IMDG, IATA HYDROCARBONS, LIQUID, N.O.S.

### 14.3 Transport hazard class(es)

ADR/RID/ADN, IMDG, IATA



**Class** 3 Flammable liquids.  
**Label** 3

### 14.4 Packing group

ADR/RID/ADN, IMDG, IATA III

### 14.5 Environmental hazards:

**Marine pollutant:** Yes  
>5l: Symbol (fish and tree)  
**Special marking (ADR/RID/ADN):** >5l: Symbol (fish and tree)  
**Special marking (IATA):** >5l: Symbol (fish and tree)

(Contd. on page 9)



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2023

Version: 4.00 (replaces version 3.00)

Revision: 05.05.2023

**Trade name: SONAX Soft Top+Fabric Water Proof Impregnation**

(Contd. of page 8)

**14.6 Special precautions for user** Warning: Flammable liquids.

**14.7 Maritime transport in bulk according to IMO instruments** Not applicable.

**Transport/Additional information:**

**ADR/RID/ADN**  
**Limited quantities (LQ)** 5L  
**Transport category** 3  
**Tunnel restriction code** D/E

**UN "Model Regulation":** UN 3295 HYDROCARBONS, LIQUID, N.O.S., 3, III

### SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
**European Directives:**

Directive 2010/75/EU (VOC) 90.60 %  
**Catégorie SEVESO (DIRECTIVE 2012/18/EU)**  
 E2 Hazardous to the Aquatic Environment  
 P5c FLAMMABLE LIQUIDS  
**REGULATION (EU) 2019/1148**

**Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

**Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

**National regulations:**

**Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.  
 Employment restrictions concerning pregnant and lactating women must be observed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

**Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

**Classification according to Regulation (EC) No 1272/2008**

Flammable liquids	On basis of test data
Skin corrosion/irritation Serious eye damage/irritation Aspiration hazard Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.05.2023

Version: 4.00 (replaces version 3.00)

Revision: 05.05.2023

**Trade name: SONAX Soft Top+Fabric Water Proof Impregnation**

(Contd. of page 9)

**Date of previous version: 02.09.2021****Version number of previous version: 3.00****Abbreviations and acronyms:***RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)**NOEL = No Observed Effect Level**NOEC = No Observed Effect Concentration**LC = lethal Concentration**EC50 = half maximal effective concentration**log POW = Octanol / water partition coefficient**GHS: Globally Harmonized System of Classification and Labelling of Chemicals**ATE: acute toxicity estimate**ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**IATA: International Air Transport Association**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**DNEL: Derived No-Effect Level (UK REACH)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**IOELV = indicative occupational exposure limit values**Flam. Liq. 2: Flammable liquids – Category 2**Flam. Liq. 3: Flammable liquids – Category 3**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Dam. 1: Serious eye damage/eye irritation – Category 1**Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**Asp. Tox. 1: Aspiration hazard – Category 1**Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1**Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2***\* Data compared to the previous version altered.**