

Printing date 31.10.2019 Version number 1910 Revision: 31.10.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: MANNOL Tar Remover 5L
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Cleaning agent/ Cleaner
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

SCT-Vertriebs GmbH Feldstrasse 154 22880 WEDEL DEUTSCHLAND

info@sct-germany.de

- · Further information obtainable from: Product safety department.
- 1.4 Emergency telephone number: Giftinformationszentrum-Nord +49-551-19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 1 H224 Extremely flammable liquid and vapour.



GHS08 health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 31.10.2019 Version number 1910 Revision: 31.10.2019

Trade name: MANNOL Tar Remover 5L

(Contd. of page 1)

· Hazard pictograms







GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

toluene

dichloromethane

Kerosine (petroleum)

· Hazard statements

H224 Extremely flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H361d Suspected of damaging the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P260 Do not breathe dust/fume/gas/mist/vapours/spray. P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P301+P310

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

Take off contaminated clothing and wash it before reuse. P362+P364

Store locked up. P405

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. vPvB: Not applicable.



Printing date 31.10.2019 Version number 1910 Revision: 31.10.2019

Trade name: MANNOL Tar Remover 5L

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous compor	nents:	
CAS: 108-88-3 EINECS: 203-625-9	toluene Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	22–32%
CAS: 8008-20-6 EINECS: 232-366-4	Kerosine (petroleum) Asp. Tox. 1, H304	13–20%
CAS: 67-63-0 EINECS: 200-661-7	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	7–14%
CAS: 25551-13-7 EINECS: 247-099-9	Trimethylbenzene Flam. Liq. 3, H226; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319	7–14%
CAS: 75-09-2 EINECS: 200-838-9	dichloromethane Carc. 2, H351	4–9%
CAS: 111-76-2	2-butoxyethanol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	4–9%
· Not dangerous sub	stances	
CAS: 1338-43-8 EINECS: 215-665-4	Sorbitan oleate	1–2%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2. Do not use water.

Foam

(Contd. on page 4)



Printing date 31.10.2019 Version number 1910 Revision: 31.10.2019

Trade name: MANNOL Tar Remover 5L

(Contd. of page 3)

Fire-extinguishing powder

Sand

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Particular danger of slipping on leaked/spilled product.

Wear protective clothing.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

3B -



Printing date 31.10.2019 Version number 1910 Revision: 31.10.2019

Trade name: MANNOL Tar Remover 5L

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingre	dients with limit values that require monitoring at the workplace:
108-8	8-3 toluene (32.0%)
WEL	Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm Sk
67-63	-0 propan-2-ol (14.0%)
WEL	Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm
75-09	-2 dichloromethane (9.0%)
WEL	Short-term value: 706 mg/m³, 200 ppm Long-term value: 353 mg/m³, 100 ppm BMGV, Sk
111-7	6-2 2-butoxyethanol (9.0%)
WEL	Short-term value: 246 mg/m³, 50 ppm Long-term value: 123 mg/m³, 25 ppm Sk, BMGV

· Ingredients with biological limit values:

75-09-2 dichloromethane (9.0%)

BMGV 30 ppm

Medium: end-tidal breath Sampling time: post shift Parameter: carbon monoxide

111-76-2 2-butoxyethanol (9.0%)

BMGV 240 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: butoxyacetic acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 6)



Printing date 31.10.2019 Version number 1910 Revision: 31.10.2019

Trade name: MANNOL Tar Remover 5L

· Protection of hands:





Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Safety glasses

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:
Colour:
Transparent
Characteristic
Odour threshold:
Not determined.

PH-value:
Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 34 °C

· Flash point: -18 °C

· Flammability (solid, gas): Not applicable.

Decomposition temperature: Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

• **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 7)



Printing date 31.10.2019 Version number 1910 Revision: 31.10.2019

Trade name: MANNOL Tar Remover 5L

		(Contd. of page
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapour pressure:	Not determined.	
Density at 20 °C:	0.838 g/cm ³	
Relative density	Not determined.	
· Vapour density	Not determined.	
Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	37–64 %	
VOC (EC)	37–64 %	
Solids content:	0.0 %	
9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Carbon monoxide

Aldehyde

Poisonous gases/vapours

Carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	LD/LC50 values relevant for classification:		
ATE (Acu	te Toxicity	/ Estimates)	
Oral	LD50	2,519–5,208 mg/kg	
Dermal	LD50	2,839–6,111 mg/kg	
Inhalative	LC50/4 h	122–275 mg/l	

(Contd. on page 8)



Printing date 31.10.2019 Version number 1910 Revision: 31.10.2019

Trade name: MANNOL Tar Remover 5L

(Contd. of page 7)

108-88-3 t	oluene		
Oral	LD50	5,000 mg/kg (rat)	
Dermal	LD50	12,124 mg/kg (rabbit)	
Inhalative	LC50/4 h	5,320 mg/l (mouse)	
67-63-0 pi	ropan-2-o		
Oral	LD50	5,045 mg/kg (rat)	
Dermal	LD50	12,800 mg/kg (rabbit)	
Inhalative	LC50/4 h	30 mg/l (rat)	
75-09-2 di	75-09-2 dichloromethane		
Oral	LD50	1,600 mg/kg (rat)	
Inhalative	LC50/4 h	88 mg/l (rat)	
111-76-2 2	111-76-2 2-butoxyethanol		
Oral	LD50	1,480 mg/kg (rat)	
Dermal	LD50	400 mg/kg (rab)	

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity
- Suspected of causing cancer.
- Reproductive toxicity
- Suspected of damaging the unborn child.
- · STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.

(Contd. on page 9)



Printing date 31.10.2019 Version number 1910 Revision: 31.10.2019

Trade name: MANNOL Tar Remover 5L

(Contd. of page 8)

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Europ	pean waste catalogue
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP6	Acute Toxicity
HP7	Carcinogenic
HP10	Toxic for reproduction

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number	
ADR, IMDG, IATA	UN1993
14.2 UN proper shipping name	
ADR	1993 FLAMMABLE LIQUID, N.O.S. (TOLUEN ISOPROPANOL (ISOPROPYL ALCOHOL))
· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (TOLUEN ISOPROPANOL (ISOPROPYL ALCOHOL))
· 14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
· ADR, IMDG, IATA	3 Flammable liquids.
	3 Flammable liquids. 3
Class	• • • • • • • • • • • • • • • • • • •
· Class · Label	• • • • • • • • • • • • • • • • • • •
Class Label 14.4 Packing group	• • • • • • • • • • • • • • • • • • •
Class Label 14.4 Packing group ADR, IMDG, IATA	3 I
Class Label 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards:	I Not applicable.
Class Label 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: 14.6 Special precautions for user	I Not applicable. Warning: Flammable liquids.



Printing date 31.10.2019 Version number 1910 Revision: 31.10.2019

Trade name: MANNOL Tar Remover 5L

	(Contd. of page
· 14.7 Transport in bulk according to Ann Marpol and the IBC Code	ex II of Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	0
· Excepted quantities (EQ)	Code: E3
, ,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 300 ml
· Transport category	1
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	0
Excepted quantities (EQ)	Code: E3
, ,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 300 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (TOLUENI
S	ISOPROPANOL (ISOPROPYL ALCOHOL)), 3, I

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5a FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 10 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48, 59
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H361d Suspected of damaging the unborn child.

(Contd. on page 11)



Printing date 31.10.2019 Version number 1910 Revision: 31.10.2019

Trade name: MANNOL Tar Remover 5L

(Contd. of page 10)

H373 May cause damage to organs through prolonged or repeated exposure.

· **Department issuing SDS:** Product safety department.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 1: Flammable liquids - Category 1

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Carc. 2: Carcinogenicity - Category 2

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

* Data compared to the previous version altered.