

SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier Trade name or designation of the mixture	MASTER ECO V 0W-20	
Registration number	-	
Synonyms	None.	
Product code	RP_0004D	
1.2. Relevant identified uses of the	ne substance or mixture and uses advised against	
Identified uses	Automotive applications.	
Uses advised against	All other uses.	
1.3. Details of the supplier of the safety data sheet		
Company name	REPSOL LUBRICANTES Y ESPECIALIDADES, S.A.	
Address	Méndez Álvaro, 44 28045 - MADRID, Spain	
Telephone	+34 917538000 /+34 917538100	
Fax	+34 902303145	
Email address	FDSRLESA@repsol.com	
1.4. Emergency telephone numb	er	

 Carechem 24
 +34 91 114 2520 / +44 1235 239670

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

This mixture does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Laber according to Regulation (LOJ NO. 1272/2000 as amended
Hazard pictograms	None.
Signal word	None.
Hazard statements	The mixture does not meet the criteria for classification.
Precautionary statements	
Prevention	Not assigned.
Response	Not assigned.
Storage	Not assigned.
Disposal	Not assigned.
Supplemental information on the label	EUH208 - Contains C14-16-18 Alkyl phenol. May produce an allergic reaction. EUH210 - Safety data sheet available on request.
2.3. Other hazards	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Please refer to Sections 5, 6 and 7 of this SDS for information on other hazards, different from classification hazards but which may contribute to the overall hazards of the product.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Distillates (petroleum), hydrotreated heavy paraffinic	50 - 60	64742-54-7 265-157-1	01-2119484627-25-XXXX	649-467-00-8	
Classification:	Asp. Tox.	1;H304			L

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 2,2 - 3,7 72623-86-0 276-737-9 01-2119474878-16-XXXX 649-482-00-X Classification: Asp. Tox. 1;H304 L Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based 2,2 - 3,7 72623-87-1 276-738-4 01-2119474889-13-XXXX 649-483-00-5 Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based 2,2 - 3,7 72623-87-1 276-738-4 01-2119474889-13-XXXX 649-483-00-5 Classification: Asp. Tox. 1;H304 L L L L L Bis(nonylphenyl)amine 1,3 - 2,7 36878-20-3 253-249-4 01-2119488911-28-XXXX - Classification: Aquatic Chronic 4;H413 Distillates (petroleum), 0,1 - 1,4 64742-65-0 265-169-7 01-2119471299-27-XXXX 649-474-00-6 Classification: Asp. Tox. 1;H304 L
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based 2,2 - 3,7 72623-87-1 276-738-4 01-2119474889-13-XXXX 649-483-00-5 Classification: Asp. Tox. 1;H304 L Bis(nonylphenyl)amine 1,3 - 2,7 36878-20-3 253-249-4 01-2119488911-28-XXXX - Classification: Aquatic Chronic 4;H413 01-2119471299-27-XXXX 649-474-00-6 - Distillates (petroleum), solvent-dewaxed heavy paraffinic 0,1 - 1,4 64742-65-0 265-169-7 01-2119471299-27-XXXX 649-474-00-6 Distillates (petroleum), solvent-dewaxed heavy paraffinic 0,1 - 1,4 64742-65-0 265-169-7 01-2119480132-48-XXXX 649-469-00-9 Distillates (petroleum), 0,1 - 1,4 0,1 - 1,4 64742-56-9 01-2119480132-48-XXXX 649-469-00-9
hydrotreated neutral oil-based 276-738-4 Classification: Asp. Tox. 1;H304 L Bis(nonylphenyl)amine 1,3 - 2,7 36878-20-3 01-2119488911-28-XXXX - Classification: Aquatic Chronic 4;H413 Classification: Aquatic Chronic 4;H413 01-2119471299-27-XXXX 649-474-00-6 Distillates (petroleum), solvent-dewaxed heavy paraffinic 0,1 - 1,4 64742-65-0 01-2119471299-27-XXXX 649-474-00-6 Classification: Asp. Tox. 1;H304 L Distillates (petroleum), 0,1 - 1,4 64742-56-9 01-2119480132-48-XXXX 649-469-00-9
Bis(nonylphenyl)amine 1,3 - 2,7 36878-20-3 253-249-4 01-2119488911-28-XXXX - Classification: Aquatic Chronic 4;H413 01-2119471299-27-XXXX 649-474-00-6 Distillates (petroleum), solvent-dewaxed heavy paraffinic 0,1 - 1,4 64742-65-0 265-169-7 01-2119471299-27-XXXX 649-474-00-6 Classification: Asp. Tox. 1;H304 L Distillates (petroleum), solvent-dewaxed heavy paraffinic 0,1 - 1,4 64742-56-9 01-2119480132-48-XXXX 649-469-00-9
253-249-4 Classification: Aquatic Chronic 4;H413 Distillates (petroleum), solvent-dewaxed heavy paraffinic 0,1 - 1,4 64742-65-0 265-169-7 01-2119471299-27-XXXX 649-474-00-6 Classification: Asp. Tox. 1;H304 L Distillates (petroleum), 0,1 - 1,4 0,1 - 1,4 64742-56-9 01-2119480132-48-XXXX 649-469-00-9
Distillates (petroleum), solvent-dewaxed heavy paraffinic 0,1 - 1,4 64742-65-0 265-169-7 01-2119471299-27-XXXX 649-474-00-6 Classification: Asp. Tox. 1;H304 L Distillates (petroleum), 0,1 - 1,4 64742-56-9 01-2119471299-27-XXXX 649-474-00-6
solvent-dewaxed heavy paraffinic 265-169-7 Classification: Asp. Tox. 1;H304 L Distillates (petroleum), 0,1 - 1,4 64742-56-9 01-2119480132-48-XXXX 649-469-00-9
Distillates (petroleum), 0,1 - 1,4 64742-56-9 01-2119480132-48-XXXX 649-469-00-9
Classification: Asp. Tox. 1;H304
Paraffin oils (petroleum), catalytic 0,1 - 1,4 64742-70-7 01-2119487080-42-XXXX 649-477-00-2 dewaxed heavy 265-174-4
Classification: Asp. Tox. 1;H304
C14-16-18 Alkyl phenol < 0,15 1190625-94-5 01-2119498288-19-XXXX - 931-468-2
Classification: Skin Sens. 1B;H317, STOT RE 2;H373
Composition comments IP346 method DMSO extract for base oil substances: <3.0%.
All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are percent by volume. The full text for all H-statements is displayed in section 16. SECTION 4: First aid measures General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to
4.1. Description of first aid measures
Inhalation Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
Ingestion Rinse mouth. Get medical attention if symptoms occur.
 4.2. Most important symptoms Exposure may cause temporary irritation, redness, or discomfort. and effects, both acute and delayed
4.3. Indication of any Treat symptomatically. immediate medical attention and special treatment needed
SECTION 5: Firefighting measures
General fire hazards Will burn if involved in a fire.
5.1. Extinguishing media Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing Do not use water jet as an extinguisher, as this will spread the fire. media
5.2. Special hazards arising from the substance or mixture During fire, gases hazardous to health may be formed such as: Carbon oxides. Nitrogen Oxide Zinc oxides. Phosphorus oxides.
5.3. Advice for firefighters Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Special fire fightingMove containers from fire area if you can do so without risk.procedures
Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

MASTER ECO V 0W-20

SECTION 6: Accidental release measures

6.1	. Personal precautions, protect	tive equipment and emergency procedures
	For non-emergency personnel	Avoid breathing mist/vapours. Follow standard emergency procedure. Wear appropriate personal protective equipment (See Section 8).
	For emergency responders	Keep unnecessary personnel away. Ensure adequate ventilation. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
6.2	. Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
	. Methods and material for ntainment and cleaning up	The product is immiscible with water and will spread on the water surface.
	Этр	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
		Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
		Never return spills to original containers for re-use.
	. Reference to other ctions	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.
SE	CTION 7: Handling and	storage
	. Precautions for safe ndling	Avoid prolonged exposure. Observe good industrial hygiene practices. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition.

7.2. Conditions for safe Store in tightly closed container. Store away from incompatible materials (see section 10 of the storage, including any SDS). incompatibilities

Automotive applications. 7.3. Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Spain. Occupational Exposure Limits				
Product	Туре	Value	Form	
Oil mist, mineral	STEL	10 mg/m3	Mist.	
	TWA	5 mg/m3	Mist.	
Biological limit values	No biological exposure limits noted f	or the ingredient(s).		
Recommended monitoring	Follow standard monitoring procedures.			

Recommended monitoring

procedures

Derived no effect levels (DNELs)

	General	Population
--	---------	-------------------

Components	Value	Assessment factor	Notes
Bis(nonylphenyl)amine (CAS 36878-20-3)			
Long-term, Systemic, Dermal	2,5 mg/kg bw/day	400	Repeated dose toxicity
Long-term, Systemic, Oral	0,25 mg/kg bw/day	400	Repeated dose toxicity
Distillates (petroleum), hydrotreated heavy part	raffinic (CAS 64742-54-7)		
Short-term, Local, Inhalation	1,19 mg/m3	75	Repeated dose toxicity
Distillates (petroleum), solvent-dewaxed heavy	y paraffinic (CAS 64742-65-0)		
Long-term, Local, Inhalation	1,19 mg/m3		Repeated dose toxicity
zinc bis[o-(6-methylheptyl)] bis[o-(sec-butyl)] b	ois(dithiophosphate) (CAS 938	319-94-4)	
Long-term, Systemic, Dermal	0,29 mg/kg bw/day	240	Repeated dose toxicity
Long-term, Systemic, Inhalation	2,11 mg/m3	60	Repeated dose toxicity
Long-term, Systemic, Oral	0,24 mg/kg bw/day	600	Repeated dose toxicity
<u>Workers</u>			
Components	Value	Assessment factor	Notes
Bis(nonylphenyl)amine (CAS 36878-20-3)			
Long-term, Systemic, Dermal	5 mg/kg bw/day	200	Repeated dose toxicity
C14-16-18 Alkyl phenol (CAS 1190625-94-5)			
Long-term, Systemic, Dermal	0,3 mg/kg	300	Repeated dose toxicity

Long-term, Systemic, Inh		1,17 mg/m3	75	Repeated dose toxicity
Distillates (petroleum), hydrot				
Short-term, Local, Inhalat		5,58 mg/m3	45	Repeated dose toxicity
Distillates (petroleum), solven	-		§5-0)	Dependent days to visity
Long-term, Local, Inhalat		5,58 mg/m3		Repeated dose toxicity
Reaction mass of isomers of:			• • • • •	
Long-term, Local, Derma Long-term, Systemic, De		0,006 mg/cm2 0,22 mg/kg bw/day	72 180	Repeated dose toxicity Repeated dose toxicity
Short-term, Local, Derma		1 mg/cm2	20	Acute toxicity
Short-term, Systemic, De		20 mg/kg	100	Repeated dose toxicity
zinc bis[o-(6-methylheptyl)] bi	s[o-(sec-butyl)] bi	s(dithiophosphate) (CAS	\$ 93819-94-4)	
Long-term, Systemic, De	rmal	0,58 mg/kg bw/day	120	Repeated dose toxicity
Long-term, Systemic, Inh	alation	8,31 mg/m3	30	Repeated dose toxicity
redicted no effect concentration	ons (PNECs)			
Components		Value	Assessment factor	Notes
Bis(nonylphenyl)amine (CAS	36878-20-3)			
Freshwater		0,412 mg/l	10	
Marine water		0,041 mg/l	100	
Sediment (freshwater)		1 mg/kg	100 1000	
Sediment (marine water)	1100625 04 5)	0,1 mg/kg	1000	
C14-16-18 Alkyl phenol (CAS Freshwater	1190020-94-0)	0.1 mg/l	1000	
Freshwater Marine water		0,1 mg/l 0,01 mg/l	1000 10000	
Secondary poisoning		3,3 mg/kg	300	Oral
Sediment (freshwater)		4266,16 mg/kg	500	Orai
Sediment (marine water)		426,62 mg/kg		
Soil		852,58 mg/kg		
STP		100 mg/l	10	
Distillates (petroleum), hydrot	reated heavy para	affinic (CAS 64742-54-7))	
Secondary poisoning		9,33 mg/kg		Oral
Lubricating oils (petroleum), C	20-50, hydrotreat	ed neutral oil-based (C/	AS 72623-87-1)	
Secondary poisoning		9,33 mg/kg	,	Oral
Reaction mass of isomers of:	C7-9-alkvl 3-(3.5-		henvl)propionate (CAS 125	5643-61-0)
Freshwater		0,004 mg/l	1000	
Marine water		0 mg/l	10000	
Secondary poisoning		0,033 mg/kg	90	Oral
Sediment (freshwater)		233 mg/kg		
Sediment (marine water)		23,3 mg/kg		
Soil		189 mg/kg		
STP		10 mg/l	10	
zinc bis[o-(6-methylheptyl)] bi	s[o-(sec-butyl)] bi			
Freshwater		4 µg/l	100	
Intermittent releases		21 µg/l	100	
Marine water		4,6 µg/l	10000	Oral
Secondary poisoning		10,67 mg/kg	300	Oral
Sediment (freshwater) Sediment (marine water)		0,012 mg/kg 0,001 mg/kg		
Soil		0,005 mg/kg		
STP		100 mg/l	100	
2. Exposure controls				
ppropriate engineering	Good general v	entilation should be use	d. Ventilation rates should	be matched to conditions. If
ontrols	applicable, use maintain airborr	process enclosures, loc ne levels below recomm	al exhaust ventilation, or o ended exposure limits. If e	ther engineering controls to xposure limits have not been
dividual protection		intain airborne levels to	-	
dividual protection measures, General information	-			t in each case depends, among
				ons in which it is carried out. To
				e safety officer and/or equipmer
		essary, to make the right	nt choice. In any case, the	equipment must comply with th
	currently applic	able CEN standards. We		it must have received the
	currently applic required training	g in the use of the same		
Eye/face protection	currently applic required training	g in the use of the same		should meet standard EN 166

- Hand protection	Wear appropriate chemical resistant gloves. Always wear chemical-resistant protective gloves that comply with EN 374 to handle this product. Observe good industrial hygiene practices and wash gloves with soap and water before removing them. Assess the working conditions and always consult your glove supplier for information on the most suitable type of glove for each task and the required material, thickness, and breakthrough time specifications. The use of type-B gloves in accordance with EN 374 is recommended as a minimum protection against intermittent or splash contact. Consult your supplier to find the most suitable option for the product in question. The requirements of EN 388 must be taken into account for applications involving mechanical hazards with the risk of abrasion or incision. The requirements outlined in EN 407 must be taken into consideration for tasks involving thermal hazards.
- Other	Wear suitable protective clothing.
Respiratory protection	In case of inadequate ventilation or risk of inhalation of oil mist, suitable respiratory equipment with combination filter (type A2/P2) can be used. Respiratory protection should meet standard EN 14387. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection. Appropriate respirator selection should be made by a qualified professional.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels. Product should not reach the environment through wastewater or sewage. Measures to take in case of accidental release can be found in Section 6 of this SDS.

SECTION 9: Physical and chemical properties

9.1. Information on basic physic	al and chemical properties
Physical state	Liquid.
Form	Liquid.
Colour	2,5 max.
Odour	Characteristic.
Melting point/freezing point	-45 °C (-49 °F)
Boiling point or initial boiling point and boiling range	Property has not been measured.
Flammability	Will burn if involved in a fire.
Lower and upper explosion limit	:
Explosive limit - lower (%)	Property has not been measured.
Explosive limit – upper (%)	Property has not been measured.
Flash point	> 200 °C (> 392 °F)
Auto-ignition temperature	Property has not been measured.
Decomposition temperature	Not applicable as the product is not unstable.
рН	The product is insoluble in water.
Kinematic viscosity	8,1 mm²/s (100 °C (212 °F)) 41 mm²/s (40 °C (104 °F))
Solubility	
Solubility (water)	Insoluble (< 0,1%)
Partition coefficient (n-octanol/water) (log value)	Not applicable, product is a mixture.
Vapour pressure	Property has not been measured.
Density and/or relative density	
Density	0,844 g/cm ³
Relative density	0,844
Vapour density	Property has not been measured.
Particle characteristics	Not applicable, material is a liquid.
9.2. Other information	
9.2.1. Information with regard to physical hazard classes	No relevant additional information available.

9.2.2. Other safety	No relevant additional information available.
characteristics	

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed.
Symptoms	Exposure may cause temporary irritation, redness, or discomfort.

11.1. Information on toxicological effects

Acute toxicity

Product	Species	Test Results
MASTER ECO V 0W-20 (CAS Mi	xture)	
Acute		
Dermal		
ATE		> 5000 mg/kg
Oral		
ATE		> 5000 mg/kg
Components	Species	Test Results
Distillates (petroleum), solvent-de	waxed heavy paraffinic (CAS 64742-65-0)	
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg
Inhalation		
Aerosol	-	
LC50	Rat	> 5,53 mg/l, 4 Hours
Oral	-	"
LD50	Rat	> 5000 mg/kg
	waxed light paraffinic (CAS 64742-56-9)	
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
Aerosol LC50	Rat	
	Rai	2,18 mg/l, 4 Hours
Oral LD50	Rat	5 5000 mg//cg
		> 5000 mg/kg
	30, hydrotreated neutral oil-based (CAS 72623-86-0)	
<u>Acute</u>		
Dermal	Rabbit	> 5000 mg/kg 24 Hours
LD50	Rappil	> 5000 mg/kg, 24 Hours

Components	Species	Test Results
Inhalation		
Aerosol		
LC50	Rat	> 5,53 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Lubricating oils (petroleum), C20-5	50, hydrotreated neutral oil-base	d (CAS 72623-87-1)
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 5000 mg/kg
Inhalation		
Aerosol	Det	F000
LC50	Rat	> 5000 mg/m³, 4 hours
Oral		5000
LD50	Rat	> 5000 mg/kg
Paraffin oils (petroleum), catalytic	dewaxed heavy (CAS 64742-70-	-7)
<u>Acute</u>		
Dermal LD50	Rabbit	> 5000 ma/ka
	RADDI	> 5000 mg/kg
Inhalation LC50	Rat	s 5 mg/L / Hours
	Rai	> 5 mg/l, 4 Hours
Oral	Det	
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation		of data the classification is not possible.
Serious eye damage/eye irritation	Due to partial or complete lack	of data the classification is not possible.
Respiratory sensitisation	Due to partial or complete lack	of data the classification is not possible.
Skin sensitisation	The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals.	
Germ cell mutagenicity	Due to partial or complete lack of data the classification is not possible.	
Carcinogenicity	Due to partial or complete lack of data the classification is not possible.	
IARC Monographs. Overall	Evaluation of Carcinogenicity	
	olvent-dewaxed light paraffinic	3 Not classifiable as to carcinogenicity to humans.
(CAS 64742-56-9)		
Highly refined mineral oil		3 Not classifiable as to carcinogenicity to humans. amount of substance that is suspected of damaging fertility or the
Reproductive toxicity	unborn child.	
Specific target organ toxicity - single exposure	Due to partial or complete lack	of data the classification is not possible.
Specific target organ toxicity - repeated exposure	Due to partial or complete lack	of data the classification is not possible.
Aspiration hazard	Due to partial or complete lack	of data the classification is not possible.
Mixture versus substance information	No information available.	
11.2. Information on other hazar	rds	
Endocrine disrupting properties		components considered to have endocrine disrupting properties 7(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) higher.
Other information		with used oil may cause serious skin diseases. ealth effects of this product are assessed on the basis of the s for classification.
SECTION 12: Ecological in	nformation	
· ·		lassification criteria are not met for hazardous to the aquatic
12.1. Toxicity	environment.	ימסטוויטעוטרו טוונפוומ מיפ ווטג ווופג וטו וומבמוטטעט נט נוופ מעטמונט

Components		Species	Test Results
Distillates (petroleum), hydrotreat	ed heavy parat	ffinic (CAS 64742-54-7)	
Aquatic			
Acute			
Algae	NOEL	Pseudokirchneriella subcapitata	> 100 mg/l, 72 hours
Crustacea	EL50	Daphnia magna	> 1000 mg/l, 48 hours
Fish	LL50	Pimephales promelas	> 100 mg/l, 96 hours
Lubricating oils (petroleum), C15-	30, hydrotreate	ed neutral oil-based (CAS 72623-86-0)	
Aquatic			
Acute			
Algae	NOEL	Pseudokirchneriella subcapitata	> 100 mg/l, 72 hours
Crustacea	EL50	Daphnia magna	> 10000 mg/l, 48 hours
Fish	LL50	Pimephales promelas	> 100 mg/l, 96 hours
12.2. Persistence and degradability	No data is available on the degradability of this product.		
12.3. Bioaccumulative potential	No data ava	ailable.	
Partition coefficient n-octanol/water (log Kow)	Not availabl	е.	
Bioconcentration factor (BCF)	Not availabl	e.	
12.4. Mobility in soil	No data ava	ailable.	
12.5. Results of PBT and vPvB assessment	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.		
12.6. Endocrine disrupting properties	The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.		
12.7. Other adverse effects	Oil spills are generally hazardous to the environment.		
SECTION 13: Disposal co	nsideratior	IS	
13.1. Waste treatment methods			
Residual waste	Dispose of i	n accordance with local regulations. Emp	ty containers or liners may retain some

Residual wasteDispose of in accordance with local regulations. Empty containers or liners may re product residues. This material and its container must be disposed of in a safe ma Disposal instructions).	
Contaminated packaging Since emptied containers may retain product residue, follow label warnings even a emptied. Empty containers should be taken to an approved waste handling site for disposal.	
EU waste code The Waste code should be assigned in discussion between the user, the producer disposal company.	and the waste
Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site	
Special precautions Dispose in accordance with all applicable regulations.	

SECTION 14: Transport information

ADR

ADIN	
14.1. UN number	Not regulated as dangerous goods.
14.2. UN proper shipping	Not regulated as dangerous goods.
name	
14.3. Transport hazard class	(es)
Class	Not assigned.
Subsidiary risk	-
Hazard No. (ADR)	Not assigned.
Tunnel restriction code	Not assigned.
14.4. Packing group	Not assigned.
14.5. Environmental hazards	No.
14.6. Special precautions	Not assigned.
for user	
RID	
14.1. UN number	Not regulated as dangerous goods.
14.2. UN proper shipping	Not regulated as dangerous goods.
name	
14.3. Transport hazard class	(es)
Class	Not assigned.
Subsidiary risk	-
MASTER ECO V 0W-20	

14.4. Packing group	Not assigned.
14.5. Environmental hazards	No.
14.6. Special precautions	Not assigned.
for user	
ADN	
14.1. UN number	Not regulated as dangerous goods.
14.2. UN proper shipping	Not regulated as dangerous goods.
name	
14.3. Transport hazard class((es)
Class	Not assigned.
Subsidiary risk	-
14.4. Packing group	Not assigned.
14.5. Environmental hazards	No.
14.6. Special precautions	Not assigned.
for user	
ΙΑΤΑ	
14.1. UN number	Not regulated as dangerous goods.
14.2. UN proper shipping	Not regulated as dangerous goods.
name	
14.3. Transport hazard class(es)
Class	Not assigned.
Subsidiary risk	-
14.4. Packing group	Not assigned.
14.5. Environmental hazards	-
14.6. Special precautions	Not assigned.
for user	C C
IMDG	
14.1. UN number	Not regulated as dangerous goods.
14.2. UN proper shipping	Not regulated as dangerous goods.
name	0 0 0
14.3. Transport hazard class(es)
Class	Not assigned.
Subsidiary risk	-
14.4. Packing group	Not assigned.
14.5. Environmental hazards	5
Marine pollutant	No.
EmS	Not assigned.
14.6. Special precautions	Not assigned.
for user	
14.7. Maritime transport in bulk	Not applicable.

according to IMO instruments

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorisation, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9) Paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9) Paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)

Other EU regulations

Directive 2012/18/EU on	major accident hazards involving dangerous substances, as amended
Not listed.	
Other regulations	The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.
National regulations	Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.
15.2. Chemical safety assessment	No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations	
	ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.
	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
	ATE: Acute toxicity estimate.
	CAS: Chemical Abstract Service.
	CEN: European Committee for Standardization.
	EL50: Effective level, 50%.
	IATA: International Air Transport Association.
	IMDG: International Maritime Dangerous Goods.
	IMO: International Maritime Organization.
	LC50: Lethal Concentration, 50%.
	LD50: Lethal Dose, 50%.
	LL50: Lethal level, 50%.
	NOEL: No Observed Effect Level.
	PBT: Persistent, bioaccumulative and toxic.
	RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.
	TWA: Time Weighted Average.
	vPvB: Very persistent and very bioaccumulative.
References	ECHA CHEM
	HSDB® - Hazardous Substances Data Bank
	IARC Monographs. Overall Evaluation of Carcinogenicity
Information on evaluation	The classification for health and environmental hazards is derived by a combination of calculation
method leading to the	methods and test data, if available.
classification of mixture	
Full text of any H-statements not written out in full under	
Sections 2 to 15	H304 May be fatal if swallowed and enters airways.
	H317 May cause an allergic skin reaction.
	H373 May cause damage to organs through prolonged or repeated exposure.
	H413 May cause long lasting harmful effects to aquatic life.
Training information	Follow training instructions when handling this material.

This Safety Data Sheet (SDS) refers exclusively to the substance/product specified in section 1 of this document.

The information provided in this SDS has been obtained according to the best information available on the basis of technical data that is considered reliable at the time of its preparation, and in accordance with the legal requirements in force concerning classification, packaging and labelling of dangerous substances, not involving the granting of any express or implied warranty or on the accuracy of the information contained therein or concerning its suitability for a particular use or specification.

The purchaser as the recipient of the substance/product specified in section 1 of this document to which this Safety Data Sheet (SDS) refers, is responsible for evaluating the information contained in the SDS, and for verifying that it is correct and appropriate for the intended use of the substance/product specified in section 1 of this document.

The purchaser, as the recipient of the substance/product specified in section 1 of this document referred to in this Safety Data Sheet (SDS) is also responsible for adequately managing the risks thereof in its place of work. Consequently, the purchaser is obliged, regarding its workers and representatives, as well as any other person who may handle, use or be exposed to the substance/product specified in section 1 of this document in their place of work to (i) facilitate access to the relevant information in this Safety Data Sheet (SDS), transmitting for this purpose the relevant indications included in the SDS, especially those relating to the risks of the product/substance specified in section 1 of this document for the safety and health of persons and for the environment. As well as (ii) ensuring that they receive and have adequate training in handling, using or being exposed to the product/substance specified in section 1 of this SDS.

Accordingly, no liability for damages to the recipient of the SDS arising out of the use of the information or the use of the substance/product specified in section 1 of this document shall be accepted.