

SAFETY DATA SHEET PROTECTON COLOUR RESTORER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name PROTECTON COLOUR RESTORER

Product number PRR500, PWP500

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Car maintenance product.

1.3. Details of the supplier of the safety data sheet

Supplier TETROSYL LIMITED

Bury Lancashire England BL9 7NY 0161 764 5981 0161 797 5899 info@tetrosyl.com

Manufacturer TETROSYL LIMITED

Bury Lancashire England BL9 7NY 0161 764 5981 0161 797 5899 info@tetrosyl.com

1.4. Emergency telephone number

Emergency telephone +44 (0)161 764 5981

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Hazard statements EUH208 Contains 2-METHYLISOTHIAZOL-3(2H)-ONE. May produce an allergic reaction.

Precautionary statements P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Detergent labelling 5 - < 15% aliphatic hydrocarbons, < 5% non-ionic surfactants, < 5% polycarboxylates,

Contains BENZISOTHIAZOLINONE, METHYLISOTHIAZOLINONE

PROTECTON COLOUR RESTORER

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Kerosine - unspecified 3-<5.0%

CAS number: 64742-47-8 EC number: 265-149-8 REACH registration number: 01-

2119484819-18-0001

Classification

Asp. Tox. 1 - H304

HYDROCARBONS, C9 - C11, n-ALKANES, ISOALKANES,

3-<5.0%

CYCLICS, <2% AROMATICS

CAS number: — EC number: 919-857-5 REACH registration number: 01-

2119463258-33-XXXX

Classification

Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304

ETHANEDIOL 3-<5.0%

CAS number: 107-21-1 EC number: 203-473-3 REACH registration number: 01-

2119456816-28-0000

Classification

Acute Tox. 4 - H302 STOT RE 2 - H373

Technical White Mineral Oil

CAS number: 8042-47-5 EC number: 232-455-8 REACH registration number: 01-

2119487078-27-0000

Classification

Asp. Tox. 1 - H304

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention if any discomfort continues. Move affected person to fresh air and keep

warm and at rest in a position comfortable for breathing. Effects may be delayed. Keep

affected person under observation.

Inhalation Remove affected person from source of contamination. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Get medical attention if any

discomfort continues.

Ingestion Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if a

large quantity has been ingested. Show this Safety Data Sheet to the medical personnel.

PROTECTON COLOUR RESTORER

Skin contact Rinse immediately with plenty of water. Remove contaminated clothing. Get medical attention

if any discomfort continues.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Do not rub eye. Get medical attention if any

discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure. Effects may be delayed. Keep affected person under observation.

Inhalation Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion May cause discomfort if swallowed. May cause stomach pain or vomiting.

Skin contact Prolonged contact may cause redness, irritation and dry skin.

Eye contact May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam, carbon dioxide or dry powder. Water. Use fire-

extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Not relevant. No unusual fire or explosion hazards noted.

Hazardous combustion

products

No known hazardous decomposition products.

5.3. Advice for firefighters

Protective actions during

firefighting

No specific firefighting precautions known.

Special protective equipment

for firefighters

Leave danger zone immediately.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8. In case of spills, beware of slippery floors and

surfaces.

6.2. Environmental precautions

Environmental precautions Avoid discharge to the aquatic environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up No specific clean-up procedure recommended.

6.4. Reference to other sections

Reference to other sections Collect and dispose of spillage as indicated in Section 13. For personal protection, see

Section 8.

SECTION 7: Handling and storage

PROTECTON COLOUR RESTORER

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Good personal hygiene procedures should

be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Avoid contact with eyes. Avoid eating, drinking and

smoking when using the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep containers upright. Store in tightly-closed, original container.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

No exposure limits known for ingredient(s).

Kerosine - unspecified

Long-term exposure limit (8-hour TWA): WEL 1000 mg/m³

Short-term exposure limit (15-minute): WEL

ETHANEDIOL

Long-term exposure limit (8-hour TWA): WEL 20 ppm 52 mg/m³ vapour Short-term exposure limit (15-minute): WEL 40 ppm 104 mg/m³ vapour

Sk

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ particulate

Sk

PARAFFIN WAX

Long-term exposure limit (8-hour TWA): WEL 2 mg/m³ fume Short-term exposure limit (15-minute): WEL 6 mg/m³ fume

2,2'-OXYBISETHANOL

Long-term exposure limit (8-hour TWA): WEL 23 ppm 101 mg/m³

WEL = Workplace Exposure Limit Sk = Can be absorbed through the skin.

8.2. Exposure controls

Protective equipment







Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.

Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

PROTECTON COLOUR RESTORER

Hygiene measures Provide eyewash station. Use appropriate skin cream to prevent drying of skin. When using

do not eat, drink or smoke.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Beige.

Odour Characteristic.

Odour threshold Not determined. Scientifically unjustified. Not determined. Scientifically unjustified.

pH pH (concentrated solution): 8.5

Melting point Not determined. Scientifically unjustified.

Initial boiling point and range >100°C @

Flash point >61°C

Evaporation rate Not determined. Scientifically unjustified.

Upper/lower flammability or

explosive limits

Scientifically unjustified. Not determined.

Vapour pressure Not determined.

Vapour density Not determined.

Relative density 1.100-1.130 @ 20°C

Solubility(ies) Miscible with water.

Partition coefficient Not determined. Scientifically unjustified.

Auto-ignition temperature Not determined. Scientifically unjustified.

Decomposition Temperature Not determined. Scientifically unjustified.

Viscosity 3250 cP @ 20°C

Oxidising properties Not determined.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability No particular stability concerns.

10.3. Possibility of hazardous reactions

Possibility of hazardous

Not applicable.

reactions

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

PROTECTON COLOUR RESTORER

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition

Does not decompose when used and stored as recommended.

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 16,666.67

SECTION 12: Ecological information

EcotoxicityThe product contains a substance which is harmful to aquatic organisms and which may

cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Acute aquatic toxicity
Acute toxicity - fish

LC₅o, 96 hours: 2-5 (DISTILLATES (PETROLEUM) HYDROTREATED LIGHT) mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 1.4 (DISTILLATES (PETROLEUM) HYDROTREATED LIGHT) mg/l, Daphnia

magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: 1-3 (DISTILLATES (PETROLEUM) HYDROTREATED LIGHT) mg/l, Algae

12.2. Persistence and degradability

Persistence and degradability The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined. Scientifically unjustified.

12.4. Mobility in soil

Mobility The product is insoluble in water and will spread on the water surface.

Adsorption/desorption

coefficient

Not available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site

in accordance with the requirements of the local Waste Disposal Authority.

PROTECTON COLOUR RESTORER

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority. Confirm disposal procedures with environmental engineer and

local regulations.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

Transport labels

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Issued by Health & Safety Department

Revision date 20/11/2019

Revision 1

PROTECTON COLOUR RESTORER

SDS number 33483

SDS status Approved.

Hazard statements in full H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs (Kidneys) through prolonged or repeated exposure.

EUH208 Contains . May produce an allergic reaction.