

Page 1/9

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.10.2020

GHS02

Version number 14

Revision: 09.01.2017

 1.1 Product identifier Trade name: <u>PROTECTON® PENETRATING OIL 400 ML</u>. Article number: SER9702-1890702 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. Sector of Use SU21 Consumer uses: Private households / general public / consumers SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Product category PC24 Lubricants, greases, release products Process category PROCT Industrial spraying PROCT IN on industrial spraying Application of the substance / the mixture Screw loosing agent 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: MOTIP DUPLI B.V. Wolfraamweg 2 NL- 8471 XC Wolvega The Netherlands Tel: +31 (0)561 694401 Fax: +31 (0)561 694401 Fax: +31 (0)561 694401 Fax: +31 (0)561 694401 Further information obtainable from: Department Product Safety 1.4 Emergency telephone number: +31 (0)561 -694400 (09:00h - 17:00h) UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111 SECTION 2: Hazards identification Scipcation according to Regulation (EC) No 1272/2008 GHS02 flame Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heatead Aquatic Chronic 3 H412 Harnful to aquatic life with long lasting effects. 	SECTION 1: Identificat	ion of the substance/mixture and of the company/undertaking
Article number: SER9702-1890702 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. Sector of Use SU21 Consumer uses: Private households / general public / consumers SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Product category PC24 Lubricants, greases, release products Process category PROC1 Industrial spraying PROC1 Industrial spraying PROC1 Industrial spraying Application of the substance / the mixture Screw loosing agent 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: MOTIP DUPLI B.V. Wolfraamweg 2 NL- 8471 XC Wolvega The Netherlands The Netherlands The Netherlands The Netherlands The Netherlands The Netherlands The Netherlands Further information obtainable from: Department Product Safety 1.4 Emergency telephone number: +31 (0)561 694400 Fax: +31 (0)561 694400 (09:00h - 17:00h) UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111 SECTION 2: Hazards identification 2.1 Classification of the substance or mixture Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.	1.1 Product identifier	
1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. Sector of Use SU21 Consumer uses: Private households / general public / consumers SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Product category PC24 Lubricants, greases, release products Process category PROC7 Industrial spraying PROC11 Non industrial spraying Application of the substance / the mixture Screw loosing agent 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: MOTIP DUPLI B.V. Wolfraamweg 2 NL- 8471 XC Wolvega The Netherlands Tel: +31 (0)561 694400 Fax: +31 (0)561 694411 e-mail: msds@nl.motipdupli.com Further information obtainable from: Department Product Safety 1.4 Emergency telephone number: +31 (0)561 694400 (09:00h - 17:00h) UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111 SECTION 2: Hazards identification 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 Of GHS02 flame Aerosol 1	Trade name: <u>PROTECTON</u>	DPENETRATING OIL 400 ML
Manufacturer/Supplier: MOTIP DUPLI B.V. Wolfraamweg 2 NL- 8471 XC Wolvega The Netherlands Tel: +31 (0)561 694400 Fax: +31 (0)561 694411 e-mail: msds@nl.motipdupli.comFurther information obtainable from: Department Product Safety 1.4 Emergency telephone number: $+31 (0)561-694400 (09:00h - 17:00h)$ UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111SECTION 2: Hazards identification2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 \widetilde{V} Aerosol 1H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated Aquatic Chronic 3 H412Harmful to aquatic life with long lasting effects.	1.2 Relevant identified uses of No further relevant information Sector of Use SU21 Consumer uses: Privat SU22 Professional uses: Public Product category PC24 Lub Process category PROC7 Industrial spraying PROC11 Non industrial spray	f the substance or mixture and uses advised against on available. te households / general public / consumers blic domain (administration, education, entertainment, services, craftsmen) ricants, greases, release products aying
1.4 Emergency telephone number: +31 (0)561-694400 (09:00h - 17:00h) UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111 SECTION 2: Hazards identification 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 Image: GHS02 flame Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated Aquatic Chronic 3 H412	Manufacturer/Supplier: MOTIP DUPLI B.V. Wolfraamweg 2 NL- 8471 XC Wolvega The Netherlands Tel: +31 (0)561 694400 Fax: +31 (0)561 694411	
SECTION 2: Hazards identification 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 Image: Container of the substance or mixture Classification according to Regulation (EC) No 1272/2008 Image: Container of the substance or mixture Classification according to Regulation (EC) No 1272/2008 Image: Container of the substance of the	1.4 Emergency telephone nu	mber:
2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 GHS02 flame Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.	UK: NPIS National Poisons I	nformation Centre Tel: +44 0344 892 0111
2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 GHS02 flame Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.	SECTION 2. Hazards i	Instification
Classification according to Regulation (EC) No 1272/2008 GHS02 flame Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.		
Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.		
Aquatic Chronic 3 H412Harmful to aquatic life with long lasting effects.	A V	
	Aerosol 1 H222-H22	29 Extremely flammable aerosol. Pressurised container: May burst if heated.
2.2.1 shel alamanta	Aquatic Chronic 3 H412	Harmful to aquatic life with long lasting effects.
2.2 Label elements • Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. • Hazard pictograms	The product is classified and	

Page 2/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.10.2020

Version number 14

Revision: 09.01.2017

Trade name: PROTECTON® PENETRATING OIL 400 ML

<i></i>	(Contd. of page 1)
	p ord Danger
\cdot Hazard	statements
Н222-Н	229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H412	Harmful to aquatic life with long lasting effects.
• Precauti	onary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.
P410+P	412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents / container in accordance with regional regulations.
· Addition	al information:
	6 Repeated exposure may cause skin dryness or cracking.
	Contains Benzenesulfonic acid, di-C10-14-alkylderivs., calcium salts. May produce an allergic
	reaction.
Buildup	of explosive mixtures possible without sufficient ventilation.
-	r hazards
	of PBT and vPvB assessment
	of applicable.

· vPvB: Not applicable.

*

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
EC number: 918-481-9 Reg.nr.: 01-2119457273-39	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics Asp. Tox. 1, H304	- 20-<25%
CAS: 64742-55-8 EINECS: 265-158-7 Index number: 649-468-00-3 Reg.nr.: 01-2119487077-29	Distillates (petroleum), hydrotreated light paraffinic 🚯 Asp. Tox. 1, H304	_ 12.5-<20%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane	12.5-<20%
CAS: 109-66-0 EINECS: 203-692-4 Index number: 601-006-00-1 Reg.nr.: 01-2119459286-30	pentane Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336	_ 12.5-<20%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	_ 10-<12.5%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	_ 10-<12.5%
EC number: 939-603-7 Reg.nr.: 01-2119978241-36	Benzenesulfonic acid, di-C10-14-alkylderivs., calcium salts 🗘 Skin Sens. 1B, H317	<i>_</i> ≤ 0.5%

GB

Page 3/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.10.2020

Version number 14

Revision: 09.01.2017

Trade name: PROTECTON® PENETRATING OIL 400 ML

• Additional information: For the wording of the listed hazard phrases refer to section 16.

(Contd. of page 2)

SECTION 4: First aid measures

• 4.1 Description of first aid measures

· After inhalation: Supply fresh air; consult doctor in case of complaints.

• After skin contact: Generally the product does not irritate the skin.

• After eye contact: Rinse opened eye for several minutes under running water.

• After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- \cdot 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -
- Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources. Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. No special measures required.

• Information about fire - and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

• Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Keep container tightly sealed.

(Contd. on page 4)

GB

Page 4/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.10.2020

Version number 14

Revision: 09.01.2017

(Contd. of page 3)

Trade name: PROTECTON® PENETRATING OIL 400 ML

- Storage class: 2 B
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

109-66-0 pentane

WEL Long-term value: 1800 mg/m³, 600 ppm

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols.
- · Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

- · Protection of hands: Not required.
- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- Eye protection: Not required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical a General Information		
Appearance:		
Form:	Aerosol	
Colour:	Light brown	
Odour:	Aromatic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling r	ange: Not applicable, as aerosol.	
Flash point:	Not applicable, as aerosol.	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	285 °C (545 °F)	
Decomposition temperature:	Not determined.	
Explosive properties:	Not determined.	

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.10.2020

Version number 14

Revision: 09.01.2017

Trade name: PROTECTON® PENETRATING OIL 400 ML

	(Contd. of page 4)
· Explosion limits:	
<i>Lower:</i>	0.6 Vol %
Upper:	10.9 Vol %
· Vapour pressure at 20 °C (68 °F):	3500 hPa (2625.2 mm Hg)
• Density at 20 •C (68 •F):	0.7 g/cm ³ (5.8 lbs/gal)
Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	77.8 %
VOC (EC)	
	515.3 g/l
· VOC-EU%	77.84 %
· Solids content:	0.6 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

*

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rab)
Inhalative	LC50/4 h	>4951 mg/m3 (rat)
109-66-0 pentane		
Oral	LD50	>5000 mg/kg (rat)
T T T	1050 / 11	

Inhalative LC50/4h 25.3 mg/l (rat)

· Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

• Serious eye damage/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

 \cdot Germ cell mutagenicity Based on available data, the classification criteria are not met.

(Contd. on page 6)

Page 6/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.10.2020

Version number 14

Revision: 09.01.2017

(Contd. of page 5)

Trade name: PROTECTON® PENETRATING OIL 400 ML

- · Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- · STOT-single exposure Based on available data, the classification criteria are not met.
- $\cdot \textit{STOT-repeated exposure Based on available data, the classification criteria are not met.}$
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity:

109-66-0 pentane

EC50 / 48 h 9.7 mg/l (daphnia magna)

EC50/96 h 4.26 mg/l (fish)

LC50 / 96 h 4.26 mg/l (fish)

· 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground. Harmful to aquatic organisms

· 12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

20 01 13* solvents

15 01 04 metallic packaging

· Uncleaned packaging:

· Recommendation:

Disposal must be made according to official regulations. Disposal must be made according to official regulations.

14.1 UN-Number		
ADR, IMDG, IATA	UN1950	
14.2 UN proper shipping name		
ADR	1950 AEROSOLS	
·IMDG	AEROSOLS	
· IATA	AEROSOLS, flammable	

Page 7/9

· Label

· UN "Model Regulation":

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.10.2020

Version number 14

Revision: 09.01.2017

(Contd. of page 6)

Trade name: PROTECTON® PENETRATING OIL 400 ML · 14.3 Transport hazard class(es) $\cdot ADR$ · Class 2 5F Gases. · Label 2.1 · IMDG, IATA 2.1 · Class

· 14.4 Packing group · ADR, IMDG, IATA not regulated · 14.5 Environmental hazards: Not applicable. · 14.6 Special precautions for user Warning: Gases. · Hazard identification number (Kemler code): · EMS Number: F-D, S-USW1 Protected from sources of heat. · Stowage Code SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. · Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: ·ADR · Limited quantities (LQ) lLCode: E0 · Excepted quantities (EQ) Not permitted as Excepted Quantity · Transport category 2 D · Tunnel restriction code · IMDG · Limited quantities (LQ) lL• Excepted quantities (EQ) Code: E0

2.1

Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity UN 1950 AEROSOLS, 2.1

(Contd. on page 8)

GB

Page 8/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.10.2020

Version number 14

Revision: 09.01.2017

Trade name: PROTECTON® PENETRATING OIL 400 ML

(Contd. of page 7)

SECTION 15: Regulatory information

- \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

· National regulations:

- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57
- None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
Department issuing SDS: R&D legislation and regulatory advisor

- Contact: msds@nl.motipdupli.com
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organisation ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO) ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols - Category 1 Press. Gas (Comp.): Gases under pressure – Compressed gas Flam. Liq. 2: Flammable liquids – Category 2 Skin Sens. 1B: Skin sensitisation - Category 1B STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard - Category 1

(Contd. on page 9)

⁻ GB

Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.10.2020

Version number 14

Revision: 09.01.2017

Trade name: PROTECTON® PENETRATING OIL 400 ML

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 • * **Data compared to the previous version altered.** (Contd. of page 8)

GB