

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 28.09.2021

Version number 3.5

Revision: 28.09.2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Trade name:** Bremssattellack (A)

**Article number:** 2160-65, 2168-70, 2172, 2175-76, 2178

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Sector of Use** SU21 Consumer uses: Private households / general public / consumers

**Application of the substance / the mixture** Paint

#### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/Supplier:**

FOLIATEC Böhm GmbH & Co. Vertriebs KG

Neumeyerstraße 70

D-90411 Nürnberg

**Further information obtainable from:**

Abteilung Produkttechnik

techsupport@foliatec.de

#### 1.4 Emergency telephone number:

+49 - 91 19 75 44 - 0

(Montag bis Freitag, 08:00 - 17:00 Uhr)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

#### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

GHS label elements

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**



GHS02 GHS07

**Signal word** Warning

**Hazard-determining components of labelling:**

bis[4-(2,3-epoxypropoxy)phenyl]propane

n-butyl acetate

Hexandioldiglycidylether

**Hazard statements**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 28.09.2021

Version number 3.5

Revision: 28.09.2021

**Trade name: Bremssattellack (A)**

(Contd. of page 1)

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

**Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**2.3 Other hazards****Results of PBT and vPvB assessment** Not applicable.**PBT:** Not applicable.**vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

**3.2 Chemical characterisation: Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate ☠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	25-75%
CAS: 1675-54-3 EINECS: 216-823-5	bis[4-(2,3-epoxypropoxy)phenyl]propane ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥5-<25%
CAS: 1330-20-7 EINECS: 215-535-7	xylene ☠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	≥0-<10%
CAS: 111-76-2 EINECS: 203-905-0 Reg.nr.: 01-2119475108-36	2-butoxyethanol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	<3%
CAS: 16096-31-4 EINECS: 240-260-4 Reg.nr.: 01-2119463471-41	Hexandioldiglycidylether ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥1-<2.5%
CAS: 100-41-4 EINECS: 202-849-4	ethylbenzene ☠ Flam. Liq. 2, H225; ☠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332	<3%
EC number: 905-588-0	Reaktionsmasse von Ethylbenzol und Xylol ☠ Flam. Liq. 3, H226; ☠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≥0-<3%

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

**4.1 Description of first aid measures****General information:** Immediately remove any clothing soiled by the product.

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.09.2021

Version number 3.5

Revision: 28.09.2021

**Trade name: Bremssattellack (A)**

(Contd. of page 2)

**After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.**After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:** Call for a doctor immediately, present msds**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:**CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**For safety reasons unsuitable extinguishing agents:** Water with full jet**5.2 Special hazards arising from the substance or mixture** No further relevant information available.**5.3 Advice for firefighters****Protective equipment:** Wear self-contained respiratory protective device.**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

**6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.**6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

No special measures required.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling** Prevent formation of aerosols.**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:**

Protect from frost and heat. Optimal storage temperature 10 - 25 °C

**Information about storage in one common storage facility:** Not required.**Further information about storage conditions:** Keep container tightly sealed.**Storage class:** 3**7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.09.2021

Version number 3.5

Revision: 28.09.2021

Trade name: **Bremssattellack (A)**

(Contd. of page 3)

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

**Additional information about design of technical facilities:** No further data; see item 7.

#### Ingredients with limit values that require monitoring at the workplace:

##### 123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

##### 1330-20-7 xylene

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 220 mg/m<sup>3</sup>, 50 ppm  
Sk; BMGV

##### 100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m<sup>3</sup>, 125 ppm  
Long-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Sk

#### Ingredients with biological limit values:

##### 1330-20-7 xylene

BMGV 650 mmol/mol creatinine  
Medium: urine  
Sampling time: post shift  
Parameter: methyl hippuric acid

**Additional information:** The lists valid during the making were used as basis.

#### 8.2 Exposure controls

##### Personal protective equipment:

##### General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

**Respiratory protection:** Not required.

##### Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

##### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

##### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:**

Nitrile rubber, NBR

**For the permanent contact gloves made of the following materials are suitable:** Butyl rubber, BR

**For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Nitrile rubber, NBR

Chloroprene rubber, CR

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.09.2021

Version number 3.5

Revision: 28.09.2021

**Trade name: Bremssattellack (A)****Eye protection:** Tightly sealed goggles

(Contd. of page 4)

### **SECTION 9: Physical and chemical properties**

#### **9.1 Information on basic physical and chemical properties**

##### **General Information**

##### **Appearance:**

<b>Form:</b>	Fluid
<b>Colour:</b>	Various colours
<b>Odour:</b>	Ester-like

##### **Change in condition**

**Initial boiling point and boiling range:** 120-128 °C

**Flash point:** 26 °C

**Ignition temperature:** 370 °C

**Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

##### **Explosion limits:**

<b>Lower:</b>	1.1 Vol %
<b>Upper:</b>	8 Vol %

**Vapour pressure at 20 °C:** 13 hPa

**Density at 20 °C:** 1.35 g/cm<sup>3</sup>

**Solubility in / Miscibility with water:** Not miscible or difficult to mix.

##### **Viscosity:**

**Kinematic at 20 °C:** 19-27 s (DIN 53211/4)

##### **Solvent separation test:**

**Organic solvents:** >38.2-<41 %

**VOC (EC)** >516.2-<553.4 g/l

**9.2 Other information** No further relevant information available.

### **SECTION 10: Stability and reactivity**

**10.1 Reactivity** No further relevant information available.

#### **10.2 Chemical stability**

**Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

**10.3 Possibility of hazardous reactions** No dangerous reactions known.

**10.4 Conditions to avoid** No further relevant information available.

**10.5 Incompatible materials:** No further relevant information available.

**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

#### **11.1 Information on toxicological effects**

**Acute toxicity** Based on available data, the classification criteria are not met.

##### **LD/LC50 values relevant for classification:**

##### **1330-20-7 xylene**

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.09.2021

Version number 3.5

Revision: 28.09.2021

**Trade name: Bremssattellack (A)**

(Contd. of page 5)

**Primary irritant effect:****Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/irritation**

Causes serious eye irritation.

**Respiratory or skin sensitisation**

May cause an allergic skin reaction.

**Additional toxicological information:****CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)****Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure**

May cause drowsiness or dizziness.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.**Aspiration hazard** Based on available data, the classification criteria are not met.**SECTION 12: Ecological information****12.1 Toxicity****Aquatic toxicity:** No further relevant information available.**12.2 Persistence and degradability** No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**Additional ecological information:****General notes:****Water hazard class 2 (German Regulation) (Self-assessment):** hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

**12.5 Results of PBT and vPvB assessment** Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation**

Smaller quantities can be disposed of with household waste.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**Uncleaned packaging:****Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information****14.1 UN-Number****ADR, IMDG, IATA**

UN1263

**14.2 UN proper shipping name****ADR**

UN1263 PAINT

**IMDG, IATA**

PAINT

(Contd. on page 7)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.09.2021

Version number 3.5

Revision: 28.09.2021

**Trade name: Bremssattellack (A)**

(Contd. of page 6)

**14.3 Transport hazard class(es)****ADR**

**Class** 3 (F1) Flammable liquids.  
**Label** 3

**IMDG, IATA**

**Class** 3 Flammable liquids.  
**Label** 3

**14.4 Packing group****ADR, IMDG, IATA** III**14.5 Environmental hazards:** Not applicable.**14.6 Special precautions for user** Warning: Flammable liquids.**Hazard identification number (Kemler code):** 30**EMS Number:** F-E,S-E**Stowage Category** A**14.7 Transport in bulk according to Annex II of****Marpol and the IBC Code** Not applicable.**Transport/Additional information:****ADR**

**Limited quantities (LQ)** 5L  
**Excepted quantities (EQ)** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

**Transport category** 3  
**Tunnel restriction code** D/E

**IMDG**

**Limited quantities (LQ)** 5L  
**Excepted quantities (EQ)** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

**UN "Model Regulation":** UN 1263 PAINT, 3, III**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 8)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.09.2021

Version number 3.5

Revision: 28.09.2021

**Trade name: Bremssattellack (A)**

(Contd. of page 7)

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

**Department issuing SDS:** Abteilung Produkttechnik**Contact:** Hr. Fuhrmann**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

**\* Data compared to the previous version altered.**