



Putoline Hydraulic Clutch Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 22-5-2018 Revision date: 28-9-2022 Supersedes version of: 12-9-2022 Version: 1.7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Putoline Hydraulic Clutch Fluid
Product code : PW.40.13
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Industrial use, Professional use, Consumer use
Use of the substance/mixture : Hydraulic oil
Function or use category : Hydraulic fluids and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Putoline Oil
Dollegoorweg, 15
NL- 7602 EC Almelo
Netherlands
T 0031 (0)546 81 81 65
vib@putoline.com

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Cardiff Centre) University Hospital Llandough	Penlan Road CF64 2XX Llandough	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

Putoline Hydraulic Clutch Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS08

Signal word (CLP) :

Danger

Contains :

Distillates (petroleum), hydrotreated light naphthenic, Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based, Distillates (petroleum), hydrotreated light paraffinic

Hazard statements (CLP) :

H304 - May be fatal if swallowed and enters airways.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) :

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P273 - Avoid release to the environment.
P301+P310+P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments : Highly refined mineral oils and additives.

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (Note L)	CAS-No.: 72623-86-0 EC-No.: 276-737-9 EC Index-No.: 649-482-00-X REACH-no: 01-2119474878-16	50 – 80	Asp. Tox. 1, H304

Putoline Hydraulic Clutch Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated light naphthenic (Note L)	CAS-No.: 64742-53-6 EC-No.: 265-156-6 EC Index-No.: 649-466-00-2 REACH-no: 01-2119480375-34	25 – 50	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated light paraffinic (Note L)	CAS-No.: 64742-55-8 EC-No.: 265-158-7 EC Index-No.: 649-468-00-3 REACH-no: 01-2119487077-29	1 – 2,5	Asp. Tox. 1, H304
2,6-di-tert-butylphenol	CAS-No.: 128-39-2 EC-No.: 204-884-0 REACH-no: 01-2119490822-33	0,1 – 1	Skin Irrit. 2, H315 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2-ethylhexan-1-ol substance with national workplace exposure limit(s) (GB, IE); substance with a Community workplace exposure limit	CAS-No.: 104-76-7 EC-No.: 203-234-3 REACH-no: 01-2119487289-20	< 0,1	Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335

Comments : The highly refined mineral oil contains <3% (w/w) DMSOextract, according to IP346.

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.
Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Repeated exposure may cause skin dryness or cracking. Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : No additional information available.
Symptoms/effects after ingestion : Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid.

Putoline Hydraulic Clutch Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous decomposition products in case of fire : Toxic fumes may be released. Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Keep in a cool, well-ventilated place away from heat.
Storage temperature : 0 – 40 °C

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Putoline Hydraulic Clutch Fluid	
EU - Indicative Occupational Exposure Limit (IOEL)	
Exposure limits/standards for materials that can be formed when handling this product. When mists/aerosols can occur the following is recommended	5 mg/m ³ - ACGIH TLV (inhalable fraction).

Putoline Hydraulic Clutch Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-ethylhexan-1-ol (104-76-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-ethylhexan-1-ol
IOEL TWA	5,4 mg/m ³
IOEL TWA [ppm]	1 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
Ireland - Occupational Exposure Limits	
Local name	2-Ethylhexan-1-ol
OEL TWA [1]	5,4 mg/m ³
OEL TWA [2]	1 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
United Kingdom - Occupational Exposure Limits	
Local name	2-ethylhexan-1-ol
WEL TWA (OEL TWA) [1]	5,4 mg/m ³
WEL TWA (OEL TWA) [2]	1 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

Putoline Hydraulic Clutch Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	≥0.35		EN ISO 374

Other skin protection

Materials for protective clothing:

Wear suitable protective clothing

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Yellow.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: -66 °C - ASTM D5950 (pour point)
Boiling point	: Not available
Flammability	: Not applicable
Explosive properties	: Presents no particular fire or explosion hazard.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 144 °C - ASTM D92 (COC)
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 10 mm ² /s (40 °C) - ASTM D7279
Solubility	: Water: Insoluble / Slightly miscible
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 0,85 kg/l (15 °C) - ASTM D4052
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle characteristics	: Not applicable

Putoline Hydraulic Clutch Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Reacts violently with (strong) oxidizers.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No decomposition if stored normally.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

2,6-di-tert-butylphenol (128-39-2)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

2-ethylhexan-1-ol (104-76-7)

LD50 oral rat	≈ 2047 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	1950 mg/kg
LC50 Inhalation - Rat (Vapours)	> 0,89 mg/l/4h

Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)

LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rabbit	> 2000 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	> 5,53 mg/l/4h

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)

LD50 oral rat	> 5000 mg/kg (OECD 401 method)
---------------	--------------------------------

Putoline Hydraulic Clutch Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
LD50 dermal rabbit	> 2000 mg/kg (OECD 402 method)
LC50 Inhalation - Rat	> 5,53 mg/l (OECD 403 method)
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	5,53 mg/l/4h
Skin corrosion/irritation	: Not classified
Additional information	: Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
2-ethylhexan-1-ol (104-76-7)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
2-ethylhexan-1-ol (104-76-7)	
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, gas, 90 days)	120 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Aspiration hazard	: May be fatal if swallowed and enters airways.
Putoline Hydraulic Clutch Fluid	
Viscosity, kinematic	10 mm ² /s (40 °C) - ASTM D7279
Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)	
Viscosity, kinematic	9 mm ² /s
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
Viscosity, kinematic	< 20,5 mm ² /s (40 °C) - ASTM D7279
Aliphatic, alicyclic or aromatic hydrocarbon	Yes
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
Viscosity, kinematic	< 20,5 mm ² /s
Aliphatic, alicyclic or aromatic hydrocarbon	Yes

11.2. Information on other hazards

No additional information available

Putoline Hydraulic Clutch Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Ecology - water	: May cause long lasting harmful effects to aquatic life.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.
Not rapidly degradable	

2,6-di-tert-butylphenol (128-39-2)	
EC50 - Crustacea [1]	0,45 mg/l (Daphnia magna, freshwater, 48h)
EC50 72h - Algae [1]	1,4 mg/l (Selenastrum capricornutum, freshwater)

2-ethylhexan-1-ol (104-76-7)	
LC50 - Fish [1]	17,1 mg/l Test organisms (species): Leuciscus idus melanotus
LC50 - Fish [2]	28,2 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	39 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	11,5 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	16,6 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)	
LC50 - Fish [1]	> 100 mg/l (96 h)
EC50 - Crustacea [1]	> 10 g/l
EC50 72h - Algae [1]	> 100 mg/l
NOEC (acute)	≥ 100 (72h)

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
LC50 - Fish [1]	> 100 mg/l
EC50 - Crustacea [1]	> 10000 mg/l
NOEC (acute)	≥ 100 mg/l (Pseudokirchnerella subcapitata, 72h) (OECD 211 method)
NOEC chronic fish	> 1000 mg/l
NOEC chronic crustacea	> 10 mg/l (Daphnia magna, 21d) (OECD 211 method)
NOEC chronic algae	≥ 100 mg/l

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
LC50 - Fish [1]	> 100 mg/l 96h
EC50 - Crustacea [1]	> 10000 mg/l
EC50 72h - Algae [1]	≥ 100 mg/l
NOEC chronic crustacea	10 mg/l 21d

12.2. Persistence and degradability

2,6-di-tert-butylphenol (128-39-2)	
Biodegradation	5 % Sturm (28 d)

Putoline Hydraulic Clutch Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)	
Persistence and degradability	Not readily biodegradable. Inherently biodegradable.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % (28d) (OECD 301F method)
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
Persistence and degradability	Not established.
Biodegradation	31 % (OECD 301F method)

12.3. Bioaccumulative potential

2,6-di-tert-butylphenol (128-39-2)	
Partition coefficient n-octanol/water (Log Kow)	4,5 Octanol/water (0,1 d)
Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)	
Bioaccumulative potential	Bioaccumulative potential.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
Partition coefficient n-octanol/water (Log Kow)	> 6
Bioaccumulative potential	Bioaccumulative potential.
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
Partition coefficient n-octanol/water (Log Pow)	> 6
Bioaccumulative potential	Not established.

12.4. Mobility in soil

Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)	
Ecology - soil	Insoluble in water.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
Ecology - soil	Insoluble in water.

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
European List of Waste (LoW) code	: 13 01 11* - synthetic hydraulic oils

Putoline Hydraulic Clutch Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)	
Reference code	Applicable on
3.	2,6-di-tert-butylphenol ; 2-ethylhexan-1-ol
3(b)	Putoline Hydraulic Clutch Fluid ; 2,6-di-tert-butylphenol ; 2-ethylhexan-1-ol ; Distillates (petroleum), hydrotreated light naphthenic ; Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based
3(c)	Putoline Hydraulic Clutch Fluid ; 2,6-di-tert-butylphenol

Putoline Hydraulic Clutch Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

REACH Annex XIV (Authorisation List)

Contains no REACH Annex XIV substances

REACH Candidate List (SVHC)

Contains no substance on the REACH candidate list

PIC Regulation (Prior Informed Consent)

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

POP Regulation (Persistent Organic Pollutants)

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Ozone Regulation (1005/2009)

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

VOC Directive (2004/42)

VOC content : 0 %

Biocide Regulation (528/2012)

Child-resistant fastening : Applicable

Tactile warning : Applicable

Explosives Precursors Regulation (2019/1148)

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on drug precursors)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

For the following substances of this mixture a chemical safety assessment has been carried out:

Distillates (petroleum), hydrotreated light naphthenic

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Revision date	Modified	
	Supersedes	Modified	
1.2	Function or use category	Added	
1.2	Use of the substance/mixture	Added	

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value

Putoline Hydraulic Clutch Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H304	May be fatal if swallowed and enters airways.

Putoline Hydraulic Clutch Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.