

# Safety data sheet according to 1907/2006/EC, Article 31

Version number 1

Revision: 26.11.2020

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- Trade name: <u>9983 Winter diesel 1L</u>
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Additive
- · 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: UAB "SCT Lubricants" Silutes PI. 119 LIT-95112 KLAIPEDA LITHUANIA renata@sct.lt

- · Further information obtainable from: Product safety department.
- 1.4 Emergency telephone number: During normal opening times: +370/615 313 68

# **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Carc. 2 H351 Suspected of causing cancer.

2.2 Label elements

#### · Labelling according to Regulation (EC) No 1272/2008

- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labelling:
- Fuels, diesel
- Hazard statements
- H226 Flammable liquid and vapour.
- H351 Suspected of causing cancer.

#### · Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read carefully and follow all instructions.

GB

Version number 1

Revision: 26.11.2020

#### Trade name: 9983 Winter diesel 1L

(Contd. of page 1)

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor/Product Safety Department.
- Do NOT induce vomiting. P331
- P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.
- Collect spillage. P391
- P403+P235 Store in a well-ventilated place. Keep cool.
- Store locked up. P405
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### · 2.3 Other hazards

#### · Results of PBT and vPvB assessment

· **PBT:** Not applicable.

#### · vPvB:

64742-94-5 Solvent naphtha (petroleum), heavy arom.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

| nents:   |  |  |
|--|--|--|
| Fuels, diesel  | 70–90%   |  |
| Carc. 2, H351  |  |  |
| Solvent naphtha (petroleum), heavy arom.   | 0.25–5%  |  |
| Asp. Tox. 1, H304<br>vPvB  |  |  |
| naphthalene  | 0.001-0.1%   |  |
| Carc. 2, H351; Aquatic Acute 1, H400; Aquatic Chronic 1, H410;<br>Acute Tox. 4, H302   |  |  |
| ostances   |  |  |
| 1,2,4-trimethylbenzene   | 0.01-0.5%  |  |
| Flam. Liq. 3, H226; Aquatic Chronic 2, H411; Acute Tox. 4, H332;<br>Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 |  |  |
|  | Carc. 2, H351<br>Solvent naphtha (petroleum), heavy arom.<br>Asp. Tox. 1, H304<br>vPvB<br>naphthalene<br>Carc. 2, H351; Aquatic Acute 1, H400; Aquatic Chronic 1, H410;<br>Acute Tox. 4, H302<br><b>ostances</b><br>1,2,4-trimethylbenzene<br>Flam. Lig. 3, H226; Aquatic Chronic 2, H411; Acute Tox. 4, H332; |  |

• Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

#### · 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)



Printing date 26.11.2020



# Safety data sheet according to 1907/2006/EC, Article 31

Version number 1

Revision: 26.11.2020

(Contd. of page 2)

Trade name: 9983 Winter diesel 1L

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

# **SECTION 5: Firefighting measures**

- <sup>·</sup> 5.1 Extinguishing media
- Suitable extinguishing agents: CO2. Do not use water.

Foam Fire-extinguishing powder

Sand

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

# **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Particular danger of slipping on leaked/spilled product. Wear protective clothing.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
   See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling Open and handle receptacle with care.

 Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

(Contd. on page 4)

GB



# Safety data sheet according to 1907/2006/EC, Article 31

Version number 1

Revision: 26.11.2020

(Contd. of page 3)

Trade name: 9983 Winter diesel 1L

• 7.3 Specific end use(s) No further relevant information available.

# **SECTION 8: Exposure controls/personal protection**

- · 8.1 Control parameters
- Additional information about design of technical facilities: No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- **General protective and hygienic measures:** Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Store protective clothing separately.
- · Respiratory protection: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### · Eye protection:



Tightly sealed goggles

# **SECTION 9: Physical and chemical properties**

- 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance: Form:

Liquid

Colour:

Blue

(Contd. on page 5)

GB



Printing date 26.11.2020

Version number 1

Revision: 26.11.2020

#### Trade name: 9983 Winter diesel 1L

|  | (Contd. of page 4                          |
|--|--|
| · Odour:   | Characteristic                             |
| · Odour threshold:                                   | Not determined.                            |
| · pH-value:  | Not determined.                            |
| Change in condition                                  |  |
| Melting point/freezing point:                        | <-5 °C                                     |
| Initial boiling point and boiling range              |  |
| · Flash point:                                       | >55 °C                                     |
| · Flammability (solid, gas):                         | Not applicable.                            |
| · Ignition temperature:                              | 225 °C                                     |
| · Decomposition temperature:                         | Not determined.                            |
| · Auto-ignition temperature:                         | Product is not selfigniting.               |
| · Explosive properties:                              | Not determined.                            |
| · Explosion limits:                                  |  |
| Lower:   | Not determined.                            |
| Upper:   | Not determined.                            |
| · Vapour pressure:                                   | Not determined.                            |
| · Density at 20 °C:                                  | 0.8–0.845 g/cm³                            |
| Relative density                                     | Not determined.                            |
| · Vapour density                                     | Not determined.                            |
| · Evaporation rate                                   | Not determined.                            |
| <ul> <li>Solubility in / Miscibility with</li> </ul> |  |
| water:   | Not miscible or difficult to mix.          |
| · Partition coefficient: n-octanol/water:            | Not determined.                            |
| · Viscosity:   |  |
| Dynamic:   | Not determined.                            |
| Kinematic at 40 °C:                                  | 2–4.5 mm²/s                                |
| Solvent content:                                     |  |
| Organic solvents:                                    | 0-0.5 %                                    |
| VOC (EC)   | 0.01–0.5 %                                 |
| • 9.2 Other information                              | No further relevant information available. |

# **SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

(Contd. on page 6)

<sup>-</sup> GB



# Safety data sheet according to 1907/2006/EC, Article 31

Version number 1

Revision: 26.11.2020

(Contd. of page 5)

Trade name: 9983 Winter diesel 1L

Aldehyde Poisonous gases/vapours Carbon dioxide

# **SECTION 11: Toxicological information**

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

#### 91-20-3 naphthalene

Oral LD50 490 mg/kg (rat)

Dermal LD50 5,000 mg/kg (rat)

- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity
- Suspected of causing cancer.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

# **SECTION 12: Ecological information**

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

#### · vPvB:

64742-94-5 Solvent naphtha (petroleum), heavy arom.

• **12.6 Other adverse effects** No further relevant information available.

(Contd. on page 7)



Printing date 26.11.2020

Version number 1

Revision: 26.11.2020

Trade name: 9983 Winter diesel 1L

(Contd. of page 6)

# **SECTION 13: Disposal considerations**

#### · 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### · European waste catalogue

HP3 Flammable

HP7 Carcinogenic

#### · Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

| 14.1 UN-Number<br>ADR, IMDG, IATA               | UN1202  |
|---|---|
|   | 011202  |
| 14.2 UN proper shipping name                    |   |
| ADR<br>MDG, IATA                                | 1202 DIESEL FUEL<br>DIESEL FUEL                       |
| · · ·   | DIESEL FUEL   |
| 14.3 Transport hazard class(es)                 |   |
| ADR, IMDG, IATA                                 |   |
|   |   |
|   |   |
| 3   |   |
| Class   | 3 Flammable liquids.                                  |
|   | 3   |
|   | •   |
| • 14.4 Packing group<br>• ADR, IMDG, IATA       | III   |
|   |   |
| 14.5 Environmental hazards:                     | Not applicable.                                       |
| 14.6 Special precautions for user               | Warning: Flammable liquids.                           |
| Hazard identification number (Kemler code):     | 30  |
| EMS Number:                                     | F-E,S-E<br>A  |
| Stowage Category                                |   |
| 14.7 Transport in bulk according to Annex II of |   |
| Marpol and the IBC Code                         | Not applicable.                                       |
| Transport/Additional information:               |   |
| ADR   |   |
| Limited quantities (LQ)                         | 5L  |
| Excepted quantities (EQ)                        | Code: E1  |
|   | Maximum net quantity per inner packaging: 30 ml       |
| · Transport category                            | Maximum net quantity per outer packaging: 1000 n<br>3 |



Printing date 26.11.2020

Version number 1

Revision: 26.11.2020

Trade name: 9983 Winter diesel 1L

|   | (Contd. of page 7)   |
|---|--|
| • Tunnel restriction code   | D/E  |
| <ul> <li>IMDG</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul> | 5L<br>Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · UN "Model Regulation":  | UN 1202 DIESEL FUEL, 3, III  |

# **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

- · Department issuing SDS: Product safety department.
- · Contact: Mrs. Zubaite

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 9)



# Safety data sheet according to 1907/2006/EC, Article 31

Version number 1

Revision: 26.11.2020

# Trade name: 9983 Winter diesel 1L

| ELINCS: European List of Notified Chemical Substances<br>CAS: Chemical Abstracts Service (division of the American Chemical Society)<br>VOC: Volatile Organic Compounds (USA, EU)<br>LC50: Lethal concentration, 50 percent<br>D50: Lethal dose, 50 percent<br>PBT: Persistent, Bioaccumulative and Toxic<br>vPvB: very Persistent and very Bioaccumulative<br>Flam. Liq. 3: Flammable liquids – Category 3<br>Acute Tox. 4: Acute toxicity - oral – Category 4<br>Carc. 2: Carcinogenicity – Category 2<br>Asp. Tox. 1: Aspiration hazard – Category 1<br>Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1<br>Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1<br>• * Data compared to the previous version altered. | CAS: Chemical Abstracts Service (division of the American Chemical Society)<br>VOC: Volatile Organic Compounds (USA, EU)<br>LC50: Lethal concentration, 50 percent<br>LD50: Lethal dose, 50 percent<br>PBT: Persistent, Bioaccumulative and Toxic<br>vPvB: very Persistent and very Bioaccumulative<br>Flam. Liq. 3: Flammable liquids – Category 3<br>Acute Tox. 4: Acute toxicity - oral – Category 4<br>Carc. 2: Carcinogenicity – Category 2<br>Asp. Tox. 1: Aspiration hazard – Category 1<br>Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1<br>Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 |
|---|---|
|---|---|