



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Product code : 891693

Unique Formula Identifier (UFI) : POX1-1PQV-C30E-JANE

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline
Wieldrechtseweg 39
3316 BG Dordrecht
Netherlands

Telephone : +31 (0)78 654 3500 (in the Netherlands), or contact your local
CSR contact person

E-mail address of person responsible for the SDS : SDS@valvoline.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number
at 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Skin irritation, Category 2

H315: Causes skin irritation.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

Serious eye damage, Category 1

H318: Causes serious eye damage.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms

:



Signal word

:

Danger

Hazard statements

:

H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary statements

:

Prevention:

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Hazardous components which must be listed on the label:

Benzenesulfonic acid, 4-C10-13-sec-alkyl derivati

Benzenesulfonic acid, C10-13-alkyl derivs., calcium salt

CALCIUM HYDROXIDE

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25- xxxx	Asp. Tox. 1; H304	>= 25 - < 40
Benzenesulfonic acid, 4-C10-13-sec- alkyl derivati	85536-14-7 287-494-3 05-2114643612-53- 0000 05-2114668720-45- 0000 05-2114691266-40- 0000 05-2114767133-50- 0000 05-2114660384-47- 0000 05-2114766712-43- 0000 05-2114690043-53- 0000 05-2114664466-39- 0000 05-2114692152-50- 0000 05-2114664452-48- 0000 05-2114722070-67- 0000 05-2114676344-43- 0000 05-2114689788-18- 0000 05-2114728102-62- 0000 05-2114768048-40- 0000 05-2114694399-26- 0000 05-2114693704-38- 0000 05-2114699305-38- 0000	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412	>= 2.5 - < 3



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

	05-2114697629-24-0000 05-2114723331-62-0000 05-2114676343-45-0000 05-2114680648-33-0000 05-2114767441-47-0000 05-2114691034-51-0000 05-2114668889-19-0000 05-2114647810-49-0000 05-2114697787-20-0000 05-2114668050-56-0000 05-2114668721-43-0000		
Benzenesulfonic acid, C10-13-alkyl derivs., calcium salt	1335202-81-7 01-2119560592-37-xxxx	Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Chronic 3; H412	>= 2.5 - < 3
HEXYLENE GLYCOL	107-41-5 203-489-0 603-053-00-3 01-2119539582-35-xxxx	Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 2.5 - < 5
CALCIUM HYDROXIDE	1305-62-0 215-137-3	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system)	>= 1 - < 2.5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

- | | | |
|-------------------------|---|---|
| If inhaled | : | If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician. |
| In case of skin contact | : | If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes. |
| In case of eye contact | : | Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : | Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital. |

4.2 Most important symptoms and effects, both acute and delayed

- | | | |
|----------|---|---|
| Symptoms | : | No symptoms known or expected. |
| Risks | : | Causes skin irritation.
Causes serious eye damage. |

4.3 Indication of any immediate medical attention and special treatment needed

- | | | |
|-----------|---|--|
| Treatment | : | No hazards which require special first aid measures.

Treat symptomatically. |
|-----------|---|--|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | | |
|------------------------------|---|--|
| Suitable extinguishing media | : | Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. |
|------------------------------|---|--|



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
HEXYLENE GLYCOL	107-41-5	TWA	25 ppm 123 mg/m3	GB EH40
		STEL	25 ppm 123 mg/m3	GB EH40



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

CALCIUM HYDROXIDE	1305-62-0	TWA	5 mg/m3	GB EH40
		TWA (Respirable fraction)	1 mg/m3	GB EH40
		STEL (Respirable fraction)	4 mg/m3	GB EH40
		TWA (Respirable fraction)	1 mg/m3	2017/164/EU
Further information: Indicative				
		STEL (Respirable fraction)	4 mg/m3	2017/164/EU
Further information: Indicative				

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : neoprene, nitrile rubber
Break through time : >= 240 min
Glove thickness : >= 0.35 mm
Directive : Equipment should conform to EN 374

Remarks

: The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove.
The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

concentration of the dangerous substance at the work place.

Respiratory protection : No personal respiratory protective equipment normally required.

B

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Odour	: No data available
Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: > 260 °C Method: Cleveland open cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: ca. 0.9 g/cm ³ (15.6 °C)
Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

Partition coefficient: n-octanol/water : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : ca. 270 mm²/s (40 °C)

Oxidizing properties : No data available

9.2 Other information

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Acids
Fluorine
maleic anhydride
nitroparaffins
nitropropane
Organic materials
phosphorus
Strong bases
Strong oxidizing agents
strong reducing agents
water



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Acute oral toxicity : LD50 (Rat): > 15 g/kg
Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Benzenesulfonic acid, 4-C10-13-sec-alkyl derivati:

Acute oral toxicity : LD50 (Rat): 1,470 mg/kg
Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: No mortality observed at this dose.
The toxicological data has been taken from products of similar composition.

Benzenesulfonic acid, C10-13-alkyl derivs., calcium salt:

Acute oral toxicity : LD50 (Rat, female): 4,445 mg/kg
Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

HEXYLENE GLYCOL:

Acute oral toxicity : LD50 (Rat): 4,700 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 60 ppm



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

	Exposure time: 1 h
	Test atmosphere: vapour
	Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	: LD50 (Rat): > 2,000 mg/kg
	Assessment: The substance or mixture has no acute dermal toxicity

CALCIUM HYDROXIDE:

Acute oral toxicity	: LD50 (Rat): 7,340 mg/kg
Acute inhalation toxicity	: Remarks: Corrosive by inhalation.

Skin corrosion/irritation

Causes skin irritation.

Product:

Result	: Severe skin irritation
Remarks	: Extremely corrosive and destructive to tissue.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Assessment	: Slight, transient irritation
Result	: Slight, transient irritation

Benzenesulfonic acid, 4-C10-13-sec-alkyl derivati:

Species	: Rabbit
Result	: Corrosive after 1 to 4 hours of exposure

Benzenesulfonic acid, C10-13-alkyl derivs., calcium salt:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: Irritating to skin.

HEXYLENE GLYCOL:

Species	: Rabbit
Result	: Slight, transient irritation

CALCIUM HYDROXIDE:

Result	: Irritating to skin.
--------	-----------------------



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Assessment	:	No eye irritation
Result	:	No eye irritation

Benzenesulfonic acid, 4-C10-13-sec-alkyl derivati:

Species	:	Rabbit
Result	:	Corrosive

Benzenesulfonic acid, C10-13-alkyl derivs., calcium salt:

Species	:	Rabbit
Method	:	OECD Test Guideline 405
Result	:	Corrosive

HEXYLENE GLYCOL:

Species	:	Rabbit
Result	:	Irritating to eyes.

CALCIUM HYDROXIDE:

Assessment	:	Corrosive
Result	:	Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Benzenesulfonic acid, 4-C10-13-sec-alkyl derivati:

Test Type	:	Maximisation Test
Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

HEXYLENE GLYCOL:

Test Type	:	Maximisation Test
Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.
Method	:	OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components:

Benzenesulfonic acid, 4-C10-13-sec-alkyl derivati:

Genotoxicity in vitro	:	Test Type: Ames test
		Test system: Salmonella typhimurium
		Metabolic activation: with and without metabolic activation
		Result: negative

HEXYLENE GLYCOL:

Genotoxicity in vitro	:	Test Type: Ames test
		Test system: Salmonella typhimurium
		Metabolic activation: with and without metabolic activation
		Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Carcinogenicity - Assessment	:	Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)
------------------------------	---	---

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

Components:

CALCIUM HYDROXIDE:

Assessment	:	May cause respiratory irritation.
------------	---	-----------------------------------



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Toxicity to fish	: LL50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	: EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	: NOEC: 10 mg/l Species: Fish
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: 10 mg/l Species: Aquatic invertebrates



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

Ecotoxicology Assessment

Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.

Benzenesulfonic acid, 4-C10-13-sec-alkyl derivati:

Toxicity to fish	:	LC50 (Lepomis macrochirus (Bluegill sunfish)): 1.67 mg/l Exposure time: 96 h Test Type: static test Remarks: The toxicological data has been taken from products of similar composition.
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Aquatic invertebrates): > 1 - 10 mg/l Exposure time: 96 h Remarks: The toxicological data has been taken from products of similar composition.
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus): 127.9 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Remarks: The toxicological data has been taken from products of similar composition. NOEC (Desmodesmus subspicatus): 2.1 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Remarks: The toxicological data has been taken from products of similar composition.
Toxicity to fish (Chronic toxicity)	:	NOEC: 1 mg/l Exposure time: 28 d Species: Lepomis macrochirus (Bluegill sunfish) Test Type: flow-through test Method: OECD Test Guideline 204 Remarks: The toxicological data has been taken from products of similar composition.
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 1.18 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Test Type: flow-through test Method: OECD Test Guideline 211 Remarks: The toxicological data has been taken from



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

products of similar composition.

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.
Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Benzenesulfonic acid, C10-13-alkyl derivs., calcium salt:

Toxicity to fish : LC50 : > 1 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
Toxicity to fish (Chronic toxicity) : NOEC: 0.23 mg/l
Exposure time: 72 d
Species: Oncorhynchus mykiss (rainbow trout)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1.18 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 2; Toxic to aquatic life.
Chronic aquatic toxicity : Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

HEXYLENE GLYCOL:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 8,690 mg/l
Exposure time: 96 h
Test Type: flow-through test
Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 5,410 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 429 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.
Chronic aquatic toxicity : Not classified based on available information.

CALCIUM HYDROXIDE:

Toxicity to fish : LC50 (*Gambusia affinis* (Mosquito fish)): 240 mg/l
Exposure time: 24 h
Method: Static
Remarks: Mortality

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.
Chronic aquatic toxicity : Not classified based on available information.

12.2 Persistence and degradability

Components:

Benzenesulfonic acid, 4-C10-13-sec-alkyl derivati:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 84 %
Exposure time: 28 d
Method: OECD Test Guideline 301A

Benzenesulfonic acid, C10-13-alkyl derivs., calcium salt:

Biodegradability : Result: Readily biodegradable.

HEXYLENE GLYCOL:

Biodegradability : Inoculum: activated sludge
Result: Readily biodegradable.
Biodegradation: 81 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

Components:

Benzenesulfonic acid, 4-C10-13-sec-alkyl derivati:

Partition coefficient: n-octanol/water : Pow: 3.2



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

Benzenesulfonic acid, C10-13-alkyl derivs., calcium salt:

Partition coefficient: n-octanol/water : log Pow: 2.89 (20 °C)

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

Waste Code : The Waste code should be assigned in discussion between the user and the waste disposal company.
The following Waste Codes are only suggestions:



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

13 02 05, mineral-based non-chlorinated engine, gear and
lubricating oils

SECTION 14: Transport information

14.1 UN number

ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA_P	:	Not regulated as a dangerous good

14.2 UN proper shipping name

ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA_P	:	Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA_P	:	Not regulated as a dangerous good

14.4 Packing group

ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA (Cargo)	:	Not regulated as a dangerous good
IATA_P (Passenger)	:	Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH) : Not applicable

The components of this product are reported in the following inventories:

TCSI : Not in compliance with the inventory

TSCA : Product contains substance(s) not listed on TSCA inventory.

AIIC : Not in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : Not in compliance with the inventory

NZIoC : Not in compliance with the inventory



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

15.2 Chemical safety assessment

No data available

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16: Other information

Full text of H-Statements

H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H335	: May cause respiratory irritation.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
STOT SE	: Specific target organ toxicity - single exposure
2017/164/EU	: Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
2017/164/EU / STEL	: Short term exposure limit
2017/164/EU / TWA	: Limit Value - eight hours
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ INDUSTRY CALSUL ST 1.5
GREASE

Version: 2.0

Revision Date: 29.03.2023

Print Date: 04/07/2023

International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Internal information : 000000276742

Classification of the mixture:

Skin Irrit. 2	H315
Eye Dam. 1	H318

Classification procedure:

Based on product data or assessment
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN