SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 Valvoline™ EARTH OPEN GEAR 3 GREASE

Version: 3.0 Revision Date: 29.03.2023 Print Date: 04/07/2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Valvoline™ EARTH OPEN GEAR 3 Trade name

GREASE

Product code : 891703

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline

> Wieldrechtseweg 39 3316 BG Dordrecht

Netherlands

Telephone +31 (0)78 654 3500 (in the Netherlands), or contact your local

CSR contact person

E-mail address of person

responsible for the SDS

SDS@valvoline.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number at 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Long-term (chronic) aquatic hazard,

H412: Harmful to aquatic life with long lasting

Category 3

effects.

SAFETY DATA SHEET cording to Regulation (EC) No. 1907/



according to Regulation (EC) No. 1907/2006 Valvoline™ EARTH OPEN GEAR 3 GREASE

Version: 3.0 Revision Date: 29.03.2023 Print Date: 04/07/2023

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P273 Avoid release to the environment.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Additional Labelling

EUH208 Contains Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts. May

produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
	Index-No.		
	Registration number		
Phosphorodithioic acid, mixed O,O-	85940-28-9	Skin Irrit. 2; H315	>= 2.5 - < 5
bis(2-ethylhexyl and iso-Bu and iso-	288-917-4	Eye Irrit. 2; H319	
Pr) esters, zinc salts		Aquatic Chronic 2;	
		H411	
Benzenesulfonic acid, di-C10-14-	Not Assigned	Skin Sens. 1B;	>= 1 - < 2.5
alkyl derivs., calcium salts		H317	
	01-2119978241-36-		
	XXXX		
Substances with a workplace exposure	e limit :		
MOLYBDENUM DISULFIDE	1317-33-5		>= 2.5 - < 5
	215-263-9		
	05-2114678942-33-		
	0000		
	05-2114644836-38-		



according to Regulation (EC) No. 1907/2006 Valvoline™ EARTH OPEN GEAR 3 GREASE

Version: 3.0 Revision Date: 29.03.2023 Print Date: 04/07/2023

0000	
05-2114700532-63-	
0000	
05-2114683333-47-	
0000	
05-2114690535-40-	
0000	
05-2114646176-46-	
0000	
05-2114662415-48-	
0000	
05-2114726400-62-	
0000	
05-2114781039-42-	
0000	
05-2114692569-27-	
0000	
05-2114693303-48-	
0000	
05-2114670914-40-	
0000	
05-2114672118-46-	
0000	
05-2114693116-45-	
0000	
05-2114685148-38-	
0000	
05-2114677248-36-	
0000	
05-2114746905-38-	
0000	
05-2114685130-55-	
0000	
05-2114695705-34-	
0000	
05-2114785902-37-	
0000	
05-2114718794-39-	
0000	
05-2114781593-38-	
0000	
05-2114721495-48-	
0000	
05-2114767684-33-	
0000	
05-2114716490-55-	
0000	
05-2114690510-52-	



according to Regulation (EC) No. 1907/2006 Valvoline™ EARTH OPEN GEAR 3 GREASE

Version: 3.0 Revision Date: 29.03.2023 Print Date: 04/07/2023

	0000 05-2114694136-42- 0000 05-2114696600-45- 0000 05-2114671376-41- 0000		
GRAPHITE	7782-42-5 231-955-3	Flam. Sol. 1; H228	>= 1 - < 2.5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.



according to Regulation (EC) No. 1907/2006 Valvoline™ EARTH OPEN GEAR 3 GREASE

Version: 3.0 Revision Date: 29.03.2023 Print Date: 04/07/2023

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

carbon dioxide and carbon monoxide

Oxides of phosphorus

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 Valvoline™ EARTH OPEN GEAR 3 GREASE

Revision Date: 29.03.2023 Version: 3.0 Print Date: 04/07/2023

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Avoid contact with skin and eyes.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the

technological safety standards.

Further information on

storage stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits



according to Regulation (EC) No. 1907/2006 Valvoline™ EARTH OPEN GEAR 3 GREASE

Version: 3.0 Revision Date: 29.03.2023 Print Date: 04/07/2023

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
MOLYBDENUM DISULFIDE	1317-33-5	TWA	10 mg/m3 (Molybdenum)	GB EH40
		STEL	20 mg/m3 (Molybdenum)	GB EH40
GRAPHITE	7782-42-5	TWA (inhalable dust)	10 mg/m3	GB EH40
		TWA (Respirable dust)	4 mg/m3	GB EH40

Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
GRAPHITE	Sewage treatment plant	50 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Hand protection

Material : neoprene, nitrile rubber

Break through time : >= 240 minGlove thickness : >= 0.35 mm

Directive : Equipment should conform to EN 374

Remarks : The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the

protective glove.

The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Valvoline_{TM}

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 Valvoline™ EARTH OPEN GEAR 3 GREASE

Version: 3.0 Revision Date: 29.03.2023 Print Date: 04/07/2023

Respiratory protection : No personal respiratory protective equipment normally

required.

В

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Odour : No data available

No data available

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

No data available

Boiling point/boiling range : No data available

Flash point : > 240 °C

Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : ca. 0.9 g/cm3 (15.6 °C)

Solubility(ies)

Water solubility : immiscible



according to Regulation (EC) No. 1907/2006 Valvoline™ EARTH OPEN GEAR 3 GREASE

Version: 3.0 Revision Date: 29.03.2023 Print Date: 04/07/2023

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : ca. 400 mm2/s (40 °C)

Oxidizing properties : No data available

9.2 Other information

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 Valvoline™ EARTH OPEN GEAR 3 GREASE

Version: 3.0 Revision Date: 29.03.2023 Print Date: 04/07/2023

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:

Acute oral toxicity : LD50 (Rat): 2,570 - 3,700 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.3 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute

inhalation toxicity

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 20,000 mg/kg

MOLYBDENUM DISULFIDE:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.82 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute

inhalation toxicity

GRAPHITE:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Acute inhalation toxicity : Assessment: The substance or mixture has no acute

inhalation toxicity

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 Valvoline™ EARTH OPEN GEAR 3 GREASE

Version: 3.0 Revision Date: 29.03.2023 Print Date: 04/07/2023

Species : Rabbit

Result : Irritating to skin.

Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

MOLYBDENUM DISULFIDE:

Result : No skin irritation

GRAPHITE:

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system

and the skin.

Components:

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:

Species : Rabbit

Result : Irritating to eyes.

Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

MOLYBDENUM DISULFIDE:

Result : No eye irritation

GRAPHITE:

Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 Valvoline™ EARTH OPEN GEAR 3 GREASE

Version: 3.0 Revision Date: 29.03.2023 Print Date: 04/07/2023

Respiratory sensitisation

Not classified based on available information.

Product:

Assessment : Does not cause skin sensitisation.

Components:

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:

Test Type : Buehler Test
Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts:

Assessment : The product is a skin sensitiser, sub-category 1B.

GRAPHITE:

Species : Mouse

Method : Local lymph node assay

Result : Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

GRAPHITE:

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

GRAPHITE:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 Valvoline™ EARTH OPEN GEAR 3 GREASE

Version: 3.0 Revision Date: 29.03.2023 Print Date: 04/07/2023

Effects on fertility : Species: Rat

Application Route: Oral

Symptoms: No effects on reproduction parameters

Effects on foetal : Species: Rat

development Application Route: Oral

Symptoms: No specific developmental abnormalities

Method: OECD Test Guideline 422

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Components:

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 4.5 mg/l

Exposure time: 96 h
Test Type: semi-static test

Remarks: The toxicological data has been taken from

products of similar composition.

Toxicity to daphnia and other:

EC50 (Daphnia magna (Water flea)): 5.4 mg/l

aquatic invertebrates

Exposure time: 48 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 Valvoline™ EARTH OPEN GEAR 3 GREASE

Version: 3.0 Revision Date: 29.03.2023 Print Date: 04/07/2023

Test Type: static test
Test substance: WAF

Toxicity to algae/aquatic

plants

(Selenastrum capricornutum (green algae)): 2.1 mg/l

End point: Growth inhibition

Exposure time: 96 h
Test Type: static test
Test substance: WAF

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity: Not classified based on available information.

MOLYBDENUM DISULFIDE:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity: Not classified based on available information.

GRAPHITE:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 96 h
Test Type: semi-static test

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia (water flea)): > 100 mg/l

Exposure time: 48 h
Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

: NOEC (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h
Test Type: static test

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 Valvoline™ EARTH OPEN GEAR 3 GREASE

Version: 3.0 Revision Date: 29.03.2023 Print Date: 04/07/2023

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

12.2 Persistence and degradability

Components:

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 1.5 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Remarks: The toxicological data has been taken from

products of similar composition.

12.3 Bioaccumulative potential

Components:

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:

Partition coefficient: n-

octanol/water

: log Pow: 8.8 Remarks: QSAR

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting

potential

: The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological : An environmental hazard cannot be excluded in the event of

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 Valvoline™ EARTH OPEN GEAR 3 GREASE

Version: 3.0 Revision Date: 29.03.2023 Print Date: 04/07/2023

information unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Waste Code : The Waste code should be assigned in discussion between

the user and the waste disposal company.

The following Waste Codes are only suggestions:

13 02 05, mineral-based non-chlorinated engine, gear and

lubricating oils

SECTION 14: Transport information

14.1 UN number

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA_P : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA_P : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 Valvoline™ EARTH OPEN GEAR 3 GREASE

Version: 3.0 Revision Date: 29.03.2023 Print Date: 04/07/2023

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA_P : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA_P (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixtureRelevant EU provisions transposed through retained EU law

UK REACH Candidate list of substances of very high : Not applicable

concern (SVHC) for Authorisation

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great

Britain)

Not applicable

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

: Not applicable

UK REACH List of substances subject to authorisation

(Annex XIV)

Not applicable

Control of Major Accident Hazards Regulations

Not applicable

2015 (COMAH)

Valvoline_{TM}

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 Valvoline™ EARTH OPEN GEAR 3 GREASE

Version: 3.0 Revision Date: 29.03.2023 Print Date: 04/07/2023

The components of this product are reported in the following inventories:

TCSI : Not in compliance with the inventory

TSCA: Product contains substance(s) not listed on TSCA inventory.

AIIC : Not in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : Not in compliance with the inventory

NZIoC : Not in compliance with the inventory

15.2 Chemical safety assessment

No data available

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16: Other information

Full text of H-Statements

H228 : Flammable solid. H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H319 : Causes serious eve irritation.

H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Irrit. : Eye irritation
Flam. Sol. : Flammable solids
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 Valvoline™ EARTH OPEN GEAR 3 GREASE

Version: 3.0 Revision Date: 29.03.2023 Print Date: 04/07/2023

Materials: bw - Body weight: CLP - Classification Labelling Packaging Regulation: Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation: DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory: LC50 - Lethal Concentration to 50 % of a test population: LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose): MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level: NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Internal information: 000000276730

Classification of the mixture:

Classification procedure:

Aquatic Chronic 3 H412 Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



according to Regulation (EC) No. 1907/2006 Valvoline™ EARTH OPEN GEAR 3 GREASE

Version: 3.0 Revision Date: 29.03.2023 Print Date: 04/07/2023

GB / EN