according to 1907/2006/EC, Article 31

Printing date 29.04.2021 Version number 3 Revision: 29.04.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Cartechnic ZN-Phosphatgrund
- · **UFI:** PS30-F04J-T004-XS5E
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Priming
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Auto-Teile-Ring GmbH

Marie-Curie-Str. 3

73770 Denkendorf

Deutschland / Germany

Telefon: +49 (0)711 918979-0

info@cartechnic.de www.cartechnic.de

· 1.4 Emergency telephone number: Giftinformationszentrum Mainz - Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms









GHS02 GHS07

GHS08 GHS0

· Signal word Warning

(Contd. on page 2)

according to 1907/2006/EC, Article 31

Printing date 29.04.2021 Version number 3 Revision: 29.04.2021

Trade name: Cartechnic ZN-Phosphatgrund

(Contd. of page 1)

· Hazard-determining components of labelling:

Xvlene

Hydrocarbons, C9, aromatics

isobutanol

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

EUH208 Contains cobalt bis(2-ethylhexanoate), 2-Butanone oxime. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

	Dangerous components:		
Γ	CAS: 64742-95-6	Hydrocarbons, C9, aromatics	≥2.5-<15%
	EC number: 918-668-5	🚸 Flam. Liq. 3, H226; 🗞 Asp. Tox. 1, H304; 🌜 Aquatic	
	Reg.nr.: 01-2119455851-35	Čhronic 2, Ĥ411; 🔷 STŎT SĒ 3, H335-H336	
	CAS: 1330-20-7	Xylene	≥10-<15%
	EINECS: 215-535-7	♠ Flam. Liq. 3, H226; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ↑ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit.	
	Reg.nr.: 01-2119488216-32	H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit.	
		2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
	CAS: 7779-90-0	Trizinc bis(orthophosphate)	2.5-<10%
	EINECS: 231-944-3	4 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
	Reg.nr.: 01-2119485044-40		
_	•		(Contd. on page 3)

(Contd. on page 3)

according to 1907/2006/EC, Article 31

Printing date 29.04.2021 Version number 3 Revision: 29.04.2021

Trade name: Cartechnic ZN-Phosphatgrund

		(Contd. of page
CAS: 100-41-4	ethylbenzene	<2.5%
EINECS: 202-849-4	🚸 Flam. Liq. 2, H225; 🗞 STOT RE 2, H373; Asp. Tox. 1,	
Reg.nr.: 01-2119489370-35		
	2, H319; Aquatic Chronic 3, H412	
EC number: 919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2%	<2.5%
Reg.nr.: 01-2119463258-33	aromatics	
	♠ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♠ STOT SE 3, H336	
CAS: 78-83-1	isobutanol	≥1-<2.5%
EINECS: 201-148-0	🏇 Flam. Liq. 3, H226; 🥎 Eye Dam. 1, H318; 🕦 Skin Irrit.	
Reg.nr.: 01-2119484609-23		
EC number: 939-607-9	Quaternary ammonium compounds, C12-14 (even-	≥0.25-<1%
	numbered)-alkylethyldimethyl, ethyl sulphates	
	Acute Tox. 3, H311; 🔷 Skin Corr. 1C, H314; Eye Dam. 1,	
	H̃318; ♠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410;	
	♠ Acute Tox. 4, H302	
CAS: 96-29-7	2-Butanone oxime	≥0.1-<1%
EINECS: 202-496-6	♦ Carc. 2, H351; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4,	
Reg.nr.: 01-2119539477-28		
CAS: 1314-13-2	zinc oxide	<i>≥</i> 0.025-<0.25%
EINECS: 215-222-5	🕸 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
Reg.nr.: 01-2119463881-32	V 4,,,,,,,, -	
Additional information: For	the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

according to 1907/2006/EC, Article 31

Printing date 29.04.2021 Version number 3 Revision: 29.04.2021

Trade name: Cartechnic ZN-Phosphatgrund

(Contd. of page 3)

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with	limit values th	iat require m	nonitoring at t	he workplace:
--------------------	-----------------	---------------	-----------------	---------------

1330-20-7 Xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm

Long-term value: 441 mg/m³, 100 ppm

Sk

78-83-1 isobutanol

WEL Short-term value: 231 mg/m³, 75 ppm Long-term value: 154 mg/m³, 50 ppm

· Ingredients with biological limit values:

1330-20-7 Xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

(Contd. on page 5)

according to 1907/2006/EC, Article 31

Printing date 29.04.2021 Version number 3 Revision: 29.04.2021

Trade name: Cartechnic ZN-Phosphatgrund

(Contd. of page 4)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined. **Initial boiling point and boiling range:** 136 °C

• Flash point: 24 °C (DIN EN ISO 1523:2002)

· Flammability (solid, gas): Not applicable.

(Contd. on page 6)

Printing date 29.04.2021 Version number 3 Revision: 29.04.2021

Trade name: Cartechnic ZN-Phosphatgrund

	(Contd. of page 5
Ignition temperature:	450 °C (DIN 51794)
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
Explosion limits:	
Lower:	0.7 Vol %
Upper:	7.5 Vol %
Vapour pressure at 20 °C:	6.7-8.2 hPa
Density at 20 °C:	1.53 g/cm³ (DIN EN ISO 2811-1)
Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	95-105 s (DIN 53211/4)
· Solvent content:	
VOC (EC)	28.78 %
Solids content (weight-%):	71.5 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:		
64742-95	64742-95-6 Hydrocarbons, C9, aromatics		
Oral	LD50	>2,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rabbit)	
1330-20-2	1330-20-7 Xylene		
Oral	LD50	5,251 mg/kg (rat)	
Dermal	LD50	>5,000 mg/kg (rabbit)	(C +1 - T

(Contd. on page 7)

Printing date 29.04.2021 Version number 3 Revision: 29.04.2021

Trade name: Cartechnic ZN-Phosphatgrund

		(Contd. of page 6)	
Inhalative	LC50/4 h	29 mg/l (rat)	
7779-90-0	7779-90-0 Trizinc bis(orthophosphate)		
Oral	LD50	>5,000 mg/kg (rat)	
Quaternary ammonium compounds, C12-14 (even-numbered)-alkylethyldimethyl, ethyl sulphates			
Oral	LD50	>300-2,000 mg/kg (rat)	
Dermal	LD50	528 mg/kg (rabbit)	

- Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

(Contd. on page 8)

Printing date 29.04.2021 Version number 3 Revision: 29.04.2021

Trade name: Cartechnic ZN-Phosphatgrund

(Contd. of page 7)

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

· 14.1 UN-Number · ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name · ADR · IMDG	UN1263 PAINT, ENVIRONMENTALLY HAZARDOUS PAINT (Solvent naphtha, Trizinc bis(orthophosphate MARINE POLLUTANT
· IATA	PAINT
· 14.3 Transport hazard class(es)	
· ADR	
· Class · Label	3 (F1) Flammable liquids. 3
· IMDG	
Class	3 Flammable liquids.
· Label 	3
· IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Product contains environmentally hazardous substance Solvent naphtha
· Marine pollutant: · Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30 E E S E
· EMS Number: · Stowage Category	F-E, <u>S-E</u> A
· 14.7 Transport in bulk according to Annex II o	
Marpol and the IBC Code	Not applicable.

Printing date 29.04.2021 Version number 3 Revision: 29.04.2021

Trade name: Cartechnic ZN-Phosphatgrund

	(Contd. of page
· Transport/Additional information:	
· ADR	
· Transport category	3
· Tunnel restriction code	D/E
· Remarks:	≤ 5 l: 2.2.3.1.5 ADR
· IMDG	
· Limited quantities (LQ)	5L
Remarks:	≤ 5 l: 2.2.3.1.5 IMDG
· UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALL HAZARDOUS

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
I	<1
NK	25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

(Contd. on page 10)

Printing date 29.04.2021 Version number 3 Revision: 29.04.2021

Trade name: Cartechnic ZN-Phosphatgrund

(Contd. of page 9)

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category I

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* * Data compared to the previous version altered.