according to 1907/2006/EC, Article 31

Printing date 12.01.2023

Version number 3 (replaces version 2)

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Cartechnic Verlaufsmittel für Cartechnic 3000
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Paint additive
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Auto-Teile-Ring GmbH

Marie-Curie-Str. 3

73770 Denkendorf

Deutschland / Germany

Telefon: +49 (0)711 918979-0

info@cartechnic.de www.cartechnic.de

· 1.4 Emergency telephone number: Giftinformationszentrum Mainz - Tel.: +49 (6131) 19240

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



Acute Tox. 4 H332 Harmful if inhaled.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

5-methylhexan-2-one

· Hazard statements

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H361 Suspected of damaging fertility or the unborn child.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

(Contd. on page 2)

Revision: 12.01.2023

according to 1907/2006/EC, Article 31

Printing date 12.01.2023 Version number 3 (replaces version 2) Revision: 12.01.2023

#### Trade name: Cartechnic Verlaufsmittel für Cartechnic 3000

(Contd. of page 1)

*P103* Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

## · Dangerous components:

Additional information: For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

*In case of unconsciousness place patient stably in side position for transportation.* 

- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

50-100%

according to 1907/2006/EC, Article 31

Printing date 12.01.2023 Version number 3 (replaces version 2) Revision: 12.01.2023

Trade name: Cartechnic Verlaufsmittel für Cartechnic 3000

(Contd. of page 2)

- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

### SECTION 6: Accidental release measures

#### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 7: Handling and storage

#### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

## 110-12-3 5-methylhexan-2-one

WEL Short-term value: 475 mg/m³, 100 ppm Long-term value: 95 mg/m³, 20 ppm Sk

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

(Contd. on page 4)

according to 1907/2006/EC, Article 31

Printing date 12.01.2023 *Version number 3 (replaces version 2)* Revision: 12.01.2023

Trade name: Cartechnic Verlaufsmittel für Cartechnic 3000

(Contd. of page 3)

#### · Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### · Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Eye/face protection



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

· Odour: Characteristic Not determined. · Odour threshold: · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range

144 °C (110-12-3 5-methylhexan-2-one)

Flammable. · Flammability

· Lower and upper explosion limit

Not determined. · Lower: · Upper: Not determined.

36 °C (DIN EN ISO 1523:2002) · Flash point:

455 °C (DIN 51794) · Ignition temperature: · Decomposition temperature: Not determined. Not determined.  $\cdot pH$ 

· Viscosity:

12 s (DIN 53211/4) · Kinematic viscosity at 20 °C · Dynamic: Not determined.

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure at 20 °C: 5.3 hPa

Density and/or relative density

· Density at 20 °C: 0.812 g/cm³ (DIN EN ISO 2811-1)

· Relative density Not determined.

(Contd. on page 5)

according to 1907/2006/EC, Article 31

Printing date 12.01.2023 Version number 3 (replaces version 2) Revision: 12.01.2023

Trade name: Cartechnic Verlaufsmittel für Cartechnic 3000

Not determined. · Vapour density · 9.2 Other information · Appearance: · Form: Fluid Important information on protection of health and environment, and on safety. · Auto-ignition temperature: Product is not selfigniting. · Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible. · Solvent content: · VOC (EC) 100.00 % · Solids content (weight-%): 0.0% · Change in condition · Evaporation rate Not determined. · Information with regard to physical hazard classes · Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Flammable liquid and vapour. · Flammable solids Void · Self-reactive substances and mixtures Void Void · Pyrophoric liquids

Void

Void

Void

Void

Void

Void

Void

Void

# SECTION 10: Stability and reactivity

· Self-heating substances and mixtures

gases in contact with water

· Substances and mixtures, which emit flammable

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability

· Pyrophoric solids

· Oxidising liquids

Oxidising solidsOrganic peroxides

· Corrosive to metals

· Desensitised explosives

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

## SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Harmful if inhaled.

· LD/LC50 values relevant for classification:		
110-12-3 5-methylhexan-2-one		
Oral	LD50   3,200 mg/kg (rat)	

(Contd. on page 6)

(Contd. of page 4)

according to 1907/2006/EC, Article 31

Printing date 12.01.2023 Version number 3 (replaces version 2) Revision: 12.01.2023

Trade name: Cartechnic Verlaufsmittel für Cartechnic 3000

(Contd. of page 5)

Dermal LD50 10,000 mg/kg (rabbit)

- Reproductive toxicity Suspected of damaging fertility or the unborn child.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

## SECTION 14: Transport information

- · 14.1 UN number or ID number
- · ADR, IMDG, IATA UN1263
- · 14.2 UN proper shipping name
- · ADR UN1263 PAINT RELATED MATERIAL
- · IMDG, IATA PAINT RELATED MATERIAL
- · 14.3 Transport hazard class(es)
- $\cdot ADR$



Class 3 (F1) Flammable liquids.

(Contd. on page 7)

# **Safety data sheet** according to 1907/2006/EC, Article 31

Printing date 12.01.2023 *Version number 3 (replaces version 2)* Revision: 12.01.2023

Trade name: Cartechnic Verlaufsmittel für Cartechnic 3000

	(Contd. of pag
· Label	3
· IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
· EMS Number:	F-E, <u>S-E</u>
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IM	
instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Transport category	3
· Tunnel restriction code	<i>D/E</i>
· IMDG	
· Limited quantities (LQ)	5L
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III

# SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	50-100

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

(Contd. on page 8)

# **Safety data sheet** according to 1907/2006/EC, Article 31

Printing date 12.01.2023 Version number 3 (replaces version 2) Revision: 12.01.2023

Trade name: Cartechnic Verlaufsmittel für Cartechnic 3000

(Contd. of page 7)

H361 Suspected of damaging fertility or the unborn child.

## · Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4 Repr. 2: Reproductive toxicity – Category 2

\* \* Data compared to the previous version altered.