according to UK REACH Regulation

Cartechnic Brake-Cleaner + 5L 40 27289 04166 7

Revision date: 12.05.2022 Product code: 1106766 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Cartechnic Brake-Cleaner + 5L 40 27289 04166 7

UFI: 0CD4-W0UF-K00A-8788

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaner

1.3. Details of the supplier of the safety data sheet

Auto-Teile-Ring GmbH Company name: Street: Marie-Curie-Straße 3 Place: D-73770 Denkendorf Telephone: + 49 (0) 711/91 89 79-99 info@cartechnic.de e-mail·

111 NHS (National Health Service) 1.4. Emergency telephone

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3: H336 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane Acetone

Signal word:

Danger

Pictograms:









Hazard statements

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

according to UK REACH Regulation

Cartechnic Brake-Cleaner + 5L 40 27289 04166 7						
Revision date: 12.05.2022	Product code: 1106766	Page 2 of 12				
	smoking.					
P233	Keep container tightly closed.					
P243	Take action to prevent static discharges.					
P261	Avoid breathing vapours.					
P271	Use only outdoors or in a well-ventilated area.					
P273	Avoid release to the environment.					
P280	Wear protective gloves and eye/face protection.					
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.					
P331	Do NOT induce vomiting.					
P302+P352	IF ON SKIN: Wash with plenty of water.					
P332+P313	If skin irritation occurs: Get medical advice/attention.					
P304+P312	IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.					
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if					
	present and easy to do. Continue rinsing.					
P337+P313	If eye irritation persists: Get medical advice/attention.					
P403+P235	Store in a well-ventilated place. Keep cool.					

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity		
	EC No	Index No	REACH No			
	Classification (GB CLP Regulation)					
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, is	soalkanes, cyclics, < 5% n-hexane		50 - < 100 %		
	921-024-6		01-2119475514-35			
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411					
64-17-5	ethanol			25 - < 50 %		
	200-578-6	603-002-00-5	01-2119457610-43			
	Flam. Liq. 2, Eye Irrit. 2; H225 H319	9				
67-64-1	Acetone	Acetone				
	200-662-2	606-001-00-8	01-2119471330-49			
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066					

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc. Limits, M-factors and ATE				
92128-66-0	921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	50 - < 100 %		
	inhalation: LC50 = > 25,2 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = > 5000 mg/kg				
64-17-5	200-578-6	ethanol	25 - < 50 %		
	inhalation: LC50 = 95,6 mg/l (vapours); dermal: LD50 = >20000 mg/kg; oral: LD50 = 6200 mg/kg Eye Irrit. 2; H319: >= 50 - 100				
67-64-1	200-662-2	Acetone	10 - < 20 %		
	inhalation: LC5	0 = 76 mg/l (vapours); dermal: LD50 = 20000 mg/kg; oral: LD50 = 5800 mg/kg			

according to UK REACH Regulation

Cartechnic Brake-Cleaner + 5L 40 27289 04166 7

Revision date: 12.05.2022 Product code: 1106766 Page 3 of 12

Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

according to UK REACH Regulation

Cartechnic Brake-Cleaner + 5L 40 27289 04166 7

Revision date: 12.05.2022 Product code: 1106766 Page 4 of 12

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

Hints on joint storage

 $\label{thm:condition} \mbox{Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feeding stuffs.}$

Further information on storage conditions

Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

Cleaner

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL

according to UK REACH Regulation

Cartechnic Brake-Cleaner + 5L 40 27289 04166 7

Revision date: 12.05.2022 Product code: 1106766 Page 5 of 12

DNEL/DMEL values

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
92128-66-0 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane						
Worker DNEL, long-term		inhalation	systemic	2035 mg/m³		
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day		
Consumer DNEL, long-term		inhalation	systemic	608 mg/m³		
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day		
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day		

Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long-term exposure:

d before next shift

blood (B) Urine (U)

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.

EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min

Thickness of the glove material 0,45 mm

EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)...

Filtering device with filter or ventilator filtering device of type: A

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour: colorless, clear

according to UK REACH Regulation

Cartechnic Brake-Cleaner + 5L 40 27289 04166 7

Revision date: 12.05.2022 Product code: 1106766 Page 6 of 12

Odour: solvent like

Test method

Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and

56 °C

boiling range:

Flash point: -18 °C ISO 3679

Flammability

Solid/liquid: not applicable
Gas: not applicable

Explosive properties

The product is not: Explosive.

Lower explosion limits:1 vol. %Upper explosion limits:15 vol. %Auto-ignition temperature:not determinedDecomposition temperature:not determined

pH-Value (at 20 °C):

Viscosity / dynamic:

DIN 19268

DIN 53019-1

Viscosity / kinematic: DIN EN ISO 3104

(at 40 °C)

Flow time: DIN EN ISO 2431

(at 20 °C)

Water solubility:

The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: not determined

Density (at 20 °C): 0,7371 g/cm³ DIN 51757

Relative vapour density: not determined

9.2. Other information

Information with regard to physical hazard classes

Oxidizing properties

The product is not: oxidising.

Other safety characteristics

Solid content: not determined Evaporation rate: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.

10.2. Chemical stability

The product is stable under normal conditions.

according to UK REACH Regulation

Cartechnic Brake-Cleaner + 5L 40 27289 04166 7

Revision date: 12.05.2022 Product code: 1106766 Page 7 of 12

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
92128-66-0	Hydrocarbons, C6-C7, n	-alkanes, isoall	kanes, cyc	lics, < 5% n-hexane			
	oral	LD50 =	> 5000	Rat			
	dermal	LD50 > 3100 mg/kg	> 2800 -	Rat	Study report (1977)	The acute toxicity of SBP 100/140 was de	
	inhalation (4 h) vapour	LC50 >	> 25,2	Rat	Study report (1988)	Group of rats were exposed to test subst	
64-17-5	ethanol						
	oral	LD50 6	6200	Rat	IUCLID		
	dermal	LD50 =	>20000	Rat			
	inhalation (4 h) vapour	LC50 9	95,6 mg/l	Rat	RTECS		
67-64-1	Acetone						
	oral	LD50 t	5800	Rat			
	dermal	LD50 2 mg/kg	20000	Rabbit			
	inhalation (4 h) vapour	LC50	76 mg/l	Rat			

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

according to UK REACH Regulation

Cartechnic Brake-Cleaner + 5L 40 27289 04166 7

Revision date: 12.05.2022 Product code: 1106766 Page 8 of 12

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indications of human carcinogenicity exist.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No information available.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Special hazards arising from the substance or mixture!

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
92128-66-0	Hydrocarbons, C6-C7, n-	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane							
	Acute fish toxicity	LC50 mg/l	> 1-10	96 h	Pimephales promelas				
	Acute algae toxicity	ErC50 mg/l	10 - 30	72 h	Pseudokirchneriella subcapitata	Study report (1995)	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	> 1-10	48 h	Daphnia magna				
	Fish toxicity	NOEC mg/l	2,045	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a		
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211		
64-17-5	ethanol					•			
	Acute fish toxicity	LC50 mg/l	14200	96 h	Pimephales promelas (fathead minnow)				
	Acute crustacea toxicity	EC50 14221 mg	9268 - /I	48 h	Daphnia magna	IUCLID			
67-64-1	Acetone					•			
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss				
	Acute algae toxicity	ErC50 mg/l	5000	96 h	Desmodesmus subspicatus				
	Acute crustacea toxicity	EC50 mg/l	6100	48 h	Daphnia magna				

according to UK REACH Regulation

Cartechnic Brake-Cleaner + 5L 40 27289 04166 7

Revision date: 12.05.2022 Product code: 1106766 Page 9 of 12

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name					
	Method	Value	d	Source		
	Evaluation					
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane					
	OECD Guideline 301 F	98%	28			
	Easily biodegradable (concerning to the criteria of the OECD)					

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	3,4 - 5,2
64-17-5	ethanol	-0,31
67-64-1	Acetone	-0,24

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors:

chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors; hazardous waste

List of Wastes Code - used product

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors;

hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE

CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances;

hazardous waste

Contaminated packaging

Water (with cleaning agent). Completely emptied packages can be recycled.

according to UK REACH Regulation

Cartechnic Brake-Cleaner + 5L 40 27289 04166 7

Revision date: 12.05.2022 Product code: 1106766 Page 10 of 12

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C6-C7, n-alkanes,

isoalkanes, cyclics, < 5% n-hexane; Acetone)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1

Special Provisions: 274 601 640C

Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C6-C7, n-alkanes,

isoalkanes, cyclics, < 5% n-hexane; Acetone)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1

Special Provisions: 274 601 640C

Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C6-C7, n-alkanes,

isoalkanes, cyclics, < 5% n-hexane; Acetone)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Marine pollutant:yesSpecial Provisions:274Limited quantity:1 LExcepted quantity:E2EmS:F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C6-C7, n-alkanes,

isoalkanes, cyclics, < 5% n-hexane; Acetone)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:A3Limited quantity Passenger:1 LPassenger LQ:Y341Excepted quantity:E2

IATA-packing instructions - Passenger: 353

according to UK REACH Regulation

Cartechnic Brake-Cleaner + 5L 40 27289 04166 7

Revision date: 12.05.2022 Product code: 1106766 Page 11 of 12

IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes

Danger releasing substance: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC): No information available. 2004/42/EC (VOC): No information available.

Information according to 2012/18/EU

(SEVESO III):

Additional information: P5c

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

E2 Hazardous to the Aquatic Environment

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL: Workplace Exposure Limits
TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

ATEL (EC): Short Term Exposure Limit

LC50: Lethal Concentration

according to UK REACH Regulation

Cartechnic Brake-Cleaner + 5L 40 27289 04166 7

Revision date: 12.05.2022 Product code: 1106766 Page 12 of 12

EC50:half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)