



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 16

LOCTITE MR 5922 known as Loctite 5922

SDS No. : 153784
V004.1

Revision: 15.08.2022

printing date: 27.09.2023

Replaces version from: 16.06.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE MR 5922 known as Loctite 5922

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Sealant

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

ua-productsafety.uk@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Serious eye irritation

Category 2

H319 Causes serious eye irritation.

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

rosin

Signal word:	Warning
Hazard statement:	H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.
Supplemental information	EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.
Precautionary statement:	***** ***For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of contents/container in accordance with national regulation.***
Precautionary statement: Prevention	P280 Wear protective gloves.
Precautionary statement: Response	P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

None if used properly.
Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
This product contains modified rosin.

Following substances are present in a concentration $\geq 0,1\%$ and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in concentration $\geq$ the concentration limit that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
rosin 8050-09-7 232-475-7 01-2119480418-32	10- 20 %	Skin Sens. 1, H317		
Propan-2-ol 67-63-0 200-661-7 01-2119457558-25	10- 20 %	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336		
Titanium dioxide 13463-67-7 236-675-5 01-2119489379-17	1- < 5 %	Carc. 2, Inhalation, H351		

**For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

EYE: Irritation, conjunctivitis.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media**Suitable extinguishing media:**

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Scrape up as much material as possible.

Sweep up spilled material. Avoid creating dust.

Store in a partly filled, closed container until disposal.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Refer to Technical Data Sheet

7.3. Specific end use(s)

Sealant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Kaolin 1332-58-7 [KAOLIN, RESPIRABLE DUST]		2	Time Weighted Average (TWA):		EH40 WEL
Rosin 8050-09-7 [ROSIN-BASED SOLDER FLUX FUME]		0,05	Time Weighted Average (TWA):		EH40 WEL
Rosin 8050-09-7 [ROSIN-BASED SOLDER FLUX FUME]		0,15	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Propan-2-ol 67-63-0 [PROPAN-2-OL]	400	999	Time Weighted Average (TWA):		EH40 WEL
Propan-2-ol 67-63-0 [PROPAN-2-OL]	500	1.250	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Kaolin 1332-58-7 [KAOLIN]		2	Time Weighted Average (TWA):		IR_OEL
Rosin 8050-09-7 [ROSIN CORE SOLDER PYROLYSIS PRODUCTS]		0,05	Time Weighted Average (TWA):		IR_OEL
Rosin 8050-09-7 [ROSIN CORE SOLDER PYROLYSIS PRODUCTS]		0,15	Short Term Exposure Limit (STEL):	15 minutes	IR_OEL
Propan-2-ol 67-63-0 [ISOPROPYL ALCOHOL]	200		Time Weighted Average (TWA):		IR_OEL
Propan-2-ol 67-63-0 [ISOPROPYL ALCOHOL]			Skin designation:	Can be absorbed through the skin.	IR_OEL
Propan-2-ol 67-63-0 [ISOPROPYL ALCOHOL]	400		Short Term Exposure Limit (STEL):	15 minutes	IR_OEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		10	Time Weighted Average (TWA):		IR_OEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		4	Time Weighted Average (TWA):		IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
rosin 8050-09-7	aqua (freshwater)		0,002 mg/l				
rosin 8050-09-7	aqua (marine water)		0,0002 mg/l				
rosin 8050-09-7	sediment (freshwater)				0,007 mg/kg		
rosin 8050-09-7	sediment (marine water)				0,001 mg/kg		
rosin 8050-09-7	Soil				0 mg/kg		
rosin 8050-09-7	sewage treatment plant (STP)		1000 mg/l				
rosin 8050-09-7	aqua (intermittent releases)		0,016 mg/l				
Propan-2-ol 67-63-0	aqua (freshwater)		140,9 mg/l				
Propan-2-ol 67-63-0	aqua (marine water)		140,9 mg/l				
Propan-2-ol 67-63-0	sediment (freshwater)				552 mg/kg		
Propan-2-ol 67-63-0	sediment (marine water)				552 mg/kg		
Propan-2-ol 67-63-0	Soil				28 mg/kg		
Propan-2-ol 67-63-0	aqua (intermittent releases)		140,9 mg/l				
Propan-2-ol 67-63-0	sewage treatment plant (STP)		2251 mg/l				
Propan-2-ol 67-63-0	oral				160 mg/kg		
Titanium dioxide 13463-67-7	Predator						no potential for bioaccumulation

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
rosin 8050-09-7	Workers	inhalation	Long term exposure - local effects		10 mg/m3	
rosin 8050-09-7	Workers	dermal	Long term exposure - systemic effects		2,131 mg/kg	
rosin 8050-09-7	General population	dermal	Long term exposure - systemic effects		1,065 mg/kg	
rosin 8050-09-7	General population	oral	Long term exposure - systemic effects		1,065 mg/kg	
Propan-2-ol 67-63-0	Workers	dermal	Long term exposure - systemic effects		888 mg/kg	
Propan-2-ol 67-63-0	Workers	inhalation	Long term exposure - systemic effects		500 mg/m3	
Propan-2-ol 67-63-0	General population	dermal	Long term exposure - systemic effects		319 mg/kg	
Propan-2-ol 67-63-0	General population	inhalation	Long term exposure - systemic effects		89 mg/m3	
Propan-2-ol 67-63-0	General population	oral	Long term exposure - systemic effects		26 mg/kg	
Titanium dioxide 13463-67-7	Workers	inhalation	Long term exposure - local effects		10 mg/m3	no potential for bioaccumulation
Titanium dioxide 13463-67-7	General population	oral	Long term exposure - systemic effects		700 mg/kg	no potential for bioaccumulation

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Dust mask, P2 particle filter.

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	solid
Delivery form	paste
Colour	black
Odor	characteristic
Solidification temperature	Not applicable, Product is a solid.
Initial boiling point	82 °C (179.6 °F)None
Flammability	Currently under determination
Explosive limits	Currently under determination
Flash point	Product is a solid. (ASTM D 4359)
Auto-ignition temperature	Not applicable, Product is a solid.
Decomposition temperature	Currently under determination
pH	Not applicable
Viscosity (kinematic)	Not applicable, Product is a solid.
Viscosity, dynamic	500.000 - 700.000 mPa.s LCT STM 10; Viscosity
(Brookfield; Instrument: RVT; 25 °C (77 °F);	Brookfield
speed of rotation: 5 min-1; Spindle No: 7)	
Solubility (qualitative)	Partially soluble
(23 °C (73.4 °F); Solvent: Water)	
Partition coefficient: n-octanol/water	Currently under determination
Vapour pressure	33 mm hg
(20 °C (68 °F))	
Density	1,5 g/cm3 None
(25 °C (77 °F))	
Relative vapour density:	2,07
Particle characteristics	Currently under determination

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used properly.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

None if used properly.

SECTION 11: Toxicological information**1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
rosin 8050-09-7	LD50	2.800 mg/kg	rat	not specified
Propan-2-ol 67-63-0	LD50	5.840 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Titanium dioxide 13463-67-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
rosin 8050-09-7	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Propan-2-ol 67-63-0	LD50	12.870 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Titanium dioxide 13463-67-7	LD50	> 10.000 mg/kg	rabbit	not specified

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Titanium dioxide 13463-67-7	LC50	> 6,82 mg/l	dust	4 h	rat	not specified

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
rosin 8050-09-7	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Propan-2-ol 67-63-0	slightly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Titanium dioxide 13463-67-7	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
rosin 8050-09-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Propan-2-ol 67-63-0	Category II		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Titanium dioxide 13463-67-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Propan-2-ol 67-63-0	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Titanium dioxide 13463-67-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Titanium dioxide 13463-67-7	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
rosin 8050-09-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propan-2-ol 67-63-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Propan-2-ol 67-63-0	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Titanium dioxide 13463-67-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Titanium dioxide 13463-67-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Titanium dioxide 13463-67-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Titanium dioxide 13463-67-7	negative	in vitro mammalian cell micronucleus test	without		equivalent or similar to OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
Propan-2-ol 67-63-0	negative	intraperitoneal		mouse	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Titanium dioxide 13463-67-7	negative	oral: gavage		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Propan-2-ol 67-63-0		inhalation: vapour	104 w 6 h/d, 5 d/w	rat	male/female	OECD Guideline 451 (Carcinogenicity Studies)
Titanium dioxide 13463-67-7	not carcinogenic	oral: feed	103 w daily	rat	male/female	not specified

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Propan-2-ol 67-63-0	NOAEL P 853 mg/kg	One generation study	oral: drinking water	rat	equivalent or similar to OECD Guideline 415 (One- Generation Reproduction Toxicity Study)
Propan-2-ol 67-63-0	NOAEL P 500 mg/kg NOAEL F1 1.000 mg/kg	Two generation study	oral: gavage	rat	equivalent or similar to OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
Titanium dioxide 13463-67-7	NOAEL P >= 1.000 mg/kg NOAEL F1 >= 1.000 mg/kg	one- generation study	oral: feed	rat	OECD Guideline 443 (Extended One-Generation Reproductive Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Propan-2-ol 67-63-0		inhalation: vapour	at least 104 w 6 h/d, 5 d/w	rat	OECD Guideline 451 (Carcinogenicity Studies)
Titanium dioxide 13463-67-7	NOAEL > 1.000 mg/kg	oral: gavage	92 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Propan-2-ol 67-63-0	1,8 mm ² /s	40 °C	ASTM Standard D7042	

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
rosin 8050-09-7	LC50	Toxicity > Water solubility	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Propan-2-ol 67-63-0	LC50	> 9.640 - 10.000 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Titanium dioxide 13463-67-7	LC50	Toxicity > Water solubility	48 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
rosin 8050-09-7	EL50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Propan-2-ol 67-63-0	NOEC	30 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Titanium dioxide 13463-67-7	NOEC	Toxicity > Water solubility	21 d	Daphnia magna	OECD Guideline 202 (Daphnia sp. Chronic Immobilisation Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
rosin 8050-09-7	EL50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
rosin 8050-09-7	NOELR	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	EC50	> 1.000 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	NOEC	1.000 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide 13463-67-7	NOEC	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
rosin 8050-09-7	EC20	Toxicity > Water solubility	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Propan-2-ol 67-63-0	EC50	> 1.000 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Titanium dioxide 13463-67-7	EC0	Toxicity > Water solubility	24 h	Pseudomonas fluorescens	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
rosin 8050-09-7	readily biodegradable	aerobic	71 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Propan-2-ol 67-63-0	readily biodegradable	aerobic	70 - 84 %	30 d	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
rosin 8050-09-7	> 3 - 6,2		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Propan-2-ol 67-63-0	0,05		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
rosin 8050-09-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Propan-2-ol 67-63-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Titanium dioxide 13463-67-7	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information**14.1. UN number**

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): Not applicable

Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): Not applicable

Persistent organic pollutants (Regulation (EU) 2019/1021): Not applicable

VOC content 27,8 %
(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H225 Highly flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.