

Version: 3
Date of issue: 30.01.2024
Number of updates: 0
Data of updates: -

1 of 7

Page number:

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Trade name: CONCENTRATE MS-G11+

1.2. Relevant identified uses of the substance/mixture and uses advised against

Recommended use: Filling the cooling system of internal combustion engines after dilution with water

1.3. Details of the supplier of the safety data sheet

Company: Master-Sport Automobiltechnik (MS) Production-Distribution Center

ul. 11 Listopada 68, 38-300 Gorlice, Poland

Tel.: +48 18 35 35 475 sekretariat@master-sport.com.pl

www.master-sport.de

1.4. Emergency telephone number: 112 (general emergency number), 998 (fire department), 999 (medical emergency)

SECTION 2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Product classification:

Acute Tox. 4, H302, STOT RE 2, H373

Please consult chapter 16 of this SDS for full text of mentioned H phrases.

Physical and chemical hazards:

none.

Human health hazards:

- harmful if swallowed
- may cause damage to organs through prolonged or repeated exposure.

Environmental hazards:

- none.

2.2. Label elements

Hazard pictograms:





Signal Word: WARNING

H Phrases:

H302 Harmful if swallowed

H373 May cause damage to organs through prolonged or repeated exposure

P Phrases:

P102 Keep out of reach of children

P260 Do not breathe vapours/ spray

P264 Wash hands thoroughly after handling

P270 Do not eat, drink or smoke when using this product

P301+P312 IF SWALLOWED: Call a POISON CENTRE/ doctor if you feel unwell

P314 Get medical advice/attention if you feel unwell

P501 Dispose of contents/container to hazardous or special waste collection point

Contents: Ethane-1,2-diol

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB at concentration equal to or greater than 0,1% by weight. The mixture does not contain components considered to have endocrine disrupting properties at levels of 0.1% or higher.



Version: 3

Date of issue: 30.01.2024

Number of updates: 0
Data of updates: Page number: 2 of 7

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

N.A.

3.2. Mixtures

94.0% - 95.0% Ethane-1.2-diol

Index No: 603-027-00-1 CAS No: 107-21-1 EC No: 203-473-3

REACH No: 01-2119456816-28-0004 Acute Tox. 4, H302, STOT RE 2, H373

< 0.4% Potassium hydroxide

Index No: 019-002-00-8 CAS No: 1310-58-3 EC No: 215-181-3

REACH No: 01-2119487136-33-XXXX

Met. Corr. 1, H290, Acute Tox. 4, H302, Skin Corr. 1A, H314

Specific Conc. Limits: Skin Corr. 1A; H314: C ≥ 5%; Skin Corr. 1B; H314: 2% ≤ C < 5%; Skin Irrit. 2; H315: 0.5% ≤

C < 2%; Eye Irrit. 2; H319: $0.5\% \le C < 2\%$

< 0.4% Dipotassium tetraborate

Index No: – CAS No: 12045-78-2 EC No: 215-575-5

Repr. 2, H361d

Please consult chapter 16 of this SDS for full text of mentioned H phrases.

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

In case of Inhalation:

- remove to open air, keep person warm and calm
- if breathing is irregular or stopped, administer artificial respiration
- in case of accident or unwellness, consult a doctor immediately and show him packing or label.

In case of skin contact:

- immediately take off all contaminated clothing
- immediately wash with plenty of water
- if irritation persists, obtain immediate medical attention
- wash contaminated clothing separately before using them again.

In case of eyes contact:

- remove contact lenses, if present
- irrigate copiously with clean, fresh water form at least 15 minutes, protect the clean eye from dirt
- if irritation persists, obtain immediate medical attention.

In case of Ingestion:

- rinse mouth thoroughly with water
- induce vomiting only if indicated by the doctor
- give nothing by mouth to an unconscious person
- get medical attention if any discomfort continues
- show this safety data sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

- suitable extinguishing media: chemical powders (ABC or BC type), CO₂, foam, nebulized water
- extinguishing media which must not be used for safety reasons: water jet

5.2. Special hazards arising from the substance or mixture

- do not inhale explosion and combustion gases
- burning produces heavy smoke (CO, CO₂)
- cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk
- cool containers exposed to flames with water until well after the fire is out.

5.3. Advice for firefighters

- use suitable breathing apparatus



Version: 3
Date of issue: 30.01.2024
Number of updates: 0

Data of updates: –
Page number: 3 of 7

- collect contaminated fire extinguishing water separately. This must not be discharged into drains
- move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

- wear personal protection equipment
- remove all sources of ignition
- evacuate area
- provide adequate ventilation
- use appropriate respiratory protection.

6.2. Environmental precautions

- do not allow to enter into soil/subsoil; do not allow to enter into surface water or drains
- retain contaminated washing water and dispose it
- in case entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

- immediately remove the product using appropriate personal protective equipment
- eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage
- retain contaminated washing water and dispose it
- contain and collect spillage with non-combustible, absorbent material e.g. sand or earth
- flush contaminated area with plenty of water.

6.4. Reference to other sections

See also section 8 and 13.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

- use localized ventilation system
- do not smoke, do not use matches or lighters
- avoid breathing vapor
- avoid contact with eyes and skin
- wear personal protection equipment
- keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
- do not eat or drink while working, keep away from food, drink and feed, keep out of reach of children.

7.2. Conditions for safe storage, including any incompatibilities

- always keep the containers tightly closed, in a dry, cool and well-ventilated place (under 40 °C)
- keep only in the original container
- keep containers upright
- keep away from food, drink and feed
- keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
- cool and adequately ventilated
- do not store with incompatible substances (see section 10).

7.3. Specific end use(s)

See section 1.2.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limit values:

Ethane-1,2-diol:

LTEL/8h: 20 ppm - 52 mg/m³ (Skin) STEL: 40 ppm - 104 mg/m³ (Skin)

DNEL - Ethane-1,2-diol:

Application Area Exposure routes Health effect Value 106 mg/kg BW/d Workers Skin contact Long-term systemic effects Workers Inhalation Long-term local effects 35 mg/m³ Long-term systemic effects 53 mg/kg BW/d Consumers Skin contact Long-term local effects 7 mg/m³ Consumers Inhalation

PNEC - Ethane-1,2-diol:

CompartmentValueFresh water10 mg/lMarine water1 mg/l



Version: 3
Date of issue: 30.01.2024
Number of updates: 0

Data of updates: 0
Page number: 4 of 7

Aquatic intermittent release 10 mg/l
Fresh water sediment 20.9 mg/kg
Soil 1.53 mg/kg
Sewage treatment plant 199.5 mg/l

8.2. Exposure controls

Eye protection:

- if possible exposure use close fitting safety goggles, masks suitable for the product
- adequate ventilation of the room where the product is stored or worked with
- tight devices and pipelines, avoiding product spills
- keep the product away from sources of open flame.

Protection for skin and hands:

use protective gloves, protective clothing (rubberized apron and safety shoes). The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

Respiratory protection:

- use adequate protective respiratory equipment
- good ventilation is essential when handling this material do not breathe vapour
- in case of mist or spray exposure wear suitable personal respiratory protection (breathing mask) and protective suit.

Thermal Hazards:

None.

Environmental exposure controls:

- do not allow to enter into soil/subsoil; do not allow to enter into surface water or drains.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

(a) Physical state: homogeneous liquid, without sediments

(b) Colour: various (c) Odour: N.A.

(d) Melting point/freezing point: -37 °C (after dilution with water 1:1)

(e) Boiling point or initial boiling point and boiling range: > 100 °C

(f) Flammability:
N.A.
(g) Lower and upper explosion limit:
N.A.
3.2% vol./15.3% vol. (Ethane-1,2-diol)

(h) Flash point: > 60 °C

(i) Auto-ignition temperature: 398 °C (Ethane-1,2-diol)

(j) Decomposition temperature:

(k) pH:

(l) Kinematic viscosity:

N.A.

N.A.

(m) Solubility: soluble in water

(n) Partition coefficient n-octanol/water (log value): -1.36 (Ethane-1,2-diol)

(o) Vapour pressure: N.A.

(p) Density and/or relative density: 1.100-1.120 g/cm³

(g) Relative vapour density: 2.14 (Air = 1) (Ethane-1,2-diol)

(r) Particle characteristics: Not applicable

9.2. Other information

Other solvents: alcohol, acetone, ether.

Dynamic viscosity: 16.1 mPas (20 °C) (Ethane-1,2-diol)

Critical temperature: 446 °C (Ethane-1,2-diol)

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

N.A.

10.4. Conditions to avoid

- keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
- avoid accumulating electrostatic charge.



Version: 30.01.2024 Date of issue: Number of updates: 0 Data of updates:

5 of 7

Page number:

10.5. Incompatible materials

strong oxidizing

strong bases and acids.

10.6. Hazardous decomposition products

None.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

a) Acute toxicity:

Harmful if swallowed.

Mixture:

Oral: 300 < ATEmix ≤ 2000 (mg/kg bodyweight)

Ethane-1,2-diol:

Oral: Rat LD₅₀ 7112 mg/kg Skin: Rat $LD_{50} > 3500 \text{ mg/kg}$ Inhalation: Rat $LC_{50} > 2.5 \text{ mg/l}$

Potassium hydroxide:

Rat LD₅₀ 333-388 mg/kg Oral:

<u>Dipotassium tetraborate:</u>

Oral: Rat LD₅₀ 3690 mg/kg

Rabbit LD₅₀ 2000-5000 mg/kg Skin:

Inhalation: Rat $LC_{50} > 2 \text{ g/m}^3/4\text{h}$

b) Skin corrosion/irritation:

N.A.

c) Serious eye damage/irritation:

N.A.

d) Respiratory or skin sensitization:

e) Germ cell mutagenicity: NΑ

f) Carcinogenicity: N.A.

g) Reproductive toxicity:

h) STOT-single exposure:

i) STOT-repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

j) Aspiration hazard:

N.A.

11.2. Information on other hazards:

None.

SECTION 12. **ECOLOGICAL INFORMATION**

Adopt good working practices, so that the product is not released into the environment. Prevent product entering water courses, sewers and prevent penetration of the product into the earth.

12.1. Toxicity:

N.A.

Ethane-1.2-diol:

EC₅₀: 13 900-57 600 mg/l - toxicity to Daphnia magna, 48h

EC₅₀: 6 500-13 000 mg/l – toxicity to algae Pseudokirchneriella subcapitata, 96h

LC₅₀: 72 860 mg/l - toxicity to fish Pimephales promelas, 96h NOEC: 15 380 mg/l - toxicity to fish Pimephales promelas, 7d

Dipotassium tetraborate:

LC₅₀: 80-627 mg/l - toxicity to fish

EC₅₀: 133 mg/l - toxicity to Daphnia magna

12.2. Persistence and degradability:

N.A.

Ethane-1,2-diol - this substance is easily biodegradable



Version: 3
Date of issue: 30.01.2024
Number of updates: 0
Data of updates: -

6 of 7

Page number:

12.3. Bioaccumulative potential:

N.A.

Potassium hydroxide - Partition coefficient n-octanol/water: 0.65

12.4. Mobility in soil:

N.A.

Ethane-1,2-diol - it is not adsorbed in the solid phase of the soil

12.5. Results of PBT and vPvB assessment:

On the basis of available data, the product does not contain any PBT or vPvB at concentration equal to or greater than 0,1% by weight.

12.6. Endocrine disrupting properties:

The mixture does not contain components considered to have endocrine disrupting properties at levels of 0.1% or higher.

12.7. Other adverse effects:

Information not available.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods:

Reuse, when possible. Product residues should be considered special hazardous waste. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. TRANSPORT INFORMATION

14.1.	UN number or ID number:	N.A.
14.2.	UN proper shipping name:	N.A.
14.3.	Transport hazard class(es):	N.A.
14.4.	Packing group:	N.A.
14.5.	Environmental hazards:	N.A.
14.6.	Special precautions for user:	N.A.
14.7.	Maritime transport in bulk according to IMO instruments:	N.A.

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- 1. REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing
- 2. REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC
- 3. COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. OTHER INFORMATION

This document was prepared by a competent person who has received appropriate training. This safety data sheet has been prepared on the basis of data provided by the manufacturer.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This document must not be regarded as a guarantee on any specific product property

ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

IMDG: International Maritime Code for Dangerous Goods.

EC₅₀: Half maximal effective concentration

LC₅₀: Lethal concentration, for 50 percent of test population.



Version: 3
Date of issue: 30.01.2024
Number of updates: 0
Data of updates: –

7 of 7

Page number:

LD₅₀: Lethal dose, for 50 percent of test population.

STOT: Specific Target Organ Toxicity

Acute Tox. 4 Acute toxicity 4

Eye Irrit. 2 Serious eye damage/eye irritation 2
Met. Corr. 1 Substance or mixture corrosive to metals 1

Repr. 2 Reproductive toxicity 2 Skin Corr. 1A Skin corrosion/irritation 1A Skin Corr. 1B Skin corrosion/irritation 1B Skin Irrit. 2 Skin corrosion/irritation 2

STOT RE 2 Specific target organ toxicity — repeated exposure 2

Full text of phrases referred to in Section 3:

H290 May be corrosive to metals H302 Harmful if swallowed

H314 Causes severe skin burns and eye damage

H315 Causes skin irritation

H319 Causes serious eye irritation

H361d Suspected of damaging the unborn child

H373 May cause damage to organs through prolonged or repeated exposure

Updating the card is caused by a change in the chemical composition of the product, by a change in section 8.1, 9.1, 11.1, 12.1, 12.3, 16 and change of regulatory information.

This document was prepared by: Master-Sport Automobiltechnik (MS) Production-Distribution Center

sekretariat@master-sport.com.pl

www.master-sport.de