Page 1/11

*

*



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.11.2019

Version number 7

Revision: 01.10.2019

1.1 Product identifier	
Trade name: <u>DUPLI</u> -	COLOR GLITTER SPRAY gold / silver transparent
No further relevant inj Sector of Use	d uses of the substance or mixture and uses advised against formation available.
SU22 Professional u. Product category PC9	s: Private households / general public / consumers ses: Public domain (administration, education, entertainment, services, craftsmen) Da Coatings and paints, thinners, paint removers
Process category PROC7 Industrial sp PROC11 Non industri	rial spraying
	bstance / the mixture Lacquer
Manufacturer/Supplie	
MOTIP DUPLI GmbH Kurt Vogelsang Strass	
D-74855 Haßmersheit	
Tel.: +49/6266/75-0	
msds@de.motipdupli.o	com
1.4 Emergency teleph Tel.:+49 6266-75-310)
$Fax +49\ 6266-75-362$	2)4:00 pm, Fr 08:00 am - 00:30 pm)
(110 11 00:00 um 0	1.00 pm, 17 00.00 um 00.00 pm)
SECTION 2. Har	ando idoutification
	ards identification
ů ů	he substance or mixture
	ing to Regulation (EC) No 1272/2008
GHS02 flam	ne
Aerosol 1 H222-H2	29 Extremely flammable aerosol. Pressurised container: May burst if heated.
GHS07	
	Causes serious eye irritation.
Eye Irrit. 2 H319	
•	May cause drowsiness or dizziness.
<i>Eye Irrit.</i> 2 <i>H319</i> <i>STOT SE 3 H336</i> 2.2 Label elements	May cause drowsiness or dizziness.

Page 2/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.11.2019

Version number 7

Revision: 01.10.2019

Trade name: DUPLI-COLOR GLITTER SPRAY gold / silver transparent

	(Contd. of page
Hazard p	ictograms
$\mathbf{\wedge}$	▲
JH.	
<u>9</u>	
GHS02	GHS07
GH502	00307
Signal we	ord Danger
Hazard-d	letermining components of labelling:
acetone	
n-butyl ad	cetate
2-methox	y-1-methylethyl acetate
Hazard s	
H222-H2	29 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
Precautio	onary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.
P410+P4	12 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents / container in accordance with regional regulations.
Additiond	al information:
EUH066	Repeated exposure may cause skin dryness or cracking.
	f explosive mixtures possible without sufficient ventilation.
2.3 Other	
Results of	f PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

*

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220 Press. Gas (Comp.), H280	12.5-<20%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane Flam. Gas 1, H220 Press. Gas (Comp.), H280	12.5-<20%
		(Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.11.2019

Version number 7

Revision: 01.10.2019

Trade name: DUPLI-COLOR GLITTER SPRAY gold / silver transparent

		(Contd. of page 2)
CAS: 123-86-4	n-butyl acetate	10-<12.5%
EINECS: 204-658-1	🚸 Flam. Liq. 3, H226	
Index number: 607-025-00-1	(1) STOT SE 3, H336	
Reg.nr.: 01-2119485493-29		
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	5-<10%
EINECS: 203-603-9	🚸 Flam. Liq. 3, H226	-
Index number: 607-195-00-7	(1) STOT SE 3, H336	
Reg.nr.: 01-2119475791-29		
CAS: 75-28-5	isobutane	5-<10%
EINECS: 200-857-2	🚸 Flam. Gas 1, H220	-
Index number: 601-004-00-0	Press. Gas (Comp.), H280	
Reg.nr.: 01-2119485395-27		
CAS: 9004-70-0	cellulose nitrate	2.5-<5%
	🚸 Flam. Sol. 1, H228	-
EC number: 905-588-0	xylene	<2.5%
Index number: 601-022-00-9	🚸 Flam. Liq. 3, H226	-
Reg.nr.: 01-2119488216-32	🚯 STOT RÊ 2, H373; Asp. Tox. 1, H304	
	Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315;	
	<i>Eye Irrit. 2, H319; STOT SE 3, H335</i>	
CAS: 64-17-5	ethanol	<2.5%
EINECS: 200-578-6	🚸 Flam. Liq. 2, H225	-
Index number: 603-002-00-5	() Eye Irrit. 2, H319	
Reg.nr.: 01-2119457610-43		

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply. xylene: Contains ethylbenzene CAS 100-41-4

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- General information: Take affected persons out into the fresh air.
- \cdot After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

*

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire extinguishing methods suitable to surrounding conditions.

- · 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -

• Protective equipment:

Wear self-contained respiratory protective device. Do not inhale explosion gases or combustion gases.

(Contd. on page 4)

GB

Page 4/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.11.2019

Version number 7

Revision: 01.10.2019

Trade name: DUPLI-COLOR GLITTER SPRAY gold / silver transparent

Mouth respiratory protective device.

(Contd. of page 3)

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Keep away from ignition sources. Ensure adequate ventilation Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.
 • 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight. Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air). Ensure good ventilation/exhaustion at the workplace.

- Information about fire and explosion protection: Fumes can combine with air to form an explosive mixture. Keep ignition sources away - Do not smoke. Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:

• Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Storage class: 2 B
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

(Contd. on page 5)

G

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.11.2019

Version number 7

Revision: 01.10.2019

Trade name: DUPLI-COLOR GLITTER SPRAY gold / silver transparent

100 4	(Contd. of page
	5-6 2-methoxy-1-methylethyl acetate
WEL	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm
	Sk
xylen	2
WEL	Short-term value: 441 mg/m³, 100 ppm
	Long-term value: 220 mg/m³, 50 ppm
	Sk; BMGV
64-17	-5 ethanol
WEL	Long-term value: 1920 mg/m³, 1000 ppm
Ingre	dients with biological limit values:
xylen	-
•	V 650 mmol/mol creatinine
DinO	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid
1 1 1:+	ional information: The lists valid during the making were used as basis.
Auuu	onal information. The fists valia during the making were used as basis.
	cposure controls
	nal protective equipment:
	al protective and hygienic measures:
	t eat, drink, smoke or sniff while working.
	away from foodstuffs, beverages and feed.
	diately remove all soiled and contaminated clothing
	hands before breaks and at the end of work.
	t inhale gases / fumes / aerosols.
	contact with the eyes and skin.
	contact with the eyes.
	ratory protection:
	ecessary if room is well-ventilated.
	e of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposu
	lf-contained respiratory protective device.
	ction of hands:
	e of contact with spray dust protective gloves made of butyl shoud be used (min. 0.4 mm thick), e.g.
	Camatril, article no. 898 or similar products
	nt resistant gloves o missing tests no recommendation to the glove material can be given for the product/ the preparation
	o missing tests no recommendation to the glove material can be given for the product/ the preparation. emical mixture.
	love material has to be impermeable and resistant to the product/ the substance/ the preparation.
	ion of the glove material on consideration of the penetration times, rates of diffusion and the
	dation
	ial of gloves
	rubber, BR
	election of the suitable gloves does not only depend on the material, but also on further marks of quali
	aries from manufacturer to manufacturer. As the product is a preparation of several substances, the
	ance of the glove material can not be calculated in advance and has therefore to be checked prior to the
	ration.
	ration time of glove material
	rubber gloves with a thickness of 0.4 mm are resistant to:
	meser gloves min a mexicos of our min are resistant to: me: 480 min
	acetate: 60 min
-	acetate: 170 min
	ne: 42 min
•	xact break through time has to be found out by the manufacturer of the protective gloves and has to be
	ved.
onser	

Page 6/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.11.2019

Version number 7

Revision: 01.10.2019

Trade name: DUPLI-COLOR GLITTER SPRAY gold / silver transparent

- (Contd. of page 5) · For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable: Natural rubber, NR
- · Eye protection:



*

Tightly sealed goggles

· Body protection: Light weight protective clothing

9.1 Information on basic physical and c	hemical properties	
General Information		
Appearance:	A 7	
Form:	Aerosol	
Colour: Odour:	Silver grey Characteristic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range	e: Not applicable, as aerosol.	
Flash point:	Not applicable, as aerosol.	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	333 °C (631.4 °F)	
Decomposition temperature:	Not determined.	
Explosive properties:	Not determined.	
Explosion limits:		
Lower:	1.2 Vol %	
Upper:	13 Vol %	
Vapour pressure at 20 $^{\circ}C$ (68 $^{\circ}F$):	8300 hPa (6225.5 mm Hg)	
Density at 20 °C (68 °F):	0.8 g/cm ³ (6.7 lbs/gal)	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	91.5 %	
VOC (EC)		
	731.9 g/l	
VOC-EU%	91.48 %	
Solids content:	7.7 %	

Page 7/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.11.2019

Version number 7

Revision: 01.10.2019

Trade name: DUPLI-COLOR GLITTER SPRAY gold / silver transparent

(Contd. of page 6)

• 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:		
67-64-1 ac	67-64-1 acetone		
Oral	LD50	5800 mg/kg (rat)	
Dermal	LD50	>15800 mg/kg (rabbit)	
Inhalative	LC50/4h	76 mg/l (rat)	
123-86-4 n	123-86-4 n-butyl acetate		
Oral	LD50	10800 mg/kg (rat) (OECD 401)	
Dermal	LD50	>17600 mg/kg (rabbit)	
Inhalative	LC50/4 h	>21 mg/m3 (rat)	
108-65-62	108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	8530 mg/kg (rat)	
Dermal	LD50	>5000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>10000 mg/m3 (rat)	
xylene			
Oral	LD50	3523 mg/kg (rat)	
Dermal	LD50	2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	29000 mg/m3 (rat)	
64-17-5 eti	hanol	•	
Oral	LD50	10470 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rat)	
Inhalative	LC50/4h	120 mg/l (rat)	

· Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

• Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

• Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 8)

GB

Page 8/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.11.2019

Version number 7

Revision: 01.10.2019

Trade name: DUPLI-COLOR GLITTER SPRAY gold / silver transparent

(Contd. of page 7)

· Aspiration hazard Based on available data, the classification criteria are not met.

· 12.1 Toxicity

• Aquatic toxicity:

67-64-1 acetone

LC50/96h 8300 mg/l (fish)

EC50/96h 7200 mg/l (algae)

LC50/48 h 8450 mg/l (crustacean (water flea))

108-65-6 2-methoxy-1-methylethyl acetate

EC50/48 h >500 mg/l (daphnia magna)

LC50 / 96 h 100-180 mg/l (oncorhynchus mykiss / Regenbogenforelle)

xylene

EC50 / 48 h 7.4 mg/l (daphnia magna)

LC50/96 h 13.5 mg/l (fish)

64-17-5 ethanol

LC50/96h 13000 mg/l (oncorhynchus mykiss / Regenbogenforelle)

EC50/48 h 12900 mg/l (algae)

LC50 / 48 h 12340 mg/l (daphnia magna)

· 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- $\cdot \textit{Additional ecological information:}$
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European	waste	catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

15 01 04 metallic packaging

15 01 10* packaging containing residues of or contaminated by hazardous substances

• Uncleaned packaging:

• Recommendation:

Dispose of packaging according to regulations on the disposal of packagings. Non contaminated packagings may be recycled.

(Contd. on page 9)

Page 9/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.11.2019

Version number 7

Revision: 01.10.2019

Trade name: DUPLI-COLOR GLITTER SPRAY gold / silver transparent

(Contd. of page 8)

· 14.1 UN-Number	
ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
· IMDG, IATA	
· Class	2.1
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	not regulated
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 li
	Category A. For AEROSOLS with a maximum capacity of 1 ii Category A. For AEROSOLS with a capacity above 1 li
	Category B. For WASTE AEROSOLS: Category C, Cle
	of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 li.
	Segregation as for class 9. Stow "separated from" class
	except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class
14.7 Transport in bulk according to Ann Marpol and the IBC Code	e x II of Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (\widetilde{EQ})	Code: E0
-	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D

Page 10/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.11.2019

Version number 7

Revision: 01.10.2019

Trade name: DUPLI-COLOR GLITTER SPRAY gold / silver transparent

		(Contd. of page 9)
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity	
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

 \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

 \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

• REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

• Information about limitation of use: Employment restrictions concerning juveniles must be observed.

· Other regulations, limitations and prohibitive regulations

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H228 Flammable solid. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

(Contd. on page 11)

GB

Page 11/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.11.2019

Version number 7

Revision: 01.10.2019

(Contd. of page 10)

Trade name: DUPLI-COLOR GLITTER SPRAY gold / silver transparent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases - Category 1 Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Flam. Sol. 1: Flammable solids – Category 1 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 \cdot * Data compared to the previous version altered.

GB -