

Safety Data Sheet

according to Commission Regulation (EU) 2020/878 as amended

ENGINE FLUSH

TEC-2000 LTD.

P. O. BOX 285, HERTS., SG4 9WQ, Hitchin, U.K.

info@TEC-2000.co.uk

01462-433 660 01462-674 468 FAX: MOB: 07831-105 386

PH:

Version Number: 21	Revision date: 21-November-2023
SECTION 1: Identification of the substan	ce/mixture and of the company/undertaking
1.1 Product identifier	TEC-2000 ENGINE FLUSH
Substance / mixture	mixture
UFI:	6000-A0PG-V007-2K48
1.2 Relevant identified uses of the substa	ance or mixture and uses advised against
Mixture's intended use	-
Cleaner for lubrication system of interna	l combustion engines.
Main intended use	·
PC-CLN-OTH	Other cleaning, care and maintenance products (excludes biocidal products)
Mixture uses advised against	
The product should not be used in ways	other than those referred in Section 1.
1.3 Details of the supplier of the safety da	
Manufacturer:	
Name or trade name	TEC-2000 LIMITED
Address	PO Box 285, Hitchin, Hertfordshire, SG4 9WQ, United Kingdom
VAT Reg No	GB626640834
Phone	+44 (0) 1462 433 660
E-mail	mike@tec-2000.co.uk
Web address	www.tec-2000.co.uk
Competent person responsible for th	
Name	TEC-2000 LIMITED
E-mail	mike@tec-2000.co.uk
1.4 Emergency telephone number	<u>1111Ke(@tec-2000.co.uk</u>
0044 (Ø) 7831 105386 (24hrs)	
NHS Direct: 111	
	e (NPIS): 0344 892 0111 (healthcare professionals only).
	entre (NPIC): (01) 809 2566 (healthcare professionals only).
SECTION 2: Hazards identification	
21 Classification of the cubetenes of the	
2.1 Classification of the substance or mix	
Classification according to Regulatio	
Classification according to Regulatio The mixture is classified as dangerous	
Classification according to Regulatio The mixture is classified as dangerous Flam. Liq. 3, H226	
Classification according to Regulatio The mixture is classified as dangerous Flam. Liq. 3, H226 Asp. Tox. 1, H304	
Classification according to Regulatio The mixture is classified as dangerous Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315	
Classification according to Regulatio The mixture is classified as dangerous Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319	
Classification according to Regulatio The mixture is classified as dangerous Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335, H336	
Classification according to Regulatio The mixture is classified as dangerous Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335, H336 Repr. 2, H361d	
Classification according to Regulatio The mixture is classified as dangerous Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335, H336 Repr. 2, H361d STOT RE 2, H373	
Classification according to Regulatio The mixture is classified as dangerous Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335, H336 Repr. 2, H361d	
Classification according to Regulatio The mixture is classified as dangerous Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335, H336 Repr. 2, H361d STOT RE 2, H373	n (EC) No 1272/2008
Classification according to Regulatio The mixture is classified as dangerous Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335, H336 Repr. 2, H361d STOT RE 2, H373 Aquatic Chronic 2, H411	n (EC) No 1272/2008 statements is given in the section 16.
Classification according to Regulatio The mixture is classified as dangerous Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335, H336 Repr. 2, H361d STOT RE 2, H373 Aquatic Chronic 2, H411 Full text of all classifications and hazard	n (EC) No 1272/2008 statements is given in the section 16.
Classification according to Regulatio The mixture is classified as dangerous Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335, H336 Repr. 2, H361d STOT RE 2, H373 Aquatic Chronic 2, H411 Full text of all classifications and hazard Most serious adverse physico-chemi	n (EC) No 1272/2008 statements is given in the section 16. cal effects
Classification according to Regulatio The mixture is classified as dangerous Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335, H336 Repr. 2, H361d STOT RE 2, H373 Aquatic Chronic 2, H411 Full text of all classifications and hazard Most serious adverse physico-chemi Flammable liquid and vapour Most serious adverse effects on hum	n (EC) No 1272/2008 statements is given in the section 16. cal effects an health and the environment
Classification according to Regulatio The mixture is classified as dangerous Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335, H336 Repr. 2, H361d STOT RE 2, H373 Aquatic Chronic 2, H411 Full text of all classifications and hazard Most serious adverse physico-chemi Flammable liquid and vapour Most serious adverse effects on hum May be fatal if swallowed and enters air	n (EC) No 1272/2008 statements is given in the section 16. cal effects an health and the environment ways. May cause respiratory irritation. May cause drowsiness or dizziness.
Classification according to Regulatio The mixture is classified as dangerous Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335, H336 Repr. 2, H361d STOT RE 2, H373 Aquatic Chronic 2, H411 Full text of all classifications and hazard Most serious adverse physico-chemi Flammable liquid and vapour Most serious adverse effects on hum May be fatal if swallowed and enters ain May cause damage to organs through pr	n (EC) No 1272/2008 statements is given in the section 16. cal effects an health and the environment ways. May cause respiratory irritation. May cause drowsiness or dizziness. olonged or repeated exposure. Suspected of damaging the unborn child. Causes skin irritation. Causes
Classification according to Regulatio The mixture is classified as dangerous Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335, H336 Repr. 2, H361d STOT RE 2, H373 Aquatic Chronic 2, H411 Full text of all classifications and hazard Most serious adverse physico-chemi Flammable liquid and vapour Most serious adverse effects on hum May be fatal if swallowed and enters ain May cause damage to organs through pr serious eye irritation. Toxic to aquatic life	n (EC) No 1272/2008 statements is given in the section 16. cal effects an health and the environment ways. May cause respiratory irritation. May cause drowsiness or dizziness. olonged or repeated exposure. Suspected of damaging the unborn child. Causes skin irritation. Causes
Classification according to Regulatio The mixture is classified as dangerous Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335, H336 Repr. 2, H361d STOT RE 2, H373 Aquatic Chronic 2, H411 Full text of all classifications and hazard Most serious adverse physico-chemi Flammable liquid and vapour Most serious adverse effects on hum May be fatal if swallowed and enters air May cause damage to organs through pr serious eye irritation. Toxic to aquatic life 2.2 Label elements	n (EC) No 1272/2008 statements is given in the section 16. cal effects an health and the environment ways. May cause respiratory irritation. May cause drowsiness or dizziness. olonged or repeated exposure. Suspected of damaging the unborn child. Causes skin irritation. Causes
Classification according to Regulatio The mixture is classified as dangerous Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335, H336 Repr. 2, H361d STOT RE 2, H373 Aquatic Chronic 2, H411 Full text of all classifications and hazard Most serious adverse physico-chemi Flammable liquid and vapour Most serious adverse effects on hum May be fatal if swallowed and enters ain May cause damage to organs through pr serious eye irritation. Toxic to aquatic life	n (EC) No 1272/2008 statements is given in the section 16. cal effects an health and the environment ways. May cause respiratory irritation. May cause drowsiness or dizziness. olonged or repeated exposure. Suspected of damaging the unborn child. Causes skin irritation. Causes
Classification according to Regulatio The mixture is classified as dangerous Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335, H336 Repr. 2, H361d STOT RE 2, H373 Aquatic Chronic 2, H411 Full text of all classifications and hazard Most serious adverse physico-chemi Flammable liquid and vapour Most serious adverse effects on hum May be fatal if swallowed and enters air May cause damage to organs through pr serious eye irritation. Toxic to aquatic life 2.2 Label elements	n (EC) No 1272/2008 statements is given in the section 16. cal effects an health and the environment ways. May cause respiratory irritation. May cause drowsiness or dizziness. olonged or repeated exposure. Suspected of damaging the unborn child. Causes skin irritation. Causes
Classification according to Regulatio The mixture is classified as dangerous Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335, H336 Repr. 2, H361d STOT RE 2, H373 Aquatic Chronic 2, H411 Full text of all classifications and hazard Most serious adverse physico-chemi Flammable liquid and vapour Most serious adverse effects on hum May be fatal if swallowed and enters air May cause damage to organs through pr serious eye irritation. Toxic to aquatic life 2.2 Label elements	n (EC) No 1272/2008 statements is given in the section 16. cal effects an health and the environment ways. May cause respiratory irritation. May cause drowsiness or dizziness. olonged or repeated exposure. Suspected of damaging the unborn child. Causes skin irritation. Causes
Classification according to Regulatio The mixture is classified as dangerous Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335, H336 Repr. 2, H361d STOT RE 2, H373 Aquatic Chronic 2, H411 Full text of all classifications and hazard Most serious adverse physico-chemi Flammable liquid and vapour Most serious adverse effects on hum May be fatal if swallowed and enters air May cause damage to organs through pr serious eye irritation. Toxic to aquatic life 2.2 Label elements	n (EC) No 1272/2008 statements is given in the section 16. cal effects an health and the environment ways. May cause respiratory irritation. May cause drowsiness or dizziness. olonged or repeated exposure. Suspected of damaging the unborn child. Causes skin irritation. Causes





Registered office: Second Floor, 2 Walsworth Road, Hitchin, Hertfordshire, SG4 9SP Registered in England No. 460 8392

Signal word: Danger

Hazardous substances

Hydrocarbons, C9, Aromatics

toluene	
Hazard statements	
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects
Precautionary statem	nents:
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands and exposed parts of the body thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a doctor
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
D240	Continue rinsing.
P312 P321	Call a POISON CENTER/doctor if you feel unwell
P321 P331	Specific treatment (see additional first aid instructions on this label). Do NOT induce vomiting.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/container to according to local/by regional/according to national/by international regulations
Supplemental inform	

Supplemental information

>=30 % aromatic hydrocarbons, <5 % non-ionic surfactants

Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger. Container must be fitted with child-resistant fastening.

2.3 Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical characterization Mixture.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name		Classification according to Regulation (EC) No 1272/2008	Note
CAS: 64742-95-6	Petroleum Light aromatic C9	50-100	Flam. Liq. 3, H226	
EC: 918-668-5			Asp. Tox. 1, H304	
Registration number:			STOT SE 3, H335, H336	
01-2119455851-35-XXXX			Aquatic Chronic 2, H411	

Version Number: 21

TEC-2000 Engine Flush

Revision date: 21-November-2023

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 601-021-00-3 CAS: 108-88-3 EC: 203-625-9 Registration number: 01-2119471310-51-XXXX	toluene	10-<20	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Repr. 2, H361d STOT RE 2, H373 Aquatic Chronic 3, H412	2, 3
CAS: 51-03-6 EC: 200-076-7 Registration number: 01-2119537431-46- XXXX	1,3-Benzodioxole, 5-[[2-(2- butoxyethoxy) ethoxy]methyl]-6-propyl-	<10	Acute Tox. 3, H311 Aquatic Chronic 2, H411	
CAS: 68515-88-8 EC: 271-114-8 Registration number: 01-2120263350-66- XXXX	Pentene, 2,4,4-trimethyl-, sulfurized	<2,5	not classified as dangerous	
CAS: 27247-96-7 EC: 248-363-6 Registration number: 01-2119539586-27- XXXX	2-ethylhexyl nitrate	<2,5	Acute Tox. 4, H302+H312+H332 Aquatic Chronic 2, H411	
Index: 006-025-00-3 CAS: 28434-00-6 EC: 249-013-5	(S)-3-allyl-2-methyl-4-oxocyclopent-2- enyl (1R,3R)-2,2-dimethyl-3-(2-methylprop-1- enyl)cyclopropanecarboxylate	<1	Acute Tox. 4, H302+H332 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	1
Index: 649-424-00-3 CAS: 64742-94-5 EC: 265-198-5 Registration number: 01-2119510128-50- XXXX	Solvent naphtha (petroleum), heavy arom.	<1	Asp. Tox. 1, H304 Resp. Sens. 1, H334	
Index: 601-052-00-2 CAS: 91-20-3 EC: 202-049-5 Registration number: 01-2119561346-37- XXXX	naphthalene	<0,25	Acute Tox. 4, H302 Carc. 2, H351 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	2

Notes

1- Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

2- Substance with a Union workplace exposure limit

3- The use of the substance is restricted by Annex XVII of REACH Regulation.

Full text of all classifications and hazard statements is given in the section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

Do not perform artificial respiration without self-protection (e.g. a mask). Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

Version Number: 21	TEC-2000 Engine Flush	Revision date: 21-November-2023
--------------------	-----------------------	---------------------------------

If inhaled

Take care of your own safety, do not let the affected person walk! Terminate the exposure immediately; move the affected person to fresh air. Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible. **If swallowed**

If the affected person vomits, make sure to prevent inhalation of the vomit (as there is a danger of lung damage after inhalation of these liquids in the airways also in infinitesimal amount). Ensure medical treatment considering the frequent need of further observation for at least 24 hours. Bring an original container with the label and the Safety Data Sheet of the given substance as appropriate.

4.2 Most important symptoms and effects, both acute and delayed

If inhaled

Cough, headache. May cause respiratory irritation. May cause drowsiness or dizziness.

If on skin Causes skin irritation.

If in eyes Causes serious eye irritation.

If swallowed

Irritation, nausea.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting Measures

5.1 Extinguishing media

Suitable extinguishing agents:

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3 Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

6.2 Environmental precautions:

Do not allow to enter drains. Prevent contamination of the soil and entering surface or ground water.

6.3 Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4 Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling:

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. No smoking. Obtain special instructions before use. Wash hands and exposed parts of the body thoroughly after handling. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges. Avoid release to the environment.

7.2 Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

7.3 Specific end use(s):

not available

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union

Substance name (component)	Туре	Value	Note
	OEL 8 hours	192 mg/m³	
toluono (CAS: 109.99.2)	OEL 8 hours	50 ppm	Skin
toluene (CAS: 108-88-3)	OEL 15 minutes	384 mg/m ³	SKII
	OEL 15 minutes	100 ppm	

Commission Directive 2006/15/EC

Commission Directive 91/322/FFC

European Union

Substance name (component)	Туре	Value	Note	
naphthalene (CAS: 91-20-3)	OEL 8 hours	50 mg/m³		
	OEL 8 hours	10 ppm		

DNEL

2-ethylhexyl nitrate

Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Dermal	1 mg/kg bw/day	Systemic chronic effects		
Workers	Inhalation	0.35mg/m³	Systemic chronic effects		
Workers	Dermal	0.044 mg/cm ²	Local acute effects		

PNEC

2-ethylhexyl nitrate

Route of exposure	Value	Value determination	Source
Drinking water	0.8 µg/l		
Seawater	0.08 μg/l		
Freshwater sediment	0.74 μg/l		

8.2 Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection Protective goggles. **Skin protection**

Hand protection: Protective gloves resistant to the product. (eg. PVC gloves, Nitrile rubber, NBR) EN ISO 374-1. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Contaminated skin should be washed thoroughly.

Respiratory protection

Mask with a filter against organic vapours in a poorly ventilated environment.

Thermal hazard

Data not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2. Collect spillage.

SECTION 9: Physical And Chemical Properties

9.1 Information on basic physical and chemical propert	ies
Physical state	liquid
Colour	green
Odour	after solvents
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	110 °C
Flammability	data not available

le
le
water)
le
ļ

10.2 Chemical stability

The product is stable under normal conditions.

- 10.3 Possibility of hazardous reactions:
- Unknown.

10.4 Conditions to avoid:

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

- 10.5 Incompatible materials:
- Strong oxidizing agents. Water. **10.6 Hazardous decomposition products:**

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire. Hydrogen sulphide.

SECTION 11: Toxicological Information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture. Acute toxicity

Based on available data the classification criteria are not met. 1.3-Benzodioxole, 5-[[2-(2-butoxyethoxy)ethoxy]methyl]-6-propyl-

Route of exposure	Parameter	Value	Exposure time	Species	Sex		
Oral	LD ₅₀	7181 mg/kg		Rat			
Dermal	LD ₅₀	>2000 mg/kg		Rabbit			
Inhalation	LC ₅₀	>5.9 mg/l	4 hour	Rat			

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Dermal	LD ₅₀	>4820 mg/kg		Rabbit	
Oral	LD_{50}	>9640 mg/kg		Rat	
naphthalene	•		•	•	

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD ₅₀	490 mg/kg		Rat	
Dermal	LD ₅₀	5000 mg/kg		Rabbit	
toluene					

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD ₅₀	5000 mg/kg		Rat	
Dermal	LD ₅₀	12124 mg/kg		Rabbit	
Inhalation	LC ₅₀	5320 mg/l	4 hour	Mouse	

Skin corrosion/irritation Causes skin irritation. Serious eye damage/irritation Causes serious eye irritation. Respiratory or skin sensitisation

2.2 Persistence and degradability: Biodegradability Petroleum light aromatic C9 Parameter Value Exposure time Envi >60 % 28 day Image: Second S	
Acute toxicity Toxic to aquatic life with long lasting effects. Petroleum light aromatic C9 Parameter Value Exposure time Spe EC_50 3.2 mg/l 48 hour Da 2.2 Persistence and degradability: Biodegradability Petroleum light aromatic C9 Parameter Value Exposure time Envi Parameter Value Exposure time Envi 2.3 Bioaccumulative potential: >60 % 28 day The mixture is biodegradable. 2.3 Bioaccumulative potential: Data not available. 2.4 Mobility in soil: Data not available. 2.4 Mobility in soil: Data not available. 2.5 Results of PBT and vPvB assessment Product does not contain any substance meeting the criteria for PBT or vPvB in accordance 1907/2006 (REACH) as amended 2.6 Endocrine disrupting properties: not available 2.7 Other adverse effects Data not available ECTION 13: Disposal Considerations 3.1 Waste treatment methods Hazard of environmental contamination; dispose of the waste in accordance with the local a with valid regulations on waste disposal. Any unused product and contaminated packagir collection and submitted for disposal to a person authorised for waste removal (a specializint ot empty unused product in drainage systems. The product must not b	
Parameter Value Exposure time Spe EC ₅₀ 3.2 mg/l 48 hour Da 2.2 Persistence and degradability: Biodegradability Petroleum light aromatic C9 Exposure time Envi Parameter Value Exposure time Envi >60 % 28 day Envi State The mixture is biodegradable. 2.3 Bioaccumulative potential: Data not available. Data not available. 2.4 Mobility in soil: Data not available. 2.5 Results of PBT and vPvB assessment Product does not contain any substance meeting the criteria for PBT or vPvB in accordance 1907/2006 (REACH) as amended 2.6 Endocrine disrupting properties: not available 2.7 Other adverse effects Data not available 3.1 Waste treatment methods Hazard of environmental contamination; dispose of the waste in accordance with the local a with valid regulations on waste disposal. Any unused product and contaminated packagir collection and submitted for disposal to a person authorised for waste removal (a specializ not empty unused product in drainage systems. The product must not be disposed of with at waste incinerators to produce energy or deposited in a dump with appropriate classificatig for recycling.	
EC ₅₀ 3.2 mg/l 48 hour Date 2.2 Persistence and degradability: Biodegradability Petroleum light aromatic C9 Exposure time Envi Parameter Value Exposure time Envi >60 % 28 day The mixture is biodegradable. 2.3 Bioaccumulative potential: Data not available. 2.3 Bioaccumulative potential: Data not available. 2.4 Mobility in soil: Data not available. 2.5 Results of PBT and vPvB assessment Product does not contain any substance meeting the criteria for PBT or vPvB in accordance 1907/2006 (REACH) as amended 2.6 Endocrine disrupting properties: not available not available 2.7 Other adverse effects Data not available 2.5 3.1 Waste treatment methods 4.3 montal contamination; dispose of the waste in accordance with the local a with valid regulations on waste disposal. Any unused product and contaminated packagir collection and submitted for disposal to a person authorised for waste removal (a specializ not empty unused product in drainage systems. The product must not be disposed of with at waste incinerators to produce energy or deposited in a dump with appropriate classificatio for recycling.	s Environment
2.2 Persistence and degradability: Biodegradability Petroleum light aromatic C9 Parameter Value Exposure time Envi >60 % 28 day Image: Comparison of the state of the	nnia
 Data not available. 2.4 Mobility in soil: Data not available. 2.5 Results of PBT and vPvB assessment Product does not contain any substance meeting the criteria for PBT or vPvB in accordance 1907/2006 (REACH) as amended 2.6 Endocrine disrupting properties: not available 2.7 Other adverse effects Data not available ECTION 13: Disposal Considerations 3.1 Waste treatment methods Hazard of environmental contamination; dispose of the waste in accordance with the local a with valid regulations on waste disposal. Any unused product and contaminated packagir collection and submitted for disposal to a person authorised for waste removal (a specializ not empty unused product in drainage systems. The product must not be disposed of with at waste incinerators to produce energy or deposited in a dump with appropriate classificatio for recycling. 	nment Result Biodegradable
3.1 Waste treatment methods Hazard of environmental contamination; dispose of the waste in accordance with the local a with valid regulations on waste disposal. Any unused product and contaminated packagir collection and submitted for disposal to a person authorised for waste removal (a specializ not empty unused product in drainage systems. The product must not be disposed of with at waste incinerators to produce energy or deposited in a dump with appropriate classification for recycling.	vith the Annex XIII of Regulation (EC) No
Hazard of environmental contamination; dispose of the waste in accordance with the local a with valid regulations on waste disposal. Any unused product and contaminated packagir collection and submitted for disposal to a person authorised for waste removal (a specializ not empty unused product in drainage systems. The product must not be disposed of with at waste incinerators to produce energy or deposited in a dump with appropriate classification for recycling.	
Waste management legislation Directive 2008/98/EC of the European Parliament and of the Council of 19 November 200 establishing a list of wastes, as amended.	should be put in labelled containers for waste d company) that is entitled for such activity. Do unicipal waste. Empty containers may be used Perfectly cleaned containers can be submitted
ECTION 14: Transport Information 4.1 UN Number or ID number	

- 14.2 UN proper shipping name FLAMMABLE LIQUID, N.O.S. (Petroleum light aromatic C9, toluene)
 14.3 Transport hazard class(es) 3 Flammable liquids
 14.4 Packing group II substances presenting medium danger

	sion Number: 21	TEC-2000 Engine Flush	Revision date: 21-November-20
.5	Environmental hazards:		
6	not relevant Special precautions for	lisor	
.0	not available	user	
.7		Ik according to IMO instruments	
••	not relevant		
	Additional information:		
	Hazard identification No.	33	
	UN number	1993	
	Classification code	F1 3+hazardous for the environment	
	Safety signs		
		3	
	Road transport - ADR		
	Special provisions	274, 601	
	Limited quantities Excepted quantities	5 L E1	
	Packaging	El	
	Packing instructions	P001, IBC03, LP01, R001	
	Mixed packing provisions	MP19	
	Portable tanks and bulk		
	Guidelines	T4	
	Special provisions ADR tank	TP1, TP29	
	Tank code	LGBF	
	Vehicles for tank carriage	FL	
	Transport category	3	
	Tunnel restriction code Special provision for	(D/E)	
	packages	V12	
	operation	S2	
	Railway transport - RID		
	Special provisions	274, 601	
	Excepted quantities	E1	
	Packaging		
	Packing instructions	P001, IBC03, LP01, R001	
	Mixed packing provisions	MP19	
	Portable tanks and bulk	containers	
	Guidelines	Τ4	
	Special provisions	TP1, TP29	
	RID Tanks		
	Tank code	LGBF	
	Transport category	0	
	Special provision for		
	packages	W 12	
	Marine transport - IMDG		
	EmS (emergency plan)	F-E, S-E	
	MFAG	310	

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended. TEC-2000 Engine Flush

REGULATION (EC) No 648/2004 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 31 March 2004 on detergents, as amended.

Restrictions pursuant to Annex XVII of Regulation (EC) No. 1907/2006 (REACH), as amended

toluene	
Restriction	Conditions of restriction
48	Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

15.2 Chemical safety assessment:

not available

SECTION 16: Other Information.

A list of standard ris	k phrases used in the safety data sheet
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H302+H332	Harmful if swallowed or if inhaled.
H302+H312+H332	Harmful if swallowed, in contact with skin or if inhaled.
	nandling used in the safety data sheet
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P271	Use only outdoors or in a well-ventilated area.
P301+P310	IF SWALLOWED: Immediately call a doctor.
P331	Do NOT induce vomiting.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/container to according to local/by regional/according to national/by international regulations.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands and exposed parts of the body thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P321	Specific treatment (see additional first aid instructions on this label).
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue
F 303+F 331+F 330	rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P362+P364	Take off contaminated clothing and wash it before reuse.
P332+P313	If skin irritation occurs: Get medical advice/attention.
Other important info	rmation about human health protection
The product must not	be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1.
The user is responsib	le for adherence to all related health protection regulations.
Key to abbreviations	s and acronyms used in the safety data sheet
ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
DNEL	Derived no-effect level
EC ₅₀	Concentration of a substance when it is affected 50% of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
	Page 0 / 10

Version Number: 21		TEC-2000 Engine Flush	Revision date: 21-November-2023			
ES	Identificati	ion code for each substance listed in EINECS				
EU	European	Union				
EuPCS	European Product Categorisation System					
IATA		International Air Transport Association				
IBC		nal Code For The Construction And Equipment of Ships Carrying Dangerous Ch	emicals			
ICAO		nal Civil Aviation Organization				
IMDG		nal Maritime Dangerous Goods				
INCI		nal Nomenclature of Cosmetic Ingredients				
ISO		nal Organization for Standardization				
IUPAC		nal Union of Pure and Applied Chemistry				
LC ₅₀		ncentration of a substance in which it can be expected death of 50% of the popu	lation			
LD ₅₀		se of a substance in which it can be expected death of 50% of the population				
log Kow		vater partition coefficient				
MARPOL		nal Convention for the Prevention of Pollution from Ships				
OEL		nal Exposure Limits				
PBT		t, Bioaccumulative and Toxic				
PNEC		no-effect concentration				
ppm	Parts per					
REACH		on, Evaluation, Authorisation and Restriction of Chemicals				
RID		nt on the transport of dangerous goods by rail	ulationa			
UN		e identification number of the substance or article taken from the UN Model Reg				
UVCB VOC		es of unknown or variable composition, complex reaction products or biological i	naterials			
vOC vPvB		ganic compounds				
Acute Tox.	Acute toxi	istent and very Bioaccumulative				
Aquatic Acute		s to the aquatic environment				
Aquatic Acute		s to the aquatic environment (chronic)				
Asp. Tox.	Aspiration					
Carc.	Carcinoge					
Eye Irrit.	Eye irritati					
Flam. Liq.	Flammable liquid					
Repr.	Reproductive toxicity					
Resp. Sens.						
Skin Irrit.	Skin irritat					
STOT RE Specific target organ toxicity - repeated exposure						
STOT SE		arget organ toxicity - single exposure				

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product. Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.

REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 2.0 replaces the SDS version from 06.08.2021. Change of product composition.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.