

## **Safety Data Sheet**

according to Regulation (EC)
No 1907/2006 (REACH) as amended

# INDUCTION CLEANER (Diesel & Petrol)

TEC-2000 LTD.

P. O. BOX 285, Hitchin, HERTS., SG4 9WQ, U.K.

info@TEC-2000.co.uk

PH: 01462-433 660 FAX: 01462-674 468 MOB: 07831-105 386

Version Number: 09 Revision Date: 01-May-2023

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product Identifier TEC2000 INDUCTION CLEANER

Substance / mixture mixture

UFI H000-A0PG-V008-2157

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

## Mixture's intended use

Aerosol Cleaning induction tract in Diesel and Petrol internal Combustion Engines.

Main intended use

PC-CLN-OTH Other cleaning, care and maintenance products (excludes biocidal products)

The use descriptors

PC 35 Washing and cleaning products

Mixture uses advised against

The product should not be used in ways other then those referred in Section 1.

## 1.3 Details of the supplier of the safety data sheet

## Manufacturer

Name or trade name TEC-2000 LIMITED

Address PO Box 285, Hitchin, Hertfordshire, SG4 9WQ, United Kingdom

VAT Reg No GB111112414

Phone +44 (0) 1462 433 660

E-mail mike@tec-2000.co.uk

Web address www.tec-2000.co.uk

Competent person responsible for the safety data sheet

Name TEC-2000 LIMITED E-mail mike@tec-2000.co.uk

## 1.4 Emergency telephone number

0044 (Ø) 7831 105386 (24hrs)

NHS Direct: 111

UK-National Poisons Information Service (NPIS): 0344 892 0111 (healthcare professionals only). Ireland - National Poisons Information Centre (NPIC): (01) 809 2566 (healthcare professionals only).

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

## Classification of the mixture in accordance with Regulation (EC) 1272/2008

The mixture is classified as dangerous.

The mixture is classified as dangerous.

Aerosol 1, H222, H229

Asp. Tox. 1, H304

Skin Irrit. 2, H315

Eye Dam. 1 H318

STOT SE 3 H336, H335

Aquatic Chronic 2 H411

Full text of all classifications and hazard statements is given in the section 16.

## Most serious adverse physico-chemical effects

Extremely flammable aerosol. Pressurised container: May burst if heated.

## Most serious adverse effects on human health and the environment

May cause drowsiness or dizziness. May cause respiratory irritation. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye damage. Toxic to aquatic life with long lasting effects.





## 2.2 Label elements Hazard pictograms:









Signal word:

Danger

## Hazardous substances Petroleum Light aromatic C9

acetone propan-2-ol

poly(oxy-1,2-ethanediyl),  $\alpha$ -tridecyl- $\omega$ -hydroxy-

#### Hazard statements:

H222- Extremely flammable aerosol

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H318 Causes serious eye damage.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

## Precautionary statements:

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P391 Collect spillage. P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C.

P501 Dispose of contents/container to by handing over to the person authorized to dispose of waste or by returning to the

supplier

## Supplemental information

>=30 % aliphatic hydrocarbons, 15-<30 % aromatic hydrocarbons, <5 % non-ionic surfactants

## 2.3 Other hazards:

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

## **SECTION 3: Composition/information on ingredients**

## 3.2 Mixtures

## Chemical characterization

Mixture of substances and additives specified below.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
CAS: 64742-95-6 EC: 918-668-5 Registration number: 01- 2119455851-35- XXXX	Petroleum Light aromatic C9	32,5	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335, H336 Aquatic Chronic 2, H411	
Index: 606-001-00-8 CAS: 67-64-1 EC: 200-662-2 Registration number: 01- 2119471330-49- XXXX	acetone	23,5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	2
Index: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 Registration number: 01- 2119457558-25- XXXX	propan-2-ol	22,5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	

}	<b>TEC-2000</b> Induction Cleaner (Diesel & Petrol)	Revision Date: 01-May-2023
---	---	----------------------------

Identification numbers	Kilhetanca nama	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 Registration number: 01- 2119488216-32- XXXX	xylene	17,5	Flam. Liq. 3, H226 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315	1, 2
CAS: 24938-91-8	poly(oxy-1,2-ethanediyl), α-tridecyl-ω- hydroxy-	4	Acute Tox. 4, H302 Eye Dam. 1, H318	

#### **Notes**

Version Number: 09

- 1 Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- 2 Substance with a Union workplace exposure limit.

Full text of all classifications and hazard statements is given in the section 16.

#### **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

Do not perform artificial respiration without self-protection (e.g. a mask). If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

#### If inhaled

Take care of your own safety, do not let the affected person walk! Terminate the exposure immediately; move the affected person to fresh air. Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

#### If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible.

#### If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. No neutralization should be performed in any case! Rinsing should be continued for 10-30 minutes from the inner to the outer eye corner to make sure that the other eye is not involved. Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible. Everyone must be referred for treatment even if affected only a little.

## If swallowed

If the affected person vomits, make sure to prevent inhalation of the vomit (as there is a danger of lung damage after inhalation of these liquids in the airways also in infinitesimal amount). Ensure medical treatment considering the frequent need of further observation for at least 24 hours. Bring an original container with the label and the Safety Data Sheet of the given substance as appropriate.

## 4.2 Most important symptoms and effects, both acute and delayed

## If inhaled

Inhaling vapours can cause corrosion of the breathing system. Cough, headache. May cause respiratory irritation. May cause drowsiness or dizziness.

## If on skin

Causes skin irritation.

## If in eyes

Causes serious eye damage.

## If swallowed

Corrosion of the digestion system can occur.

## 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

## **SECTION 5: Firefighting Measures**

## 5.1 Extinguishing media

## Suitable extinguishing agents:

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

## Unsuitable extinguishing media

Water - full jet.

## 5.2 Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

## 5.3 Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

## **TEC-2000** Induction Cleaner (Diesel & Petrol)

#### Revision Date: 01-May-2023

## **SECTION 6: Accidental Release Measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Extremely flammable aerosol. Pressurised container: May burst if heated. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale aerosols. Prevent contact with skin and eyes.

## 6.2 Environmental precautions:

Do not allow to enter drains. Prevent contamination of the soil and entering surface or ground water.

## 6.3 Methods and material for containment and cleaning up

Ventilate the room. Use neutralising agent. Absorb spillage to prevent material damage. Dispose of the collected material according to the instructions in the section 13.

## 6.4 Reference to other sections

See the Section 7, 8 and 13.

## **SECTION 7: Handling and Storage**

## 7.1 Precautions for safe handling:

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale aerosols. Prevent contact with skin and eyes. No smoking. Protect against direct sunlight. Do not pierce or burn, even after use. Wash hands and exposed parts of the body thoroughly after handling. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Avoid release to the environment.

## 7.2 Conditions for safe storage, including any incompatibilities:

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Store locked up. Protect from sunlight. Keep container tightly closed. Do not expose to temperatures exceeding 50 °C.

#### 7.3 Specific end use(s

not available

## **SECTION 8: Exposure Controls/Personal Protection**

#### 8.1 Control parameters

The mixture contains substances for which occupational exposure limits are set.

## **European Union**

## Commission Directive 2000/39/EC

Substance name (component)	Туре	Value	Note
	OEL 8 hours	1210 mg/m³	
acetone (CAS: 67-64-1)	OEL 8 hours	500 ppm	
	OEL 8 hours	221 mg/m³	
	OEL 8 hours	50 ppm	
xylene (CAS: 1330-20-7)	OEL 15minutes	442 mg/m³	Skin
,	OEL 15minutes	100 ppm	

## 8.2 Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

## Eye/face protection

Protective goggles or face shield (based on the nature of the work performed). EN166 - Personal Eye Protection Standard.

## Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

## Respiratory protection

In case of inadequate ventilation wear respiratory protection.

#### Thermal hazard

Data not available.

## **Environmental exposure controls**

Observe usual measures for protection of the environment, see Section 6.2. Collect spillage.

## **SECTION 9: Physical and Chemical Properties**

## 9.1 Information on basic physical and chemical properties

Physical state liquid
Colour white
Odour after solvents
Melting point/freezing point data not available

## Version Number: 09 **TEC-2000 Induction Cleaner (Diesel & Petrol)** Revision Date: 01-May-2023

56 °C

not determined

Boiling point or initial boiling point and boiling range

Flammability

Lower and upper explosion limit

bottom 0,8 % upper 13,3 % Flash point 0  $^{\circ}$ C

Auto-ignition temperature data not available not determined pH non-soluble (in water)

Kinematic viscosity <7 mm²/s at 40 °C

Solubility in water

Solubility in water miscible
Partition coefficient n-octanol/water (log value) not determined
Vapour pressure 590-1760 kPa at 45 °C

Density and/or relative density

Density not determined

Relative density 0,815

Relative vapour density data not available Particle characteristics not applicable

Form aerosol dispenser: spray aerosol

9.2 Other information

Ignition temperature: 230 °C

## **SECTION 10: Stability and Reactivity**

## 10.1 Reactivity:

When used in the standard way, there is not any dangerous reaction with other substances.

## 10.2 Chemical stability:

The product is stable under normal conditions.

## 10.3 Possibility of hazardous reactions:

Unknown.

#### 10.4 Conditions to avoid:

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

Pressurised container: May burst if heated.

## 10.5 Incompatible materials:

Protect against oxidizing agents.

## 10.6 Hazardous decomposition products:

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

## **SECTION 11: Toxicological Information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

#### Acute toxicity

Based on available data the classification criteria are not met.

acetone

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD <sub>50</sub>	5800 mg/kg		Rat	
Dermal	LD <sub>50</sub>	20000 mg/kg		Rabbit	
propan-2-ol					

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD <sub>50</sub>	5840 mg/kg		Rat	
Dermal	LD <sub>50</sub>	12800 mg/kg		Rabbit	
Inhalation	LC <sub>50</sub>	30 mg/l	4 hour	Rat	

xylene

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD <sub>50</sub>	4300 mg/kg		Rat	
Dermal	LD <sub>50</sub>	2000 mg/kg		Rabbit	

## Skin corrosion/irritation:

Causes skin irritation.

## Serious eye damage/irritation:

Causes serious eye damage.

## **TEC-2000** Induction Cleaner (Diesel & Petrol)

#### Revision Date: 01-May-2023

## Respiratory or skin sensitization

Based on available data the classification criteria are not met.

## Germ cell mutagenicity:

Based on available data the classification criteria are not met.

## Carcinogenicity:

Based on available data the classification criteria are not met

## Reproductive toxicity

Based on available data the classification criteria are not met.

## Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness. May cause respiratory irritation.

## Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

#### Aspiration hazard

May be fatal if swallowed and enters airways.

## 11.2 Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### **Acute toxicity**

Toxic to aquatic life with long lasting effects.

## Petroleum Light aromatic C9

Farailletei	value	Exposure time	Species	Environment
EC <sub>50</sub>	3.2 mg/l	48 hour	Daphnia	
propan-2-ol				
Parameter	Value	Exposure time	Species	Environment
	0040 //	001	F: 1	

Parameter	Value	Exposure time	Species	Environment
LC <sub>50</sub>	9640 mg/l	96 hour	Fishes	
LC <sub>50</sub>	>10000 mg/l	24 hour	Daphnia	
xvlene				

Parameter	Value	Exposure time	Species	Environment
LC <sub>50</sub>	24-30 mg/l	96 hour	Fishes	
LC <sub>50</sub>	100-1000 mg/l	24 hour	Daphnia (Daphnia magna)	

## **Chronic toxicity**

propan-2-ol

Parameter	Value	Exposure time	Species	Environment
i arameter	Value	Exposure time	Opecies	LIIVII OIIIIIEIIL
NOEC	1050 mg/l		Microorganisms	

#### 12.2 Persistence and degradability:

## Biodegradability

Petroleum Light aromatic C9

outstant Light distribute 55					
Parameter	Value	Exposure time	Environment	Result	
	>60 %	28 day		Biodegradable	

The mixture is biodegradable.

## 12.3 Bioaccumulative potential:

Data not available.

#### 12.4 Mobility in soil:

Data not available.

## 12.5 Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

## 12.6 Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

## 12.7 Other adverse effects:

Not available.

## **SECTION 13: Disposal Considerations**

## 13.1 Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification.

## **TEC-2000** Induction Cleaner (Diesel & Petrol)

Revision Date: 01-May-2023

Perfectly cleaned containers can be submitted for recycling.

## Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

## **SECTION 14: Transport Information**

#### 14.1 UN Number or ID number

UN 1950

## 14.2 UN proper shipping name

2 Gases

## 14.3 Transport hazard class(es)

**AEROSOLS** 

## 14.4 Packing group

not relevant

#### 14.5 Environmental hazards

not relevant

## 14.6 Special precautions for user

Reference in the Sections 4 to 8.

#### 14.7 Maritime transport in bulk according to IMO instruments not relevant

Additional information:

Hazard identification No.

**UN** number

Classification code 5F

Safety signs 2.1+hazardous for the environment



## Road transport - ADR

Limited quantities

Sign



## Air transport - ICAO/IATA

Packaging instructions passenger Cargo packaging instructions

Marine transport - IMDG

EmS (emergency plan) F-D, S-U **MFAG** 620

## **SECTION 15: Regulatory Information.**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

203

203

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended. REGULATION (EC) No 648/2004 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 31 March 2004 on detergents, as amended. Product contains reportable explosives precursors: Reporting of suspicious transactions, disappearances and thefts according to Regulation (EU) 2019/1148, Article 9.

## 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other Information.**

## A list of standard risk phrases used in the safety data sheet

H222 Extremely flammable aerosol.

Highly flammable liquid and vapour. H225 Flammable liquid and vapour. H226

H229 Pressurised container: May burst if heated.

H302 Harmful if swallowed. TEC-2000 Induction Cleaner (Diesel & Petrol) Revision Date: 01-May-2023

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation. H318 Causes serious eve d

Version Number: 09

H312+H332

H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Guidelines for safe handling used in the safety data sheet

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

Harmful in contact with skin or if inhaled.

P251 Do not pierce or burn, even after use.

P391 Collect spillage. P405 Store locked up.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C.

P501 Dispose of contents/container to by handing over to the person authorized to dispose of waste or by returning to the supplier.

A list of additional standard phrases used in the safety data sheet

EUH066 Repeated exposure may cause skin dryness or cracking.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR European agreement concerning the international carriage of dangerous goods by road

BCF Bioconcentration Factor
CAS Chemical Abstracts Service

CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures

EC<sub>50</sub> Concentration of a substance when it is affected 50% of the population EINECS European Inventory of Existing Commercial Chemical Substances

EmS Emergency plan

ES Identification code for each substance listed in EINECS

EU European Union

EuPCS European Product Categorisation System IATA International Air Transport Association

IBC International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals

ICAO International Civil Aviation Organization IMDG International Maritime Dangerous Goods

INCI International Nomenclature of Cosmetic Ingredients
ISO International Organization for Standardization
IUPAC International Union of Pure and Applied Chemistry

 $LC_{50}$  Lethal concentration of a substance in which it can be expected death of 50% of the population Lethal dose of a substance in which it can be expected death of 50% of the population

log Kow Octanol-water partition coefficient

MARPOL International Convention for the Prevention of Pollution from Ships

NOEC

No observed effect concentration

OEL

Occupational Exposure Limits

PBT

Persistent, Bioaccumulative and Toxic

ppm Parts per million

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Agreement on the transport of dangerous goods by rail

UN Four-figure identification number of the substance or article taken from the UN Model Regulations UVCB Substances of unknown or variable composition, complex reaction products or biological materials

VOC Volatile organic compounds

vPvB Very Persistent and very Bioaccumulative

Acute Tox. Acute toxicity Aerosol Aerosol

Aguatic Chronic Hazardous to the aguatic environment (chronic)

Asp. Tox. Aspiration hazard
Eye Dam. Serious eye damage
Eye Irrit. Eye irritation
Flam. Liq. Flammable liquid
Skin Irrit. Skin irritation

STOT SE Specific target organ toxicity - single exposure

Version Number: 09

## **TEC-2000** Induction Cleaner (Diesel & Petrol)

Revision Date: 01-May-2023

## Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

## Recommended restrictions of use

not available

## Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

#### More information

Classification procedure - calculation method.

## Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.