

Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.02.2020 Version number 1.0 Revision: 27.02.2020

- * 1 Identification of the substance/mixture and of the company/undertaking
 - · Product identifier
 - · Trade name: Racoon WHEEL SHIELD Felgenversiegelung
 - \cdot Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Sealing
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Racoon Cleaning Products UG Haftungsbeschränkt Kaiserstrasse 44 D - 66121 Saarbrücken Tel. + 49 (0) 681 765 907 30

Mail info@racoon-cleaner.com

www.racoon-cleaner.com

· Emergency telephone number: Gift Notruf Uni Mainz +49 6131-19240

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS05 GHS07

· Signal word Danger

Printing date 27.02.2020 Version number 1.0 Revision: 27.02.2020

Trade name: Racoon WHEEL SHIELD - Felgenversiegelung

(Contd. of page 1)

· Hazard-determining components of labelling:

3-aminopropyltriethoxysilane

n-butyl acetate

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P103 Read label before use.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.
- · Dangerous components:

CAS: 108-65-6	2-methoxy-1-methylethyl acetate	10-30%
EINECS: 203-603-9	♦ Flam. Liq. 3, H226	
CAS: 123-86-4	n-butyl acetate	10-30%
EINECS: 204-658-1	♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	
CAS: 1330-20-7	xylene	<10%
EINECS: 215-535-7	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 919-30-2	3-aminopropyltriethoxysilane	<5%
EINECS: 213-048-4	♦ Skin Corr. 1B, H314; ♦ Acute Tox. 4, H302	
CAS: 108-88-3	toluene	<0.5%

H304; Skin Irrit. 2, H315; STOT SE 3, H336

• Additional information: For the wording of the listed hazard phrases refer to section 16.

EINECS: 203-625-9 🍪 Flam. Liq. 2, H225; 🗞 Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1,

4 First aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

Printing date 27.02.2020 Version number 1.0 Revision: 27.02.2020

Trade name: Racoon WHEEL SHIELD - Felgenversiegelung

(Contd. of page 2)

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

Printing date 27.02.2020 Version number 1.0 Revision: 27.02.2020

Trade name: Racoon WHEEL SHIELD - Felgenversiegelung

(Contd. of page 3)

- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

108-88-3 toluene

WEL Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm Sk

· Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.


(Contd. on page 5)

Printing date 27.02.2020 Version number 1.0 Revision: 27.02.2020

Trade name: Racoon WHEEL SHIELD - Felgenversiegelung

(Contd. of page 4)

· Eye protection:



9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:
Colour:
Colour:
Colour:
Colour:
Colourless
Like alcohol
Not determined.

PH-value:
Not determined.

· Change in condition

Melting point/freezing point:Undetermined.Initial boiling point and boiling range:124-128 ℃

· Flash point: 16 ℃

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 315 ℃

Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

 Lower:
 1.2 Vol %

 Upper:
 10.8 Vol %

 • Vapour pressure at 20 ℃:
 10.7 hPa

Density: Not determined.
Relative density Not determined.
Vapour density Not determined.
Evaporation rate Not determined.

· Solubility in / Miscibility with

water: Fully miscible.

• Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined. Kinematic: Not determined.

· Solvent content:

 Organic solvents:
 30.5-<70.5 %</td>

 VOC (EC)
 30.5-<70.5 %</td>

Solids content: 0.0 %

Other information
 No further relevant information available.

GB (Contd. on page 6)

Printing date 27.02.2020 Version number 1.0 Revision: 27.02.2020

Trade name: Racoon WHEEL SHIELD - Felgenversiegelung

(Contd. of page 5)

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral LD50 >35,600 mg/kg (rat)
Dermal LD50 >20,000 mg/kg (rabbit)

Inhalative LC50 (4h) >110 mg/l

108-65-6 2-methoxy-1-methylethyl acetate

Oral LD50 8,532 mg/kg (rat) Inhalative LC50 (4h) 35.7 mg/l (rat)

123-86-4 n-butyl acetate

Oral LD50 13,100 mg/kg (rat)
Dermal LD50 >5,000 mg/kg (rabbit)

Inhalative LC50 (4h) >21 mg/l (rat)

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)
Dermal LD50 2,000 mg/kg (rabbit)

919-30-2 3-aminopropyltriethoxysilane

Oral LD50 1,780 mg/kg (rat)
Dermal LD50 4,000 mg/kg (rabbit)

108-88-3 toluene

Oral LD50 5,000 mg/kg (rat)

Dermal LD50 12,124 mg/kg (rabbit)

Inhalative LC50 (4h) 5,320 mg/l (mouse)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes sérious eve damage.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

Printing date 27.02.2020 Version number 1.0 Revision: 27.02.2020

Trade name: Racoon WHEEL SHIELD - Felgenversiegelung

(Contd. of page 6)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

HP3 Flammable

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport information

· UN-Number

· ADR, IMDG, IATA

UN2924

· UN proper shipping name

· ADR 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. (BUTYL ACETATES, 2-methoxy-1-methylethyl acetate)

· IMDG, IATA

FLAMMABLE LIQUID, CORROSIVE, N.O.S. (BUTYL

ACETATES, 2-methoxy-1-methylethyl acetate)

- · Transport hazard class(es)
- · ADR





· Class 3 Flammable liquids.

(Contd. on page 8)

Printing date 27.02.2020 Version number 1.0 Revision: 27.02.2020

Trade name: Racoon WHEEL SHIELD - Felgenversiegelung

(Contd. of page 7)

· Label 3+8

· IMDG



· Class 3 Flammable liquids.

· Label 3/8

· IATA



· Class 3 Flammable liquids.

- Label 3 (8)

· Packing group

· ADR, IMDG, IATA

· Environmental hazards: Not applicable.

· Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler code): 38
EMS Number: F-E,S-C

- Stowage Category E

· Stowage Code SW2 Clear of living quarters.

· Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

· Transport/Additional information:

ADR

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

Transport categoryTunnel restriction codeD/E

· IMDG

Limited quantities (LQ)
Excepted quantities (EQ)
Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S.

(BUTYL ACETATES, 2-METHOXY-1-METHYLETHYL

ACETATE), 3 (8), II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

Printing date 27.02.2020 Version number 1.0 Revision: 27.02.2020

Trade name: Racoon WHEEL SHIELD - Felgenversiegelung

(Contd. of page 8)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

*16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- · Contact: MSDS authorized Person
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - dermal – Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

* Data compared to the previous version altered.