



Revision date: 19 Aug 2022 Version: 4 Print date: 19 Aug 2022

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

RAVENOL WATERCRAFT Teilsynth. 2-Takt

Article No.:

1152210

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Lubricant

* 1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

Ravensberger Schmierstoffvertrieb GmbH

Produktsicherheit

Jöllenbecker Str. 2

33824 Werther

Germany

Telephone: +49 5203 9719 0

Telefax: +49 5203 9719 40

E-mail: kontakt@ravenol.de

Website: www.ravenol.de

E-mail (competent person): sdb@ravenol.de

* 1.4. Emergency telephone number

24 hr. emergency phone number, 24h: +49 700 24 112 112 (Contract ID: RAV) / +1 872 5888271
(Contract ID: RAV)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

* 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard statements: none

Supplemental hazard information

EUH208	Contains Mixture of dicalcium (bis(2-hydroxy-5-tetra- propenyl phenyl methyl) methylamine) dihydroxide. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

Precautionary statements: none

* 2.3. Other hazards

Other adverse effects:

The mixture contains substances fulfilling the PBT and / or vPvB criteria according to REACH, Annex XIII.



Revision date: 19 Aug 2022 Version: 4 Print date: 19 Aug 2022

SECTION 3: Composition/information on ingredients

* 3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 64741-76-0 EC No.: 265-077-7 REACH No.: 01-2119486951-26	Distillates (petroleum), heavy hydrocracked Asp. Tox. 1 (H304) Danger	10 - < 25 weight-%
EC No.: 420-470-4 Index No.: 020-003-00-0 REACH No.: 01-0000016710-77	Mixture of dicalcium (bis(2-hydroxy-5-tetra- propenyl phenyl methyl) methylamine) dihydroxide Eye Irrit. 2 (H319), Skin Irrit. 2 (H315), Skin Sens. 1 (H317) Warning Additional information: PBT-substance.	0 - < 0.25 weight-%
CAS No.: 64742-94-5 REACH No.: 01-2119463588-24	Hydrocarbons, C10-C13, Aromatics, >1% Naphthalene Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Carc. 2 (H351), STOT SE 3 (H336) Danger	0 - < 0.006 weight-%
CAS No.: 91-20-3 EC No.: 202-049-5 Index No.: 601-052-00-2	naphthalene Acute Tox. 4 (H302), Aquatic Acute 1 (H400), Aquatic Chronic 1 (H410), Carc. 2 (H351) Warning	0 - < 0.001 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing. If unconscious but breathing normally, place in recovery position and seek medical advice. Do not leave affected person unattended.

Following inhalation:

Provide fresh air. Consult a doctor immediately.

In case of skin contact:

After contact with skin, wash immediately with plenty of water and soap. Consult a doctor immediately.

After eye contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion:

Rinse mouth thoroughly with water. Do NOT induce vomiting. Consult a doctor immediately.

Self-protection of the first aider:

Use personal protection equipment. No direct artificial respiration to be given by first aider.

* 4.2. Most important symptoms and effects, both acute and delayed

Contains Mixture of dicalcium (bis(2-hydroxy-5-tetra- propenyl phenyl methyl) methylamine) dihydroxide. May produce an allergic reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Observe risk of aspiration if vomiting occurs.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Co-ordinate fire-fighting measures to the fire surroundings.

Carbon dioxide (CO2)

Extinguishing powder

alcohol resistant foam

Use water spray jet to protect personnel and to cool endangered containers.

Unsuitable extinguishing media:

Full water jet



Revision date: 19 Aug 2022 Version: 4 Print date: 19 Aug 2022

5.2. Special hazards arising from the substance or mixture

During heating or in case of fire, toxic gases is possible.

The formation of combustible vapours is possible at temperatures above: Flash point

Hazardous combustion products:

Carbon monoxide, Carbon dioxide (CO₂), Nitrogen oxides (NO_x),

During heating or in case of fire, toxic gases is possible.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Protective clothing.

5.4. Additional information

Do not inhale explosion and combustion gases. Move undamaged containers from immediate hazard area if it can be done safely. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

* 6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Use personal protection equipment. Special danger of slipping by leaking/spilling product.

Protective equipment:

Personal protection equipment: see section 8

Emergency procedures:

Eliminate all ignition sources if safe to do so. Remove persons to safety. Provide adequate ventilation.

6.1.2. For emergency responders

Personal protection equipment:

Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment:

Suitable material for taking up: Sand, Kieselguhr, Universal binder, Chemical binding agents, containing acids

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up:

Remove from the water surface (e.g. skimming, sucking). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information:

Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

6.5. Additional information

Clear spills immediately. Use appropriate container to avoid environmental contamination.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Personal protection equipment: see section 8.

When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Do not put any product-impregnated cleaning rags into your trouser pockets. Clear spills immediately. Use appropriate container to avoid environmental contamination.

Fire prevent measures:

No special fire protection measures are necessary.



Revision date: 19 Aug 2022 Version: 4 Print date: 19 Aug 2022

Environmental precautions:

Shafts and sewers must be protected from entry of the product.

Advices on general occupational hygiene

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

Requirements for storage rooms and vessels:

Suitable container/equipment material: Floors should be impervious, resistant to liquids and easy to clean. Shafts and sewers must be protected from entry of the product.

Keep/Store only in original container.

Hints on storage assembly:

not required

Storage class (TRGS 510, Germany): 10 - Combustible liquids that cannot be assigned to any of the above storage classes

Further information on storage conditions:

Store in a cool dry place. Keep away from heat.

7.3. Specific end use(s)

Recommendation:

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

* 8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
TRGS 900 (DE)	Hydrocarbons, C10-C13, Aromatics, >1% Naphthalene CAS No.: 64742-94-5	① 50 mg/m ³ ② 100 mg/m ³ ⑤ (C9-C14 Aromaten)
VLA (FR)	Hydrocarbons, C10-C13, Aromatics, >1% Naphthalene CAS No.: 64742-94-5	① 150 mg/m ³ ⑤ (hydrocarbures, benzène C9-C12)
NO	Hydrocarbons, C10-C13, Aromatics, >1% Naphthalene CAS No.: 64742-94-5	① 25 ppm (120 mg/m ³) ⑤ (White Spirit (aromatinnhold > 22 %))
CH	Hydrocarbons, C10-C13, Aromatics, >1% Naphthalene CAS No.: 64742-94-5	① 100 ppm (525 mg/m ³) ⑤ Messmeth: OSHA
MAK (AT)	Hydrocarbons, C10-C13, Aromatics, >1% Naphthalene CAS No.: 64742-94-5	① 20 mL/m ³ ② 40 mL/m ³ ⑤ (für Kohlenwasserstoffgemische mit einem Gehalt an aromatischen Kohlenwasserstoffen von mehr als 25 %)
MAK (AT)	Hydrocarbons, C10-C13, Aromatics, >1% Naphthalene CAS No.: 64742-94-5	① 70 mL/m ³ ② 140 mL/m ³ ⑤ (für Kohlenwasserstoffgemische mit einem Gehalt an aromatischen Kohlenwasserstoffen von 1 % bis 25 % und an Hexanen von weniger als 1 %)
WEL (GB)	Hydrocarbons, C10-C13, Aromatics, >1% Naphthalene CAS No.: 64742-94-5	① 500 mg/m ³ ⑤ (Aromatics)
SI	Hydrocarbons, C10-C13, Aromatics, >1% Naphthalene CAS No.: 64742-94-5	① 50 mg/m ³



Revision date: 19 Aug 2022 Version: 4 Print date: 19 Aug 2022

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
CH	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³) ⑤ (Dampf und Aerosol; kann über die Haut aufgenommen werden) H C2; Tox: Blut OAW Auge; Messmeth: NIOSH OSHA
BE	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (53 mg/m ³) ② 15 ppm (80 mg/m ³) ⑤ (peut être absorbé par la peau) D
CZ	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 9.4 ppm (50 mg/m ³) ② 18.8 ppm (100 mg/m ³)
PL	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 20 mg/m ³ ② 50 mg/m ³ ⑤ (może przenikać przez skórę do organizmu) skóra
NO	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³) ⑤ E
IE	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³) ⑤ IOELV
HTP (FI)	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 1 ppm (5 mg/m ³) ② 2 ppm (10 mg/m ³)
LT	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³) ⑤ (Kancerogeninės) K
SE	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³) ③ 15 ppm (80 mg/m ³)
NPEL (SK)	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³) ② 15 ppm (80 mg/m ³)
TRGS 900 (DE)	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 0.4 ppm (2 mg/m ³) ② 1.6 ppm (8 mg/m ³) ⑤ (Aerosol und Dampf, kann über die Haut aufgenommen werden) AGS, H, Y, 11, 27
DK	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³) ② 20 ppm (100 mg/m ³)
BG	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 50 mg/m ³ ② 75 mg/m ³
HR	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³)
ES	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (53 mg/m ³) ② 15 ppm (80 mg/m ³) ⑤ (puede ser absorbido a través dérmica)
RO	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³) ⑤ C2
EE	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³)
LV	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³)



Revision date: 19 Aug 2022 Version: 4 Print date: 19 Aug 2022

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
Alberta (CA)	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (52 mg/m ³) ② 15 ppm (79 mg/m ³)
BC (CA)	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm ⑤ (may be absorbed through the skin) Skin; 2B
MY	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (52 mg/m ³)
IOELV (EU)	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³)
VLA (FR)	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³)
SI	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 50 mg/m ³ ② 50 mg/m ³ ⑤ (frakcija ki jo je mogoče vdihniti računati je treba z možnostjo prodiranja skozi kožo) K, Y, EU0
TW	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (52 mg/m ³)
KR	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³) ② 15 ppm (75 mg/m ³)
IS	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³)
CN	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 50 mg/m ³ ② 75 mg/m ³ ⑤ (#####)
RU	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	③ 20 mg/m ³
HU	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 50 mg/m ³ ⑤ i
GR	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³)
NL	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 50 mg/m ³ ② 80 mg/m ³
MAK (AT)	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³) ⑤ (kann über die Haut aufgenommen werden) III B, H
SI	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm ② 10 ppm ⑤ (računati je treba z možnostjo prodiranja skozi kožo) K, Y, EU0
TR	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³)
IDLH (US)	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 250 ppm



Revision date: 19 Aug 2022 Version: 4 Print date: 19 Aug 2022

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
Québec (CA)	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (52 mg/m ³) ② 15 ppm (79 mg/m ³)
OSHA (US)	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³)
NIOSH (US)	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³) ② 15 ppm (75 mg/m ³)
ACGIH (US)	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (52 mg/m ³) ② 15 ppm (79 mg/m ³) ⑤ (may be absorbed through the skin)

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
Mixture of dicalcium (bis(2-hydroxy-5-tetra- propenyl phenyl methyl) methylamine) dihydroxide EC No.: 420-470-4	8.7 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
Mixture of dicalcium (bis(2-hydroxy-5-tetra- propenyl phenyl methyl) methylamine) dihydroxide EC No.: 420-470-4	104 mg/m ³	① DNEL worker ② Acute - inhalation, systemic effects
Mixture of dicalcium (bis(2-hydroxy-5-tetra- propenyl phenyl methyl) methylamine) dihydroxide EC No.: 420-470-4	52 mg/m ³	① DNEL worker ② Long-term - inhalation, local effects
Mixture of dicalcium (bis(2-hydroxy-5-tetra- propenyl phenyl methyl) methylamine) dihydroxide EC No.: 420-470-4	104 mg/m ³	① DNEL worker ② Acute - inhalation, local effects
Mixture of dicalcium (bis(2-hydroxy-5-tetra- propenyl phenyl methyl) methylamine) dihydroxide EC No.: 420-470-4	3.3 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
Mixture of dicalcium (bis(2-hydroxy-5-tetra- propenyl phenyl methyl) methylamine) dihydroxide EC No.: 420-470-4	40 mg/kg bw/day	① DNEL worker ② Acute - dermal, systemic effects
Mixture of dicalcium (bis(2-hydroxy-5-tetra- propenyl phenyl methyl) methylamine) dihydroxide EC No.: 420-470-4	20 mg/kg bw/day	① DNEL worker ② Long-term - dermal, local effects
Mixture of dicalcium (bis(2-hydroxy-5-tetra- propenyl phenyl methyl) methylamine) dihydroxide EC No.: 420-470-4	20 mg/kg bw/day	① DNEL worker ② Acute - dermal, local effects
naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	25 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	25 mg/m ³	① DNEL worker ② Long-term - inhalation, local effects



Revision date: 19 Aug 2022 Version: 4 Print date: 19 Aug 2022

Substance name	DNEL value	① DNEL type ② Exposure route
naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	3.57 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects

Substance name	PNEC Value	① PNEC type
Mixture of dicalcium (bis(2-hydroxy-5-tetra- propenyl phenyl methyl) methylamine) dihydroxide EC No.: 420-470-4	66 µg/L	① PNEC aquatic, freshwater
Mixture of dicalcium (bis(2-hydroxy-5-tetra- propenyl phenyl methyl) methylamine) dihydroxide EC No.: 420-470-4	66 µg/L	① PNEC aquatic, marine water
Mixture of dicalcium (bis(2-hydroxy-5-tetra- propenyl phenyl methyl) methylamine) dihydroxide EC No.: 420-470-4	20 µg/L	① PNEC sewage treatment plant
Mixture of dicalcium (bis(2-hydroxy-5-tetra- propenyl phenyl methyl) methylamine) dihydroxide EC No.: 420-470-4	66 µg/L	① PNEC aquatic, intermittent release
naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	2.4 µg/L	① PNEC aquatic, freshwater
naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	2.4 µg/L	① PNEC aquatic, marine water
naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	2.9 mg/L	① PNEC sewage treatment plant
naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	20 µg/L	① PNEC aquatic, intermittent release

8.2. Exposure controls

8.2.1. Appropriate engineering controls

See section 7. No additional measures necessary.

8.2.2. Personal protection equipment



Eye/face protection:

During transfer: Eye glasses with side protection

Wear eye/face protection. EN 166

Skin protection:

Hand protection

Suitable material: NBR (Nitrile rubber), PVC (polyvinyl chloride), CR (polychloroprene, chloroprene rubber)

Thickness of the glove material: ≥ 0,4 mm

Breakthrough time: 480 min

Breakthrough times and swelling properties of the material must be taken into consideration.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Tested protective gloves must be worn: EN ISO 374

Suitable protective clothing: Protective clothing

Respiratory protection:

Usually no personal respiratory protection necessary.

8.2.3. Environmental exposure controls

See section 7. No additional measures necessary.



Revision date: 19 Aug 2022 Version: 4 Print date: 19 Aug 2022

SECTION 9: Physical and chemical properties

* 9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Colour: blue

Odour: characteristic

Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	not applicable		
Melting point	not determined		
Freezing point	not determined		
Initial boiling point and boiling range	not determined		
Decomposition temperature	not determined		
Flash point	168 °C		
Evaporation rate	not determined		
Auto-ignition temperature	not determined		
Upper/lower flammability or explosive limits	not determined		
Vapour pressure	not determined		
Vapour density	not determined		
Density	869 kg/m ³	15 °C	
Relative density	not determined		
Bulk density	not determined		
Water solubility	practically insoluble		
Partition coefficient: n-octanol/water	not determined		
Dynamic viscosity	not determined		
Kinematic viscosity	68 mm ² /s	40 °C	

* 9.2. Other information

Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

No known hazardous reactions. Risk of explosion if heated under confinement.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

To avoid thermal decomposition do not overheat.

10.5. Incompatible materials

Materials to avoid: Acid, Oxidising agent, Reducing agent

* 10.6. Hazardous decomposition products

Hazardous combustion products: Carbon monoxide, Carbon dioxide (CO₂), Nitrogen oxides (NO_x), During heating or in case of fire, toxic gases is possible.

SECTION 11: Toxicological information

* 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Distillates (petroleum), heavy hydrocracked CAS No.: 64741-76-0 EC No.: 265-077-7
LD₅₀ oral: 5,000 mg/kg (Rat)
LD₅₀ dermal: >2,000 mg/kg (Rab)
LC₅₀ Acute inhalation toxicity (gas): 5,000 mg/m ³ (Rat)



Revision date: 19 Aug 2022 Version: 4 Print date: 19 Aug 2022

naphthalene CAS No.: 91-20-3 EC No.: 202-049-5
LD₅₀ oral: >533 mg/kg (Mouse)
LD₅₀ dermal: >16,000 mg/kg (Rat)
LC₅₀ Acute inhalation toxicity (dust/mist): >0.4 mg/L 4 h (Rat)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation:

Contains Mixture of dicalcium (bis(2-hydroxy-5-tetra- propenyl phenyl methyl) methylamine) dihydroxide.
 May produce an allergic reaction.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Observe risk of aspiration if vomiting occurs.

For viscosity data, see section 9.

Additional information:

Frequently or prolonged contact with skin may cause dermal irritation.

* **11.2. Information on other hazards**

Endocrine disrupting properties:

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

* **12.1. Toxicity**

Distillates (petroleum), heavy hydrocracked CAS No.: 64741-76-0 EC No.: 265-077-7
LC₅₀: 100 mg/L 4 d (fish)
NOEC: 100 mg/L -∞ h (fish)
EC₅₀: 10,000 mg/L 2 d (crustaceans)
NOEC: 100 mg/L -∞ h (crustaceans)
NOEC: 100 mg/L -∞ h (Algae/water plant)
IC₅₀: 100 mg/L 3 d (Algae/water plant)
naphthalene CAS No.: 91-20-3 EC No.: 202-049-5
LC₅₀: >1.2 - <2.1 mg/L 4 d (fish)
EC₅₀: >2.16 mg/L 2 d (crustaceans)
EC₅₀: >2.96 mg/L 4 d (Algae/water plant)

Assessment/classification:

The substance/mixture does not fulfill the criteria of the acute aquatic toxicity according to Regulation (EC) No 1272/2008 [CLP], Annex I.

Additional ecotoxicological information:

Do not allow uncontrolled discharge of product into the environment.



Revision date: 19 Aug 2022 Version: 4 Print date: 19 Aug 2022

* **12.2. Persistence and degradability**

Distillates (petroleum), heavy hydrocracked CAS No.: 64741-76-0 EC No.: 265-077-7

Biodegradation: Yes, slowly

Biodegradation:

Not readily biodegradable (according to OECD criteria)

* **12.3. Bioaccumulative potential**

Distillates (petroleum), heavy hydrocracked CAS No.: 64741-76-0 EC No.: 265-077-7

Log K_{OW}: 6

naphthalene CAS No.: 91-20-3 EC No.: 202-049-5

Log K_{OW}: 3.7

Bioconcentration factor (BCF): 168

Accumulation / Evaluation:

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

* **12.5. Results of PBT and vPvB assessment**

Distillates (petroleum), heavy hydrocracked CAS No.: 64741-76-0 EC No.: 265-077-7

Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

Mixture of dicalcium (bis(2-hydroxy-5-tetra- propenyl phenyl methyl) methylamine) dihydroxide
 EC No.: 420-470-4

Results of PBT and vPvB assessment: PBT-substance.

Hydrocarbons, C10-C13, Aromatics, >1% Naphthalene CAS No.: 64742-94-5

Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

naphthalene CAS No.: 91-20-3 EC No.: 202-049-5

Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

The mixture contains substances fulfilling the PBT and / or vPvB criteria according to REACH, Annex XIII.

* **12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste according to applicable legislation.

Waste treatment options

Appropriate disposal / Product:

Dispose of waste according to applicable legislation.

Appropriate disposal / Package:

Non-contaminated packages may be recycled.

Other disposal recommendations:

Consult the appropriate local waste disposal expert about waste disposal.

13.2. Additional information

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.



Revision date: 19 Aug 2022 Version: 4 Print date: 19 Aug 2022

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.2. UN proper shipping name			
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.
14.3. Transport hazard class(es)			
not relevant	not relevant	not relevant	not relevant
14.4. Packing group			
not relevant	not relevant	not relevant	not relevant
14.5. Environmental hazards			
not relevant	not relevant	not relevant	not relevant
14.6. Special precautions for user			
not relevant	not relevant	not relevant	not relevant

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

* 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Other regulations (EU):

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]: This product is not assigned to a hazard category.

Safety data sheet available on request.

15.1.2. National regulations

[DE] National regulations

Störfallverordnung (12. BImSchV)

for substances contained in the product:

This product is not assigned to a hazard category.

Technische Anleitung zur Reinhaltung der Luft (TA-Luft)

Remark:

To follow: 5.2.5

Water hazard class

WGK:

2 - deutlich wassergefährdend

Source:

Self-classification (mixture; calculation rule).

Identification number 436

Technische Regeln für Gefahrstoffe

TRGS 510

TRGS 500

Berufsgenossenschaftliche Vorschriften (DGUV-Vorschriften)

Berufsgenossenschaftliche Informationen (DGUV-Informationen) 868

Berufsgenossenschaftliche Regeln (DGUV-Regeln) 189, 190, 192, 195

Other regulations, restrictions and prohibition regulations

Altöl-Verordnung (AltöIV)

[DK] National regulations

Other regulations, restrictions and prohibition regulations

Dänemark: Bekendtgørelse af lov om arbejdsmiljø: Beskæftigelsesministeriets lovbekendtgørelse nr. 1072 af 7. september 2010

Lister over stoffer og processer, der anses for at være kræftfremkaldende

[FR] National regulations

Other regulations, restrictions and prohibition regulations

Frankreich: Tableaux de maladies professionnelles

Nomenclature des installations classées pour la protection de l'environnement

Articles L. 4523-1 à L. 4523-17, L. 4611-1 à L. 4614-16, R. 4523-1 à R. 4523-17 et R. 4612-1 à R. 4615-21 du Code du travail



Revision date: 19 Aug 2022 Version: 4 Print date: 19 Aug 2022

[NL] National regulations

Other regulations, restrictions and prohibition regulations

Nederlandse: Lijst van kankerverwekkende, mutagene en voor de voortplanting giftige stoffen (SZW)
 Algemeene beoordelingsmethodiek Water (ABM)
 Nederlandse emissierichtlijn (NeR)
 NIET-Limitatieve lijst aan voor de voortplanting giftige stoffen - Borstvoeding
 NIET-Limitatieve lijst aan voor de voortplanting giftige stoffen - Vruchtbaarheid
 NIET-Limitatieve lijst aan voor de voortplanting giftige stoffen - Ontwikkeling
 SZW-lijst van kankerverwekkende stoffen
 SZW-lijst van mutagene stoffen
 Wet van 18 maart 1999, houdende bepalingen ter verbetering van de arbeidsomstandigheden
 (Arbeidsomstandighedenwet)
 Wet op de ondernemingsraden 1971

[CH] National regulations

Other regulations, restrictions and prohibition regulations

Mengenschwelle (Schweiz - StFV)
 Gefahrencode
 Brandverhütung, BVD (Schweiz)

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

15.3. Additional information

No data available.

SECTION 16: Other information

* 16.1. Indication of changes

1.3.	Details of the supplier of the safety data sheet
1.4.	Emergency telephone number
2.2.	Label elements
2.3.	Other hazards
3.2.	Mixtures
4.2.	Most important symptoms and effects, both acute and delayed
6.1.	Personal precautions, protective equipment and emergency procedures
8.1.	Control parameters
9.1.	Information on basic physical and chemical properties
9.2.	Other information
10.6.	Hazardous decomposition products
11.1.	Information on hazard classes as defined in Regulation (EC) No 1272/2008
11.2.	Information on other hazards
12.1.	Toxicity
12.2.	Persistence and degradability
12.3.	Bioaccumulative potential
12.5.	Results of PBT and vPvB assessment
12.6.	Endocrine disrupting properties
15.1.	Safety, health and environmental regulations/legislation specific for the substance or mixture
16.1.	Indication of changes
16.5.	Relevant R-, H- and EUH-phrases (Number and full text)

16.2. Abbreviations and acronyms

See overview table at www.euphrac.eu

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

16.3. Key literature references and sources for data

67/548/EEC - Dangerous Substances Directive
 1999/45/EEC - Dangerous Preparations Directive
 EC 1907/2006 - REACH Regulation
 1272/2008 EC - Regulation on classification, labeling and packaging of substances and mixtures, and amending Directives 67/548/EEC and 1999/45/EC and Regulation (EC) No 1907/2006
 Regulation (EC) No 1907/2006 (REACH), Annex II



Revision date: 19 Aug 2022 Version: 4 Print date: 19 Aug 2022

European Chemicals Agency (ECHA), C & L classification and labeling inventory
European Chemicals Agency (ECHA), ECHA CHEM Registered substances
OECD The Global Portal to Information on Chemical Substances (ChemPortal)
Institute for Occupational Safety and Health of the German Social Accident Insurance (IFA): GESTIS
substance database and International limit values for chemical substances
Federal Environment Agency, Section IV 2.4: Documentation and Information Centre substances
hazardous to water Rigoletto (catalog substances hazardous to water)

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

* 16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements	
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

16.6. Training advice

No data available

16.7. Additional information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

* Data changed compared with the previous version.