# **SAFETY DATA SHEET**



MOBIL DELVAC MODERN 10W-40 SUPER DEFENSE

### **Section 1. Identification**

Product name : MOBIL DELVAC MODERN 10W-40 SUPER DEFENSE

Product description : base oil and additives

Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Engine oil

Uses advised against : This product is not recommended for any industrial, professional or consumer use

other than the Identified Uses above.

Supplier : EXXONMOBIL

407, EMARAT ATRIUM SHEIKH ZAYED ROAD P.O. BOX 33369

DUBAI

United Arab Emirates

24 Hour Emergency

**Telephone** 

: +44 20 3885 0382 / +1-703-527-3887 (CHEMTREC)

Supplier General Contact : +20 2 795 4850 (ARABIC, ENGLISH, FRENCH)

### Section 2. Hazard identification

Classification of the substance or mixture

: Not classified.

Supplemental label

elements

: Not applicable.

Other hazards which do not

result in classification

: None known.

Nota

: This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% by weight	Identifiers
distillates (petroleum), solvent-dewaxed light paraffinic	≤3	REACH #: 01-2119480132-48 EC: 265-159-2 CAS: 64742-56-9
distillates (petroleum), solvent-dewaxed heavy paraffinic	≤3	REACH #: 01-2119471299-27 EC: 265-169-7 CAS: 64742-65-0
distillates (petroleum), solvent-refined light paraffinic	≤3	REACH #: 01-2119487067-30 EC: 265-091-3 CAS: 64741-89-5

Date of issue/Date of revision : 10 August Date of previous issue : 6/1/2023 Version : 1.01 1/10 2024

MOBIL DELVAC MODERN 10W-40 SUPER DEFENSE

# Section 3. Composition/information on ingredients

distillates (petroleum), hydrotreated light paraffinic	≤3	REACH #: 01-2119487077-29 EC: 265-158-7 CAS: 64742-55-8
distillates (petroleum), hydrotreated heavy paraffinic	≤3	REACH #: 01-2119484627-25 EC: 265-157-1 CAS: 64742-54-7
paraffin oils (petroleum), catalytic dewaxed heavy	≤3	REACH #: 01-2119487080-42 EC: 265-174-4 CAS: 64742-70-7
zinc bis[o-(6-methylheptyl)] bis[o-(sec-butyl)] bis(dithiophosphate)	<2.5	REACH #: 01-2119543726-33 EC: 298-577-9 CAS: 93819-94-4

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First-aid measures

#### **Description of necessary first aid measures**

Eye contact : Immediately

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation

occurs.

**Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Get medical attention if symptoms occur.

**Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may

significantly reduce the ultimate extent of injury.

Ingestion : Wash out mouth with water. If material has been swallowed and the exposed

person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms

occur.

#### Most important symptoms/effects, acute and delayed

### Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

### Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : Local necrosis as evidenced by delayed onset of pain and tissue damage a few

hours after injection.

Ingestion : No specific data.

Date of issue/Date of revision : 10 August Date of previous issue : 6/1/2023 Version : 1.01 2/10

### Section 4. First-aid measures

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** 

No specific treatment.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training.

### See toxicological information (Section 11)

### Section 5. Firefighting measures

#### **Extinguishing media**

Suitable extinguishing media

: Use dry chemical, CO2, water spray (fog) or foam.

**Unsuitable extinguishing** media

: Do not use water jet.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous combustion** products

: Aldehydes, Incomplete combustion products, Oxides of carbon, Smoke, Fume, sulfur oxides

**Special protective actions** for fire-fighters

: Use standard firefighting procedures and consider the hazards of other involved materials. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Assure an extended cooling down period to prevent reignition. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

### **NOTIFICATION PROCEDURES**

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Date of issue/Date of revision Version : 1.01 : 10 August Date of previous issue : 6/1/2023 3/10 2024

### Section 6. Accidental release measures

### Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Confine the spill immediately with booms. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants. Warn other shipping. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

### Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Avoid contact with used product.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### **Static Accumulator**

: This material is a static accumulator. A liquid is typically considered a nonconductive, static accumulator if its conductivity is below 100 pS/m (100x10E-12 Siemens per meter) and is considered a semiconductive, static accumulator if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semiconductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, anti-static additives and filtration can greatly influence the conductivity of a liquid.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

### **Control parameters**

### Occupational exposure limits

Product/ingredient name	Exposure limit values
distillates (petroleum), hydrotreated heavy paraffinic	ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly and severely refined]
	TWA 8 hours: 5 mg/m³. Form: Inhalable fraction.
distillates (petroleum), solvent-dewaxed heavy paraffinic	ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly and severely refined]
ľ	TWA 8 hours: 5 mg/m³. Form: Inhalable fraction.
distillates (petroleum), solvent-dewaxed light paraffinic	ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly and severely refined]
	TWA 8 hours: 5 mg/m³. Form: Inhalable fraction.
distillates (petroleum), solvent-dewaxed heavy paraffinic	ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly and severely refined]
distillates (petroleum), solvent-refined light	TWA 8 hours: 5 mg/m³. Form: Inhalable fraction.  ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly

Date of issue/Date of revision : 10 August Date of previous issue : 6/1/2023 Version : 1.01 4/10

## Section 8. Exposure controls/personal protection

paraffinic and severely refined] TWA 8 hours: 5 mg/m<sup>3</sup>. Form: Inhalable fraction. ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly distillates (petroleum), hydrotreated light paraffinic and severely refined] TWA 8 hours: 5 mg/m<sup>3</sup>. Form: Inhalable fraction. distillates (petroleum), hydrotreated heavy ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly paraffinic and severely refined] TWA 8 hours: 5 mg/m<sup>3</sup>. Form: Inhalable fraction. ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly paraffin oils (petroleum), catalytic dewaxed heavy and severely refined] TWA 8 hours: 5 mg/m³. Form: Inhalable fraction.

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

# Appropriate engineering controls

**Environmental exposure** controls

- : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

### **Skin protection**

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. > 8 hours (breakthrough time): Nitrile, minimum 0.38 mm thickness or comparable protective barrier material

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: particulate filter

# Section 9. Physical and chemical properties and safety characteristics

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Appearance**

Physical state : Liquid.
Colour : Amber

Date of issue/Date of revision : 10 August Date of previous issue : 6/1/2023 Version : 1.01 5/10

# Section 9. Physical and chemical properties and safety characteristics

Odour : Characteristic
Odour threshold : Not available.

pH : Not applicable.

Melting point/freezing point : Not available.

boiling point and boiling

**Boiling point or initial** 

range

Flash point : Open cup: >200°C (>392°F) [ASTM D-92]

: >316°C (>600.8°F)

Evaporation rate : Not available.
Flammability : Ignitable
Lower and upper explosion
limit/flammability limit : Lower: 0.9%
Upper: 7%

Vapour pressure : <0.1 mm Hg [20 °C]

Relative vapour density : >2 [Air = 1]

Relative density : 0.867 [ASTM D1298]

Solubility in water : Negligible
Partition coefficient: n- : >3.5

octanol/water

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

**Viscosity** : 14.7 cSt [100 °C] [ASTM D 445]

100.1 cSt [40 °C] [ASTM D 445]

**Particle characteristics** 

Median particle size : Not applicable.

Pour point : <-27°C [ASTM D97]

DMSO Extract (mineral oil : <3 % by weight

only), IP-346

### Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : High energy sources of ignition. Excessive heat.

Incompatible materials : Strong oxidisers

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Date of issue/Date of revision : 10 August Date of previous issue : 6/1/2023 Version : 1.01 6/10

## Section 11. Toxicological information

### Information on toxicological effects

#### **Acute toxicity**

**Conclusion/Summary** 

Inhalation : Minimally Toxic. No end point data for material. Based on assessment of the

components.

**Dermal** Minimally Toxic. No end point data for material. Based on assessment of the

components.

Oral : Minimally Toxic. No end point data for material. Based on assessment of the

components.

#### **Irritation/Corrosion**

**Conclusion/Summary** 

Skin : Negligible irritation to skin at ambient temperatures. No end point data for material.

Based on assessment of the components.

: May cause mild, short-lasting discomfort to eyes. No end point data for material. Eyes

Based on assessment of the components.

Negligible hazard at ambient/normal handling temperatures. No end point data for Respiratory

material.

### Respiratory or skin sensitization

### **Conclusion/Summary**

Skin : Not expected to be a skin sensitizer. No end point data for material. Based on

assessment of the components.

Respiratory : Not expected to be a respiratory sensitizer. No end point data for material.

**Mutagenicity** 

**Conclusion/Summary** : Not expected to be a germ cell mutagen. No end point data for material. Based on

assessment of the components.

**Carcinogenicity** 

**Conclusion/Summary** : Not expected to cause cancer. No end point data for material. Based on assessment

of the components.

Reproductive toxicity

**Conclusion/Summary** : Not expected to be a reproductive toxicant. No end point data for material. Based on

assessment of the components.

### Specific target organ toxicity (single exposure)

**Conclusion/Summary** : Not expected to cause organ damage from a single exposure. No end point data for

material.

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Target organs
MOBIL DELVAC MODERN 10W-40 SUPER DEFENSE	Not applicable.	-

**Conclusion/Summary** 

: Not expected to cause organ damage from prolonged or repeated exposure. No end point data for material. Based on assessment of the components.

**Aspiration hazard** 

**Conclusion/Summary** : Not expected to be an aspiration hazard. Based on physico-chemical properties of

the material. Data available.

### **Other information**

**Contains** 

: Base oil severely refined: Not carcinogenic in animal studies. Representative material passes IP-346, Modified Ames test, and/or other screening tests. Dermal and inhalation studies showed minimal effects; lung non-specific infiltration of immune cells, oil deposition and minimal granuloma formation. Not sensitising in test animals.

Date of issue/Date of revision Version : 1.01 : 10 August Date of previous issue : 6/1/2023 7/10 2024

# **Section 11. Toxicological information**

#### Produc

: Diesel engine oils: Not carcinogenic in animals tests. Used and unused diesel engine oils did not produce any carcinogenic effects in chronic mouse skin painting studies. Oils that are used in gasoline engines may become hazardous and display the following properties: Carcinogenic in animal tests. Caused mutations in vitro. Possible allergen and photoallergen. Contains polycyclic aromatic compounds (PAC) from combustion products of gasoline and/or thermal degradation products.

# **Section 12. Ecological information**

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

#### **Toxicity**

#### **Conclusion/Summary**

**Acute toxicity** : Not expected to be harmful to aquatic organisms.

Chronic toxicity : Not expected to demonstrate chronic toxicity to aquatic organisms

### Persistence and degradability

Biodegradability: Base oil component -- Expected to be inherently biodegradable

### **Bioaccumulative potential**

<u>Conclusion/Summary</u>: Base oil component -- Has the potential to bioaccumulate, however metabolism or

physical properties may reduce the bioconcentration or limit bioavailability.

#### **Mobility in soil**

**Mobility** : Base oil component -- Expected to partition to sediment and wastewater solids. Low

solubility and floats and is expected to migrate from water to the land.

### Other ecological information

Other adverse effects : No known significant effects or critical hazards.

Nota :

# Section 13. Disposal considerations

### **Disposal methods**

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

# **Section 14. Transport information**

	ADR	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-

Date of issue/Date of revision : 10 August Date of previous issue : 6/1/2023 Version : 1.01 8/10

MOBIL DELVAC MODERN 10W-40 SUPER DEFENSE				
Section 14.	Transport in	formation		
Environmental hazards	No.	No.	No.	

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

# Section 15. Regulatory information

### **International regulations**

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### **Montreal Protocol**

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

**Inventory list** 

Australia inventory (AIIC)

Canada inventory (DSL-NDSL)

China inventory (IECSC)

Japan inventory (CSCL)

China inventory (IECSC)

All components are listed or exempted.

Japan inventory (industrial Salety and

**Health Act)** 

New Zealand Inventory of Chemicals

(NZIoC)

Philippines inventory (PICCS) : All components are listed or exempted.

Korea inventory (KECI) : All components are listed or exempted.

**Taiwan Chemical Substances Inventory** 

(TCSI)

United States inventory (TSCA 8b) : All components are active or exempted.

# **Section 16. Other information**

**History** 

Date of issue/Date of : 8/10/2024

revision

Date of previous issue : 1 June 2023

Version : 1.01

Date of issue/Date of revision: 10 AugustDate of previous issue: 6/1/2023Version: 1.019/102024

: All components are listed or exempted.

: All components are listed or exempted.

MOBIL DELVAC MODERN 10W-40 SUPER DEFENSE

### Section 16. Other information

### Key to abbreviations

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

#### Procedure used to derive the classification

Not classified.

**References** : Not available.

✓ Indicates information that has changed from previously issued version.

**Product code** : 20152040U720\_1167969

#### Notice to reader

"The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, ""ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest."

Date of issue/Date of revision : 10 August Date of previous issue : 6/1/2023 Version : 1.01 10/10

2024