Page 1/9

*

*



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2018

Version number 51

Revision: 18.12.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking
· 1.1 Product identifier
· Trade name: MOTIP® ANTI GRAVEL OVERSPRAYABLE MEDIUM SOLID BLACK 1 LTR
 Article number: 000011 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. Sector of Use SU21 Consumer uses: Private households / general public / consumers SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Product category PC9a Coatings and paints, thinners, paint removers Process category PROC7 Industrial spraying PROC10 Roller application or brushing PROC11 Non industrial spraying Application of the substance / the mixture Anticorrosion additive
 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: MOTIP DUPLI B.V. Wolfraamweg 2 NL- 8471 XC Wolvega The Netherlands Tel: +31 (0)561 694400 Fax: +31 (0)561 694411 e-mail info@nl.motipdupli.com Further information obtainable from: Department Product Safety 1.4 Emergency telephone number: +31 (0)561-694400 (09:00h - 17:00h)
UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111
SECTION 2: Hazards identification · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008
GHS02 flame
Flam. Liq. 2H225 Highly flammable liquid and vapour.
GHS09 environment
Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation. (Contd. on page 2)

Page 2/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2018 Version number 51 Revision: 18.12.2017 Trade name: MOTIP® ANTI GRAVEL OVERSPRAYABLE MEDIUM SOLID BLACK 1 LTR (Contd. of page 1) STOT SE 3 H336 May cause drowsiness or dizziness. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS02 GHS07 GHS09 · Signal word Danger · Hazard-determining components of labelling: Naphtha (petroleum), hydrotreated light ethyl acetate Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Hydrocarbons, C9, aromatics · Hazard statements H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. · Precautionary statements If medical advice is needed, have product container or label at hand. P101 P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe mist/vapours/spray. Use only outdoors or in a well-ventilated area. P271 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents / container in accordance with regional regulations. · 2.3 Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

*

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components: EC number: 927-510-4 Naphtha (petroleum), hydrotreated light 25-<50% Reg.nr.: 01-2119475515-33 🚳 Flam. Liq. 2, H225 & Asp. Tox. 1, H304 🚯 Aquatic Chronic 2, H411 🚯 Skin Irrit. 2, H315; STOT SE 3, H336 CAS: 141-78-6 ethyl acetate 12.5-<20% EINECS: 205-500-4 🚸 Flam. Liq. 2, H225 Index number: 607-022-00-5 🔥 Eye Irrit. 2, H319; STOT SE 3, H336 Reg.nr.: 01-2119475103-46 (Contd. on page 3)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2018

Version number 51

Revision: 18.12.2017

Trade name: MOTIP® ANTI GRAVEL OVERSPRAYABLE MEDIUM SOLID BLACK 1 LTR

	(0	Contd. of page 2)
EC number: 920-750-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	5-<10%
Index number: 649-328-00-1	🛞 Flam. Liq. 2, H225	
Reg.nr.: 01-2119473851-33	🚯 Asp. Tox. 1, H304	
	🚯 Aquatic Chronic 2, H411	
	🚯 STOT SE 3, H336	
EC number: 918-668-5	Hydrocarbons, C9, aromatics	2.5-<5%
Reg.nr.: 01-2119455851-35	🚸 Flam. Liq. 3, H226	
	🗞 Asp. Tox. 1, H304	
	🚯 Aquatic Chronic 2, H411	
	🚯 STOT SE 3, H335-H336	
	the wording of the listed hazand physics refer to section 16	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- \cdot **General information:** Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

×

×

- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Ensure adequate ventilation Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
 6.4 Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

(Contd. on page 4)

GB

Page 4/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2018

Version number 51

Revision: 18.12.2017

Trade name: MOTIP® ANTI GRAVEL OVERSPRAYABLE MEDIUM SOLID BLACK 1 LTR

See Section 13 for disposal information.

(Contd. of page 3)

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- · Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. *Keep respiratory protective device available.*

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed. Store in cool, dry conditions in well sealed receptacles.

• Storage class: 3

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

141-78-6 ethyl acetate

WEL Short-term value: 400 ppm

Long-term value: 200 ppm

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Avoid contact with the eyes.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the

Page 5/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2018

Version number 51

Revision: 18.12.2017

Trade name: MOTIP® ANTI GRAVEL OVERSPRAYABLE MEDIUM SOLID BLACK 1 LTR

(Contd. of page 4) resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



*

Tightly sealed goggles

9.1 Information on basic physical and c	chemical properties
General Information	
Appearance:	
Form:	Fluid
Colour:	Black
Odour: Odour threshold:	Solvent-like Not determined.
pH-value:	Not determined.
-	
Change in condition Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	
Flash point:	-5 °C (23 °F)
Flammability (solid, gas):	Not applicable.
Ignition temperature:	>200 °C (>392 °F)
	200 °C (392 °F)
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
Explosion limits:	
Lower:	0.9 Vol %
	0.6 %
Upper:	11.5 Vol %
	10.5 %
Vapour pressure at 20 °C (68 °F):	160 hPa (120 mm Hg)
	97 hPa (72.8 mm Hg)
Density at 20 °C (68 °F):	1.04 g/cm ³ (8.68 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
<i>Dynamic at 20 •C (68 •F):</i>	690 mPas
Kinematic:	Not determined.

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2018

Version number 51

Revision: 18.12.2017

Trade name: MOTIP® ANTI GRAVEL OVERSPRAYABLE MEDIUM SOLID BLACK 1 LTR

		(Contd. of page 5)
· Solvent content:		
Organic solvents:	52.9 %	
· EU-VOC:	550.2 g/l	
• EU-VOC in %:	52.90 %	
\cdot VOC (EC)		
	550.2 g/l	
· VOC-EU%	52.90 %	
· Solids content:	47.1 %	
• 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:

×

- · Skin corrosion/irritation
- Causes skin irritation.
- · Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- · STOT-single exposure
- May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- \cdot Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

(Contd. on page 7)

Page 7/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2018

Version number 51

Revision: 18.12.2017

Trade name: MOTIP® ANTI GRAVEL OVERSPRAYABLE MEDIUM SOLID BLACK 1 LTR

(Contd. of page 6)

Toxic for aquatic organisms • 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation


Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	
15 01 04	metallic packaging	
	metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers	

· Uncleaned packaging:

· Recommendation: Non contaminated packagings may be recycled.



Page 8/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2018

Version number 51

Revision: 18.12.2017

Trade name: MOTIP® ANTI GRAVEL OVERSPRAYABLE MEDIUM SOLID BLACK 1 LTR

	(Contd. of page
IATA	
Class Label	3 Flammable liquids. 3
	5
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards:	
Marine pollutant:	Yes
	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33
EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>
Stowage Category	В
14.7 Transport in bulk according to Ann Marpol and the IBC Code	ex II of Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities $(\widetilde{E}Q)$	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
	Code: E2
	Maximum net quantity per inner packaging: 30 ml
Transport category	Maximum net quantity per outer packaging: 500 ml 2
Tunnel restriction code	Z D/E
	······
IMDG Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
Letter quantum (LE)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1139 COATING SOLUTION, SPECIAL PROVISION
8	640D, 3, II, ENVIRONMENTALLY HAZARDOUS

*

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category

E2 Hazardous to the Aquatic Environment P5c FLAMMABLE LIQUIDS

 \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

 \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

(Contd. on page 9)

[·] Directive 2012/18/EU

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2018

Version number 51

Revision: 18.12.2017

Trade name: MOTIP® ANTI GRAVEL OVERSPRAYABLE MEDIUM SOLID BLACK 1 LTR

• REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40

· National regulations:

· Other regulations, limitations and prohibitive regulations

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: R&D legislation and regulatory advisor

· Contact: K. Smedeman

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 $\cdot \ast$ Data compared to the previous version altered.

(Contd. of page 8)