

Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.05.2018 Version number 35 Revision: 30.03.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: MOTIP® WAXCOATING TRANSPARENT BROWN 500 ML
- · Article number: 00129
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC9a Coatings and paints, thinners, paint removers
- · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Application of the substance / the mixture Preparation
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTIP DUPLI B.V.

Wolfraamweg 2

NL- 8471 XC Wolvega

The Netherlands

Tel: +31 (0)561 694400 *Fax:* +31 (0)561 694411

e-mail info@nl.motipdupli.com

- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:

+31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Version number 35 Revision: 30.03.2018 Printing date 16.05.2018

Trade name: MOTIP® WAXCOATING TRANSPARENT BROWN 500 ML

(Contd. of page 1)

· Hazard pictograms





· Signal word Danger

· Hazard-determining components of labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source. P211

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents / container in accordance with regional regulations. P501

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

| EC number: 921-024-6 | Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n- | 20-<25% |
|---|---|------------|
| | hexane | |
| | Flam. Liq. 2, H225 | - |
| | A specific Character 2 HALL | |
| | Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336 | |
| EC number: 919-857-5 | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% | 12.5-<20% |
| Reg.nr.: 01-2119463258-33 | aromatics | 12.3-\2070 |
| | ♦ Flam. Liq. 3, H226 | - |
| | & Asp. Tox. 1, H304 | |
| | ♦ STOT SE 3, H336 | |
| CAS: 74-98-6 | propane | 12.5-<20% |
| EINECS: 200-827-9 Index number: 601-003-00-5 | Flam. Gas 1, H220 | |
| Reg.nr.: 01-2119486944-21 | 1 ress. Gas C, 11200 | |
| CAS: 106-97-8 | butane | 10-<12.5% |
| EINECS: 203-448-7 | ◈ Flam. Gas 1, H220 | - |
| Index number: 601-004-00-0 | Press. Gas C, H280 | |
| Reg.nr.: 01-2119474691-32 | | |
| CAS: 75-28-5 | isobutane | 10-<12.5% |
| EINECS: 200-857-2 | Flam. Gas 1, H220 | |
| Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27 | Press. Gas C, H280 | |

(Contd. on page 3)

Printing date 16.05.2018 Version number 35 Revision: 30.03.2018

Trade name: MOTIP® WAXCOATING TRANSPARENT BROWN 500 ML

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B

(Contd. on page 4)

Printing date 16.05.2018 Version number 35 Revision: 30.03.2018

Trade name: MOTIP® WAXCOATING TRANSPARENT BROWN 500 ML

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Not required.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol
Colour: Brown

Odour: Solvent-like
Odour threshold: Not determined.

(Contd. on page 5)

Printing date 16.05.2018 Version number 35 Revision: 30.03.2018

Trade name: MOTIP® WAXCOATING TRANSPARENT BROWN 500 ML

| | (Contd. of page |
|--|---|
| pH-value: | Not determined. |
| Change in condition Melting point/freezing point: Initial boiling point and boiling range: | Undetermined. Not applicable, as aerosol. |
| Flash point: | <0 °C (<32 °F) Not applicable, as aerosol. |
| Flammability (solid, gas): | Not applicable. |
| Ignition temperature: | >200 °C (>392 °F) |
| Decomposition temperature: | Not determined. |
| Auto-ignition temperature: | Product is not selfigniting. |
| Explosive properties: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| Explosion limits: Lower: Upper: | 0.6 Vol % 10.9 Vol % |
| Vapour pressure at 20 °C (68 °F): | 8 hPa (6 mm Hg) |
| Density at 20 °C (68 °F): Relative density Vapour density Evaporation rate | 0.67 g/cm³ (5.59 lbs/gal) Not determined. Not determined. Not applicable. |
| Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
| Partition coefficient: n-octanol/water: | Not determined. |
| Viscosity: Dynamic: Kinematic: | Not determined. Not determined. |
| Solvent content: Organic solvents: EU-VOC: EU-VOC in %: VOC (EC) | 81.2 % 543.4 g/l 81.17 % 543.4 g/l |
| VOC-EU% | 81.17 % |
| Solids content: 9.2 Other information | 18.8 % No further relevant information available. |

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

GB

Printing date 16.05.2018 Version number 35 Revision: 30.03.2018

Trade name: MOTIP® WAXCOATING TRANSPARENT BROWN 500 ML

(Contd. of page 5)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

 Oral
 LD50
 >5,840 mg/kg (rat)

 Dermal
 LD50
 >2,920 mg/kg (rab)

 Inhalative
 LC50 / 4h
 >25.2 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

EC50 / 48 h 3 mg/l (daphnia magna)

EC50 / 72 h | 30-100 mg/l (algae)

 $LC50/96 \ h \ 11.4 \ mg/l \ (fish)$

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Printing date 16.05.2018 Version number 35 Revision: 30.03.2018

Trade name: MOTIP® WAXCOATING TRANSPARENT BROWN 500 ML

(Contd. of page 6)

| · European | waste catalogue | (Conta. or page o) |
|------------|---|--------------------|
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances | |
| 15 01 04 | metallic packaging | |

- · Uncleaned packaging:
- · Recommendation: Non contaminated packagings may be recycled.

| ADR, IMDG, IATA 14.2 UN proper shipping name ADR IMDG IATA 14.3 Transport hazard class(es) ADR | 1950 AEROSOLS AEROSOLS AEROSOLS, flammable |
|--|--|
| ADR IMDG IATA 14.3 Transport hazard class(es) | AEROSOLS |
| IATA 14.3 Transport hazard class(es) | |
| 14.3 Transport hazard class(es) | AEROSOLS, flammable |
| - · · · · · · · · · · · · · · · · · · · | |
| ADR | |
| ** | |
| 2 | |
| Class | 2 5F Gases. |
| Label | 2.1 Guses. |
| IMDG, IATA | |
| Class Label | 2.1 2.1 |
| 14.4 Packing group ADR, IMDG, IATA | not regulated |
| 14.5 Environmental hazards: | Not applicable. |
| 14.6 Special precautions for user | Warning: Gases. |
| Danger code (Kemler): | - |
| EMS Number: | F-D,S-U |
| Stowage Code | SWI Protected from sources of heat. |
| | SW22 For AEROSOLS with a maximum capacity of 1 litt |
| | Category A. For AEROSOLS with a capacity above 1 litt Category B. For WASTE AEROSOLS: Category C, Clea. |
| | of living quarters. |
| Segregation Code | SG69 For AEROSOLS with a maximum capacity of 1 litr |
| ~-00 | Segregation as for class 9. Stow "separated from" class I |
| | except for division 1.4. For AEROSOLS with a capacity |
| | above 1 litre: Segregation as for the appropriate |
| | subdivision of class 2. For WASTE AEROSOLS: |
| | Segregation as for the appropriate subdivision of class 2. |

(Contd. on page 8)

Printing date 16.05.2018 Version number 35 Revision: 30.03.2018

Trade name: MOTIP® WAXCOATING TRANSPARENT BROWN 500 ML

(Contd. of page 7)

· Transport/Additional information:

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

Code: E0

Not permitted as Excepted Quantity

· Transport category · Tunnel restriction code D

· IMDG

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

Code: E0

Not permitted as Excepted Quantity

UN 1950 AEROSOLS, 2.1 · UN "Model Regulation":

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Oualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40
- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

- · Department issuing SDS: R&D legislation and regulatory advisor
- · Contact: K. Smedeman
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

(Contd. on page 9)

Printing date 16.05.2018 Version number 35 Revision: 30.03.2018

Trade name: MOTIP® WAXCOATING TRANSPARENT BROWN 500 ML

(Contd. of page 8)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas C: Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* * Data compared to the previous version altered.

CD